```
<!-- drive.component.html -->
<div class="h-full flex flex-col bg-gray-50">
 <!-- Header with search and controls -->
 <div class="bg-white border-b p-4 flex items-center justify-between">
  <div class="flex items-center space-x-4 flex-1">
   <!-- Search -->
   <div class="relative flex-1 max-w-xl">
     <input
      type="text"
      placeholder="Search files and folders..."
      [(ngModel)]="searchQuery"
      (ngModelChange)="onSearchChange()"
      class="w-full pl-10 pr-4 py-2 border rounded-lg focus:outline-none focus:ring-2
focus:ring-blue-500"
    />
    <i class="fas fa-search absolute left-3 top-2.5 text-gray-400"></i>
   </div>
   <!-- Upload buttons -->
   <div class="relative">
     <but
      (click)="isUploadMenuOpen = !isUploadMenuOpen"
      class="px-4 py-2 bg-blue-600 text-white rounded-lg flex items-center space-x-2
hover:bg-blue-700"
      <i class="fas fa-upload"></i>
      <span>New</span>
      <i class="fas fa-chevron-down"></i>
     </button>
     <div
      *nglf="isUploadMenuOpen"
      class="absolute top-full right-0 mt-2 bg-white rounded-lg shadow-lg border p-2
w-48"
      <a href="class="block p-2 hover:bg-gray-100">-100</a> rounded cursor-pointer">
       <input
        tvpe="file"
        multiple
        (change)="handleFileUpload($event)"
        class="hidden"
       />
       <span class="flex items-center space-x-2">
        <i class="fas fa-upload"></i>
        <span>Upload files</span>
       </span>
      </label>
      <label class="block p-2 hover:bg-gray-100 rounded cursor-pointer">
```

```
<input
       type="file"
       webkitdirectory
       directory
       (change)="handleFileUpload($event)"
       class="hidden"
      />
      <span class="flex items-center space-x-2">
       <i class="fas fa-folder-plus"></i>
       <span>Upload folder</span>
      </span>
     </label>
   </div>
  </div>
  <!-- View mode toggles -->
  <div class="flex items-center space-x-2">
   <but
    (click)="viewMode = 'grid'"
    [class.bg-gray-200]="viewMode === 'grid'"
    class="p-2 rounded hover:bg-gray-100"
     <i class="fas fa-grid-2"></i>
   </button>
   <but
    (click)="viewMode = 'list'"
    [class.bg-gray-200]="viewMode === 'list'"
    class="p-2 rounded hover:bg-gray-100"
     <i class="fas fa-list"></i>
   </button>
  </div>
 </div>
</div>
<!-- Sort controls -->
<div class="bg-white border-b px-4 py-2 flex items-center space-x-4">
 <but
  (click)="handleSort('name')"
  [class.bg-gray-200]="sortConfig.key === 'name'"
  class="px-3 py-1 rounded hover:bg-gray-100"
>
  Name
  <i
   *nglf="sortConfig.key === 'name'"
   [class.fa-sort-up]="sortConfig.direction === 'asc'"
   [class.fa-sort-down]="sortConfig.direction === 'desc'"
   class="fas"
```

```
></i>
  </button>
  <but
   (click)="handleSort('date')"
   [class.bg-gray-200]="sortConfig.key === 'date'"
   class="px-3 py-1 rounded hover:bg-gray-100"
   Date
    <i
     *nglf="sortConfig.key === 'date'"
     [class.fa-sort-up]="sortConfig.direction === 'asc'"
     [class.fa-sort-down]="sortConfig.direction === 'desc'"
     class="fas"
   ></i>
  </button>
  <but
   (click)="handleSort('size')"
   [class.bg-gray-200]="sortConfig.key === 'size'"
   class="px-3 py-1 rounded hover:bg-gray-100"
  >
   Size
   <i
     *nglf="sortConfig.key === 'size'"
     [class.fa-sort-up]="sortConfig.direction === 'asc'"
     [class.fa-sort-down]="sortConfig.direction === 'desc'"
     class="fas"
   ></i>
  </button>
 </div>
 <!-- Storage info -->
 <div class="bg-white border-b px-4 py-3">
  <div class="flex items-center justify-between mb-2">
   <span class="text-sm text-gray-600">Storage</span>
   <span class="text-sm text-gray-600" *nglf="diskDetails">
     {{ formatSize(diskDetails.free) }} free of {{
     formatSize(diskDetails.size) }}
   </span>
  </div>
  <div class="w-full bg-gray-200 rounded-full h-2">
   <div
     class="bg-blue-600 h-2 rounded-full"
     [style.width.%]="diskDetails? ((diskDetails.size - diskDetails.free) /
diskDetails.size) * 100 : 0"
   ></div>
  </div>
 </div>
```

```
<!-- Breadcrumb navigation -->
 <div class="bg-white border-b px-4 py-2 flex items-center space-x-2">
  <but
   *nglf="currentPath.length"
   (click)="navigateUp()"
   class="text-gray-600 hover:text-gray-800"
   <i class="fas fa-arrow-left"></i>
  </button>
  <ng-container *ngFor="let path of currentPath; let last = last">
   <span [class.font-semibold]="last">{{ path }}</span>
   <span *nglf="!last" class="text-gray-400">/</span>
  </ng-container>
 </div>
 <!-- File grid/list view -->
 <div class="flex-1 overflow-auto p-4">
  <!-- Grid View -->
  <div
    *nglf="viewMode === 'grid'"
   class="grid grid-cols-1 sm:grid-cols-2 md:grid-cols-3 lg:grid-cols-4 xl:grid-cols-5
gap-4"
  >
   <div
     *ngFor="let item of currentFolder"
     (click)="item.isFolder? navigateToFolder(item): null"
     class="bg-white p-4 rounded-lg shadow hover:shadow-md transition-shadow
cursor-pointer"
     <div class="aspect-square mb-2 flex items-center justify-center">
      <ng-container [ngSwitch]="true">
       <i
         *ngSwitchCase="item.isFolder"
         class="fas fa-folder text-yellow-500 text-4xl"
       ></i>
       <imq
         *ngSwitchCase="item.isImage"
        [src]="item.imageData"
        [alt]="item.name"
        class="w-full h-full object-cover rounded"
       />
       <div
         *ngSwitchDefault
         class="w-16 h-16 bg-gray-200 rounded flex items-center justify-center text-sm"
        {{ item.name.split('.').pop().toUpperCase() }}
       </div>
```

```
</ng-container>
    </div>
    {{ item.name }}
    {{ formatSize(item.stats.size) }}
   </div>
  </div>
  <!-- List View -->
  <div *nglf="viewMode === 'list'" class="bg-white rounded-lg shadow">
    *ngFor="let item of currentFolder"
    (click)="item.isFolder? navigateToFolder(item): null"
    class="flex items-center px-4 py-3 border-b last:border-b-0 hover:bg-gray-50
cursor-pointer"
   >
    <div class="w-8">
     <ng-container [ngSwitch]="true">
      <i
        *ngSwitchCase="item.isFolder"
       class="fas fa-folder text-yellow-500"
      ></i>
      <imq
        *ngSwitchCase="item.isImage"
       [src]="item.imageData"
       [alt]="item.name"
       class="w-5 h-5 object-cover rounded"
      />
      <div
        *ngSwitchDefault
       class="w-5 h-5 bg-gray-200 rounded flex items-center justify-center text-xs"
       {{ item.name.split('.').pop().toUpperCase() }}
      </div>
     </ng-container>
    </div>
    <div class="flex-1 min-w-0">
     {{ item.name }}
    </div>
    <div class="text-sm text-gray-500 w-32">
     {{ item.stats.mtime | date }}
    </div>
    <div class="text-sm text-gray-500 w-24 text-right">
     {{ formatSize(item.stats.size) }}
    </div>
   </div>
  </div>
 </div>
```