




Expansion Rate




Generation Rate




Trading Rate




Accumulated Expansion




Accumulated Generation




Accumulated Trading




InventoryProduction(X_t)





Price(S_t)





Forward_Loss vs Batch







Inventory @ Delivery - P1



Inventory @ Delivery - P2




Terminal Y Values



- Target: $1 * \text{sigmoid}(X_{T_1} < 0.9)$
- Learnt: Y_{T_1}

- Target: $1 * \text{sigmoid}(X_{T_2} < 0.9)$
- Learnt: Y_{T_2}



Save The Models

```
In [ ]: print(f"{len(main_models1.loss)} steps\nStarted @ {start_time}\nSaved @ {end_time}")  ## to examine whether the loss attribute is updated in t
dir_path=pathlib.Path(os.getcwd(),
                      'Results',
                      'Best Models Saved',
                      'sigmoid_sig_0.001lr_0.03delta_500steps_MSE_1w') # 0.25, 0.5, 0.75  ## 0.01delta
dir_path.mkdir()
path1=pathlib.Path(dir_path,'pop1.pt')
path2=pathlib.Path(dir_path,'pop2.pt')
main_models1.save_entire_models(path=path1)
main_models2.save_entire_models(path=path2)
```

500 steps

Started @ September 16 - 10:36:45

Saved @ September 16 - 23:10:28

Load The Models

```
In [ ]: import numpy as np
import torch as torch
import torch.nn as nn
import torch.nn.functional as F
import torch.optim as optim
import seaborn as sns
import pandas as pd
import matplotlib.pyplot as plt
from datetime import datetime
import random
from scipy.stats import norm

import os
import pathlib

from Model import *
from utils import *

torch.autograd.set_detect_anomaly(True)
start_time=datetime.now().strftime('%B %d - %H:%M:%S')
```

```
In [ ]: #Global parameters
GlobalParams1=Params(param_type='k1',target_type='sigmoid',trick='clamp',loss_type='MSELoss',delta=0.03,w=1,lr=0.001)
dB1 = SampleBMIncr(GlobalParams=GlobalParams1)
init_x1 = Sample_Init(GlobalParams=GlobalParams1)
init_c1= torch.zeros_like(init_x1)

GlobalParams2=Params(param_type='k2',target_type='sigmoid',trick='clamp',loss_type='MSELoss',delta=0.03,w=1,lr=0.001)
dB2 = SampleBMIncr(GlobalParams=GlobalParams2)  ## TODO: same dB????
init_x2 = Sample_Init(GlobalParams=GlobalParams2)
init_c2= torch.zeros_like(init_x2)

NT1=GlobalParams1.NT1
NT2=GlobalParams1.NT2
dt=GlobalParams1.dt
device=GlobalParams1.device
learning_rate = GlobalParams1.lr

#Forward Loss
forward_losses = []

#How many batches
MaxBatch= 500

#How many optimization steps per batch
OptimSteps= 25

#Train on a single batch?
single_batch = True
```



```

#Set up main models for y0, yt1, and z (z will be list of models)
y0_model_main1 = Network(scaler_type='sigmoid')
yt1_model_main1 = Network(scaler_type='sigmoid')
zy_models_main1 = [Network() for i in range(NT2)]
main_models1=Main_Models(GlobalParams=GlobalParams1)
main_models1.create(y0_model=y0_model_main1,
                    yt1_model=yt1_model_main1,
                    zy_models=zy_models_main1,
                    forward_loss=forward_losses,
                    dB=dB1,
                    init_x=init_x1,
                    init_c=init_c1)

y0_model_main2 = Network(scaler_type='sigmoid')
yt1_model_main2 = Network(scaler_type='sigmoid')
zy_models_main2 = [Network() for i in range(NT2)]
main_models2=Main_Models(GlobalParams=GlobalParams2)
main_models2.create(y0_model=y0_model_main2,
                    yt1_model=yt1_model_main2,
                    zy_models=zy_models_main2,
                    forward_loss=forward_losses,
                    dB=dB2,
                    init_x=init_x2,
                    init_c=init_c2)

pop1_dict={'dB':dB1,
          'init_x':init_x1 ,
          'init_c':init_c1 ,
          'GlobalParams':GlobalParams1,
          'main_models':main_models1}

pop2_dict={'dB':dB2,
          'init_x':init_x2 ,
          'init_c':init_c2 ,
          'GlobalParams':GlobalParams2,
          'main_models':main_models2}

```

```

In [ ]: #Define optimization parameters
params=[]
params = list(main_models1.y0_model.parameters())+\
          list(main_models1.yt1_model.parameters())+\
          list(main_models2.y0_model.parameters())+\
          list(main_models2.yt1_model.parameters())

for i in range(NT2):
    params += list(main_models1.zy_models[i].parameters())
    params += list(main_models2.zy_models[i].parameters())

#Set up optimizer and scheduler
optimizer = optim.Adamax(params, lr=learning_rate)

```



```

scheduler = torch.optim.lr_scheduler.StepLR(optimizer, step_size=100, gamma=0.95)

for k in range(0,MaxBatch):

    print("Batch Number: ", k+1)
    sloss=0
    #optimize main network wrt the foward loss
    for l in range(0,OptimSteps):
        optimizer.zero_grad()
        loss = get_foward_loss(pop1_dict=pop1_dict, pop2_dict=pop2_dict)
        loss.backward()
        # torch.nn.utils.clip_grad_norm_(parameters=params,max_norm=0.7)
        optimizer.step()
        scheduler.step()
        nloss = loss.detach().numpy()
        sloss += nloss
        # print('OptimStep: ' + str(l+1))
        # print('forward_loss: ' + str(nloss))
    avgloss = sloss/OptimSteps
    print("Average Error Est: ", avgloss)
    forward_losses.append(avgloss)

    #Generate a new batch if using multiple batches
    if(not single_batch):

        dB1 = SampleBMIncr(GlobalParams=GlobalParams1)
        init_x1 = Sample_Init(GlobalParams=GlobalParams1)
        init_c1= torch.zeros_like(init_x1)
        pop1_dict={'dB':dB1,
                  'init_x':init_x1 ,
                  'init_c':init_c1 ,
                  'GlobalParams':GlobalParams1,
                  'main_models':main_models1}

        dB2 = SampleBMIncr(GlobalParams=GlobalParams2)  ## TODO: same dB?????
        init_x2 = Sample_Init(GlobalParams=GlobalParams2)
        init_c2= torch.zeros_like(init_x2)
        pop2_dict ={'dB':dB2,
                   'init_x':init_x2 ,
                   'init_c':init_c2 ,
                   'GlobalParams':GlobalParams2,
                   'main_models':main_models2}
end_time=datetime.now().strftime('%B %d - %H:%M:%S')

```