

Lab10 SQL Injection

https://seedsecuritylabs.org/Labs_20.04/Web/Web_SQL_Injection/

```
Terminal
izzatalsmadi@VM:~$ cd Downloads/Quiz5
izzatalsmadi@VM:~/Downloads/Quiz5$ ls
Labsetup
izzatalsmadi@VM:~/Downloads/Quiz5$ cd Labsetup/
izzatalsmadi@VM:~/Downloads/Quiz5/Labsetup$ ls
docker-compose.yml image_mysql image_www
izzatalsmadi@VM:~/Downloads/Quiz5/Labsetup$ sudo docker-compose build
```

- You have two containers in two folders, you need to build and up each one separate


The screenshot shows a terminal window with the following output:

```
----> Using cache
----> f3d8f2a7946e
Step 5/5 : RUN a2ensite apache_sql_injection.conf
----> Using cache
----> def53ca1054a
Successfully built def53ca1054a
Successfully tagged seed-image-www-sqli:latest
Building mysql
Step 1/7 : FROM mysql:8.0.22
8.0.22: Pulling from library/mysql
a076a628af6f: Pull complete
f6c208f3f991: Pull complete
88a9455a9165: Pull complete
406c9b8427c6: Pull complete
7c88599c0b25: Pull complete
25b5c6debda5: Pull complete
43a5816f1617: Pull complete
69dd1fbf9190: Pull complete
5346a60dcee8: Extracting [=====>
18.94MB/112.8MB Download complete
fd04d935b852: Download complete
050c49742ea2: Download complete
1208/1208
```

Below the terminal window, there is a section titled "3 Lab Tasks" with a list of instructions.

3 Lab Tasks

- If both containers build properly you should see this up in your Browser
Check etc/hosts



A terminal window with a dark purple background and white text. The window title is "Terminal". It contains a list of IP addresses and domain names for various security labs. The text is as follows:

```
# For DNS Rebinding Lab
192.168.60.80    www.seedIoT32.com

# For SQL Injection Lab
10.9.0.5        www.SeedLabSQLInjection.com

# For XSS Lab
10.9.0.5        www.xsslabelgg.com
10.9.0.5        www.example32a.com
10.9.0.5        www.example32b.com
10.9.0.5        www.example32c.com
10.9.0.5        www.example60.com
10.9.0.5        www.example70.com

# For CSRF Lab
10.9.0.5        www.csrflabelgg.com
10.9.0.5        www.csrfiab-defense.com
10.9.0.105      www.csrfiab-attacker.com

# For Shellshock Lab
10.9.0.80       www.seedlab-shellshock.com

izzatalsmadi@VM:~/Downloads/Quiz5/Labsetup/image_mysql$
```


- I have to reinstall Apache and copy code folder (rename it SQL_Injection) to /var/www/html

```

izzatalsmadi@VM:/var/www$ ls
html SQL_Injection
izzatalsmadi@VM:/var/www$ cd SQL_Injection/
izzatalsmadi@VM:/var/www/SQL_Injection$ ls
css      index.html  seed_logo.png      unsafe_edit_frontend.php
defense  logoff.php  unsafe_edit_backend.php  unsafe_home.php
izzatalsmadi@VM:/var/www/SQL_Injection$ cd ..
izzatalsmadi@VM:/var/www$ sudo nano /etc/apache2/sites-available/000-default.conf
f
izzatalsmadi@VM:/var/www$ sudo /etc/init.d/apache2 restart
Restarting apache2 (via systemctl): apache2.service.
izzatalsmadi@VM:/var/www$ sudo nano /etc/apache2/sites-available/000-default.conf
f
izzatalsmadi@VM:/var/www$ sudo /etc/init.d/apache2 restart
Restarting apache2 (via systemctl): apache2.service.
izzatalsmadi@VM:/var/www$ sudo nano /etc/apache2/sites-available/
000-default.conf default-ssl.conf
izzatalsmadi@VM:/var/www$ sudo nano /etc/apache2/sites-available/default-ssl.conf
f
izzatalsmadi@VM:/var/www$ ls
html SQL_Injection
izzatalsmadi@VM:/var/www$ sudo nano /etc/apache2/sites-available/html/

```

- Now if I type in the Browser localhost, I can see the web app



To help you started with thi stask, we explain how authentication is implemented in the web application. The PHP code unsafe home.php, located in the /var/www/SQL_Injection directory, isused to conduct user authentication. The following code snippet show how users are authenticated.

```

$input_uname = $_GET['username'];
$input_pwd = $_GET['Password'];
$hashed_pwd = sha1($input_pwd);
...
$sql = "SELECT id, name, eid, salary, birth, ssn, address, email,
        nickname, Password
        FROM credential
        WHERE name= '$input_uname' and Password='$hashed_pwd'";
$result = $conn -> query($sql);

```


```

// The following is Pseudo Code
if(id != NULL) {
    if(name=='admin') {
        return All employees information;
    } else if (name !=NULL){
        return employee information;
    }
} else {
    Authentication Fails;
}

```

Task 2.1: SQL Injection Attack from webpage. Your task is to log into the web application as the administrator from the login page, so you can see the information of all the employees. We assume that you do know the administrator's account name which is `admin`, but you do not the password. You need to decide what to type in the `Username` and `Password` fields to succeed in the attack.

- I first tried (`admin and 1=1'`) but didn't work



```

SEED Labs connect_error { echo "
"; echo "

echo "

"; die("Connection failed: " . $conn->connect_error . "\n"); echo "
} return $conn; } // create a connection $conn = getDB(); // Sql query to authenticate the user $sql = "SELECT
, name, eid, salary, birth, ssn, phoneNumber, address, email,nickname,Password FROM credential WHERE
ame= '$input_uname' and Password='$hashed_pwd'"; if (!$result = $conn->query($sql)) { echo ""; echo ""; echo

"; die('There was an error running the query [' . $conn->error . ']\n'); echo "
} /* convert the select return result into array type */ $return_arr = array(); while($row =
result->fetch_assoc()){ array_push($return_arr,$row); } /* convert the array type to json format and read out*/
son_str = json_encode($return_arr); $json_a = json_decode($json_str,true); $id = $json_a[0]['id']; $name =
son_a[0]['name']; $eid = $json_a[0]['eid']; $salary = $json_a[0]['salary']; $birth = $json_a[0]['birth']; $ssn =
son_a[0]['ssn']; $phoneNumber = $json_a[0]['phoneNumber']; $address = $json_a[0]['address']; $email =
son_a[0]['email']; $pwd = $json_a[0]['Password']; $nickname = $json_a[0]['nickname']; if($id!=""){ // If id exists
at means user exists and is successfully authenticated
rawLayout($id,$name,$eid,$salary,$birth,$ssn,$pwd,$nickname,$email,$address,$phoneNumber); }else{ // User
uthentication failed echo ""; echo ""; echo "

```

- Login to mysql container

```

Processing triggers for libc-bin (2.34-1) ...
lzzatalsnadi@VM:~/Downloads/Quiz5/Labsetup/image_www$ mysql -u root -pseedubuntu
mysql: [Warning] Using a password on the command line interface can be insecure.
ERROR 2002 (HY000): Can't connect to local MySQL server through socket '/var/run/mysqld/mysqld.sock' (2)
lzzatalsnadi@VM:~/Downloads/Quiz5/Labsetup/image_www$ sudo docker ps
CONTAINER ID   IMAGE                                COMMAND                  CREATED        STATUS        PORTS
NAMES
cc036fabde0e   seed-image-www-sqli               "/bin/sh -c 'service..." 13 hours ago   Up 20 minutes
www-10.9.0.5
edbe360c30df   seed-image-mysql-sqli            "docker-entrypoint.s..." 13 hours ago   Up 25 minutes   3306/tcp, 33060/t
mysql-10.9.0.6
lzzatalsnadi@VM:~/Downloads/Quiz5/Labsetup/image_www$ sudo docker exec -it seed-image-mysql-sqli bash
Error: No such container: seed-image-mysql-sqli
lzzatalsnadi@VM:~/Downloads/Quiz5/Labsetup/image_www$ sudo docker exec -it mysql-10.9.0.6 bash
root@edbe360c30df:/#

```

```

bash: mysql-u: command not found
root@edbe360c30df:/# mysql -u root -pdees
mysql: [Warning] Using a password on the command line interface can be insecure.
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 8
Server version: 8.0.22 MySQL Community Server - GPL

Copyright (c) 2000, 2020, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>

```

```

root@edbe360c30df:/# mysql -u root -pdees
mysql: [Warning] Using a password on the command line interface can be insecure.
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 8
Server version: 8.0.22 MySQL Community Server - GPL

Copyright (c) 2000, 2020, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> usesqlab_users;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL s
right syntax to use near 'usesqlab_users' at line 1
mysql> use sqlab_users;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show tables;
+-----+
| Tables_in_sqlab_users |
+-----+
| credential             |
+-----+
1 row in set (0.00 sec)

mysql>

```