

Compact CVPR table layout — execution-package preview

All result cells are placeholders. This is not a benchmark report. The three tables share result identities; additional metrics and logs belong in the supplement.

Table 1: Complete-system results. The upper block is attributed context from OVI-MAP Table 3, not rerun here; exact external prediction protocols are not independently verified. The lower block is our paired reproduction. AP denotes the loaded released APall definition.

Method	Replica-8			ScanNet-CF18		
	AP↑	AP50↑	mIoU↑	AP↑	AP50↑	mIoU↑
<i>Reported in OVI-MAP (source values; not our measurements)</i>						
Mask3D + OpenMask3D	—	—	—	—	—	—
Segment3D + OpenMask3D	—	—	—	—	—	—
OVO-SLAM	—	—	—	—	—	—
<i>Paired evaluation under our fixed released-code protocol</i>						
OVI-MAP (reproduced, A0)	—	—	—	—	—	—
Ours: refinement only (A1)	—	—	—	—	—	—
Ours: refinement + recovery (A3)	—	—	—	—	—	—

Table 2: Controlled ablations on the same geometry. E is fixed D2 refinement; R is independent single-view FC recovery. A0–A3 form the $E \times R$ design. A4 uses the same G1 view with native recognition. A5 uses the same incumbent FC evidence, with unknown output where unavailable; it has no native fallback.

Configuration	Existing	Recovery	Replica-8			ScanNet-CF18		
			AP	AP50	mIoU	AP	AP50	mIoU
A0: native	Native	None	—	—	—	—	—	—
A1: E only	D2	None	—	—	—	—	—	—
A2: R only	Native	G1-FC	—	—	—	—	—	—
A3: E + R	D2	G1-FC	—	—	—	—	—	—
A4: native recovery	D2	G1-Native	—	—	—	—	—	—
A5: FC-only	FC	G1-FC	—	—	—	—	—	—

Table 3: Recovery on Replica-8. n/N is recovered owners over the same prelocked candidate pool, not true positives. TP/FP are added released-matcher score entries at IoU .50. Time is feature-cache-cold incremental recovery with the model resident, averaged over all eight scenes; model loading, mapping and evaluation are separate.

Entry	Max views	n/N	TP50	FP50	AP	mIoU	Time (s)
None (A1)	0	0/ N	0	0	—	—	0
Archived U2	1	—	—	—	—	—	—
Independent G1 (A3)	1	—	—	—	—	—	—
Independent G3	3	—	—	—	—	—	—