

## 4 Liquid types for Elm

### 4.1 Formal definition of Elm

#### 4.1.1 Syntax

Elm differentiates variables depending on the capitalization of the first letter. For the formal language we define  $\langle \text{upper-var} \rangle \in \mathcal{T}$  for variables with the first letter capitalized and  $\langle \text{lower-var} \rangle \in \mathcal{T}$  for variables without.

Syntactically we can build our types from booleans, integers, lists, tuples, records, functions, custom types and type variables.

We will define our syntax in a Backus-Naur-Form [Bac59].

##### Definition 4.1: Type Signiture Syntax

We define the following types:

```

<upper-var> ∈  $\mathcal{T}$ 
<lower-var> ∈  $\mathcal{T}$ 
<list-lower-var> ::= " | <lower-var> <list-lower-var>
<list-type-fields> ::= "
    | <lower-var> ":" <type> "," <list-type-fields>
<list-type> ::= " | <type> <list-type>
<type> ::= "Bool"
    | "Int"
    | "List" <type>
    | "(" <type> "," <type> ")"
    | "{" <list-type-fields> "}"
    | <type> "->" <type>
    | <upper-var> <list-type>
    | <lower-var>
```

For matching expressions we allow various pattern.

##### Definition 4.2: Pattern Syntax

We define the following types:

```

<list-pattern-list> ::= " | <pattern> "," <list-pattern-list>
<list-pattern-sort> ::= " | <pattern> <list-pattern-sort>
```

```

<list-pattern-vars> ::= "" | <lower-var> ", " <list-pattern-vars>

<pattern> ::= <bool>
           | <int>
           | "[" <list-pattern-list> "]"
           | "(" <pattern> , <pattern> ")"
           | <upper-var> <list-pattern-sort>
           | <lower-var>
           | <pattern> "as" <lower-var>
           | "{" <list-pattern-vars> "}"
           | <pattern> "::" <pattern>
           | "_"

```

Because Elm is a pure functional programming language, a program contains just a single expression.

#### Definition 4.3: Expression Syntax

We define the following types:

```

<list-exp-field> ::= <lower-var> "=" <exp>
                 | <lower-var> "=" <exp> ", " <list-exp-field>

<maybe-signature> ::= "" | <lower-var> ":" <type> ";"

<list-case> ::= <pattern> "->" <exp>
              | <pattern> "->" <exp> ";" <list-case>

<bool> ::= "True" | "False"

<int> ::= "0" | "-1" | "1" | "-2" | "2" | ...

<list-exp> ::= "" | <exp> ", " <list-exp>

```

The definition of <exp> can be found in figure 1.

Additionally, Elm also allows global constants, type aliases and custom types.

#### Definition 4.4: Statement Syntax

We define the following types:

```

<list-sort> ::= <upper-var> <list-type>
              | <upper-var> <list-type> | <list-sort>

<list-statement> ::= "" | <statement> ";" <list-statement>

```

```

<exp> ::= "foldl"
        | "(::)"
        | "(+)" | "(-)" | "(*)" | "(//)"
        | "<" | "(==)"
        | "not" | "&&" | "(||)"
        | <exp> ">" <exp>
        | <exp> ">>" <exp>
        | "if" <exp> "then" <exp> "else" <exp>
        | "{" <list-exp-field> "}"
        | "{}"
        | "{" <lower-var> "|" <list-exp-field> "}"
        | <lower-var> "." <lower-var>
        | "let" <maybe-signature> <lower-var> "=" <exp> "in" <exp>
        | "case" <exp> "of" "[" <list-case> "]"
        | <exp> <exp>
        | <bool>
        | <int>
        | "[" <list-exp> "]"
        | "(" <exp> "," <exp> ")"
        | "\" <pattern> "->" <exp>
        | <upper-var>
        | <lower-var>

```

Figure 1: Syntax for Expressions

```

<statement> ::= <maybe-signature> <lower-var> "=" <exp>
              | "type" "alias" <upper-var> <list-lower-var>
              "=" <type>
              | "type" <upper-var> <list-lower-var>
              "=" <upper-var> <list-sort>

<maybe-main-sign> ::= ""|"main" ":" <type> ";"

<program> ::= <list-statement> <maybe-main-sign> "main" "=" <exp>

```

### Example 4.1

Using this syntax we can now write a function that reverses a list.

```

reverse : List a -> List a
reverse =
  foldl
    (::)
    [];

main : Int
main =
  case [1,2,3] |> reverse of
  [
    a :: _ ->
    a;
    - ->
    -1
  ]

```

`foldl` iterates over the list from left to right. It takes the function `(::)`, that appends an element to a list, and the empty list as the starting list. The `main` function reverses the list and returns the first element: 3. Elm requires you also provide return values for other cases that may occur, like the empty list. In that case we just return `-1`. This will never happen, as long as the reverse function is correctly implemented.

## References

- [Bac59] John W. Backus. "The syntax and semantics of the proposed international algebraic language of the Zurich ACM-GAMM Conference". In: *IFIP Congress*. 1959, pp. 125–131.