

THE INTELLIGENT AGENT

Fundamentals of Artificial Intelligence



UMEÅ UNIVERSITY

THE INTELLIGENT AGENT



**Fundamentals of
Artificial Intelligence**



UMEÅ UNIVERSITY

THE INTELLIGENT AGENT



**Fundamentals of
Artificial Intelligence**



UMEÅ UNIVERSITY

LECTURE PLAN

1. What are agents?
2. What are intelligent agents?
3. Types of task environment
BREAK
4. Types of agents
5. Representing the world

PLEASE GO TO: www.menti.com CODE:13 94 26 9



UMEÅ UNIVERSITY

1. WHAT ARE AGENTS?



UMEÅ UNIVERSITY

AGENTS & ENVIRONMENT


environment



UMEÅ UNIVERSITY

AGENTS & ENVIRONMENT


environment



UMEÅ UNIVERSITY

AGENTS & ENVIRONMENT


environment



UMEÅ UNIVERSITY

AGENTS & ENVIRONMENT


environment



UMEÅ UNIVERSITY

AGENTS & ENVIRONMENT

environment



UMEÅ UNIVERSITY


**CAN YOU THINK OF SOME
AGENTS?**



UMEÅ UNIVERSITY

AGENTS & ENVIRONMENT


environment



UMEÅ UNIVERSITY

AGENTS & ENVIRONMENT

environment



UMEÅ UNIVERSITY

HOW CAN WE REPRESENT AGENTS?

- Ideally, an intelligent agent's actions depend on **what it has perceived**.

Anything it has ever perceived=**percept sequence**

What it is perceiving at a **specific instant**=**percept**

- So, if we know which action the agent will take for **any possible percept sequence**, we know **everything** about the agent.




THROUGH A FUNCTION

We can **describe** the agent with an **agent function**:

$$u = f(y)$$

action

percept sequence



This is an **external** representation: it does not tell us *how* the agent computes the actions internally.



THROUGH THEIR PROGRAM

In an artificial agent, these actions are **implemented** through an **agent program** that is running.

Function *Agent*(location, status) **Returns** action {

 process inputs;

 update the internal representation;

 construct a plan;

return action;

}

The agent function **describes** the agent, and the agent program is an **implementation** of the agent.



2. WHAT ARE *INTELLIGENT* AGENTS?



AI TIP: TO DEVELOP A COMPUTER WITH
THE INTELLIGENCE OF A SIX-YEAR-OLD
CHILD, START WITH ONE AS SMART AS
AN ADULT AND LET ME TEACH IT STUFF.



RATIONAL AGENTS

Always doing the right thing.

?



UMEÅ UNIVERSITY

RATIONAL AGENTS


Always doing the right thing.
?

environment → percepts → actions → changes in the environment




RATIONAL AGENTS

Doing the right thing.
?



RATIONAL AGENTS

Doing the right thing.
?



To know what the right action at the right time is, we check if we **change the environment** in the way that we want it to change.



PERFORMANCE MEASURE & RATIONALITY

A performance measure **evaluates any given sequence of environment states.**

A performance measure is a **choice by the designer!**

A rational agent is an agent that, for each possible percept selects an action that is expected to maximize its performance measure.



PERFORMANCE MEASURE

There isn't one fixed performance measure for all tasks, agents and environments.

Let's imagine we are designing an autonomous vacuum cleaner.

POLL: WHAT COULD BE A GOOD PERFORMANCE MEASURE THAT THE AGENT NEEDS TO MAXIMISE?



UMEÅ UNIVERSITY

PERFORMANCE MEASURE

There isn't one fixed performance measure for all tasks, agents and environments.

Let's imagine we are designing an autonomous vacuum cleaner.

POLL: WHAT COULD BE A GOOD PERFORMANCE MEASURE THAT THE AGENT NEEDS TO MAXIMISE?

As a piece of advice, R&N say: As a general rule, it is better to design performance measures according to what one actually wants in the environment, rather than according to how one thinks the agent should behave.




PERFORMANCE MEASURE

- For the same performance measure, different strategies can be equally effective.
- **Ex: Vacuum at low power all day, versus full power for 5 mins every hour, or at the end of the day.**
- With respect to the amount of clean square meters performance measure, both these strategies are equally good.
- We can of course add elements to our measure to distinguish strategies that we prefer, like electricity consumption.



PERFORMANCE MEASURE



Source and rest of the story: <https://www.smbc-comics.com/comic/paperclip>

Based on the paperclip maximiser *thought experiment* by Nick Bostrom:

https://en.wikipedia.org/wiki/Instrumental_convergence



UMEÅ UNIVERSITY

RATIONAL AGENTS

Doing the right thing.

A **rational agent** is an agent that, for each possible percept selects an action that is expected to maximize its performance measure, given the evidence provided by the percept sequence and whatever built-in knowledge the agent has.



RATIONAL AGENTS

Doing the right thing.

A rational agent is an agent that, for each possible percept, selects an **action** that is expected to maximize its **performance measure**, given the evidence provided by the **percept sequence** and whatever **built-in knowledge** the agent has.



RATIONAL AGENTS

Doing the right thing.

A rational agent is an agent that, for each possible percept, selects an **action** that is expected to maximize its **performance measure**, given the evidence provided by the **percept sequence** and whatever **built-in knowledge** the agent has.

The **rationality** of an agent depends on:

1. Possible actions
2. Performance measure
3. Percept sequence
4. Built-in knowledge




RATIONAL AGENTS

IS THE AGENT GIVEN BY THE PROGRAM BELOW
RATIONAL?



The agent
doesn't know
in which
square it will
be placed or
where the dirt
is.

A	B
	

Percept	Action
A, Clean	Move Right
A, Dirty	Clean
B, Clean	Move Left
B, Dirty	Clean

Performance measure: Number of clean squares

Knowledge: Clean squares stay clean.




UMEÅ UNIVERSITY

RATIONAL AGENTS

IS THE AGENT GIVEN BY THE PROGRAM BELOW
RATIONAL?



The agent
doesn't know
which square it
will be placed
in and where
the dirt is.

A	B
	

Percept	Action
A, Clean	Move Right
A, Dirty	Clean
B, Clean	Move Left
B, Dirty	Clean

Performance measure: Number of clean squares

Knowledge: A is never dirty.



UMEÅ UNIVERSITY


RATIONALITY IS NOT OMNISCIENCE

- Rationality depends on the **agent's knowledge**.
- **In most environments, it is impossible to know everything!**
- Rationality is about maximising **expected** performance.

Gathering information and **learning** are part of rationality: they change the agents knowledge and can maximise expected performance by adjusting the expectations to reality.



3. TYPES OF TASK ENVIRONMENTS



UMEÅ UNIVERSITY

AGENTS AND THEIR ENVIRONMENT

- The environment in which an agent **acts** affects how we should design it.
- There are a number of concepts that we have defined today that are related to the environment:
 - An agent perceives the environment through **sensors**, and acts on it through **actuators**.
 - The changes in the environment are evaluated with a **performance measure**.
- We call this collection the **task environment**, and it can be described by

PEAS (**P**erformance, **E**nvironment, **A**ctuators, **S**ensors)



UMEÅ UNIVERSITY

TYPES OF TASK ENVIRONMENT

Task environments are hugely varied (since they depend on the deployment context and the agent itself).

Still, we can look at some **properties**:

1. Partly vs. fully observable
2. Static vs. dynamic
3. Discrete vs. continuous
4. Episodic vs. sequential
5. Deterministic vs. stochastic
6. Single vs. multi agent
7. Known vs. unknown



FULLY VS PARTIALLY OBSERVABLE

- A task environment is fully observable if the agents' sensors detect all aspects that are **relevant** to the choice of action.
 - Depends on the **sensors**, the **environment** and the **performance measure** (what is *relevant*?).
 - *Eg. A thermostat.*



- Otherwise, it is **partially observable**.
 - *Eg. An autonomous vehicle (cannot see objects behind a corner).*



- If there are no sensors, the task environment is **unobservable**.



KNOWN VS UNKNOWN

- This is a property of **the agent**, rather than of the environment.
- In a **known** environment, the *laws* of the environment are part of the knowledge of the agent.
 - The outcomes or outcome probabilities (*how an action will modify the environment*) are known.
 - This doesn't mean the environment is fully observable (*card game*).
- In an **unknown environment**, the agent does not know the outcome of its actions.
 - *Eg. A game for which the agent does not know the rules.*



STATIC VS DYNAMIC

- If the environment can change while the agent is deliberating (deciding on an action), it is **dynamic**.
 - *Eg. A cooking robot, where the food can burn while deciding whether to switch off the heat or not.*



Source:
<https://www.nytimes.com/2010/02/24/dining/24robots.html>

- If the world does not change, but the performance score does, the environment is **semidynamic**.
 - *Eg. When the performance measure depends on the time it takes to complete an action.*
- If the agent can take a percept and produce a response without considering the time it takes to produce that response, the environment is **static**.
 - *Eg. A sudoku-solving agent.*



DISCRETE VS CONTINUOUS

- **Discrete** environments can be divided into a finite number of distinct states.
 - *E.g. A sudoku grid has a finite number of possible states; the vacuum cleaning example from before where the states could be summarized in a table.*
- **Continuous** environments cannot be divided into separate states.
 - The environment may change continuously (*weather conditions*), the agent may be receiving percepts continuously (*infrared sensor*) and/or acting in a continuous manner (*driving*).
- Many environments that are actually continuous are treated as discrete, and viceversa.
 - *E.g. The physical chess board, where time passes continuously.*
 - *Eg. Input from digital cameras is discrete but can be modeled as a continuous smooth input.*



EPISODIC VS SEQUENTIAL

- An **episodic** task environment is composed of **atomic** (individual) **episodes**.
 - In each **episode**, the agent receives a percept and performs an action in response.
 - What happens in an episode does not affect the next ones.
 - Each episode could be discrete or continuous.
 - *Eg. An agent looking for defective parts in manufacturing.*
- In a **sequential** environment, a decision can affect future decisions.
 - The agent may still ignore previous states in its decision (reactive agent).
 - Can be both continuous (*driving*) and discrete time (*chess*).



DETERMINISTIC VS STOCHASTIC

- An environment where the next state can be completely determined based on the previous state and the agent's action, is **deterministic**.

- *Eg. A sudoku-solving agent, the vacuum robot from previous example (because clean squares remained clean).*



- If an environment is not deterministic, it's *stochastic*.
 - Stochastic environments can't be perfectly predicted, but can still be modeled using models that include uncertainty
 - Note that stochastic is not the same as random, a stochastic process depends both on the previous state and a random element
 - *Eg. An autonomous vehicle (pedestrians modify the environment unpredictably).*



SINGLE VS MULTI AGENT

- In a **single agent** environment, there is a single agent. In a **multi-agent** environment, there are several agents. **But... what counts as another agent in the environment?**
- If the other entity has a performance measure that **depends on the actions of the first agent**, we are in a multi-agent environment.
 - *Eg. A card game, a fleet of cleaning robots.*
 - **cooperative** (actions can increase all agents' performance), **competitive** (all performances cannot be increased at the same time), or a combination of both.
- Designing multi-agent systems is a whole field by itself.
 - Communication between agents, organizational structures, decision-making processes...
 - Designing a single agent that will operate in a multi-agent environment is also a different challenge: will it need to communicate? Predict other agents' actions?



IN SUMMARY

- The task environment is not a description of the environment for a robot, it is **a way to describe the task, or problem, to be solved.**


POLL: What are the characteristics of the following task environment?

A football playing robot.

- Performance measure: Winning with its team.
- Environment: A football field, playing with other robots.
- Acting: Can move and shoot the ball.
- Sensing: Can see the ball, the lines on the field, the other robots, and the goalposts.



IN SUMMARY



BREAK



UMEÅ UNIVERSITY

4. TYPES OF AGENTS

TWO TYPES OF PEOPLE



RIGHT PEOPLE AND WRONG PEOPLE



UMEÅ UNIVERSITY

AGENT TYPES

1. Simple vs Model-based
2. Reactive
3. Goal based
4. Utility based
5. Learning agents

This classification showcases different ways to design and implement intelligent agents.



AGENT TYPES

- At the beginning of the lecture, we described a vacuum agent with a **table** that contains every possible state of the world, and the corresponding action from the agent.
- This is not possible to do in most cases! The table would be huge.
 - No way to store it.
 - A long time to look it up.
 - A long time to complete it by the designer.
 - A complete knowledge of the state space is needed.
- Effective agent programs also account for **complexity and efficiency**, i.e. they are meant to produce rational agents from a small program.



SIMPLE & MODEL-BASED AGENTS

- **Simple** agents do not store an internal representation of the state of the world. They react exclusively to the percepts.
 - Great for fully observable scenarios.
 - Eg. thermostat
- **Model-based** agents keep an internal representation of the state of the world, and use it together with the percept to determine the correct action.
- To determine (“best guess”) the state of the world, they are endowed with a **model**: information of how the environment evolves around the agent+information of how the agents’ actions modify the world.
 - Great for known, partially observable environments.



REACTIVE AGENTS

- **Reactive** agents select actions on the basis of the *current* percept, ignoring the rest of the percept history.
 - *Eg. The vacuum robot from earlier. Just needs to know if its current square is clean or dirty in order to choose its action.*
 - They do not need memory.
 - Can be described by if-then rules, but in practice there are more sophisticated implementations.
- Pros: Simple, transparent, effective in dynamic, known environments.



GOAL-BASED AGENTS

- **Goal-based** agents choose their action in order to **achieve a specific goal**.



- Pros: Adaptation to the environment, no need to anticipate all the scenarios, good for dynamic environments.



GOAL-BASED AGENTS

- When a goal needs a sequence of actions to be achieved in a dynamic environment, it is necessary to deal with hypothetical scenarios: *what will happen if I do this-then-that?*
 - Often, this means that the agent **models** both the environment and the goal.
 - There are also other techniques where the environment is not modeled, only how to act in order to achieve a specific goal.
- Choosing a goal that will maximise the performance measure is also sometimes part of the problem.
- The research areas related to choosing the right actions to execute a goal are those of **search** and **planning**.



UTILITY-BASED AGENTS

- Sometimes, **we cannot capture with a single goal** all of the behaviours we want from the agent.
 - For an autonomous vehicle we may want to balance safety, speed to reach destination, electricity consumption, passenger satisfaction...
- **Utility-based** agents choose the action or sequence of actions that are expected to maximise a **utility function**.
- **Utility functions** assign a numerical value to each state of the environment, so that a state the satisfies more preferences has a higher value.



UTILITY-BASED AGENTS

- Building a utility function can be hard!
 - Can account for different weights between all the factors (more important to not hit pedestrians than to drive fast), but we have to understand what is the right balance.
 - Describing preferences in a way that a variable/number can be assigned is difficult.
 - The agent needs to have a good model of the environment to predict the expected utility of its actions.
- **Pros:** can capture complex drives, good for unknown environments.




PERFORMANCE MEASURE, UTILITY AND GOALS


- Notice that both the performance measure and the utility function describe what are good **changes in the environment**.
 - The performance measure is an **external evaluation** of the agent, whereas the utility function is an **internal representation** in the agent.
 - If the utility function is the same as the performance measure, then a utility-based agent will be rational by definition.
- For agents to be rational, the choice of actions, goals or utility function need to be **aligned with the performance measure**.




LEARNING AGENTS



LEARNING AGENTS



LEARNING AGENTS



**WHAT TYPE OF AGENT DO YOU
THINK OF WHEN YOU THINK ABOUT
AI?**



UMEÅ UNIVERSITY

LEARNING AGENTS

- There are many types of learning agents, but not all of AI is about learning agents.
 - The critic component has to be aligned with the performance measure, which can be hard to implement.
 - Pros: Great for unknown environments, and for task environments with very big state space.
- Agents purely based on reasoning or planning with a full model of the world are also part of AI.




5. REPRESENTING THE WORLD



UMEÅ UNIVERSITY

Credit: Disney


ATOMIC REPRESENTATIONS



- Each state is a **discrete single entity**, we know when it is possible to transition between two states.
- There are **no sub-entities** describing each state, it is just a point in a graph.



FACTORED REPRESENTATION



- States are described by a fixed set of **variables** or **attributes**, each of which can have a **value**.
- Easier to see how to transition from one state to another (i.e. which attributes need to be changed in order to reach the new state).
- We can represent uncertainty by leaving an attribute blank.



STRUCTURED REPRESENTATION

State where my dog is waiting behind the door for me to arrive, and he has eaten the cooked chicken that I prepared for dinner.



State where I am back home and hungry, but my dog is happy.

- Each state can be described in a model, where we can represent **objects and relationships between them** (e.g like with natural language, or with first order logic).
- This representation is more detailed than assigning values to attributes. We do not need to describe every state with the same attributes, only with the same language.



REPRESENTATIONS

- We say that a representation in which we can capture more details is more **expressive**.
- A more expressive representation can capture everything a less expressive representation can, and add more details.



Thank you!



UMEÅ UNIVERSITY