Solr lab for sharding experiments

Roxana Angheluta (Xenit Solutions)
Axel Faust (Acosix GmbH)

Motivation and solution

- Large archives with >50mil documents
- No sites

- Particular use case: most of the queries are targeted to a specific client id
- Search speed <3s

Implement a new sharding method: by property (now existing in Alfresco 5.2) with targeted queries

Create a "solr lab": define relevant parameters, design relevant experiments, execute them and draw conclusions

Motivation and solution

- Large archives with >50mil documents
- No sites

- Particular use case: most of the queries are targeted to a specific client id
- Search speed <3s

Implement a new sharding method: by property (now existing in Alfresco 5.2) with targeted queries

Create a "solr lab": define relevant parameters, design relevant experiments, execute them and draw conclusions

Motivation and solution


- Large archives with >50mil documents
- No sites

- Particular use case: most of the queries are targeted to a specific client id
- Search speed <3s


Implement a new sharding method: by property (now existing in Alfresco 5.2) with targeted queries

Create a "solr lab": define relevant parameters, design relevant experiments, execute them and draw conclusions

Sharding by property - Solr side




Sharding by property - Alfresco side



- Requirements
 - Easy to start
 - Easy to replicate
 - Easy to change parameters
 - Easy to resume
 - Easy to monitor








- Requirements
 - Easy to start
 - Easy to replicate
 - Easy to change parameters
 - Easy to resume
 - Easy to monitor







core1:

image: image: hub.xenit.eu/alfresco-ethias-sharded-by-property:build-3 volumes:

- alfresco10milnoacls:/opt/alfresco/alf_data environment:
- SOLR_HOST=solr1
- SOLR_PORT=8081
- ALFRESCO_HOST=core1
- ALFRESCO PORT=8080
- JAVA XMS=6144M
- JAVA XMX=6144M
- ENABLE CLUSTERING=true
- DYNAMIC SHARD REGISTRATION=true
- DEBUG=false
- JMX ENABLED=true
- JMX RMI HOST=xxx.xxx.xxx.xxx
- GLOBAL_shardedProperty.qname={http://www.ethias.be/model/content}shardingKey
- GLOBAL_cache.node.nodesSharedCache.maxItems=1250000

solr1:

image: hub.xenit.eu/solr-sharded-by-property:5.1 volumes:

- solr10milnoacls1index:/opt/alfresco/alf_data environment:
 - ALFRESCO HOST=core1
 - ALFRESCO PORT=8080
 - SOLR HOST=solr1
 - SOLR PORT=8081
 - JAVA_XMS=7168M
 - JAVA XMX=7168M
 - SHARDING=true
 - NUM_SHARDS=3
 - NUM NODES=3
 - NODE INSTANCE=1
 - TEMPLATE=rerank
 - SHARD IDS=0
 - ALFRESCO SSL=none
 - ARCHIVE ENABLE ALFRESCO TRACKING=false
 - ARCHIVE INDEX CONTENT=false
 - ALFRESCO INDEX CONTENT=false
 - MAX_HTTP_HEADER_SIZE=65536
 - JMX ENABLED=true
 - JMX_RMI_HOST=xxx.xxx.xxx.xxx

core1:

image: image: hub.xenit.eu/alfresco-ethias-sharded-by-property:build-3 volumes:

 alfresco10milnoacls:/opt/alfresco/alf_data environment;

.....

- SOLR HOST=solr1
- SOLR_PORT=8081
- ALFRESCO HOST=core1
- ALFRESCO PORT=8080
- JAVA XMS=6144M
- JAVA XMX=6144M
- ENABLE CLUSTERING=true
- DYNAMIC_SHARD_REGISTRATION=true
- DEBUG=false
- JMX ENABLED=true
- JMX RMI HOST=xxx.xxx.xxx.xxx
- GLOBAL_shardedProperty.qname={http://www.ethias.be/model/content}shardingKey
- GLOBAL cache.node.nodesSharedCache.maxItems=1250000

solr1:

image: hub.xenit.eu/solr-sharded-by-property:5.1

- volumes:
- solr10milnoacls1index:/opt/alfresco/alf_data environment:
- ALFRESCO HOST=core1
- ALFRESCO PORT=8080
- SOLR HOST=solr1
- SOLR PORT=8081
- JAVA XMS=7168M
- JAVA XMX=7168M
- SHARDING=true
- NUM_SHARDS=3
- NUM NODES=3
- NODE_INSTANCE=1
- TEMPLATE=rerank
- SHARD IDS=0
- ALFRESCO SSL=none
- ARCHIVE_ENABLE_ALFRESCO_TRACKING=false
- ARCHIVE INDEX CONTENT=false
- ALFRESCO_INDEX_CONTENT=false
- MAX HTTP HEADER SIZE=65536
- JMX ENABLED=true
- JMX RMI HOST=xxx.xxx.xxx.xxx

Experiments – dimensions and metrics

Dimension	Values			
Size of repo	1mil	10mil	more	
Sharding method	property	acl		
Number of shards	1	3	11	
AcIs	With artificial acls	Without artificial acls		
Types of queries	simple	complex		
Query concurrency	yes	no		
Load in the same time	yes	no		

- Response times
- Me<mark>mory usage</mark>
- Load
- Caches utilization
- Database performance

Experiments – dimensions and metrics

Dimension	Values			
Size of repo	1mil	10mil	more	
Sharding method	property	acl		
Number of shards	1	3	11	
AcIs	With artificial acls	Without artificial acls		
Types of queries	simple	complex		
Query concurrency	yes	no		
Load in the same time	yes	no		

- Response times
- Me<mark>mory usage</mark>
- Load
- Caches utilization
- Database performance


Experiments - hardware

- Started experiments at Amazon, with AuroraDB as database
- Moved to Hetzner dedicated servers, tried multiple configurations, stabilized to: https://www.hetzner.de/nl/hosting/produkte_r ootserver/px121ssd
 - Intel(R) Xeon(R) CPU E5-1650 v3 @
 3.50GHz, 12 cores
 - 264GB RAM
 - 2TB SSD disks

		Database	Index 1 shard
1 mil	1 shard	8.7G	5.1G
	3 shard		1.8G
10 mil	1 shard	78G	51G
	3 shard		17G
	11 shard		4.8G
100 mil	1 shard	1.3T	500G
	3 shard		164G


Experiments - loading documents

- No content
- Custom model with >10 metadata fields, values randomly generated based on constraints or data type
- Folder structure with / without artificial acls
- Load speed at 12 threads:
 - Approx 1.3 mil docs / hour
- Solr indexing real time



Experiments - loading documents

- No content
- Custom model with >10 metadata fields, values randomly generated based on constraints or data type
- Folder structure with / without artificial acls
- Load speed at 12 threads:
 - Approx 1.3 mil docs / hour
- Solr indexing real time



Experiments – problems encountered

- Ran out of inodes on solr' partition needed to reformat the partition with small block size
- Db tunning max connections
- Memory tunning on db, alfresco + solr size
- Increased max header size in tomcat

Performance improvements:

Disabling acl-checks on Alfresco's side, post-searching

Results

Size	Shards	Context	Method	Artifical ACLs	Threads	Queries per thread	Run	Avg (ms)	Median (ms)	90% (ms)	99% (ms)	Max (ms)	Throughput/s
10mil	3	regular	acl	yes	16	150	#1	456	375	878	1433	3937	33,1
							#2	181	165	292	437	573	77,7
			property	yes	16	150	#1	292	237	539	890	3496	51,1
						(after write tests)		412	324	859	1486	2088	35,0
							#2	88	85	119	167	243	142
						(after write tests)		336	219	693	1152	4367	43,2
					16	100 (after write tests)	#1	465	342	938	3174	4605	30,8
							#2	111	95	162	375	3102	103,3
			acl	no	16	150	#1	596	490	1165	2206	4378	25,8
							#2	115	74	251	517	646	120,2
			property no 16	150	#1	404	298	734	2849	4734	36,5		
							#2	88	81	116	329	422	143,2
		with acl yes 16	16	120	#1	919	767	1554	3498	10588	16,3		
		facets						937	778	1645	3190	9628	16,3
							#2	385	364	540	764	1165	38,3
								387	365	545	852	1054	38,5
					8	240	#1	466	367	800	1871	9207	16,4
							#2	336	321	442	580	766	22,5

Conclusions

- Search slow?
- Primary culprit: DB access / cache
 - Expensive bulk load
 - Cache "sabotage": nodesSharedCache TTL (used OOTBee Support Tools for insights)

Conclusions

- Search slow?
- Primary culprit: DB access / cache
 - Expensive bulk load
 - Cache "sabotage": nodesSharedCache TTL (used OOTBee Support Tools for insights)

- Secondary culprit: Repository-tier ACL checking
 - Misleading: PermissionEvaluationMode.NONE
 - Low default size of caches for readers/readersDenied

Conclusions

- Natural best performer: property sharding + shard-targeted queries
 - ~20% (+-10%) better general performance
 - Improved scaling for parallel requests



Further work

- In progress: 100 million documents
 - Extended data model
 - Realistic value distribution for sharding property

- Planned: customer reference setup
 - Ideally: 100% live data clone, augmented via generation
 - Oracle instead of PostgreSQL



Speaker contacts

roxana.angheluta@xenit.eu axel.faust@acosix.de

