Algorithms in pseudocode for implementing natural and clamped cubic splines follow follows.

Natural Cubic Spline

To construct the cubic spline interpolant S for the function f, defined at the numbers $x_0 < x_1 < \cdots < x_n$, satisfying $S''(x_0) = S''(x_n) = 0$:

INPUT $n; x_0, x_1, \ldots, x_n; a_0 = f(x_0), a_1 = f(x_1), \ldots, a_n = f(x_n)$.

OUTPUT a_j, b_j, c_j, d_j for $j = 0, 1, \ldots, n-1$.

(*Note:* $S(x) = S_j(x) = a_j + b_j(x - x_j) + c_j(x - x_j)^2 + d_j(x - x_j)^3$ *for* $x_j \leq x \leq x_{j+1}$.)

Step 1 For $i = 0, 1, \ldots, n-1$ set $h_i = x_{i+1} - x_i$.

Step 2 For $i = 1, 2, \ldots, n-1$ set

$$\alpha_i = \frac{3}{h_i}(a_{i+1} - a_i) - \frac{3}{h_{i-1}}(a_i - a_{i-1}).$$

Step 3 Set $l_0 = 1$; (*Steps 3, 4, 5, and part of Step 6 solve a tridiagonal linear system using a method described in Algorithm 6.7.*)

$\mu_0 = 0$;
$z_0 = 0$.

Step 4 For $i = 1, 2, \ldots, n-1$
set $l_i = 2(x_{i+1} - x_{i-1}) - h_{i-1}\mu_{i-1}$;
$\mu_i = h_i / l_i$;
$z_i = (\alpha_i - h_{i-1}z_{i-1})/l_i$.

Step 5 Set $l_n = 1$;
$z_n = 0$;
$c_n = 0$.

Step 6 For $j = n-1, n-2, \ldots, 0$
set $c_j = z_j - \mu_j c_{j+1}$;
$b_j = (a_{j+1} - a_j)/h_j - h_j(c_{j+1} + 2c_j)/3$;
$d_j = (c_{j+1} - c_j)/(3h_j)$.

Step 7 OUTPUT $(a_j, b_j, c_j, d_j$ for $j = 0, 1, \ldots, n-1)$;
STOP.