Idaho Technology Authority (ITA)

ENTERPRISE GUIDELINES – G100 GENERAL

Category: G105 – ITA GLOSSARY OF TERMS

CONTENTS:

I. Definitions
II. Rationale
III. Guideline
IV. Contact Information
V. Revision History

I. DEFINITIONS

2-in-1: fall in the category of hybrid or convertible tablets but are distinct in that they run a full-featured desktop operating system and have I/O ports typically found on laptops, such as USB and DisplayPort. The most prominent element is the keyboard that allows the 2-in-1 to provide the ergonomic typing experience of a laptop. (These are also known as 2-in-1 PC, 2-in-1 tablet, 2-in-1 laptop, 2-in-1 detachable, laplet, and laptop tablet.)

6 GHz AFC (Automated Frequency Coordination): A database-driven system used in 6 GHz Wi-Fi deployments to avoid interference with licensed incumbents. Required for standard-power access points operating outdoors or at higher power levels.

802.1X: A network authentication standard providing port-based access control. In WLANs, it is used with EAP methods (such as EAP-TLS) to authenticate users or devices and control access to network resources.

Access Idaho: Access Idaho refers to the group that maintains the Idaho.gov portal.

Address: A location by reference to a thoroughfare or a landmark; or it specifies a point of postal delivery. U.S. Thoroughfare, Landmark, and Postal Address Data Standard (Feb. 2010).

Address Point: May be used synonymously with structure but is broader as it may encompass both an addressable structure and structures that usually are not assigned thoroughfare addresses.

Agency: All state departments, boards, commissions, councils and institutions of higher education; but not elected constitutional officers and their staffs, the legislature and its staff, or the judiciary (per Idaho Code, § 67-831).

Application: Any data entry, update, query, or report program that processes data for a user.

Authenticator: Something the claimant possesses and controls [typically a password, certificate, or other cryptographic module] that is used to authenticate the claimant's identity. (NIST SP 800-63-3)

Authoritative Data: Recognized geospatial data that is certified and provided by an Authoritative Source.

Best Available Data: Geospatial data available for distribution with no access restrictions, accurate, and current at the time of compilation, and metadata is complete and compliant with the Federal Geographic Data Committee (FGDC) geospatial metadata standard.

Centralized WLAN Architecture: A wireless architecture in which access point configuration, policy enforcement, and monitoring are centrally managed through a controller or cloud-managed system.

Certificate-Based Authentication: An authentication model using digital certificates (issued to devices or users) to verify identity in 802.1X/EAP-TLS deployments

Certified Data: Data maintained by an Authoritative Source using a documented and repeatable methodology, acknowledged as complete and accurate within stated limits and restrictions, and ready for publication.

Channel Plan: A structured allocation of WLAN channels across coverage areas to reduce co-channel and adjacent-channel interference.

Chief Privacy Officer (CPO): A statewide function responsible for the development of policies, standards, guidance, and procedures related to the use, collection, maintenance and sharing of PII by State of Idaho agencies. The CPO provides agencies with training and guidance related to PII security controls and the completion of agency Privacy Impact Assessments (PIA) for PII embedded programs and systems.

Cloud: Cloud computing is a computing practice where scalable and adaptable IT-enabled capabilities are delivered as a service to external customers using Cloud based solutions. Cloud services can be delivered by a third-party Cloud Service Provider (CSP), or internally through the establishment of state-owned services and infrastructure.

Cloud-Managed WLAN: A WLAN solution in which APs and controllers are managed through a vendor-hosted cloud platform supporting centralized configuration, firmware lifecycle management, and monitoring.

Cloud Telephony: A service delivering telephony functions—such as calling, faxing, voicemail, and call routing—through cloud-hosted platforms rather than on-premise equipment.

Community cloud: The cloud infrastructure is provisioned for exclusive use by a specific

community of consumers from organizations that have shared concerns (e.g., mission, security requirements, policy, and compliance considerations). It may be owned, managed, and operated by one or more of the organizations in the community, a third party, or some combination of them, and it may exist on or off premises.

Continuous Monitoring (CM): Maintaining ongoing awareness of information security, vulnerabilities, and threats to support organizational risk management decisions.

Control Point: An existing physical monument established by survey methods describing the horizontal and/or vertical position of the monument.

Corrective Action Plan (CAP): A set of actions to correct an issue, problem, non-compliance of underperformance to improve performance and/or reduce risk.

Cost-Benefit Analysis (CBA): A Cost–Benefit Analysis (CBA) is a structured evaluation of the anticipated benefits of a large-scale IT project compared to its total costs over the full lifecycle. This includes the Total Cost of Ownership (TCO), which accounts for acquisition, implementation, maintenance, and eventual retirement costs.

Cybersecurity Breach: A cybersecurity incident in which unencrypted sensitive information or personal information is disclosed. *(See also Idaho Code section § 28-51-104 for breach of the security of the system.)*

Cybersecurity Event: An unauthorized act, successful or unsuccessful, exploiting a cybersecurity threat**,** to gain access to or use of a network or system, or data stored on a network or system.

Cybersecurity Incident: A cybersecurity event that impacts the confidentiality, integrity or availability of a network, system, or data.

Cybersecurity Threat: The potential for a cybersecurity event from a person or thing exercising (accidentally or intentionally) a specific vulnerability.

Data Customer: Anyone who uses Geospatial Framework Data. This includes public citizens, private businesses, educational institutions, non-profit organizations, and government agencies at all levels.

Data Steward: The organization or individuals within or contracted by an Authoritative Source charged with creating, collecting and maintaining Authoritative Data.

Degaussing: A process whereby the magnetic media are erased, (i.e., returned to a zero state).

Demilitarized Zone (DMZ): An interface on a routing firewall that is similar to the interfaces found on the firewall's protected side. Traffic moving between the DMZ and other interfaces

on the protected side of the firewall still goes through the firewall and can have firewall protection policies applied.

Deny by Default:
To block all inbound and outbound traffic that has not been expressly permitted by firewall policy.

Desktop as a Service (DaaS): The capability provided to the consumer is to use the provider's cloud infrastructure to deploy a virtualized desktop experience, delivered to a customer on demand from a remotely hosted location. The customer accesses a customized virtualized desktop from various client devices. The consumer does not manage or control the underlying desktop infrastructure, with the possible exception of limited user-specific application configuration settings.

DFS (Dynamic Frequency Selection): A requirement in the 5 GHz band that enables Wi-Fi devices to avoid frequencies used by radar systems. Access points must detect radar use and switch channels when necessary.

EAP-TLS (Extensible Authentication Protocol – Transport Layer Security): A certificate-based authentication method used in wireless networks. EAP-TLS provides mutual authentication between the client and authentication server, supporting strong identity assurance and encryption.

Emergency Service Zones: The unique combination of fire, police and EMS response areas used to dispatch emergency calls.

Encoding: The recording or reformatting of data into a digital format. Data may be encoded to reduce storage, increase security, or to transfer it between systems using different file formats. In GIS, analog graphic data, such as paper maps and images are encoded into computer formats by scanning or digitizing. (ESRI)

Enterprise Encryption Method: A classification used in State wireless standards referring to encryption modes approved for enterprise-grade WLAN security, including WPA3-Enterprise with PMF and certificate-based 802.1X authentication.

Enterprise Model for GIS: The means by which GIS is integrated into and among the business processes of an organization.

False Easting: A numeric offset from the point of origin along the X-axis.

False Northing: A numeric offset from the point of origin along the Y-axis.

Federal Geographic Data Committee (FGDC): An interagency committee that promotes the coordinated development, use, sharing, and dissemination of geospatial data on a national basis.

Firewall: A device or program that controls the flow of network traffic between networks or hosts that employ differing security postures.

Firmware Lifecycle Management (WLAN): The process of maintaining wireless infrastructure firmware with scheduled updates, patches, and automated deployment mechanisms.

Framework: A framework dataset along with the technology, policies, standards, human resources, and related activities necessary to acquire, process, distribute, use, maintain, and preserve this spatial data. The Idaho Map (TIM) consists of a collection of frameworks.

Framework Data Theme: Spatial data that is commonly needed by a wide spectrum of GIS users with a goal toward developing and maintaining coverage statewide. Themes include: Cadastral, Geodetic Control, Land Use/Land Cover, Hydrography, Transportation, Government Boundaries, Elevation, Orthoimage, Bioscience, Geoscience, Climate, Public Safety, Reference, Parcels, Energy, Utilities and Hazards.

Framework Dataset: The GIS dataset representing all or a portion of a Framework Data Theme. It is common for a Framework Data Theme to consist of several Framework Datasets.

Full Time Positions (FTP): A full-time position is a job in which an employee works the standard number of hours defined by the employer or labor laws—typically around 40 hours per week—and is generally eligible for full employment benefits such as health insurance, paid time off, and retirement plans.

Full Time Employees (FTE): A full-time employee is someone who works the standard number of hours set by the employer or labor laws—typically about 40 hours per week—and is generally eligible for the organization’s full range of benefits, such as health insurance, paid leave, and retirement plans.

Geodetic Datum: Defines the size and shape of the earth and the origin and orientation of the coordinate systems used to map the earth.

Geographic Information Systems (GIS): Any system in which a geographic coordinate system is used to reference the location of features represented by the data. In general, typical components of a GIS are the tools to capture, store, transform, analyze, model, simulate, and display spatial and tabular data related to positions on the Earth's surface.

Geospatial Clearinghouse: A centralized location (one stop resource) for searching, collecting, classifying, storing, and distributing geographic data and metadata that makes GIS data readily available for everyone through the internet.

Geospatial Metadata: A file of information which describes the content, quality, condition, and other characteristics of a geospatial resource including but not limited to geospatial data, web services, and web applications.

Geospatial Technology: Technology used to develop spatial data including, but not limited to, remote sensing, soft-copy photogrammetry, global positioning systems (GPS), GIS, computer-aided design (CAD), and digital cartography.

Global Positioning System (GPS): A worldwide radio-navigation system formed from a constellation of twenty-four (24) satellites and their ground tracking stations that provides geolocation and time information to a GPS receiver anywhere on or near the Earth.

Guest Wireless Network: A segmented, isolated wireless network intended for non-staff users or devices. Typically uses OWE or open portal-based authentication and is separated from internal agency resources.

High-Density WLAN: A WLAN deployment optimized for environments with concentrated user/device populations requiring features like OFDMA, BSS Coloring, and MLO for performance stability.

Hybrid cloud: The cloud infrastructure is a composition of two or more distinct cloud infrastructures (private, community, or public) that remain unique entities, but are bound together by standardized or proprietary technology that enables data and application portability (e.g., cloud bursting for load balancing between clouds).

Hydrography Framework: Statewide base geospatial data representing the surface hydrography and watersheds in the State of Idaho. Hydrography Technical Working Group.

Hydrography Framework / Water Features Stewardship Plan: A document associated with the Water Features Data Exchange Standard governing the life cycle management of the Hydrography Framework/Water Features Element. Hydrography Technical Working Group.

Idaho.gov: Idaho's official State portal. For purposes of this policy, “Idaho.gov” refers to any and all State of Idaho websites.

Idaho State Plane Coordinate System: A Transverse Mercator projection in which Idaho is divided into three zones.

Idaho Transverse Mercator (IDTM): A single-zone projection system that is widely accepted for use in the State.

Identity and Access Management (IAM): A core domain within the information security discipline that covers authentication, authorization, and accounting (AAA) of users and user actions.

Industrial Control Systems (ICS): A generic term used to describe any system that gathers information on an industrial process and modifies, regulates, or manages the process to achieve a desired result. Examples of industrial control systems include: SCADA (Supervisory Control and Data Acquisition), PCS (Process Control Systems), AS

(Automation System), SIS (Safety Instrumentation System), or any other automated control system.

Infrastructure as a Service (IaaS): The capability provided to the consumer is to provision processing, storage, networks, and other fundamental computing resources where the consumer is able to deploy and run arbitrary software, which can include operating systems and applications. The consumer does not manage or control the underlying cloud infrastructure but has control over operating systems, storage, and deployed applications; and possibly limited control of select networking components (e.g., host firewalls).

Internet of Things (IoT): An expansion on modern ICS devices to be "smarter". These devices can assume a variety of forms, often with limited or proprietary operating systems, and often serves an individual and well-defined purpose. IoT devices often communicate together in a network, or with internet-facing services to provide "smart" or intelligent capabilities to a system otherwise lacking. These devices may be sensors, aggregators, communication channels, eUtilities, decision triggers, or other primitives; as defined by NIST Special Publication 800-183 "Network of 'Things'". Examples include: sensors such as thermostats, microcontrollers or microprocessors like Arduino or Raspberry Pi, electronic medical implants, and appliances such as "smart" toasters and televisions.

IoT Segmentation: A security practice isolating IoT and unmanaged devices onto restricted SSIDs or VLANs with minimal network access privileges.

IoT Wireless Network (IoT VLAN/SSID): A logically isolated wireless segment designated for Internet-of-Things devices with limited security capabilities. Restricts device communication to minimize security risks.

IT Projects Best Practice Checklist: A best practices checklist provides a series of questions designed and intended to promote successful completion of projects. It is a valuable tool for assessing critical elements of IT projects

IT Project Profile: The Agency Information Technology (IT) project profile provides details of specific IT projects that are listed in the Agency IT Plan. The project profile provides a level of detail that is much more specific than the IT Plan or the Agency's Business Plan. As such, it provides details that, upon review, highlights the integration with Agency and statewide IT and telecommunications plans and compliance with ITA policies and standards.

Jailbreak: The process of removing software restrictions imposed by Apple iOS, by way of running software exploits that permit root access to the file system. This allows the download and installation of additional applications, extensions, and themes that are unavailable through the official Apple App Store.

Landmark: A prominent or conspicuous object on land that serves as a guide, especially to ships at sea or to travelers on a road; a distinguishing landscape feature marking a site or location. Dictionary.com.

Land Cover: The physical material on the surface of the earth. Examples include grass, asphalt, trees, bare ground, and water. There are two primary methods for capturing information on land cover: field survey and analysis of remotely sensed imagery.

Least Functionality: Prohibit or restrict the use of system functions, ports, protocols, and/or services to only those that provide the essential capabilities to support agency mission and business goals (NIST SP 800-53R5, CM-7).

Least Privilege: Implement the most restrictive set of rights/privileges or access to only those needed by users and processes for the performance of specified tasks (NIST SP 800-53R5, AC-6).

Local Accuracy: A value that represents the uncertainty at the 95 percent confidence level in the coordinates of a measured point relative to the coordinates of other directly connected and adjacent points in the survey.

Map Projection: The transformation and representation of positions from a three-dimensional surface to a two-dimensional surface.

Mobile Device: A handheld or tablet-sized computer that is easily carried and which can be used to access business information. These include, but are not limited to, Smartphones, , Personal Digital Assistants (PDAs), Enterprise Digital Assistants, and Tablets. A Mobile Device is further characterized as such if it is not otherwise protected, monitored, or managed by traditional automated enterprise tools used for workstations, servers and other traditional IT systems. This definition excludes simple mobile storage or memory devices.

Multi-Factor Authentication (MFA): Authentication using two or more factors to achieve authentication. Factors include: (i) something you know (e.g. password/PIN); (ii) something you have (e.g., cryptographic identification device, token); or (iii) something you are (e.g., fingerprint biometric). (NIST IR 7298r2)

Multifactor Authentication Solution: Method of computer access control in which a user is granted access only after successfully presenting several separate pieces of evidence to an authentication mechanism – typically at least two of the following categories: knowledge (something they know), possession (something they have), and inherence (something they are).

*Multi-Link Operation (MLO):*A Wi-Fi 7 (802.11be) feature enabling a device to simultaneously send and receive data over multiple radio links (e.g., 5 GHz + 6 GHz). Enhances throughput, reliability, and latency.

Multi-State Control Point Database (MCPD): A database housed and hosted at the server located at the GIS Training and Research Center at the Idaho State University. It works as a repository of the control points in Idaho.

Network Accuracy: A value that represents the uncertainty in the coordinates of a measured point at the 95 percent confidence level relative to the National Spatial Reference System (NSRS) as determined in the survey.

Network Address Translation (NAT): A routing technology used by many firewalls to hide internal system addresses from an external network through use of an addressing schema.

Online File Storage Service: A file hosting service, cloud storage service or online file storage provider, file transfer facilitator or file share systems such as Torrent services, external storage devices, or ANY data storage and or data transfer solutions otherwise not supported and authorized by the State of Idaho that is designed to host or backup user files on the Internet. Online File Storage Services allows users to upload data, download data, store data at rest, transfer data, and share data which then is accessed over the Internet from other computers, tablets, smartphones, mobile devices, or other networked devices, by the same user or by other designated users.

Overwriting or Scrubbing: Replacing previously stored data on a drive or disk with a predetermined pattern of meaningless information.

OWE (Opportunistic Wireless Encryption / Enhanced Open): A wireless technology that provides encryption for open (unauthenticated) Wi-Fi networks without requiring a password. It uses a Diffie-Hellman key exchange to encrypt traffic between each client and the access point, improving privacy on guest/open SSIDs.

Parcel: A single cadastral unit which is the spatial extent of the current rights and interests in real property. Properties sold as single entities may be divided into multiple parcels for assessment when they fall into multiple taxing entities, such as school or fire districts. Idaho Parcel Standard Team.

Password: A combinations of letters, numbers, and special keyboard characters that is used to identify and authenticate a user.

Patch: Additional pieces of software code developed to address problems (commonly called “bugs”) in software.

Penetration Test: a specialized type of assessment conducted on information systems or individual system components to identify vulnerabilities that could be exploited by adversaries.

Perimeter Firewall: A device or program that controls the flow of network traffic between networks or hosts that employ differing security postures.

*Personal Information (PI)***:** PI is: “Personal information” as defined in Idaho Code section § 28-51-104 means an Idaho resident’s first name or first initial and last name in combination with any one (1) or more of the following data elements that relate to the resident, when either the name or the data elements are not encrypted:

(a) Social security number;
(b) Driver's license number or Idaho identification card number; or
(c) Account number, or credit or debit card number, in combination with any required security code, access code, or password that would permit access to a resident's financial account.

Any other numbers or information that can be used to access a person's financial or health resources, obtain identification, act as identification, or obtain goods or services.

Per Idaho Code § 28-51-104***, "The term 'personal information' does not include publicly available information that is lawfully made available to the general public from federal, state, or local government records or widely distributed media."***

Personally Identifiable Information (PII): Is defined by The National Institute for Standards and Technology (NIST) as personal information (as described above) that permits the identity of an individual to whom the information applies to be reasonably inferred by either direct or indirect means.

Physical Destruction: Storage devices should be physically destroyed when they are defective or cannot be economically repaired.

PMK (Pairwise Master Key): A cryptographic key used during WPA2/WPA3 authentication processes to derive session keys. In WPA3-Enterprise, the PMK is established through 802.1X/EAP methods.

Platform as a Service (PaaS): The capability provided to the consumer is to deploy onto the cloud infrastructure consumer-created or acquired applications created using programming languages, libraries, services, and tools supported by the provider. The consumer does not manage or control the underlying cloud infrastructure including network, servers, operating systems, or storage, but has control over the deployed applications and possibly configuration settings for the application-hosting environment.

Policy: A high-level directive that describes mandatory or prohibited actions, applicable to individuals who fall within the scope of the policy, which aim to protect State information assets.

Privacy Impact Assessment: Is a structured process for identifying, evaluating and mitigating privacy risks associated with the collecting, maintaining and disseminating information, ensures information handling conforms to applicable legal, regulatory, and policy requirements.

Privacy Point of Contact (PPOC): is the person within an agency responsible for overseeing privacy practices, including implementing privacy procedures, coordinating privacy-related training, reviewing materials for privacy risks before publication, and maintaining records of the agency's data-sharing agreements.

Private Cloud: A form of cloud computing that is used by only one organization, or that ensures that an organization is completely isolated from others.

Privileged Account: An information system account with authorizations of a privileged user.

Privileged User: A user or service that is trusted to perform security-relevant functions that ordinary users are not authorized to perform.

Protected Management Frames (PMF): A security feature defined in IEEE 802.11w that protects Wi-Fi management frames—such as disassociation and deauthentication—from spoofing or tampering. PMF is required for WPA3 and all 6 GHz WLANs.

Public cloud: The cloud infrastructure is provisioned for open use by the general public. It may be owned, managed, and operated by a business, academic, or government organization, or some combination of them. It exists on the premises of the cloud provider.

Publication Data: Trusted Data that is readily available to the public with limited business hours restrictions.

Remediation: The act of correcting a vulnerability or eliminating a threat. Three possible types of remediation are: installing a patch, adjusting configuration settings, or uninstalling a software application.

Removal of State of Idaho Data: Removal of State of Idaho data from storage devices and electronic media is the process of removing sensitive and/or confidential programs or data files on computer storage devices or electronic media in a manner that gives assurance that the information cannot be recovered by keyboard or laboratory attack.

Radio Frequency (RF) Planning: The process of surveying, modeling, and designing wireless coverage, capacity, transmit power, channel selection, and interference mitigation for WLAN deployments.

Risk: The probability that a particular threat will exploit a particular vulnerability.

Risk Assessment: The process of identifying risks to organizational operations (including mission, functions, image, reputation), organizational assets, individuals, other organizations, and the Nation, resulting from the operation of a system.

Risk Management: The process of identifying, assessing, and reducing risk to an acceptable level and implementing the right mechanisms to maintain that level of risk.

Rogue Access Point Detection: The capability of WLAN infrastructure to identify unauthorized or malicious access points within range of the State wireless environment.

Roled-Based Segmentation: A network segmentation approach assigning users and devices to access roles with specific policy restrictions (VLAN, ACL, or identity-based enforcement).

Root or Rooting: The process of allowing users of smartphones, tablets, and other devices running the Android mobile operating system to attain privileged control (known as root access) over various Android subsystems.

Root Mean Square Error: The square root of the average of the set of squared differences between dataset coordinate values and coordinate values from an independent source of higher accuracy for identical points.

Ruleset: A set of directives that govern the access control functionality of a firewall. The firewall uses these directives to determine how packets should be routed between its interfaces.

Screen Lock: Mechanism to hide data on a visual display while the computer continues to operate. A screen lock requires authentication to access the data. Screen locks can be activated manually or in response to rules.

Screen Timeout: Mechanism to lock the screen of a device or end a session when the device has not been used for a specified time.

Sensitive Information: Sensitive information includes state e-mail and any information defined as sensitive by any state statute, such as Idaho Code § 28-51 (Commercial Transactions, Identity Theft).

Sensitivity: A measure of the importance assigned to the information by its owner for the purpose of denoting the need for protection (ITA Policy P4130).

Session Initiation Protocol Trunk (SIP Trunk): A telecommunications service that enables voice communication over IP networks and replaces traditional PRI or analog telephone lines.

Sideloading: the process of transferring data between two local devices, between a computer and a mobile device such as a mobile phone, smartphone, PDA, tablet, portable media player or e-reader. Sideloading typically refers to media file transfer to a mobile device via USB, Bluetooth, Wi-Fi or by writing to a memory card for insertion into the mobile device.

Simple Mobile Storage or Memory Device: A device such as a simple mobile phone that is meant for phone communications or a device for use of portable storage such as an external hard drive or USB storage device.

Software as a Service (SaaS): The capability provided to the consumer is to use the provider's applications running on a cloud infrastructure. The applications are accessible

from various client devices through either a thin client interface, such as a web browser (e.g., web-based email), or a program interface. The consumer does not manage or control the underlying cloud infrastructure including network, servers, operating systems, storage, or even individual application capabilities, with the possible exception of limited user-specific application configuration settings. DropBox, Google Drive, iCloud, OneDrive, Generative AI.

Spatial Data: Digital information that identifies the geographic location of features and boundaries that are usually stored as coordinates and topology that can be mapped or used for comparative spatial analysis.

Spatial Data Infrastructure: The technology, policies, standards, human resources, and related activities necessary to acquire, process, distribute, use, maintain, and preserve spatial data.

SSID (Service Set Identifier): The unique name assigned to a wireless network. Devices use the SSID to identify and connect to a specific WLAN.

Structure: A structure is defined as “that which is built or constructed.” International Building Code (IBC), 2006.

System: A computer, server, or IT device (e.g. router, switch, gateway, firewall) to include the hardware, operating system software, and installed applications.

Technical Working Group (TWG): Long-term groups formed by the Information Technology Leadership Council (ITLC) or Idaho Geospatial Council Executive Committee (IGC-EC) to provide expertise and focused effort in specific areas of interest.

Telephony: Voice communications over the public switched telephone network (PSTN) and Internet Protocol (VoIP), including calling, voicemail, call routing, E911 location management, and related functions for State agencies and institutions.

Telephony Licensing/Software: Call control software, voicemail/Unified Messaging, IVR, call recording, contact center applications, softphone clients, client access licenses, and related subscription or perpetual licenses.

Telephony Lifecycle Management: The coordinated procurement, maintenance, upgrades, and retirement of telephony systems, licensing, and services under ITS oversight.

Telephony Peripherals & Ancillary Telephony Services: Items and integrated services required to deliver telephony capabilities (e.g. headsets, adapters, line cards, voicemail boxes, auto-attendants, number management) when directly tied to telephony systems/services.

Telephony Services (Local/Long Distance/Cloud): SIP services and local facilities, inbound/outbound long-distance and toll-free services, direct inward dialing (DID), and cloud telephony offerings (e.g. cloud fax – such as Core Fax).

Telephony Systems (Hardware/Infrastructure): Equipment and infrastructure that enable telephony services, such as PBXs/IP telephony platforms, session border controllers (SBCs), paging gateways, voice gateways, desktop handsets, conferencing phones, and softphone endpoints.

The Idaho Map (TIM): The full collection of Framework Data Theme GIS datasets.

Threat: Any circumstance or event, deliberate or unintentional, with the potential for causing harm to a system.

Transition Mode SSID: An SSID configured to support both legacy and modern security modes (e.g., WPA2 + WPA3) for a limited migration period.

Trivial User: Consumer or public-facing accounts that are most often, but not exclusively, controlled by the consumer and not the agency. These accounts handle only data classified as unrestricted and limited per ITA P4130 - Information Systems Classification Policy.

Trusted Data: Authoritative Data obtained from Authoritative Sources by a Trusted Source with documented metadata and an established data maintenance cycle or plan.

Trusted Source: A service provider or agency that publishes geospatial data from one or many authoritative sources as a result of an official agreement or process with authoritative sources. The limitations, currency, attributes of the data, and any compilation or standardization processes are known and documented. Data easily available and access is documented.

Universal Transverse Mercator (UTM): A commonly used map projection in which the unit of measure is meters. The UTM system uses zones of six degrees (6°) of longitude.

User: Anyone with authorized access to State business information systems, including permanent and temporary employees or third-party personnel such as temporaries, contractors, consultants, and other parties with valid State access accounts; OR,
An individual or (application) process acting on behalf of an individual authorized to access an information system.

Verifier: A standalone or federated authentication service, or an application, program, system, or service that implements an authentication function (e.g. a website login page).

Virtual Private Network (VPN): A VPN is a secure, logical communication channel that authenticates identities, encrypts data in transit, and authorizes access to agency resources across untrusted networks. Modern VPN implementations include IPsec IKEv2 and TLS-based remote access, integrated with enterprise identity providers and MFA to support SSO via SAML 2.0.

Vulnerability: A flaw in the design or configuration of software that has security implications. A vulnerability can be exploited by a malicious entity to gain greater access or privileges than is authorized.

Water Features Data Exchange Standard: The document associated with the Water Features Exchange Standard governing the life cycle management of the Hydrography Framework.

Well Defined Points: A visible and recoverable feature on the ground with high positional accuracy with respect to the geodetic datum, such as highway intersections and building corners.

Wi-Fi 6 (802.11ax): A wireless networking standard that improves efficiency and performance through OFDMA, BSS Coloring, and improved spectrum use. Supports 2.4 GHz and 5 GHz operation.

Wi-Fi 6E: The extension of Wi-Fi 6 into the 6 GHz band, providing additional spectrum, more non-overlapping channels, lower interference, and improved performance.
Wireless Local Area Network (WLAN): is a Local Area Network (LAN) or LAN segment that uses radio waves, instead of physical cables, to tranfer data between networked devices.

Wi-Fi 7 (802.11be): The next-generation Wi-Fi standard featuring 320 MHz channels, Multi-Link Operation, 4K QAM, and deterministic low-latency capabilities for high-performance workloads.

Wireless Configuration Compliance: The requirement that agency wireless systems maintain alignment with S3530 and G530 across configuration, monitoring, encryption, and authentication settings.

Wireless Intrusion Detection/Prevention System (WIDS/WIPS): A security system that monitors wireless networks for unauthorized devices, rogue access points, attacks, unauthorized APs, impersonation, anomalous authentication events, containment actions or policy violations. WIPS adds automated containment or mitigation capabilities.

Wireless Network Exemption: A formal approval process allowing deviations from required State wireless security controls under ITA Policy P1010.

WLAN Log Forwarding: The practice of exporting wireless authentication, AP event, and security logs to an approved enterprise logging system for monitoring and incident response.

WPA3 (Wi-Fi Protected Access 3): A Wi-Fi Alliance security certification that provides advanced authentication and encryption protections for wireless networks. WPA3 includes mandatory Protected Management Frames (PMF), stronger brute-force resistance, improved encryption for open networks, and enhanced protections for enterprise authentication via WPA3-Enterprise.

WPA3-Enterprise: An enterprise-grade wireless security mode that uses 802.1X authentication with modern cryptography (CCMP-128 or GCMP) and includes mandatory Protected Management Frames. Supports optional 192-bit CNSA security for high-assurance environments.

WPA3-Enterprise 192-bit (CNSA Suite): A high-assurance wireless security profile using 192-bit cryptographic strength in alignment with the Commercial National Security Algorithm (CNSA) Suite. Requires compatible APs and clients and is intended for workloads requiring elevated protection.

WPA3-Transition Mode: A compatibility mode that allows simultaneous support for WPA2- and WPA3-capable devices on the same SSID during migration. Intended only for temporary use during transition periods.

II. RATIONALE

This guidance was created to standardize all terms used both in ITA policy and guidance into one reference. This effort will eliminate redundancy of terms, circular reference errors, and contradictions of terms.

III. GUIDELINE

This guideline definition section should be used as the primary reference point for a glossary of terms referenced in all ITA policies, standards, and guidelines. Older policies, standards, and guidelines, when updated, will have their definitions section moved into this guidance and a reference inserted into the update to point to the glossary of terms kept in this guidance.

IV. CONTACT INFORMATION

For more information, contact the ITA Staff at (208) 605-4064.

V. REVISION HISTORY

05/05/2026 – Definitions added from: P1020, P2030, P3010, P4540, P4570, S3220, G210, G225, G230, G530, G535, S3530, S6040, S6050

04/16/2024 – Definition added from P1090

04/20/2021 - Definitions added from P1010; P1020; P2040; P4550; S3110; Revised *Technical Working Group* definition

07/18/2019 – Revised definitions for *Spatial Data Infrastructure*; and *The Idaho Map (TIM)*.

05/16/2019 - Definitions added from P1070; P5030; S4210; S4220; S4221; S4230; S4231; S4232; S4233; S4234; S4240; S4250; G340; and G350.

Effective Date: August 21, 2018