

Payment Channels Overview

Orfeas Stefanos Thyfronitis Litos

University of Edinburgh
o.thyfronitis@ed.ac.uk

Abstract. This is an overview of the existing literature on virtual payment channels. Lightning [?], Perun [?] and TeeChan [?] are considered.

1 Introduction

Payment channels are constructions that permit the secure exchange of assets between remote agents without the need for each transaction to be recorded in a global database. They are constructed in a way that gives the opportunity to the cheated agents to report the latest valid state to a global database (i.e. blockchain) and reclaim their assets.

For example, imagine that *Alice* works in *Bob*'s pin factory. They have agreed that *Alice* be paid right after she makes each pin a small amount x [?]. This can add up to hundreds, even thousands small of payments each day. Since most cryptocurrencies impose fees per transaction, it would be a waste to broadcast a new transaction for each small payment. For this reason, they turn to payment channels.

At the beginning of each month, *Bob* creates a transaction that pays e.g. 100 coins (a bit more than *Alice*'s expected pay for the month) to himself. He builds it in a way that needs both his and *Alice*'s signature to be spent (i.e. 2-of-2 multisig). This is the “bond” transaction. *Alice* confirms that the “bond” looks fine and gives *Bob* a special transaction that spends the “bond”. This transaction is the “refund” transaction. *Bob* broadcasts the “bond” (but not yet the “refund”) to the blockchain. The channel is now open.

Every time *Alice* makes a pin, *Bob* pays x to *Alice* as follows: He creates a new “refund” that pays to *Alice* the amount she already owned according to the previous “refund” plus x ; accordingly, his payment is reduced by x . The total coins in the refund are always the same. He signs the new “refund” and sends it to *Alice*. She in turn signs the new “refund” and sends it back to *Bob*. The channel is now updated.

Finally, the end of the month comes and *Alice* wants to cash out on the blockchain, so that she can use her coins elsewhere. In order to do so,

she simply broadcasts the latest “refund”. The “bond” is spent according to the latest update, so she takes her rightful payment and *Bob* takes the rest of the 100 initial coins. The channel is now closed.

Note that exactly two transactions have been broadcast on the blockchain no matter how many payments were made, so the fees are kept low. Furthermore, both parties can unilaterally close the channel at any given point and claim the coins of their latest “refund”, thus no trust is required between the two parties.

As an extension of the previous model, let *Charlie* be a colleague of *Alice*, who also has a payment channel with *Bob*. It is reasonable to imagine a system where *Alice* can pay *Charlie* without touching the blockchain, by leveraging the two pre-existing channels ($Alice \leftrightarrow Bob, Bob \leftrightarrow Charlie$) with minimal interaction with *Bob* and without having to trust him at all.

In the following sections we will summarise and compare various specific constructions that realise the high-level ideas described above. We will use the original terminology used in each paper.

2 Lightning Network

This construction is the first to achieve a functional model for payment channels. It is designed for bitcoin and requires some new opcodes and removing the malleability of transactions to function properly [?].

2.1 Simple two-party channel

The basic construction is as follows. Suppose that *Alice* and *Bob* want to create a payment channel that contains 1 BTC consisting of 0.5 BTC from each party. To achieve this, they follow these steps (see also section 3.1.2 and Figure 4 in 3.3.2 in [?]):

1. Either party (say *Alice*) creates a “Funding” transaction (F) with an input of 0.5 BTC from her and 0.5 BTC from *Bob*, and a 2-of- $\{Alice, Bob\}$ multisig as output; she then sends F to *Bob*. This transaction is not yet signed nor broadcast. F needs to be signed by both parties to be valid.
2. *Alice* creates, signs and sends to *Bob* a “Commitment” transaction ($C1b$) that spends F and has the following outputs:
 - (a) 0.5 BTC that can be spent by *Alice* immediately when $C1b$ is broadcast.

- (b) 0.5 BTC that can be spent by either party, but *Bob* can spend it only after a specified amount of blocks (say n) have been mined on top of $C1b$, whereas *Alice* can spend it only if *Bob* provides her with a “Breach Remedy” transaction (explained later) signed by him. This output is called “Revocable Sequence Maturity Contract” (RSMC).

Furthermore, *Alice* creates, signs and sends a “Revocable Delivery” transaction ($RD1b$) that pays the first of the two outputs of $C1b$ to *Bob*, but will be accepted by the network if it is in the mempool only after n blocks have been mined on top of $C1b$.

Bob similarly creates, signs and sends $C1a$ and $RD1a$ to *Alice*.

3. After *Alice* receives the signed $C1a$ and $RD1a$ from *Bob*, she verifies that they are both valid and correctly spend F . Given that everything works out right, she signs F and sends it to *Bob*.

Bob similarly verifies that $C1b$ and $RD1b$ have the correct structure, along with *Alice*’s signature on F . He then signs F and broadcasts it. Note that he does not have to trust *Alice* in any way.

The fact that *Alice* holds $C1a$ and $RD1a$, already signed by *Bob*, ensures her that her 0.5 BTC cannot be locked in the 2-of-2 multisig of F in case *Bob* stops cooperating. If she decides that *Bob* stopped cooperating, she can broadcast $C1a$, wait for it to be confirmed n times and broadcast $RD1a$ to get her money back. Thus *Alice* need not trust *Bob* either.

Observe that if *Bob* refuses to cooperate in signing F , then the blockchain has not been changed and no funds are at risk. In such case, to ensure that *Bob* cannot lock her funds in the future, she should immediately transfer her funds to a new address or periodically check the blockchain for F and broadcast $C1a$ and $RD1a$ in case she finds F on the ledger.

After initially setting up the channel, *Alice* and *Bob* can update it as follows (see also section 3.3.4 and Figures 7, 8 in [?]):

1. Both *Alice* and *Bob* follow exactly the same steps as before to create $C2a$, $C2b$, $RD2a$ and $RD2b$; the only difference these transactions have to their counterparts from the previous state of the channel is that, instead of 0.5 BTC for each player, they contain the new agreed balance of the channel (e.g. 0.4 BTC for *Alice* and 0.6 BTC for *Bob*).
2. *Alice* creates, signs and sends to *Bob* a so-called “Breach Remedy” transaction ($BR1a$). This transaction lets *Bob* redeem the RSMC output of $C1a$ as soon as $C1a$ is broadcast. *Bob* similarly creates, signs and sends $BR1b$ to *Alice*.

Note that this effectively disincentivises *Alice* from ever broadcasting *C1a*, since in such case *Bob* will have a window of n blocks during which he can claim the entire sum in *C1a*, 1 BTC, for himself. *Alice* had better purge *C1a* after *BR1a* is sent to *Bob*. Similarly *Bob* is incentivised to refrain from ever broadcasting *C1b*.

This arrangement creates a situation where both players can be confident that the state of the channel is the one expressed by *C2a*, *C2b*, *RD2a* and *RD2b*, thus they can assume that *Alice* has just paid *Bob* 0.1 BTC. No trust between the two players was needed all along. There are only two caveats: First, both players must periodically check the blockchain to ensure that the other party has not broadcast an old Commitment transaction. Second, in case of an uncooperative counterparty, one has to wait a prespecified amount of time before releasing their funds, which may be undesirable.

Thus, the necessary number of blocks mined on top of a Confirmation transaction for a subsequent Revocable Delivery to be valid (previously called n) must be carefully chosen in a way that does not lock up the funds for a long time in case of a dispute and at the same time does not require that the parties check the blockchain too often for a malicious broadcast of an already invalidated Commitment transaction.

Alice can outsource the task of the periodic check to a dedicated service by sending it all the previous Breach Remedy transactions. To incentivise the service to cooperate, *Alice* can pay a fee to it as an output of these transactions. Note that *Alice* does not need to trust the service, since the only thing it can do is to broadcast a Branch Remedy transaction that was created by *Alice*; she never discloses any of her private keys to it.

Finally, the parties can cooperatively close the channel without having to wait n blocks as follows: When both parties have agreed to closing the channel, *Alice* creates, signs and sends to *Bob* an “Exercise Settlement” transaction (*ES*) that spends the Funding transaction and has two simple outputs, each paying to the respective party the sum of the last agreed Commitment transaction. Following the previous example, this transaction would pay 0.4 BTC to *Alice* and 0.6 BTC to *Bob*. *Bob* can then also sign and broadcast the transaction to close the channel.

Once *Alice* has sent *ES*, she considers the channel as closed. If *Bob* does not broadcast *ES*, we have a dispute and she has to broadcast the latest Commitment transaction and wait for her funds to be unlocked.

2.2 Payments depending on preimage knowledge (HTLC)

Multi-hop payments can take place between players (e.g. *Alice* and *Dave*) who do not share a simple channel (i.e. an on-chain Funding transaction), but share simple channels with intermediate nodes (e.g. *Alice* with *Bob*, *Bob* with *Carol* and *Carol* with *Dave*).

To enable the creation of multi-hop channels, so-called “Hashed Time-lock Contracts” (HTLC) are used. An HTLC is an additional output in a Commitment transaction which can be redeemed by either *Alice* or *Bob*; *Alice* can redeem it after a specified number of additional blocks, say m , have been mined after the creation (*not* the broadcast) of the Commitment transaction, whereas *Bob* can redeem it at any time, but only if he produces the preimage R of a hash specified in the HTLC output (see also section 4.2 and Figure 12 in [?]).

More specifically, consider $C2a, C2b$ where, contrary to the example in the previous subsection, *Alice* has paid the 0.1 BTC to an HTLC instead of directly to *Bob*. *Bob* should be able to redeem the 0.1 BTC only if he knows the preimage R before the m blocks have been mined. In addition to $RD2a$ and $RD2b$, six additional transactions have to be signed and exchanged.

1. *Alice* signs and sends an “HTLC Execution Delivery” transaction ($HED1a$) to *Bob*. $HED1a$ pays the HTLC output of $C2a$ to *Bob*, only if he knows the required preimage R . Only *Bob* can broadcast the transaction.
2. *Bob* signs and sends a so-called “HTLC Timeout Delivery” transaction ($HTD1b$) to *Alice*. $HTD1b$ pays the HTLC output of $C2b$ to *Alice*, only after m blocks have been mined from the time $C2b$ was created. Only *Alice* can broadcast this transaction.
3. *Alice* signs and sends an “HTLC Execution” transaction ($HE1b$) to *Bob*. $HE1b$ pays the HTLC output of $C2b$ to *Bob*, only if he knows the required preimage R . Only *Bob* can broadcast this transaction. Its single output is an RSMC with duration n , spendable by *Bob*.
4. *Alice* signs and sends an “HTLC Execution Revocable Delivery” transaction ($HERD1b$) to *Bob*. This transaction spends the RSMC output of $HE1b$. *Bob* can broadcast this transaction after n blocks have been mined on top of $HE1b$.
5. *Bob* signs and sends an “HTLC Timeout” transaction ($HT1a$) to *Alice*. $HT1a$ pays the HTLC output of $C2a$ to *Alice*, only after m blocks have been mined from the time $HT1a$ was created. Its single output is an RSMC with duration n , spendable by *Alice*.

6. *Bob* signs and sends an “HTLC Timeout Revocable Delivery” transaction (*HTRD1b*) to *Alice*. This transaction spends the RSMC output of *HT1b*. *Alice* can broadcast this transaction after n blocks have been mined on top of *HE1b*.

Note that once again, no trust is necessary in the process described above. The RSMC outputs of *HT1a* and *HE1b* are necessary for future invalidation according to the “Breach Remedy” method. More details can be found in Figure 14 of section 4.3. In case of common desire to close the channel, they can be cooperatively closed using the “Exercise Settlement” method.

2.3 Multi-hop channels

With the use of HTLC outputs, it is possible to execute multi-hop payments as follows. Suppose *Alice* wants to pay *Dave* 0.001 BTC and they find out that they are connected through the preexisting channels $Alice \Leftrightarrow Bob$, $Bob \Leftrightarrow Carol$ and $Carol \Leftrightarrow Dave$. This payment can be completed with the following steps:

1. *Dave* generates a random number R and sends $hash(R)$ to *Alice*, *Bob* and *Carol*.
2. *Alice* and *Bob* update their channel with an e.g. 300-block HTLC that transfers 0.001 BTC from *Alice* to *Bob*.
3. *Bob* and *Carol* update their channel with an e.g. 200-block HTLC that transfers 0.001 BTC from *Bob* to *Carol*.
4. *Carol* and *Dave* update their channel with an e.g. 100-block HTLC that transfers 0.001 BTC from *Carol* to *Dave*.
5. *Dave* discloses R to *Carol*; he obtains 0.001 BTC from the 100-block HTLC transaction.
6. *Carol* discloses R to *Bob*; she obtains 0.001 BTC from the 200-block HTLC transaction.
7. *Bob* discloses R to *Alice*; he obtains 0.001 BTC from the 300-block HTLC transaction.

Thus *Alice* has paid *Dave* 0.001. No party can be defrauded: For example, *Carol* will pay 0.001 BTC to *Dave* if he shows her R within 100 blocks but then she can take the 0.001 BTC back by disclosing R to *Bob*; she has at least 100 more blocks to do so. In case *Dave* does not disclose R , all parties can take their funds back by settling on-chain.

On the other hand, assume that *Bob* does not cooperate after the establishment of the HTLC transactions, but keeps R hidden. In this

case *Bob* will lose his 0.001 BTC to *Carol* and no other player will be negatively affected; *Carol* and *Dave* can fulfill their part without *Bob*'s cooperation, albeit *Carol* will have to wait for her channel with *Bob* to expire, since she has to settle on-chain. Likewise *Alice* can take back her 0.001 after the 300-block HTLC lock has expired. Thus no trust between parties is needed.

One can note three things: Firstly, there is no such thing as a persistent multi-hop channel. The whole procedure must be repeated for each subsequent multi-hop payment and the successful completion of one such payment does not facilitate the creation of future payments along the same route as far as the techniques described above are concerned. Nevertheless, previous cooperation between players can obviate the need of exploring the network anew for a connecting series of preexisting channels.

Secondly, merely the existence of a channel is not enough to ensure that multi-hop payments can be achieved through it. It must be the case that the correct player holds at least as much funds as the desired payment, which can only be verified by asking the players of the channel, since the latest state is not public. Thus, in the previous example, *Bob* must own at least 0.001 BTC in the *Bob* \leftrightarrow *Charlie* channel in order for the payment to be possible. *Alice* (or *Dave*) must ask *Bob* and *Charlie* whether this is the case before initiating the multi-hop payment process.

Finally, all intermediate players have to actively engage for a multi-hop payment to go through. This means that a multi-hop payment's latency increases linearly with the length of the chain, as well as the waiting time if on-chain settlement is needed (given that the same margin of security is desired irrespective of the payment length). This reduces the scalability of the design and fosters the creation of centralized, heavily connected players that ensure that short chains are available instead of distributed, loosely connected players that exchange funds through long chains.

3 Perun

Perun [?] is a payment network designed for Turing-complete smart contract scripting languages. It has been implemented for Ethereum. Its main contribution is *multistate channels* that allow the dynamic deployment of virtual contracts, known as *nanocotracts*. Contracts of this type do not have to enter the blockchain if all parties are cooperative and only do so in case of a dispute.

The paper describes specifically the use of such multistate channels for creating virtual payment channels between parties that do not have a basic payment channel between them, but both have basic multistate channels with an intermediary. Then the intermediary could substitute for the blockchain and thus a virtual payment channel on top of the two basic multistate channels can be created. The parties need the intermediary only for setting up the channel and to close it fast. If the intermediary refuses to close the channel, they can always fall back to the blockchain in order to close it.

3.1 Basic payment channels

A basic payment channel is a tuple

$$\gamma = (\gamma.\text{id}, \gamma.\text{Alice}, \gamma.\text{Bob}, \gamma.\text{cash}, \gamma.\text{ver-num}, \gamma.\text{sign})$$

Versions of this tuple are held by *Alice* and *Bob*. $\gamma.\text{id}$ is a unique identifier for the channel, $\gamma.\text{Alice}$ and $\gamma.\text{Bob}$ are the end-users of γ and $\gamma.\text{cash}$ is a function from the end-users to a real non-negative value that denotes the amount of cash the user has in the channel. $\gamma.\text{ver-num}$ is a number that is incremented with each channel update (so that the latest state of the channel is known in case of dispute) and $\gamma.\text{sign}$ is the singature of the other party on $(\gamma.\text{id}, \gamma.\text{cash}, \gamma.\text{ver-num})$.

A payment channel has a corresponding `PaymentContract $\gamma.\text{id}$` on the ledger. End-users interact with the contract only to set up and close the channel, whereas updating the channel happens off-chain. The contract does not contain the fields $\gamma.\text{ver-num}$ and $\gamma.\text{sign}$; the two fields are kept only by the end-users.

Channel creation

The procedure of creating a channel is as follows:

1. *Alice* creates a `PaymentContract` (γ), pays it $\gamma.\text{cash}(\gamma.\text{Alice})$ coins and broadcasts it on the ledger. The fields $\gamma.\text{ver-num}$ and $\gamma.\text{sign}$ are not included.
2. The contract sends the message (`initialising`, γ) to both end-users ($\gamma.\text{Alice}$ and $\gamma.\text{Bob}$).
3. *Bob* calls the `confirm()` function of the contract and pays it the already specified amount of $\gamma.\text{cash}(\gamma.\text{Bob})$ coins.
4. The contract sends the message (`initialised`, γ) to both end-users.

5. If *Alice* does not receive (`initialised`, γ) after a predefined period Δ has passed from receiving (`initialising`, γ), she calls the contract function `refund()` and gets her deposit back.

Note that *Alice* can get her money back if *Bob* does not cooperate and *Bob* only pays the contract after he verifies that *Alice* has set up everything correctly. The contract code is public and thus end-users do not engage with it if it does not correspond to the expected code; no trust towards the contract is needed.

Channel update

Assume that the end-users want to update an existing channel balance from $\gamma.\text{cash}$ to cash' , where the total channel balance has remained unchanged:

$$\gamma.\text{cash}(\gamma.\text{Alice}) + \gamma.\text{cash}(\gamma.\text{Bob}) = \text{cash}'(\gamma.\text{Alice}) + \text{cash}'(\gamma.\text{Bob})$$

The procedure of updating to the new balance is as follows:

1. *Alice* builds a new channel tuple γ^{Alice} where
 - the fields `id` and `users` are as in γ ,
 - $\gamma^{Alice}.\text{cash} = \text{cash}'$,
 - $\gamma^{Alice}.\text{ver-num} = \gamma.\text{ver-num} + 1$ and
 - $\gamma^{Alice}.\text{sign}$ is *Alice*'s signature on $(\gamma^{Alice}.\text{id}, \gamma^{Alice}.\text{cash}, \gamma^{Alice}.\text{ver-num})$.
2. *Alice* sends γ^{Alice} to *Bob* and waits for his response.
3. *Bob* checks that all fields are as expected and replaces the old channel tuple, γ , with the newly tuple, γ^{Alice} . From his point of view, the payment has gone through.
4. *Bob* sends to *Alice* the updated channel, γ^{Bob} , of which all fields are the same as γ^{Alice} except for $\gamma^{Bob}.\text{sign}$, which is *Bob*'s signature on $(\gamma^{Bob}.\text{id}, \gamma^{Bob}.\text{cash}, \gamma^{Bob}.\text{ver-num})$.
5. If *Alice* receives the expected γ^{Bob} , she replaces the old channel tuple with γ^{Bob} . From her point of view, the payment has gone through.

The above description holds symmetrically if *Bob* initiates the channel update. If any player diverges from these steps, the other player can assume that the first has been corrupted and should close the channel immediately.

Note that after the first update, the channel tuples held by the two players are not the same, their only difference being in the signature field.

Strictly speaking, this means that the description of updating a channel above abuses the notation when it refers to γ as the common previous channel state.

Also note that the following scenario may arise: *Alice* sends the updated version of the channel along with her signature, but *Bob* does not reply. In this case, *Alice* wants to close the channel since *Bob* is assumed to be corrupt, but the latest state of which she has *Bob*'s signature is one version earlier than *Bob*'s latest state. The only way *Alice* can retrieve her funds is by broadcasting this older state. *Bob* can then broadcast his latest state, which supersedes *Alice*'s state. From the point of view of the blockchain, *Alice* has tried to close the channel with an older state.

Since there is a situation where the blockchain cannot say which player was corrupt, *Alice* cannot be punished for broadcasting an older state of the channel by losing all her funds in the channel. She should be entitled to her share, as defined by the latest channel state that has been broadcast. Thus the punishment scheme of Lightning cannot be applied here.

Closing the channel

Finally, we present the procedure of closing a channel.

1. *Alice* calls the function `close(γ^{Alice})` of `PaymentContract $_{\gamma.id}$` .
2. `PaymentContract $_{\gamma.id}$` checks that γ^{Alice} is correctly formed and holds the same total balance as the initial channel recorded in the contract. If so, it accepts γ^{Alice} as the channel state. Additionally, *Bob* can call `close()` at any time and either *Alice* or *Bob* can call `finalize()` after time Δ has passed. If γ^{Alice} does not pass the checks, the contract ignores the call.
3. If *Bob* disagrees with the channel state published by *Alice*, he calls `close(γ^{Bob})` of `PaymentContract $_{\gamma.id}$` .
4. Upon receiving a `close(γ^{Bob})` call from *Bob*, `PaymentContract $_{\gamma.id}$` checks that γ^{Bob} is correctly formed, holds the same total balance as the initial channel recorded in the contract and additionally has a higher version number than γ^{Alice} . If so, it accepts γ^{Bob} as the channel state. Either *Alice* or *Bob* can still call `finalize()` after time Δ from *Alice*'s original `close()` call has passed. If γ^{Bob} does not pass the checks, the contract ignores the call.
5. After time Δ has passed, either end-user can call `finalize()` of `PaymentContract $_{\gamma.id}$` .

6. Upon receiving a `finalize()` call from either end-user, the contract `PaymentContract γ .id` checks that time Δ has passed since the original `close()`. If so, it sends `closed` and `γ .cash(P)` to each end-user P . If not, it ignores the `finalize()` call.

The above closing sequence gives *Bob* a window of duration at least Δ to dispute the closing channel state reported by *Alice*.

Note that, in contrast to Lightning, there is no provision for cooperative closing of a channel, thus a delay of Δ must always be incurred between initiating a channel closure and getting access to the funds. The parameter Δ is decided by the parties when the channel is created and presents the same tradeoffs as the parameter n of Lightning.

3.2 Multistate channels

A basic multistate channel is a tuple

$$\gamma = (\gamma.\text{id}, \gamma.\text{Alice}, \gamma.\text{Bob}, \gamma.\text{cash}, \gamma.\text{nospace}) ,$$

where $\gamma.\text{id}$, $\gamma.\text{Alice}$, $\gamma.\text{Bob}$ and $\gamma.\text{cash}$ are as in a payment channel and $\gamma.\text{nospace}$ is a set of nanocontracts, or *nanocontracts space*.

The multistate channel γ has a corresponding contract `MSContract γ .id` on the ledger. The end-users have to interact with this contract upon channel creation, channel closure and in case of dispute over the state of a nanocontract. Note that the end-users can create new nanocontracts, as well as cooperatively update them, without touching the ledger.

A nanocontract $\nu \in \gamma.\text{nospace}$ is a tuple

$$\nu = (\nu.\text{nid}, \nu.\text{blocked}, \nu.\text{storage}, \nu.\text{ver-num}, \nu.\text{sign}) ,$$

where $\nu.\text{nid}$ is a globally unique identifier of the nanocontract, $\nu.\text{blocked}$ is a function from the end-users of the multistate channel to a real non-negative value that denotes the amount of cash the end-user has in the nanocontract and $\nu.\text{storage}$ contains the storage of the nanocontract. Like simple payment channels, the nanocontract with the highest $\nu.\text{ver-num}$ and a valid $\nu.\text{sign}$ will be accepted by the blockchain in case of registration of the state of the nanocontract on the ledger.

Nanocontract creation and update

The update mechanism for a nanocontract is similar to the update mechanism of a simple payment channel and thus will not be explained in detail. The only substantial differences are the following:

1. After *Alice* proposes a nanocontract update, *Bob* has time \mathcal{T} to reply whether he agrees with this update or not. If he agrees the update goes through, else the state of the nanocontract is not updated (apart from increasing the version number). This is not considered a dispute, so (on-chain) nanocontract state registration does not need to take place.
2. In case of a successful update, the cash balance of both end-users in the underlying multistate channel ($\gamma.\text{cash}(\text{Alice})$ and $\gamma.\text{cash}(\text{Alice})$) are updated to reflect the fact that the nanocontract update has consumed or returned some funds to the end-users.

Each nanocontract has its own $\nu.\text{ver-num}$ and $\nu.\text{sign}$ field, so that several nanocontracts of the same multistate channel can be updated in parallel. Let ν' be the state of the nanocontract ν after an update. The only requirement is that

$$\begin{aligned} \nu'.\text{blocked}(\text{Alice}) + \nu'.\text{blocked}(\text{Bob}) &\leq \\ \nu.\text{blocked}(\text{Alice}) + \nu.\text{blocked}(\text{Bob}) & . \end{aligned}$$

This ensures that no two nanocontracts will together require more funds than are available in the multistate channel and thus that all nanocontracts can be updated in parallel. If it is the case that $\nu.\text{blocked}(\text{Alice}) + \nu.\text{blocked}(\text{Bob}) = 0$, we say that the nanocontract ν is **terminated**.

To create a new nanocontract ν , users simply apply the update mechanism. They have to ensure that $\nu.\text{nid}$ is a new, globally unique identifier and that the $\nu.\text{ver-num} = 0$.

Nanocontract registration

Registration of the state of a nanocontract on **MSContract** happens in case of dispute with regard to the state of the nanocontract or when the parties want to close the multistate channel. The registration mechanism is very similar to that of closing a simple payment channel, so will not be described in detail.

Given that a nanocontract ν is registered on the **MSContract** of the underlying multistate channel of ν , any end-user can unilaterally execute a nanocontract function **fun** by calling the **MSContract** function **execute** ($\nu.\text{nid}, \text{fun}, z$). **MSContract** then updates the state of the nanocontract on the ledger and returns the output to the end-users.

Nanocontract termination

Finally, when the end-users wish to close the multistate channel, they have to update all nanocontracts such that they are **terminated**, register their state (or alternatively register their state and then execute functions on the ledger until they are **terminated**) and then initiate a procedure similar to the closing of basic payment channels, which gives the opportunity to both end-users to publish their latest version of all nanocontracts of the multistate channel. The nanocontract states with the highest version number are accepted by the ledger as valid. Each end-user receives coins equal to the initial coins they contributed to the multistate channel, amended by the changes introduced by the nanocontracts. These coins are now available to use with other users of the ledger.

It may be the case that some nanocontracts cannot be updated to a **terminated** state due to dispute between end-users or design problems of the nanocontract. The end-users can have special provision in **MSContract** for such cases to be able to kill such misbehaving nanocontracts and distribute the funds in a predefined manner. Such a mechanism is not explicitly specified.

3.3 Virtual payment channels

Virtual payment channels are channels created on top of suitable preexisting multistate channels that facilitate trustless funds exchange between parties that do not share an on-chain channel. Going into more detail, a virtual payment channel γ is a tuple:

$$(\gamma.\text{id}, \gamma.\text{Alice}, \gamma.\text{Ingrid}, \gamma.\text{Bob}, \gamma.\text{cash}, \gamma.\text{subchan}, \\ \gamma.\text{validity}, \gamma.\text{ver-num}, \gamma.\text{sign})$$

Let *Alice* have a multistate channel with *Ingrid* ($Alice \xleftrightarrow{a} Ingrid$); also let *Bob* have a multistate channel with *Ingrid* ($Bob \xleftrightarrow{b} Ingrid$).

Channel creation

To build γ , two nanocontracts ν_a and ν_b are created, each on the corresponding multistate channel. ν_a has $\gamma.\text{cash}(Alice)$ blocked by *Alice* and $\gamma.\text{cash}(Bob)$ blocked by *Ingrid*. Similarly, ν_b has $\gamma.\text{cash}(Alice)$ blocked by *Ingrid* and $\gamma.\text{cash}(Bob)$ blocked by *Bob*. At a high level, a virtual payment channel creation protocol is as follows:

0. *Alice* and *Bob* discover that *Ingrid* is an intermediary. They also agree on the initial balance of γ .

1. *Alice* sends a signed ν_a to *Ingrid*.
2. *Ingrid* sends a signed ν_b to *Bob*.
3. *Bob* replies to *Ingrid* with ν_b , signed by the former.
4. *Ingrid* replies to *Alice* with ν_a , signed by the former.

We now say that there exists the virtual payment channel γ between *Alice* and *Bob* ($Alice \xleftrightarrow{\gamma} Bob$).

Channel update

Updating the cash balance of the channel can be accomplished in the same way as for the basic payment channels, with both *Alice* and *Bob* signing the new state with an incremented version number. Note that, in contrast to Lightning, the end-users do not need to interact with *Ingrid* at all to update the channel. This decreases the number of rounds needed for an update to 2 in the optimistic case that both *Alice* and *Bob* are honest. Furthermore, it somewhat increases the privacy of the end-users.

Closing the channel

In case all three parties are honest, they agree that they want to close γ and $\gamma.\text{validity}$ time has not yet passed, then both *Alice* and *Bob* attempt to terminate their respective nanocontract with *Ingrid*, ν_a and ν_b . The end-users send their latest version of γ to the intermediary, who expects a tuple with valid signatures by the initially registered end-users and a total balance equal to that of the initial state of the channel. If both end-users send different valid tuples, then *Ingrid* chooses the one with the higher version number as valid. Thus both nanocontracts can be terminated with each of the end-users unblocking their respective balance, as defined by the valid γ , on their multistate channel with *Ingrid*. The sum of coins *Ingrid* will unblock in both multistate channels will be equal to the sum of the original coins she blocked during the virtual payment channel creation, only redistributed between the two channels as defined by the latest γ state.

Alice can unilaterally register the ν_a nanocontract state on the ledger and provide her latest γ version, thus she does not need *Ingrid*'s cooperation to unblock her funds. If *Ingrid* learns a newer valid γ version from *Bob* (which means that *Alice* tried to cheat), then *Ingrid* can publish it within a predetermined timeframe and claim her rightful funds.

Furthermore, if the channel hasn't closed after $\gamma.\text{validity}$ time has passed, any of the three parties can unilaterally finalize the nanocontract(s) she has access to and unblock the respective funds.

Thus we have seen that no trust between the parties is necessary. Similarly to Lightning though, cooperating parties can unblock their funds faster and with less interaction with the ledger (and thus lower fees).

4 Sprites

Sprites [?] constitute an improvement upon Lightning [?] regarding the worst-case time needed to settle in case of a dispute. Consider a channel of l hops, where Δ is the time given to each participant to publish their state after a counterparty has unilaterally broadcast theirs. The worst-case time to settle in the case of Lightning is $\Theta(l\Delta)$, whereas in Sprites it is $\Theta(l + \Delta)$.

To achieve this, Sprites propose a smart contract called Preimage Manager (PM). Let $\mathcal{H}(\cdot)$ be a suitable hash function. Parties can interact with PM in the following way:

- Call `publish(x)` at time T : PM stores `timestamp`[$\mathcal{H}(x)$] = T .
- Call `published(h, T)`: PM returns `True` if
 - $h \in \text{timestamp}$ and
 - `timestamp`[h] $\leq T$,`False` otherwise.

In case all parties are honest, PM is not invoked, the entire interaction happens off-chain and needs $l + 1$ rounds to complete. In case a party misbehaves by delaying sending the preimage until the last possible moment (i.e. time Δ after she received the preimage from the previous link), she will have to publish the preimage to the blockchain instead of just sharing it with the next link in the chain of payments in order to ensure she gets her funds. Thus, the rest of the (honest) players can settle the channel by asking PM whether the hash they already know has been `published()`. This action can be completed concurrently, thus the maximum delay that can be incurred is $l + \Delta$.

5 General properties of Payment Channels

1. Number of participants in the channel
2. On-chain connection(s) between participants
3. Actions: open, update, execute, close

4. Who needs to sign for each action, who is notified, how many rounds of communication?
5. What information can one obtain by observing the blockchain?
6. Under what circumstances an operation cannot complete? (e.g. concurrency issues)
7. Which participants are aware of the identity of which participants?
8. Is there an upper bound to the amount of updates? How is this number decided?
9. Can a participant unilaterally commit on-chain?
10. Up to how much money can a participant unilaterally obtain?
11. What can a malicious party do? If it corrupts more participants it can do more?
12. Can a malicious/honest-but-curious party that is a participant learn who is transacting with who?
13. How much slower is the process in case of a malicious party?
14. How expensive are the actions? (CPU, memory, storage)
15. How expensive are interactions with the blockchain? (fees, time, etc.)





Fig. 1. Protocol for opening a Lightning channel



6 State of a channel

Consider a channel between *Alice* and *Bob*. Both parties hold some data locally that correspond to ownership of some funds in the channel. Here we define a concise way of representing this data.

What *Alice* has to hold, specific for this channel:

- keys:
 - local funding secret key
 - remote funding public key
 - local $\{\text{payment, htlc, delayed_payment, revocation}\}_{\text{basepoint_secret}}$
 - remote $\{\text{payment, htlc, delayed_payment, revocation}\}_{\text{basepoint}}$
 - seed (for local $\text{per_commitment_secrets}$)
 - remote $\text{per_commitment_secret}_{1,\dots,m-1}$
 - remote $\text{per_commitment_point}_{m,m+1}$
- *Alice*'s coins
- *Bob*'s coins
- every HTLC that is included in the latest irrevocably committed (local or remote) commitment:
 - direction ($Alice \rightarrow Bob$ or $Bob \rightarrow Alice$)
 - hash
 - preimage (or \perp if still unresolved)
 - coins
 - Is it included in local commitment_n ?
 - HTLC number
- signatures:
 - signature of local commitment_n with secret key corresponding to remote funding public key
 - for every HTLC included in local commitment_n , one signature of HTLC-Timeout if outgoing, HTLC-Success if incoming with secret key corresponding to remote $\text{htlc_pubkey}_n (= \text{htlc_basepoint} + \mathcal{H}(\text{remote per_commitment_point}_n || \text{remote htlc_basepoint}) \cdot G)$

The rest of the things used in the protocol can be derived by the above.

Representation of a channel's state (from the point of view of *Alice*):

- *Alice*'s coins c_{Alice}
- *Bob*'s coins c_{Bob}
- list of (coins, $\text{state} \in \{\text{proposed, committed}\}$) preimage, whether we have a signature), HTLCs

- negative coins are outgoing, positive are incoming
- HTLCs can either be simply proposed (not in an irrevocably committed remote transaction) or committed (the opposite). After the preimage is supplied (no matter the direction), the HTLC is considered settled and is discarded.

I.e. $\text{State}_{\text{Alice}, \text{pchid}} = (c_{\text{Alice}}, c_{\text{Bob}}, ((c_1, \text{state}_1), \dots, (c_k, \text{state}_k)))$

E.g. $\text{State}_{\text{Alice}, \text{pchid}} = (4, 5, ((0.1, \text{proposed}), (-0.2, \text{signed})))$

We do not include in the state elements whose contents are irrelevant (e.g. sigs, keys, hashes).

Π_{LN} (self is *Alice*)

- 1: Initialisation:
- 2: **channels**, **pendingOpen**, **pendingPay**, **pendingClose**, **newChannels**,
 closedChannels, **unclaimedOfferedHTLCs**, **unclaimedReceivedHTLCs**, **pendingGetPaid** $\leftarrow \emptyset$
- 3:
- 4: Upon receiving (REGISTER, delay) from \mathcal{E} :
- 5: **delay** \leftarrow delay
- 6: send (READ) to $\mathcal{G}_{\text{Ledger}}$ and assign largest block number to **lastPoll**
- 7: $(pk_{\text{Alice}}, sk_{\text{Alice}}) \leftarrow \text{genKey}()$
- 8: send (REGISTER, *Alice*, **delay**, pk_{Alice}) to \mathcal{A} [**Orfeas: delay to \mathcal{A} needed?**]
- 9:
- 10: Upon receiving (REGISTERED) from \mathcal{A} :
- 11: send (READ) to $\mathcal{G}_{\text{Ledger}}$ and assign reply to Σ_{Alice}
- 12: assign the sum of all output values that are exclusively spendable by *Alice* to **onChainBalance**
- 13: send (REGISTERED) to \mathcal{E}
- 14:
- 15: Upon receiving any message (M) except for (REGISTER):
- 16: **if** if haven't received (REGISTER) from \mathcal{E} **then**
- 17: send (INVALID, M) to \mathcal{A} and ignore message
- 18: **end if**
- 19:
- 20: Upon receiving (OPENCHANNEL, $\text{pid}_{\text{Alice}}, \text{pid}_{\text{Bob}}, x$) from \mathcal{E} :
- 21: $((ph_F, sh_F), (ph_{\text{basepay}}, sh_{\text{basepay}}), (ph_{\text{basepay}}, sh_{\text{basepay}}), (ph_{\text{basehtlc}}, sh_{\text{basehtlc}}), \text{seed}, (ph_{\text{basepay}}, sh_{\text{basepay}})) \leftarrow \text{GetKeys}()$
- 22: $sh_{\text{com},1} \leftarrow \text{genFromSeed}(\text{seed}, 1)$
- 23: $ph_{\text{com},1} \leftarrow \text{pkFromSk}(sh_{\text{com},1})$
- 24: choose unique temporary ID tid \triangleright unique for the two parties

```

25:   associate keys with  $tid$ 
26:   add  $(Alice, Bob, x, \text{delay}, (ph_F, sh_F), (ph\_base_{pay}, sh\_base_{pay}), (ph\_base_{dpay},$ 
       $sh\_base_{dpay}), (ph\_base_{htlc}, sh\_base_{htlc}), (ph\_base_{com,1}, sh\_base_{com,1}),$ 
       $(ph\_base_{rev}, sh\_base_{rev}), tid)$  to pendingOpen
27:   send  $(\text{OPENCHANNEL}, x, \text{delay}, ph_F, ph\_base_{pay}, ph\_base_{dpay}, ph\_base_{htlc},$ 
       $ph_{com,1}, ph\_base_{rev}, tid)$  to  $Bob$  and  $\mathcal{A}$ 
28:
29: function GENFROMSEED(seed, index) [TODO: change font]
30:    $P \leftarrow seed$ 
31:   for B in  $\log(k)$  down to 0 do
32:     if bit B in index is 1 then
33:       flip bit B in  $P$ 
34:        $P \leftarrow \mathcal{H}(P)$ 
35:     end if
36:   end for
37:   return  $P$ 
38: end function
39:
40: Upon receiving  $(\text{OPENCHANNEL}, x, \text{BobDelay}, pt_F, pt\_base_{pay}, pt\_base_{dpay},$ 
       $pt\_base_{htlc}, pt_{com,1}, pt\_base_{rev}, tid)$  from  $Bob$ :
41:   ensure  $tid$  has not been used yet with  $Bob$ 
42:    $((ph_F, sh_F), (ph\_base_{pay}, sh\_base_{pay}), (ph\_base_{dpay}, sh\_base_{dpay}),$ 
       $(ph\_base_{htlc}, sh\_base_{htlc}), \text{seed}, (ph\_base_{rev}, sh\_base_{rev})) \leftarrow \text{GetKeys}()$ 
43:    $sh_{com,1} \leftarrow \text{genFromSeed}(\text{seed}, 1)$ 
44:    $ph_{com,1} \leftarrow \text{pkFromSk}(sh_{com,1})$ 
45:   associate keys with  $tid$  and store in pendingOpen
46:   send  $(\text{ACCEPTCHANNEL}, \text{delay}, ph_F, ph\_base_{pay}, ph\_base_{dpay}, ph\_base_{htlc},$ 
       $ph_{com,1}, ph\_base_{rev}, tid)$  to  $Bob$  and  $\mathcal{A}$ 
47:
48: Upon receiving  $(\text{ACCEPTCHANNEL}, \text{remoteDelay}, pt_F, pt\_base_{pay}, pt\_base_{dpay},$ 
       $pt\_base_{htlc}, pt_{com,1}, pt\_base_{rev}, tid)$  from  $Bob$ :
49:   ensure there is a temporary ID  $tid$  with  $Bob$  in pendingOpen on
      which ACCEPTCHANNEL hasn't been received
50:   associate received keys with  $tid$ 
51:   send (READ) to  $\mathcal{G}_{\text{Ledger}}$  and assign reply to  $\Sigma_{Alice}$ 
52:   assign to prevout a transaction output found in  $\Sigma_{Alice}$  that is
      currently exclusively spendable by  $Alice$  and has value  $y \geq x$ 

```

53: $F \leftarrow \text{TX}$ {input spends prevout with a **signature**(TX, sk_{Alice}),
 output 0 pays $y - x$ to pk_{Alice} now, output 1 pays x to $tid.ph_F \wedge pt_F$
 now}
 54: $pchid \leftarrow \mathcal{H}(F)$
 55: replace tid with $pchid$ in storage
 56: $pt_{\text{rev},1} \leftarrow pt_{\text{base_rev}} \cdot \mathcal{H}(pt_{\text{base_rev}} || pt_{\text{com},1}) + pt_{\text{com},1} \cdot \mathcal{H}(pt_{\text{com},1} || pt_{\text{base_rev}})$
 57: $ph_{\text{dpay},1} \leftarrow ph_{\text{base_dpay}} + \mathcal{H}(ph_{\text{com},1} || ph_{\text{base_dpay}})$
 58: $ph_{\text{pay},1} \leftarrow ph_{\text{base_pay}} + \mathcal{H}(ph_{\text{com},1} || ph_{\text{base_pay}})$
 59: **remoteCom**, **remoteCom**₁ $\leftarrow \text{TX}$ {input: output 1 of F , output:
 ($x, ph_{\text{pay},1}$)}
 60: **localCom** $\leftarrow \text{TX}$ {input: output 1 of F , output: ($x, pt_{\text{rev},1} \vee (ph_{\text{dpay},1}, \text{remoteDelay} + k + 1 \text{ relative})$)}
 61: add **remoteCom** and **localCom** to channel entry in **pendingOpen**
 62: **sig** $\leftarrow \text{signature}(\text{remoteCom}_1, sh_F)$
 63: **lastRemoteSigned** $\leftarrow 0$
 64: send (**FUNDINGCREATED**, tid , $pchid$, **sig**) to *Bob* and \mathcal{A}
 65:
 66: Upon receiving (**FUNDINGCREATED**, tid , $pchid$, **BobSig**₁) from *Bob*:
 67: ensure there is a temporary ID tid with *Bob* in **pendingOpen** on
 which we have sent up to **ACCEPTCHANNEL**
 68: $ph_{\text{rev},1} \leftarrow ph_{\text{base_rev}} \cdot \mathcal{H}(ph_{\text{base_rev}} || ph_{\text{com},1}) + ph_{\text{com},1} \cdot \mathcal{H}(ph_{\text{com},1} || ph_{\text{base_rev}})$
 69: $pt_{\text{dpay},1} \leftarrow pt_{\text{base_dpay}} + \mathcal{H}(pt_{\text{com},1} || pt_{\text{base_dpay}})$
 70: $pt_{\text{pay},1} \leftarrow pt_{\text{base_pay}} + \mathcal{H}(pt_{\text{com},1} || pt_{\text{base_pay}})$
 71: **localCom**, **localCom**₁ $\leftarrow \text{TX}$ {input: output 1 of F , output: ($x, pt_{\text{pay},1}$)}
 72: ensure **verify**(**localCom**₁, **BobSig**₁, pt_F) = **True**
 73: **remoteCom**, **remoteCom**₁ $\leftarrow \text{TX}$ {input: output 1 of F , output:
 ($x, ph_{\text{rev}} \vee (pt_{\text{dpay}}, \text{delay} + k + 1 \text{ relative})$)}
 74: add **BobSig**₁, **remoteCom**₁ and **localCom**₁ to channel entry in **pendingOpen**
 75: **sig** $\leftarrow \text{signature}(\text{remoteCom}_1, sh_F)$
 76: mark channel as “broadcast, no **FUNDINGLOCKED**”
 77: **lastRemoteSigned**, **lastLocalSigned** $\leftarrow 0$
 78: send (**FUNDINGSIGNED**, $pchid$, **sig**) to *Bob* and \mathcal{A}
 79:
 80: Upon receiving (**FUNDINGSIGNED**, $pchid$, **BobSig**₁) from *Bob*:
 81: ensure there is a channel ID $pchid$ with *Bob* in **pendingOpen** on
 which we have sent up to **FUNDINGCREATED**
 82: ensure **verify**(**localCom**, **BobSig**₁, pb_F) = **True**
 83: **localCom**₁ $\leftarrow \text{localCom}$
 84: **lastLocalSigned** $\leftarrow 0$
 85: add **BobSig**₁ to channel entry in **pendingOpen**

```

86:   sig ← signature( $F, sk_{Alice}$ )
87:   mark  $pchid$  in pendingOpen as “broadcast, no FUNDINGLOCKED”
88:   send (SUBMIT, (sig,  $F$ )) to  $\mathcal{G}_{Ledger}$ 
89:
90: function GETKEYS [TODO: change font]
91:   ( $p_F, s_F$ ) ← genKey()                                ▷ For  $F$  output
92:   ( $p_{pay}, s_{pay}$ ) ← genKey()                          ▷ For com output to remote
93:   ( $p_{dpay}, s_{dpay}$ ) ← genKey()                        ▷ For com output to self
94:   ( $p_{htlc}, s_{htlc}$ ) ← genKey()                        ▷ For htlc output to self
95:   seed  $\xleftarrow{\$} U(k)$                                        ▷ For per com point
96:   ( $p_{rev}, s_{rev}$ ) ← genKey()                          ▷ For revocation in com
97:   return (( $p_F, s_F$ ), ( $p_{pay}, s_{pay}$ ), ( $p_{dpay}, s_{dpay}$ ),
98:           ( $p_{htlc}, s_{htlc}$ ), seed, ( $p_{rev}, s_{rev}$ ))
99: end function
100:
101: [TODO: explicitly add keys et al to channel]
102: Upon receiving (CHECKNEW,  $Alice, Bob, x$ ) from  $\mathcal{E}$ : ▷ new message:
    represents lnd polling daemon
103:   ensure there is a matching channel in pendingOpen with id  $pchid$ 
    with a “broadcast” mark
104:   send (READ) to  $\mathcal{G}_{Ledger}$  and assign reply to  $\Sigma_{Alice}$ 
105:   ensure  $\exists$  unspent TX in  $\Sigma_{Alice}$  with ID  $pchid$  and a  $(x, ph_F \wedge pt_F)$ 
    output
106:    $sh_{com,2} \leftarrow \text{genFromSeed}(\text{seed}, 2)$ 
107:    $ph_{com,2} \leftarrow \text{pkFromSk}(sh_{com,2})$ 
108:   add TX to channel data
109:   replace “broadcast” mark in channel with “in state”
110:   if channel is marked as “in state, FUNDINGLOCKED” then
111:     move channel data from pendingOpen to channels
112:     add receipt of channel to newChannels
113:   end if
114:   send (FUNDINGLOCKED,  $pchid, ph\_base_{com,2}$ ) to  $Bob$ 
115:
116: Upon receiving (FUNDINGLOCKED,  $pchid, pt\_base_{com,2}$ ) from  $Bob$ :
117:   ensure there is a channel with ID  $pchid$  with  $Bob$  in pendingOpen
    with a “no FUNDINGLOCKED” mark
118:   ensure  $pk(st_{com,n}) = pt_{com,n}$ 
119:   replace “no FUNDINGLOCKED” mark in channel with “FUNDINGLOCKED”
120:   ensure channel has an “in state” mark

```

```

121:   generate 2nd remote delayed payment, htlc, payment keys
122:   add TX to channel data
123:   move channel data from pendingOpen to channels
124:   add receipt of channel to newChannels
125:
126: Upon receiving (POLL) from  $\mathcal{E}$ :
127:   send (READ) to  $\mathcal{G}_{\text{Ledger}}$  and assign reply to  $\Sigma_{\text{Alice}}$ 
128:   assign largest block number in  $\Sigma_{\text{Alice}}$  to lastPoll
129:   toSubmit  $\leftarrow \emptyset$ 
130:   for all  $\tau \in \text{unclaimedOfferedHTLCs}$  do
131:     if input of  $\tau$  has been spent then  $\triangleright$  by remoteHTLC-success
132:       remove  $\tau$  from unclaimedOfferedHTLCs
133:     else if input of  $\tau$  has not been spent and timelock is over
134:       then
135:         remove  $\tau$  from unclaimedOfferedHTLCs
136:         add  $\tau$  to toSubmit
137:       end if
138:     end for
139:   for all  $\text{remoteCom}_n \in \Sigma_{\text{Alice}}$  that spend  $F$  of a channel  $\in \text{channels}$ 
140:   do
141:     if we do not have  $sh_{\text{rev},n}$  then  $\triangleright$  Honest closure
142:       for all received HTLC outputs  $i$  of  $\text{remoteCom}_n$  do
143:         if we know the preimage  $R$  then
144:           TX  $\leftarrow$  {input:  $i$  HTLC output of  $\text{remoteCom}_n$  with
145:              $(ph_{\text{htlc},n}, R)$  as method, output:  $pk_{\text{Alice}}$ }
146:           sig  $\leftarrow$  signature(TX,  $sh_{\text{htlc},n}$ )
147:           add (sig, TX) to toSubmit
148:         else
149:           add (channel,  $\text{remoteCom}_n$ ,  $h$ ,  $sh_{\text{htlc},n}$ ) to unclaimedReceivedHTLCs
150:         end if
151:       end for
152:     for all unspent offered HTLC outputs  $i$  of  $\text{remoteCom}_n$  do
153:       TX  $\leftarrow$  {input:  $i$  HTLC output of  $\text{remoteCom}_n$  with
154:          $ph_{\text{htlc},n}$  as method, output:  $pk_{\text{Alice}}$ }
155:       sig  $\leftarrow$  signature(TX,  $sh_{\text{htlc},n}$ )
156:       if timelock has not expired then
157:         add (sig, TX) to unclaimedOfferedHTLCs
158:       else if timelock has expired then
159:         add (sig, TX) to toSubmit
160:       end if

```



```

157:         end for
158:     else ▷ malicious closure
159:          $\text{rev} \leftarrow \text{TX} \{ \text{inputs: all } \text{remoteCom}_n \text{ outputs, choosing } ph_{\text{rev},n} \}$ 
        method, output:  $pk_{\text{Alice}}$ 
160:          $\text{sig} \leftarrow \text{signature}(\text{rev}, sh_{\text{rev},n})$ 
161:         add (sig, rev) to toSubmit
162:     end if
163:     move channel from channels to closedChannels
164: end for
165: send (SUBMIT, toSubmit) to  $\mathcal{G}_{\text{Ledger}}$ 
166:
167: [Orfeas: maybe leak queries to global functionalities to  $\mathcal{A}$ ?]
168: Upon receiving (PAY, Bob,  $x$ ,  $\overrightarrow{\text{path}}$ , receipt) from  $\mathcal{E}$ :
169:     ensure that  $\overrightarrow{\text{path}}$  consists of valid  $pchids$ 
170:     ensure that the first  $pchid \in \overrightarrow{\text{path}}$  has the same  $pchid$  as in
        receipt
171:     ensure that receipt corresponds to the latest version of an open
        channel  $\in \text{channels}$  in which we have at least  $x$ .
172:     choose unique payment ID  $payid$  ▷ unique for Alice and Bob
173:     add (Bob,  $x$ ,  $\overrightarrow{\text{path}}$ , receipt,  $payid$ , “waiting for invoice”) to pendingPay
174:     send (SENDINVOICE,  $payid$ ) to Bob and  $\mathcal{A}$ 
175:
176: Upon receiving (SENDINVOICE,  $payid$ ) from Bob:
177:     ensure there is no (Bob,  $payid$ ) entry in pendingGetPaid
178:     choose random, unique preimage  $R$ 
179:     add (Bob,  $R$ ,  $payid$ ) to pendingGetPaid
180:     send (INVOICE,  $\mathcal{H}(R)$ ,  $payid$ ) to Bob and  $\mathcal{A}$ 
181:
182: Upon receiving (INVOICE,  $h$ ,  $payid$ ) from Bob:
183:     ensure there is a (Bob,  $x$ ,  $\overrightarrow{\text{path}}$ , receipt,  $payid$ , “waiting for in-
        voice”) entry in pendingPay
184:     ensure  $h$  is valid (in the range of  $\mathcal{H}$ )
185:     remove entry from pendingPay
186:     send (READ) to  $\mathcal{G}_{\text{Ledger}}$  and assign largest block number to  $t$ 
187:      $m \leftarrow$  the concatenation of length  $\overrightarrow{\text{path}}$  ( $x$ ,  $\text{remoteDelay}_i$ ) pairs,
        where the last  $\text{remoteDelay}$  is  $t+2k+1+\text{BobDelay}$  and every previous
         $\text{remoteDelay}$  is incremented by  $3k + \text{RHSDelay}$  [TODO: Alice doesn't
        know these Bob, RHS delays]
188:      $(\mu_0, \delta_0) \leftarrow \text{SphinxCreate}(m, \text{public keys of } \overrightarrow{\text{path}} \text{ parties})$ 

```

```

189:   let remoteComn the latest signed remote commitment tx
190:   reduce simple payment output in remoteCom by  $x$ 
191:   add an additional  $(x, ph_{\text{rev},n+1} \vee (ph_{\text{htlc},n+1} \wedge pt_{\text{htlc},n+1}, \text{ on preimage of } h) \vee ph_{\text{htlc},n+1}, \text{ largest } \mathbf{remoteDelay} \text{ absolute})$  output (all with  $n+1$  keys) to remoteCom, marked with HTLCNo
192:   increment HTLCNopchid by one and associate  $x, h, pchid$  with it
193:   mark HTLCNo as “sender”
194:   send (UPDATEADDHTLC, first  $pchid$  of  $\overrightarrow{\text{path}}$ , HTLCNopchid,  $x, h$ , largest remoteDelay,  $(\mu_0, \delta_0)$ ) to  $pchid$  channel counterparty and  $\mathcal{A}$ 
195:
196: Upon receiving (UPDATEADDHTLC,  $pchid$ , HTLCNo,  $x, h$ , remoteDelay,  $M$ ) from Bob:
197:   ensure  $pchid$  corresponds to an open channel in channels where Bob has at least  $x$ 
198:   ensure HTLCNo = HTLCNopchid + 1
199:    $(pchid', x', \mathbf{remoteDelay}', \delta) \leftarrow \text{SphinxPeel}(sk_{\text{Alice}}, M)$ 
200:   if  $\delta = \text{receiver}$  then
201:     ensure  $pchid' = \perp, x = x', \mathbf{remoteDelay} = \mathbf{remoteDelay}' = 2k + 1 + \text{delay}$ 
202:     increment HTLCNopchid by one
203:     mark HTLCNo as “receiver”
204:   else ▷ We are an intermediary
205:     ensure  $x = x', \mathbf{remoteDelay} = \mathbf{remoteDelay}' + 3k + \text{delay}$ 
206:     ensure  $pchid'$  corresponds to an open channel in channels
207:   where we have at least  $x$ 
208:     increment HTLCNopchid by one
209:     mark HTLCNo as “intermediary”
210:   end if
211:   let remoteComn the latest signed remote commitment tx
212:   reduce delayed payment output in remoteCom by  $x$ 
213:   add an  $(x, ph_{\text{rev},n+1} \vee (ph_{\text{htlc},n+1} \wedge pt_{\text{htlc},n+1}, \mathbf{remoteDelay} \text{ absolute}) \vee ph_{\text{htlc},n+1}, \text{ on preimage of } h)$  htlc output (all with  $n+1$  keys) to remoteCom, marked with HTLCNo
214:   if  $\delta = \text{receiver}$  then
215:     retrieve  $R : \mathcal{H}(R) = h$  from pendingGetPaid
216:     add (HTLCNo,  $R$ ) to pendingFulfillspchid
217:   else if  $\delta \neq \text{receiver}$  then ▷ Send HTLC to next hop
218:     retrieve  $pchid'$  data
219:     let remoteComn the latest signed remote commitment tx
220:     reduce simple payment output in remoteCom by  $x$ 

```

```

220:      add an additional  $(x, ph_{\text{rev},n+1} \vee (ph_{\text{htlc},n+1} \wedge pt_{\text{htlc},n+1})$ , on preimage
      of  $h) \vee ph_{\text{htlc},n+1}$  remoteDelay' absolute) output (all with  $n+1$  keys)
      to remoteCom, marked with HTLCNo
221:      increment HTLCNo by 1
222:       $M' \leftarrow \text{SphinxPrepare}(M, \delta, sk_{\text{Alice}})$ 
223:      send (UPDATEADDHTLC,  $pchid'$ , HTLCNo,  $x, h, \text{remoteDelay}'$ ,  $M$ )
      to  $pchid'$  counterparty
224:  end if
225:
226: Upon receiving (UPDATEFULFILLHTLC,  $pchid$ , HTLC_no,  $R$ ) from
    Bob:
227:   ensure HTLC_no  $\leq$  lastRemoteSigned, HTLC_no  $\leq$  lastLocalSigned
228:   ensure HTLC_no is an offered HTLC (localCom has  $h$  tied to a
    public key that we own)
229:   ensure  $\mathcal{H}(R) = h$ , where  $h$  is the hash in the HTLC with number
    HTLC_no
230:   add value of HTLC to delayed payment of remoteCom
231:   remove HTLC output with number HTLC_no from remoteCom
232:   if we have a channel  $pchid'$  that has a received HTLC with hash
     $h$  with number HTLCNo' then  $\triangleright$  We are intermediary
233:     if HTLCNo'  $\leq$  lastRemoteSigned' then  $\triangleright$  HTLC committed
234:       send (READ) to  $\mathcal{G}_{\text{Ledger}}$  and assign reply to  $\Sigma_{\text{Alice}}$ 
235:       if latest remoteCom' $_n \in \Sigma_{\text{Alice}}$  then  $\triangleright$  counterparty has
    gone on-chain
236:       TX  $\leftarrow$  {input: remoteCom' HTLC output with number
    HTLCNo', output:  $pk_{\text{Alice}}$ }
237:       sig  $\leftarrow$  signature(TX,  $sh_{\text{htlc},n}$ )
238:       send (SUBMIT, (sig,  $R$ , TX)) to  $\mathcal{G}_{\text{Ledger}}$   $\triangleright$  shouldn't be
    already spent by remote HTLCTimeout
239:     else  $\triangleright$  counterparty still off-chain
240:       send (UPDATEFULFILLHTLC,  $pchid'$ , HTLCNo,  $R$ ) to coun-
    terparty
241:   end if
242:   else  $\triangleright$  we haven't received REVOKEANDACK
243:     add (HTLCNo',  $R$ ) to pendingFulfills $_{pchid'}$ 
244:   end if
245: end if
246:
247: Upon receiving (COMMIT,  $pchid$ ) from  $\mathcal{E}$ :
248:   ensure that there is a channel  $\in$  channels with ID  $pchid$ 

```

```

249:   retrieve latest remote commitment tx remoteComn in channel
250:   ensure remoteCom  $\neq$  remoteComn  $\triangleright$  there are uncommitted
updates
251:   ensure channel is not marked as “waiting for REVOKEANDACK”
252:   remoteComn+1  $\leftarrow$  remoteCom
253:   ComSig  $\leftarrow$  signature(remoteComn+1, shF)
254:   HTLCSigs  $\leftarrow$   $\emptyset$ 
255:   for i from lastRemoteSigned to HTLCNo do
256:     remoteHTLCn+1,i  $\leftarrow$  TX {input: HTLC output i of remoteComn+1,
output: (chtlc,i, phrev,n+1  $\vee$  (ptdpay,n+1, delay + k + 1 relative))}
257:     add signature(remoteHTLCn+1,i, shhtlc,n+1) to HTLCSigs
258:   end for
259:   add signature(remoteHTLCn+1,m+1, shhtlc,n+1) to HTLCSigs
260:   lastRemoteSigned  $\leftarrow$  HTLCNo
261:   mark channel as “waiting for REVOKEANDACK”
262:   send (COMMITMENTSIGNED, pchid, ComSig, HTLCSigs) to pchid
counterparty
263:
264: Upon receiving (COMMITMENTSIGNED, pchid, comSign+1, HTLCSigsn+1)
from Bob:
265:   ensure that there is a channel  $\in$  channels with ID pchid with
Bob
266:   retrieve latest local commitment tx localComn in channel
267:   ensure localCom  $\neq$  localComn and localCom  $\neq$  pendingLocalCom
 $\triangleright$  there are uncommitted updates
268:   ensure verify(localCom, comSign+1, ptF) = true
269:   for i from lastLocalSigned to HTLCNo do
270:     localHTLCn+1,i  $\leftarrow$  TX {input: HTLC output i of localCom,
output: (chtlc,i, phrev,n+1  $\vee$  (ptdpay,n+1, remoteDelay + k + 1 relative))}
271:     ensure verify(localHTLCn+1,i, HTLCSigsn+1,i, pthtlc,n+1) =
true
272:   end for
273:   pendingLocalCom  $\leftarrow$  localCom
274:   mark pendingLocalCom as “irrevocably committed”
275:   shcom,n+2  $\leftarrow$  genFromSeed(seed, n + 2)
276:   phcom,n+2  $\leftarrow$  pkFromSk(shcom,n+2)
277:   send (REVOKEANDACK, pchid, shcom,n, phcom,n+2) to Bob
278:
279: Upon receiving (REVOKEANDACK, pchid, stcom,n, ptcom,n+2) from Bob:

```

```

280:   ensure there is a channel  $\in$  channels with Bob with ID pchid
      marked as “waiting for REVOKEANDACK”
281:   ensure  $pk(st_{com,n}) = pt_{com,n}$ 
282:   mark remoteComn+1 as “irrevocably committed”
283:   localComn+1  $\leftarrow$  pendingLocalCom
284:   unmark channel
285:    $sh_{rev,n} \leftarrow sh\_base_{rev} \cdot \mathcal{H}(ph\_base_{rev} || ph_{com,n}) + st_{com,n} \cdot \mathcal{H}(ph_{com,n} || ph\_base_{rev})$ 
286:    $ph_{rev,n+2} \leftarrow ph\_base_{rev} \cdot \mathcal{H}(ph\_base_{rev} || ph_{com,n+2}) + pt_{com,n+2} \cdot$ 
       $\mathcal{H}(ph_{com,n+2} || ph\_base_{rev})$ 
287:    $pt_{rev,n+2} \leftarrow pt\_base_{rev} \cdot \mathcal{H}(pt\_base_{rev} || pt_{com,n+2}) + pt_{com,n+2} \cdot$ 
       $\mathcal{H}(pt_{com,n+2} || pt\_base_{rev})$ 
288:    $ph_{dpay,n+2} \leftarrow ph\_base_{dpay} + \mathcal{H}(ph_{com,n+2} || ph\_base_{dpay})$ 
289:    $pt_{dpay,n+2} \leftarrow pt\_base_{dpay} + \mathcal{H}(pt_{com,n+2} || pt\_base_{dpay})$ 
290:    $ph_{pay,n+2} \leftarrow ph\_base_{pay} + \mathcal{H}(ph_{com,n+2} || ph\_base_{pay})$ 
291:    $pt_{pay,n+2} \leftarrow pt\_base_{pay} + \mathcal{H}(pt_{com,n+2} || pt\_base_{pay})$ 
292:    $ph_{htlc,n+2} \leftarrow ph\_base_{htlc} + \mathcal{H}(ph_{com,n+2} || ph\_base_{htlc})$ 
293:    $pt_{htlc,n+2} \leftarrow pt\_base_{htlc} + \mathcal{H}(pt_{com,n+2} || pt\_base_{htlc})$ 
294:
295: Upon receiving (PUSH, pchid) from  $\mathcal{E}$ :
296:   ensure that there is a channel  $\in$  channels with ID pchid
297:   choose a member (HTLC_no, R) of pendingFulfillspchid that
      is both in an “irrevocably committed” remoteComn and localComn
298:   remove (HTLC_no, R) from pendingFulfillspchid
299:   send (UPDATEFULFILLHTLC, pchid, HTLC_no, R) to pchid counterparty
300: Upon receiving (CLOSECHANNEL, receipt) from  $\mathcal{E}$ :
301:   ensure receipt corresponds to an open channel  $\in$  channels
302:   assign latest channel sequence number to n
303:   HTLCs  $\leftarrow \emptyset$ 
304:   for every HTLC output  $\in$  localComn with number i do
305:      $sig \leftarrow \text{signature}(\text{localHTLC}_{n,i}, sh_{htlc,n})$ 
306:     add  $(sig, \text{HTLCSigs}_{n,i}, \text{localHTLC}_{n,i})$  to HTLCs
307:   end for
308:    $sig \leftarrow \text{signature}(\text{localCom}_n, sh_F)$ 
309:   remove channel from channels
310:   send (SUBMIT, (sig, remoteSign, localComn), HTLCs) to  $\mathcal{G}_{\text{Ledger}}$ 

```

A well-formed transaction contains:

- A list of inputs

- A list of outputs
- An arbitrary payload (optional)

Each input must be connected to a single valid, previously unconnected (unspent) output in the state.

We assume a one-way, collision-free hash function \mathcal{H} that creates the id of each transaction.

A well-formed output contains:

- A value in coins
- A list of spending methods. An input that spends this output must specify exactly one of the available spending methods.

A well-formed spending method contains any combination of the following:

- Public keys in disjunctive normal form. An input that spends using this spending method must contain signatures made with the private keys that correspond to the public keys of one of the conjunctions. If empty, no signatures are needed.
- Absolute locktime in block height, transaction height or time. The output can be spent by an input to a transaction that is added to the state after the specified block height, transaction height or time. If empty, output can be spent immediately after being added to the state.
- Relative locktime in block height, transaction height or time. The output can be spent by an input that is added to the state after the current output has been part of the state for the specified number of blocks, transactions or time. If empty, output can be spent immediately after being added to the state.
- Hashlock value. The output can be spent by an input that contains a preimage that hashes to the hashlock value. If empty, the input does not need to specify a preimage.

A well-formed input contains:

- A reference to the output and the spending method it spends
- A set of signatures that correspond to one of the conjunctions of public keys in the referred spending method (if needed)
- A preimage that hashes to the hashlock value of the referred spending method (if needed)

Lastly, the sum of coins of the outputs referenced by the inputs of the transaction (to-be-spent outputs) should be greater than or equal to the sum of coins of the outputs of the transaction.

We say that an unspent output is currently exclusively spendable by a player *Alice* with a public key pk and a hash list hl if for each spending method one of the following two holds:

- It still has a locktime that has not expired and thus is currently unspendable, or
- The only specified public key is pk and if there is a hashlock, its hash is contained in hl .

If an output is exclusively spendable, we say that its coins are exclusively spendable.

Functionality $\mathcal{F}_{\text{PayNet}}$

Parameters:

- one-way, collision-free hash function \mathcal{H} (for generating transaction IDs)
-

Interface (messages from \mathcal{E}):

- (REGISTER)
 - (SETDELAY, delay)
 - (OPENCHANNEL, self, peer, selfCoins)
 - (CLOSECHANNEL, receipt)
 - (PAY, peer, coins, path, receipt)
-

Initialisation:

- 1: Initialisation:
 - 2: $\text{channels}, \text{pendingPay}, \text{pendingOpen}, \text{corrupted} \leftarrow \emptyset$
 - 3:
-

Responses to messages:

- 1: Upon receiving (REGISTER, delay) from *Alice*:
 - 2: $\text{delay}(\text{Alice}) \leftarrow \text{delay}$
 - 3: $\text{pendingUpdates}(\text{Alice}), \text{newChannels}(\text{Alice}), \text{blindTime}(\text{Alice}) \leftarrow \emptyset$
 - 4: send (READ) to $\mathcal{G}_{\text{Ledger}}$ as *Alice* and assign largest block number to $\text{lastPoll}(\text{Alice})$
 - 5: send (REGISTER, *Alice*, delay) to \mathcal{S}
 - 6:
 - 7: Upon receiving (REGISTERDONE, *Alice*, x , pubKey) from \mathcal{S} :
 - 8: send (READ) to $\mathcal{G}_{\text{Ledger}}$ as *Alice* and assign reply to Σ_{Alice}
-

```

9:   ensure that there are exactly  $x$  coins in  $\Sigma_{Alice}$  that can be exclusively spent
   by pubKey
10:  onChainBalance(Alice) ← x
11:  offChainBalance(Alice) ← 0
12:  pubKey(Alice) ← pubKey
13:  send (REGISTERED) to Alice
14:
15:  Upon receiving any message except for (REGISTER) from Alice:
16:    ignore message if Alice has not registered
17:
18:  Upon receiving (CORRUPTED, Alice) from  $\mathcal{S}$ :
19:    add Alice to corrupted
20:
21:  Upon receiving (OPENCHANNEL, Alice, Bob,  $x$ ) from Alice:
22:    choose unique channel ID fchid
23:    pendingOpen(fchid) ← (Alice, Bob, x)
24:    send (OPENCHANNEL, Alice, Bob,  $x$ , fchid) to  $\mathcal{S}$ 
25:
26:  Upon receiving (CHANNELOPENED,  $p_{Alice,F}$ ,  $p_{Bob,F}$ , fchid, pchid) from  $\mathcal{S}$ :
27:    ensure that there is no channel  $\in$  channels with ids pchid, fchid
28:     $(Alice, Bob, x) \leftarrow \text{pendingOpen}(fchid)$ 
29:    send (READ) to  $\mathcal{G}_{Ledger}$  as Alice and assign reply to  $\Sigma_{Alice}$ 
30:    ensure that there is a TX  $F \in \Sigma_{Alice}$  with a  $(x, (p_{Alice,F} \wedge p_{Bob,F}))$  output
    such that  $\mathcal{H}(F) = pchid$ 
31:    pendingOpen(fchid) ← ⊥
32:    offChainBalance(Alice) ← offChainBalance(Alice) + x [Orfeas: remove
    on/offChainBalance?]
33:    onChainBalance(Alice) ← offChainBalance(Alice) - x
34:    channel  $\leftarrow (Alice, Bob, x, 0, 0, fchid, pchid)$ 
35:    add channel to channels
36:    add receipt(channel) to newChannels(Alice) and newChannels(Bob)
37:
38:  Upon receiving (PAY, Bob,  $x$ ,  $\overrightarrow{\text{path}}$ , receipt) from Alice:
39:    ensure that  $(Alice, c) \in \text{receipt}$  and  $c \geq x$ 
40:    ensure that there is a channel  $\in$  channels : receipt(channel) = receipt
41:    ensure that  $\overrightarrow{\text{path}}$  consists of channels  $\in$  channels
42:    ensure that each consecutive pair of channels in  $\overrightarrow{\text{path}}$  has a common mem-
    ber
43:    choose unique payment ID payid
44:    add  $(Alice, Bob, x, \overrightarrow{\text{path}}, \text{payid})$  to pendingPay
45:    send (PAY, Alice, Bob,  $x$ ,  $\overrightarrow{\text{path}}$ , receipt, payid) to  $\mathcal{S}$ 
46:
47:  Upon receiving (RESOLVEPAY, payid, Charlie) from  $\mathcal{S}$ :
48:    retrieve  $(Alice, Bob, x, \overrightarrow{\text{path}})$  with ID payid and remove it from pendingPay
49:    if  $(Charlie \neq Alice$  and  $Charlie \notin \text{corrupted})$  or  $Charlie \notin \overrightarrow{\text{path}}$  then

```



```

50:      halt [Aggelos: or ignore?]
51:      [Orfeas: In the protocol, even negligent players cannot lose
money here because the next hop is done by the protocol (without
permission from the environment). So I removed negligent from the
check above.]
52:    end if
53:    for all channels  $\in \overrightarrow{\text{path}}$  starting from the one where Charlie pays do
54:      in the first iteration, Charlie is payer. In subsequent iterations, payer
is the unique player that has been paid but has not paid. The other channel
party is payee
55:      if payer has  $x$  or more in channel then
56:        update channel to the next version and transfer  $x$  from payer to
payee
57:        add receipt(channel) to both parties' pendingUpdates
58:      else
59:        revert all updates and remove them from pendingUpdates
60:        [Orfeas: entire if may be avoided by simply not sending a
message to Alice]
61:        if all players on path from Alice up to and including failed payer
are honest then
62:          send (NOTPAID, Bob,  $x$ ,  $\overrightarrow{\text{path}}$ , receipt) to Alice
63:        else
64:          send (REPORTNOTPAID, payid) to  $\mathcal{S}$  [Orfeas: TODO: split in
two messages]
65:          if reply from  $\mathcal{S}$  is (DOREPORT, payid) then
66:            send (NOTPAID, Bob,  $x$ ,  $\overrightarrow{\text{path}}$ , receipt) to Alice
67:          end if
68:        end if
69:        [Orfeas: end of possibly avoidable if]
70:      end if
71:    end for
72:    offChainBalance(Charlie)  $\leftarrow$  offChainBalance(Charlie)  $- x$ 
73:    offChainBalance(Bob)  $\leftarrow$  offChainBalance(Bob)  $+ x$ 
74:    if Charlie = Alice then
75:      send (PAID, Bob,  $x$ ,  $\overrightarrow{\text{path}}$ , receipt) to Alice
76:    end if
77:
78: Upon receiving (CLOSECHANNEL, receipt) from Alice [Aggelos: (or  $\mathcal{S}$ ) ??
] [Orfeas: @Aggelos: why  $\mathcal{S}$ ?]
79:   ensure that there is a channel  $\in$  channels : receipt(channel) = receipt
80:   retrieve fchid from channel
81:   pendingClose(fchid)  $\leftarrow$  Alice
82:   send (CLOSECHANNEL, fchid, Alice) to  $\mathcal{S}$ 
83:
84: Upon receiving (CHANNELCLOSED, fchid) from  $\mathcal{S}$ :
85:   Alice  $\leftarrow$  pendingClose(fchid)
86:   retrieve Charlie, Bob,  $x$ ,  $y$ , pchid from channel with ID fchid
87:   ensure that Charlie = Alice

```

```

88:   send (READ) to  $\mathcal{G}_{\text{Ledger}}$  as Alice and assign reply to  $\Sigma_{\text{Alice}}$ 
89:   ensure that transaction with ID pchid is in  $\Sigma_{\text{Alice}}$ , is spent,  $x$  of its coins
   are spendable or will be spendable exclusively by Alice and  $y$  of its coins are
   spendable exclusively by Bob
90:   pendingClose(fchid)  $\leftarrow \perp$ 
91:   add receipt of channel to closedChannels(Bob)
92:   remove channel from channels
93:   onChainBalance(Alice)  $\leftarrow$  onChainBalance(Alice) +  $x$ 
94:   onChainBalance(Bob)  $\leftarrow$  onChainBalance(Bob) +  $y$ 
95:   offChainBalance(Alice)  $\leftarrow$  offChainBalance(Alice) -  $x$ 
96:   offChainBalance(Bob)  $\leftarrow$  offChainBalance(Bob) -  $y$ 
97:   send (CHANNELCLOSED, receipt from channel) to Alice
98:
99: Upon receiving (POLL) from Alice:
100:  toReport(Alice)  $\leftarrow \emptyset$ 
101:  send (READ) to  $\mathcal{G}_{\text{Ledger}}$  as Alice and assign reply to  $\Sigma_{\text{Alice}}$ 
102:  assign largest block number in  $\Sigma_{\text{Alice}}$  to  $t$ 
103:  if lastPoll(Alice) + delay(Alice) <  $t$  then
104:    add [lastpoll(Alice),  $t$  - delay(Alice) - 1] to blindTime(Alice)
105:  end if
106:  lastPoll(Alice)  $\leftarrow t$ 
107:  scan  $\Sigma_{\text{Alice}}$  for honestly closed channels that contain Alice and exist in
   channels (txs that spend funding txs that have the same channel version
   as stored), remove them from channels and add them to toReport(Alice)
   (marked as “honest”)
108:  scan  $\Sigma_{\text{Alice}}$  for maliciously closed channels that contain Alice and exist
   in channels (txs that spend funding txs that have an older channel version
   than stored)
109:  for all maliciously closed channel of which the spending txs can still be
   spent by Alice do ▷ If Alice is negligent, she may be unable to punish
110:    if Alice cannot spend those spending txs then
111:      ensure that Alice has been negligent in the last interval
112:    end if
113:    add channel to toReport(Alice) (marked as “malicious”)
114:  end for
115:  send (GETCLOSEDFUNDS, toReport(Alice), Alice) to  $\mathcal{S}$ 
116:
117: Upon receiving (CHANNELSCLOSED, details, Alice) from  $\mathcal{S}$ :
118:  send (READ) to  $\mathcal{G}_{\text{Ledger}}$  as Alice and assign reply to  $\Sigma_{\text{Alice}}$ 
119:  for all channel  $\in$  details do
120:    ensure channel  $\in$  toReport(Alice)
121:    if channel is marked as “malicious” then
122:      ensure that transactions that spend the funding tx of channel and
      pay Alice the entire channel value exist in  $\Sigma_{\text{Alice}}$ 
123:    else ▷ channel is marked as “honest”
124:      ensure that transactions that spend the funding tx of channel and
      pay Alice the her part in channel exist in  $\Sigma_{\text{Alice}}$ 
125:    end if

```

```

126:         add the receipt of channel to closedChannels(Alice)
127:         remove channel from channels and toReport(Alice)
128:     end for
129:
130: Upon receiving (CHECKNEW) from Alice:
131:     clear newChannels(Alice), closedChannels(Alice), pendingUpdates(Alice)
        and send them to Alice
132:
133: At the end of each activation: [Orfeas: can this part completely go?]
134:     verify onChainbalance() for all parties is consistent with ledger (if not
        roll back the state and ignore command of activation).

```

Useful functions and procedures

```

1: function GENKEYS
2: end function
3: function RECEIPT(channel)
4:     parse channel as (Alice, Bob, cAlice, cBob, htlcs, verNo, pchid) [TODO: check if channel needs verNo]
5:     return ((Alice, cAlice), (Bob, cBob), pchid)
6: end function
7: function FUNDINGTX(funder, fundee)
8:     return TX {}
9: end function
10: function ISFUNDINGTX(tx, funder, fundee)
11:     if tx = fundingTX(funder, fundee) then
12:         return True
13:     else
14:         return False
15:     end if
16: end function
17: function COMMITMENTTX(fundingTX, c1, c2, htlcs)
18:     return TX {} [TODO: add keys, delays]
19: end function
20: function ISCOMMITMENTTX(tx, c1, c2, htlcs)
21:     if tx = commitmentTX(c1, c2, htlcs) then
22:         return True
23:     else
24:         return False
25:     end if
26: end function
27: function HTLCTX(commitmentTX, c)
28:     return TX {} [TODO: add keys, delays]

```

```

29: end function
30: function ISFUNDINGTX(tx, funder, fundee)
31:   if tx = fundingTX(funder, fundee) then
32:     return True
33:   else
34:     return False
35:   end if
36: end function

```

\mathcal{S} expects the same messages as the protocol, but messages that the protocol expects to receive from \mathcal{E} , the simulator expects to receive from $\mathcal{F}_{\text{PayNet}}$ with the name of the player appended. The simulator internally executes one copy of the protocol per player. Upon receiving any message, the simulator runs the relevant code of the protocol copy tied to the appended player name. Mimicking the real-world case, if a protocol copy sends a message to another player, that message is passed to \mathcal{A} as if sent by the player and if \mathcal{A} allows the message to reach the receiver, then the simulator reacts by acting upon the message with the protocol copy corresponding to the recipient player. A message sent by a protocol copy to \mathcal{E} will be routed by \mathcal{S} to $\mathcal{F}_{\text{PayNet}}$ instead. To distinguish which player it comes from, \mathcal{S} also appends the player name to the message.

$\mathcal{F}_{\text{PayNet}}$:

Upon receiving any message M by *Alice*: send (M, \textit{Alice}) to \mathcal{S}
 Upon receiving any message (M, \textit{Alice}) by \mathcal{S} : send M to *Alice*

7 Notes on Lightning Specification

- The relevant part of the specification can be found at <https://github.com/lightningnetwork/lightning-rfc/blob/master/02-peer-protocol.md>.
- In the current LND implementation and BOLT specification, only the opener (sender) of a channel funds it initially. In the present work, we allow both sides to fund the channel.

8 Model for Payment Channels

A payment channel is a tuple

$$PC = (\{(P_1, c_1), \dots, (P_n, c_n)\}, \{(e_1, b_1), \dots, (e_m, b_m)\}, f : \mathcal{A}^n \rightarrow \mathcal{PC})$$

where $\sum_{i=1}^n c_i \leq \sum_{i=1}^m b_i$.

(P_i, c_i) represents the i -th player and her available funds on settling.

(e_j, b_j) represents the j -th on-chain endpoint and the corresponding funds that will be released for use in the blockchain if this endpoint is settled.

f is a function from player actions to a new payment channel. The new payment channel must have at most as much funds as the old.