

# A Composable Security Treatment of the Lightning Network



Aggelos Kiayias  
Orfeas Stefanos Thyfronitis Litos  
CSF 2020

17/3/2022



# VISA

20,000 tx/s

# *bitcoin*

7 tx/s

**VISA**

instant\*

 **bitcoin**


1 hour


# Problem

All txs validated by all wallets

# Solution


- Move most txs off-chain
- Resolve disputes on-chain






# Lightning Channels

Open




# Lightning Channels

## Open




## Pay






# Lightning Channels

## Open




## Pay




# Lightning Channels


## Open



## Pay




## Close




# Lightning Channels


## Open



## Pay



## Close



# Multi-hop payments



From channels  
to network!

# Main result

Prove Lightning Network secure in the  
Universal Composability framework

# Simulation-based Security

$$\forall A \exists S : \forall \mathcal{E}$$





Figure: "Universally Composable Security",  
Ran Canetti <https://eprint.iacr.org/2000/067>

# This work


$$\exists A \exists S : \forall \mathcal{E}$$



a) Define  
functionality

# This work


$$\forall A \exists S : \forall \mathcal{E}$$





# This work

$$\forall \mathcal{A} \exists \mathcal{S} : \forall \mathcal{E}$$



# Blockchain Functionality

$\mathcal{G}_{\text{ledger}}$  [BMTZ'17, BGKRZ'18]

We prove that  
a naive, instant-finality ledger  
is unrealizable

# Functionality

## Functionality $\mathcal{F}_{\text{PayNet}}$ – interface

- from  $\mathcal{E}$ :
  - (REGISTER, delay, relayDelay)
  - (TOPPEDUP)
  - (OPENCHANNEL, *Alice*, *Bob*, *x*, *tid*)
  - (CHECKFORNEW, *Alice*, *Bob*, *tid*)
  - (PAY, *Bob*, *x*,  $\overrightarrow{\text{path}}$ , receipt)
  - (CLOSECHANNEL, receipt, *pchid*)
  - (FORCECLOSECHANNEL, receipt, *pchid*)
  - (POLL)
  - (PUSHFULFILL, *pchid*)
  - (PUSHADD, *pchid*)
  - (COMMIT, *pchid*)
  - (FULFILLONCHAIN)
  - (GETNEWS)
- to  $\mathcal{E}$ :
  - (REGISTER, *Alice*, delay(*Alice*), relayDelay(*Alice*), pubKey)
  - (REGISTERED)
  - (NEWS, newChannels, closedChannels, updatesToReport)
- from  $\mathcal{S}$ :
  - (REGISTERDONE, *Alice*, pubKey)
  - (CORRUPTED, *Alice*)
  - (CHANNELANNOUNCED, *Alice*,  $p_{\text{Alice},F}$ ,  $p_{\text{Bob},F}$ , *fchid*, *pchid*, *tid*)
  - (UPDATE, receipt, *Alice*)
  - (CLOSEDCHANNEL, channel, *Alice*)
  - (RESOLVEPAYS, *payid*, charged)
- to  $\mathcal{S}$ :
  - (REGISTER, *Alice*, delay, relayDelay)
  - (OPENCHANNEL, *Alice*, *Bob*, *x*, *fchid*, *tid*)
  - (CHANNELOPENED, *Alice*, *fchid*)
  - (PAY, *Alice*, *Bob*, *x*,  $\overrightarrow{\text{path}}$ , receipt, *payid*)
  - (CONTINUE)
  - (CLOSECHANNEL, *fchid*, *Alice*)
  - (FORCECLOSECHANNEL, *fchid*, *Alice*)
  - (POLL,  $\Sigma_{\text{Alice}}$ , *Alice*)
  - (PUSHFULFILL, *pchid*, *Alice*)
  - (PUSHADD, *pchid*, *Alice*)
  - (COMMIT, *pchid*, *Alice*)
  - (FULFILLONCHAIN, *t*, *Alice*)

# Our contributions

- Use a realistic ledger functionality
  - Prove naive ledger unrealizable
- Prove Lightning Network security in UC framework
- Derive exact time bounds for how often parties need to check the chain

# Further work

- Virtual channels
  - Channels on top of channels
  - No on-chain txs for open/close
- “Elmo: Recursive Virtual Payment Channels for Bitcoin”

<https://raw.githubusercontent.com/OrfeasLitos/virtual-payment-channels/master/virtual-channels.pdf>

# Further work

- Virtual channels
  - Channels on top of channels
  - No on-chain txs for open/close
- “Elmo: Recursive Virtual Payment Channels for Bitcoin”

<https://raw.githubusercontent.com/OrfeasLitos/virtual-payment-channels/master/virtual-channels.pdf>


Thank you! Questions?


<https://eprint.iacr.org/2019/778>



# Bonus slides: Protocol example













































Dispute period  $t$



Dispute period  $t$



Dispute period  $t$