

# What is Trust

Orfeas Stefanos Thyfronitis Litos

University of Edinburgh  
o.thyfronitis@ed.ac.uk

**Abstract.** We will try to define all the abstract properties that we would like "Trust" to have.

## 1 Introduction

Consider the UC setting, with an environment  $\mathcal{E}$ , an adversary  $\mathcal{A}$  and a set of ITIs that follow a given protocol  $\Pi$ .

**Definition 1 (Player).** *A player is an ITM that follows  $\Pi$ . Let  $\mathcal{P}$  be the set of all players.*

Intuitively, players spontaneously feel different desires of varying intensities and seek to satisfy them, either on their own, consuming part of their input tokens in the process, or by delegating the process to other players and paying them for their help with part of their input tokens. The choice depends on the perceived difference in price. Each player plays rationally, always attempting to maximize her utility.

More precisely, let  $\mathcal{D}$  be a (finite) set containing all possible desires. At arbitrary moments during execution,  $\mathcal{E}$  can provide input to any player  $Alice \in \mathcal{P}$  in the form  $(idx, d, u)$ , where  $idx \in \mathbb{N}$ ,  $d \in \mathcal{D}$ ,  $u \in \mathbb{R}^+$ .  $idx$  represents an index number that is unique for each input  $\mathcal{E}$  generates,  $d$  represents the desire, whereas  $u$  the additional utility  $Alice$  will obtain if  $d$  is satisfied.  $d$  is satisfied when  $Alice$  learns the string  $s(idx, d, Alice)$ , either by directly calculating it or by receiving it as subroutine output from another player. Some of the players, given as input the tuple  $(idx, d, Alice)$ , can calculate  $s(idx, d, Alice)$  more efficiently than  $Alice$ , which means that they need to consume less input tokens than  $Alice$  for this calculation.  $Alice$  can choose to delegate this calculation to a more efficient player  $Bob$  and provide the necessary input tokens for his computation with a surplus to compensate  $Bob$  for his effort. Both players are better off, because  $Alice$  spent less tokens than she would if she had calculated  $s(idx, d, Alice)$  herself, whilst  $Bob$  obtained some tokens which can in turn be used to satisfy some of his future desires.

**Definition 2 (Cost of desire).** *The cost of Alice's indexed desire, say  $(idx, d) \in (\mathbb{N}, \mathcal{D})$ , when satisfied by Bob is equal to the input tokens that Alice is required by Bob to give to him in order for him to calculate  $s(idx, Alice, d)$  and is represented by  $c(idx, d, Alice, Bob)$ . The cost of satisfying this desire herself is represented by  $c(idx, d, Alice)$  and is equal to the number of computational steps Alice must make in order to calculate  $s(idx, d, Alice)$ . Let  $c(idx, d, Alice, Alice) = c(idx, d, Alice)$ .*

## 2 Motivation for our Trust model

Nevertheless, one can say that at first sight it is in *Bob's* best interest to trick *Alice* into believing that he can efficiently calculate  $s(idx, Alice, d)$  and skip the computation entirely after obtaining *Alice's* input, thus keeping all the tokens of the defrauded player. Evidently *Alice* would avoid further interaction with *Bob*, but without any way to signal other players of this unfortunate encounter, *Bob* can keep defrauding others until the pool of players is depleted; if the players are numerous or their number is increasing, *Bob* may keep this enterprise very profitable for an indefinite amount of time. This being a rational strategy, every player would eventually follow it, which through a "tragedy of the commons" effect invariably leads to a world where each player must satisfy all her desires by herself, entirely missing out on the prospect of the division of labor.

One answer to that undesirable turn of events is a method through which *Alice*, prior to interacting with an aspiring helper *Bob*, consults the collective knowledge of her neighborhood of the network regarding him. There are several methods to achieve this, such as star-based global ratings. This method however has several drawbacks:

- Very good ratings cost nothing, thus convey little valuable information.
- Different players may have different preferences, global ratings fail to capture this. [Arrow's impossibility theorem](#) is possibly relevant here.
- Susceptible to Sybil attacks; mitigation techniques are ad-hoc and require (partial) centralization and secrecy/obfuscation of methods to succeed, thus undermining the decentralized, transparent nature of the system, a property that we actively seek.

## 3 Trust definitions

We thus define two kinds of trust: direct and indirect. Direct trust from *Alice* to *Bob* is represented by input tokens (initially belonging to *Alice*)

actively put by her in a common account from which *Bob* can also take them. As long as *Bob* does not take these tokens, *Alice* directly trusts him equally to the amount of tokens deposited in the common account.

This information can be used by another player *Charlie* that directly trusts *Alice* in order to derive information regarding *Bob*'s trustworthiness, even if *Charlie* does not directly trust *Bob*. Through a transitive property, *Dean*, who directly trusts *Charlie*, can in turn derive information from the direct trust from *Alice* to *Bob*. This reasoning can be extended to an arbitrary number of players, as long as they have at least one trust path to *Alice*. This is called indirect trust.

**Definition 3 (Direct Trust).** *The direct trust from Alice to Bob, represented by  $DTr_{Alice \rightarrow Bob}$ , is equal to the total tokens that Alice has given as input to  $\mathcal{F}_{Trust}$  with  $\text{entrust}(Bob, 1^{\text{tokens}})$  and also equal to the available tokens count sent by  $\mathcal{F}_{Trust}$  as a response to a message  $\text{query\_direct\_trust}(Alice, Bob)$ .*

**Definition 4 (Indirect Trust).** *The indirect trust from Alice to Bob,  $Tr_{Alice \rightarrow Bob}$ , is measured in input tokens and can be calculated deterministically given the existing direct trusts between all pairs of players. It is equal to the number sent by  $\mathcal{F}_{Trust}$  as a response to a message  $\text{query\_indirect\_trust}(Alice, Bob)$ .*

By convention  $DTr_{Alice \rightarrow Alice} = Tr_{Alice \rightarrow Alice}$  and are both equal to the quantity of input tokens *Alice* has.

We would like to provide players with an ideal functionality where they:

1. Directly trust tokens to another player
2. Steal tokens previously directly entrusted by another player
3. Retract tokens previously directly entrusted to another player
4. Query indirect trust towards another player

The following functionality provides such an interface:

$\mathcal{F}_{Trust}$

```

1 Initialization:
2 for all  $Alice, Bob \in \mathcal{P}$ 
3    $DTr_{Alice \rightarrow Bob} = 0$ 
4    $Tr_{Alice \rightarrow Bob} = 0$ 
5
6 Upon receiving input  $\text{entrust}(Bob, 1^{\text{tokens}})$  from  $Alice$ :
7    $DTr_{Alice \rightarrow Bob} += \text{tokens}$ 
```

```

8
9 Upon receiving message steal(Bob, tokens) from Alice:
10   If  $DTr_{Bob \rightarrow Alice} \geq \text{tokens}$ 
11      $DTr_{Bob \rightarrow Alice} -= \text{tokens}$ 
12     input  $1^{\text{tokens}}$  to Alice
13   Else discard request
14
15 Upon receiving message distrust(Bob, tokens) from Alice:
16   If  $DTr_{Alice \rightarrow Bob} \geq \text{tokens}$ 
17      $DTr_{Alice \rightarrow Bob} -= \text{tokens}$ 
18     input  $1^{\text{tokens}}$  to Alice
19   Else discard request
20
21 Upon receiving message query_direct_trust(Alice, Bob) from
    Charlie:
22   If  $Charlie \in \{Alice, Bob\}$  # Privacy
23     send message  $DTr_{Alice \rightarrow Bob}$  to Charlie
24   Else discard request
25
26 Upon receiving message query_indirect_trust(Alice, Bob)
    from Charlie:
27   If  $Charlie == Alice$  # Privacy
28      $Tr_{Alice \rightarrow Bob} = \text{calculate\_indirect\_trust}(Alice, Bob, \text{all}$ 
        direct trusts)
29     send message  $Tr_{Alice \rightarrow Bob}$  to Charlie
30   Else discard request

```

#### 4 Desired Properties for Indirect Trust

1.  $Tr_{Alice \rightarrow Bob} \geq DTr_{Alice \rightarrow Bob}$
2. If universe (1) and (2) are identical except for  $DTr_{Alice \rightarrow Bob}$ , then

$$Tr_{Alice \rightarrow Bob}^2 = Tr_{Alice \rightarrow Bob}^1 - DTr_{Alice \rightarrow Bob}^1 + DTr_{Alice \rightarrow Bob}^2 .$$

3. Consider an indexed desire  $(idx, d)$  *Alice* has. Let  $p(idx, d, Alice)$  be a function that returns the player that *Alice* should rationally delegate the calculation of  $s(idx, d, Alice)$  to.

- (a) If a player is cheaper and more trustworthy than all other players, delegate the calculation to him.

$$\begin{aligned}
& \exists Bob \in \mathcal{P} : \forall Charlie \in \mathcal{P} \setminus \{Bob\} \\
& (c(idx, d, Alice, Bob) < c(idx, d, Alice, Charlie) \wedge \\
& \wedge Tr_{Alice \rightarrow Bob} > Tr_{Alice \rightarrow Charlie}) \Rightarrow \\
& \Rightarrow p(idx, d, Alice) = Bob .
\end{aligned}$$

- (b) If there exists a player *Bob* that is both cheaper and more trustworthy than *Charlie*, do not delegate the calculation to *Charlie*.

$$\begin{aligned}
& \exists Bob, Charlie \in \mathcal{P} : \\
& (c(idx, d, Alice, Bob) < c(idx, d, Alice, Charlie) \wedge \\
& \wedge Tr_{Alice \rightarrow Bob} > Tr_{Alice \rightarrow Charlie}) \Rightarrow \\
& \Rightarrow p(idx, d, Alice) \neq Charlie .
\end{aligned}$$

Note that the first property can be deduced from the second.

Let  $x = (idx, d, Alice)$ . Several ideas exist as to what rules  $p(x)$  should satisfy:

1. Indirect trust is only used when offered prices are equal, otherwise the player offering the cheapest price is chosen.

$$\begin{aligned}
& c(x, Bob) < c(x, Charlie) & \Rightarrow p(x) \neq Charlie . \\
& \left. \begin{aligned} & c(x, Bob) = c(x, Charlie) \\ & Tr_{Alice \rightarrow Bob} > Tr_{Alice \rightarrow Charlie} \end{aligned} \right\} & \Rightarrow p(x) \neq Charlie .
\end{aligned}$$

## References