

Test Plan 4 — Product Roles E2E (Live Per-Role Sessions)

⚠ CURRENTLY DISABLED. The `product-setup` and `product-authenticated` projects are commented out in `playwright.config.ts`, so this group does **not** run in the default suite. The spec files under `tests/product/flows/**` (and `tests/product/support/auth.setup.ts`) are retained — re-enable the group by uncommenting both projects in `playwright.config.ts`. The cases below still describe those specs.

Projects	<code>product-setup</code> → <code>product-authenticated</code>
Specs	<code>tests/product/support/auth.setup.ts</code> , <code>tests/product/flows/roles.spec.ts</code>
Target	Dev calculator — <code>QA_TARGET_ENV</code> (default dev), per-role phone+OTP login
Cases	13 (setup 3 + authenticated 10)
Skips	Per role — no credential (setup) or no saved session (authenticated)
Skills	<code>product-roles-e2e</code> , <code>organuz-product-roles</code>

Scope

Live, per-role coverage in a real browser. This group runs as two projects that work together. `product-setup` signs each role in once, using phone number plus a one-time passcode (OTP), and saves its login state to a `storageState` file. `product-authenticated` then resumes that saved session and runs read-only checks of each role's personal area. This is the live counterpart to Plan 3's offline role contract. It stays dormant on CI until the per-role secrets exist, so the suite stays green without them.

Preconditions

- The live dev app plus its password gate (`PRODUCT_PLATFORM_PASSWORD`).
- Per-role credentials, stored in the gitignored `.env` file or as CI secrets: `<ROLE>_PHONE` / `<ROLE>_OTP_CODE` for `CUSTOMER`, `CONSULTANT`, and `COMPANY`.

Gating (sanctioned skip)

- **product-setup** : a role is skipped when it has no `<ROLE>_PHONE` credential, or when the dev app or OTP is down. When a role is skipped, no session is written for it.
- **product-authenticated** : a role's specs skip when it has no saved session (`hasSavedSession(role)` is false) or when the session cannot resume.

Cases

`auth.setup.ts` — per-role sign-in (project `product-setup`)

ID	CASE	ASSERTS
SET-01	Authenticate customer and save <code>storageState</code>	Customer phone+OTP login succeeds; session persisted
SET-02	Authenticate consultant and save <code>storageState</code>	Consultant phone+OTP login succeeds; session persisted
SET-03	Authenticate company and save <code>storageState</code>	Company phone+OTP login succeeds; session persisted

`roles.spec.ts` — live role sessions (project `product-authenticated` , `@product @roles @e2e`)

ID	CASE	ASSERTS
CUS-01	Customer resumes its saved session into the calculator shell	Session resumes; shell authenticated
CUS-02	Customer can open its personal area	Customer personal area opens
CUS-03	Customer session persists across a reload	Session survives a page reload
CON-01	Consultant resumes its saved session into the calculator shell	Session resumes; shell authenticated
CON-02	Consultant can open its personal area	Consultant personal area opens
CON-03	Consultant session persists across a reload	Session survives a page reload

ID	CASE	ASSERTS
COM-01	Company resumes its saved session into the calculator shell	Session resumes; shell authenticated
COM-02	Company can open its personal area	Company personal area opens
COM-03	Company session persists across a reload	Session survives a page reload
COM-04	Company can open the contractor pricing area	Company-only pricing area opens

Run

```
# Runs product-setup first (its dependency), then the authenticated flows:  
QA_TARGET_ENV=dev npx playwright test --project=product-authenticated
```

Notes

- Keep skip and lifecycle logic at the test edge (the spec or fixture), not inside `ProductAppPage` or `ProductFlows`. Those two **throw** typed errors instead of deciding to skip.
- `product-authenticated` depends on `product-setup`. Run the dependent project and Playwright pulls the setup in automatically. Don't shard the setup separately, or each role logs in twice.