

Test Plan 12 - Product Interactive UI

Project	product
Specs	tests/product/auth/** , tests/product/mobile/** , tests/product/wizard/**
Target	Product calculator selected by QA_TARGET_ENV (dev by default)
Cases	24 discovered
Fixtures	product , loginDialog , layered step/flow fixtures under tests/product/support/

Scope

Interactive browser coverage beyond the public API and offline matrix plans: the cellular login dialog, responsive phone layouts, the calculator characterization wizard, and the customer process.

Coverage

AREA	CASES	NOTES
Cellular login	9	Dialog entry, phone validation, registration links, close behavior, and an opt-in OTP step
Mobile viewport	7	Pixel 5 and Galaxy S9+ shell, overflow, login-dialog fit, plus one opt-in navigation diagnostic
Wizard/customer process	8	Step tracker, live address/geocode journey, wizard progression, and opt-in authenticated characterization

Gating and side effects

- All groups skip on a genuine product-app outage.
- Geocode-driving wizard cases self-skip on CI because Govmap is geo-blocked or unstable for hosted runners; deterministic step checks remain CI-enabled.
- PRODUCT_OTP_UI=true enables the single check that requests a real OTP.
- PRODUCT_WIZARD_E2E=true enables authenticated characterization; it can create a real dev project and needs customer credentials.

- `MOBILE_NAV_EXPLORE=true` enables the temporary mobile navigation diagnostic.
- OTP cooldowns produce an explicit skip instead of a false product failure.

Run

```
npx playwright test --project=product tests/product/auth tests/product/mobile tests/product/wizard
PRODUCT_OTP_UI=true npx playwright test --project=product tests/product/auth/cellular
PRODUCT_WIZARD_E2E=true npx playwright test --project=product tests/product/wizard
```