

Test Plan 9 — Local Web (Local-Only Marketing E2E)

Project	local-web
Specs	tests/local-web/** (*.local.spec.ts)
Target	Marketing site — prod https://www.organuz.ai (real Chromium)
Page objects / fixtures	HomeFlows via tests/ui/support/fixtures ; local guard in tests/local-web/support.ts
Cases	~50
Skips	Whole group self-skips on CI (process.env.CI set) — sanctioned local/CI divergence
Skill	none

Scope

A deeper, visibility-only sweep of the public marketing homepage than the chromium UI sanity group (Plan 1). It drives a real Chromium browser against production and asserts that each homepage section renders — hero and header navigation, the audience selector and "Why Organuz" tabs, the "Meet Or" / agents / projects sections, the FAQ questions, and the contact-form fields. Every check is **read-only**: nothing is filled or submitted, so no automation data reaches the real CRM.

These specs are meant to run **only on a developer machine**. Each spec calls `localOnly()` (from `tests/local-web/support.ts`), which registers a `beforeEach` guard that `test.skip`s every test in the file when `process.env.CI` is set. As a result the group runs (and passes) locally but is **skipped on GitHub Actions**, and the `local-web` project is **not in the CI matrix**. This is a sanctioned local/CI divergence — see the `test-suite-parity` skill.

Preconditions

- Public internet access to `www.organuz.ai` ; no credentials required.
- Run locally (i.e. `CI` unset). On CI the whole group self-skips by design.

- The site is Hebrew / right-to-left (RTL), so some assertions match Hebrew strings (for example the hero contains "אור").

Cases

Grouped by spec file (all tagged `@ui @local-only`, visibility-only):

SPEC	COVERS
<code>home-hero-nav.local.spec.ts</code>	Hero H1 + it contains "אור", hero subtitle, header CTA visible and its href targets the app, and each primary nav link (Why Organuz, Meet Or, Agents, Sample Projects, Knowledge Hub, FAQ) is visible
<code>home-audiences-why.local.spec.ts</code>	Each audience button (Private homes, Residential buildings, Businesses, Agriculture, Authorities, Market players) is visible; the "Why Organuz" heading and each of its tabs (Property owners, Solar companies, Authorities & corporations, Investors & financiers) is visible
<code>home-or-agents-projects.local.spec.ts</code>	"Meet Or" heading + "Talk to Or" link, the agents-section heading and each agent card (<code>AgentNames</code>), and the active-projects heading
<code>home-faq.local.spec.ts</code>	The FAQ section heading, plus each known FAQ question (<code>FaqQuestions</code>) rendered as an accordion button or plain text (tolerant locator)
<code>home-contact.local.spec.ts</code>	Each contact-form field (Full name, Email, Phone, Message, Submit) is visible — never filled or submitted

Section rosters (`AgentNames` , `FaqQuestions` , nav links, audiences, tabs) come from `tests/constants.ts` , so the exact per-file count tracks those lists; the group totals ~50 cases.

Run

```
# Local only — leave CI unset:
npx playwright test --project=local-web
```

Notes

- The group is a **superset in depth** of Plan 1 (UI sanity). Plan 1 is the CI-safe `@other-smoke` subset; this group is the fuller local-only sweep.
- Keep it read-only against production — never fill or submit the contact form.
- If the group ever needs to run on CI, remove the `localOnly()` guard and add `local-web` to the CI matrix in lockstep (`test-suite-parity` skill); until then, its skip on CI is expected and must stay green.