

# pXp analysis

Luiz Emediato (Sao Paulo)

Tom McDowell, Cory Rude, Jane Nachtman (Iowa)

Mike Albrow (FNAL)

# Overview

1. 4-track code: `luianaRP4.cc` (github)
  - important: **`make -f LUMakefile4`** to compile the code
  - for now 4 pions per event only
  - 4-track 2015 data
2. Hand notes: `luianaRP-scheme.pdf` (140MB google drive only)
  - helps to understand the logic
  - not in github, it allows only 25MB/file
  - “pula” is the portuguese for skip or jump
  - if you want to print the code in syntax-oriented colors use emacs:  
C-u M(ESC)-x ps-print-buffer-with-faces
  - for2 loop: tracks per event
  - for3 loop: vertices per event

- main loops:
  - loop over data files
  - loop over events
  - sub loop over tracks
  - sub loop over vertices

3. number of vertices nvtx : now 1 or 2 (originally 1)

## 5. cuts:

a- fiducialRegion: 4 tracks, each pion  $\eta < \eta_{\text{Cut}}=2.5$

b- fiducialRegionPt: 4 tracks, each pion  $p_t > p_{t\text{Cut}}=0.2\text{GeV}/c$  (changed to 0.1)

definition:

$CT_{\text{pycut}} = |CMSP_{\text{y}} + TOTEMP_{\text{y}}| < 0.06$  (applied to all cuts)

$CT_{\text{pxcut}} = |CMSP_{\text{x}} + TOTEMP_{\text{x}}| < 0.15$

$RP_{\text{vertex}} = |x_{VtxL} - x_{VtxR}| < 3e-5$

$CT_{\text{vertex}} = -0.04 < (x_{vtx} - x_{vtxT} \cdot 100) \text{ .AND. } (x_{vtx} - x_{vtxT} \cdot 100) < 0.18$

- cut 1: a, b  $\rightarrow$  hm2rec

a, b,  $Q=0 \rightarrow$  hm2recOS (hm4recOS)

a, b,  $Q \neq 0 \rightarrow$  hm2recSS

- cut 2: a, b,  $Q=0$ ,  $RP_{\text{vertex}}$ ,  $CT_{\text{pxcut}}$ ,  $CT_{\text{vertex}} \rightarrow$  hm2rec2OS (hm4rec2OS)

a, b,  $Q \neq 0$ ,  $RP_{\text{vertex}}$ ,  $CT_{\text{pxcut}}$ ,  $CT_{\text{vertex}} \rightarrow$  hm2rec2SS

need to be fixed

- cut 3: a, b,  $Q=0$ , RPvertex, CTpxcut  $\rightarrow$  hm2rec3OS (hm4rec3OS)  
a, b,  $Q \neq 0$ , RPvertex, CTpxcut  $\rightarrow$  hm2rec3SS
  
- cut 4: a, b,  $Q=0$ , RPvertex, CTpxcut, CTvertex,  $|z_{vtx}| < 5.0$   $\rightarrow$  hm4rec4OS  
a, b,  $Q \neq 0$ , RPvertex, CTpxcut, CTvertex,  $|z_{vtx}| < 5.0$   $\rightarrow$  hm4rec4SS
  
- cut 5: a, b,  $Q=0$ , Rpvertex, CTvertex  $\rightarrow$  hm4rec5OS  
a, b,  $Q \neq 0$ , RPvertex, CTvertex  $\rightarrow$  hm4rec5SS
  
- cut 6: a, b,  $Q=0$ , RPvertex, CTpxcut, CTvertex, etaCut2  
each pion  $|\eta| < \text{etaCut2}=1.5$   $\rightarrow$  hm4rec6OS  
a, b,  $Q \neq 0$ , RPvertex, CTpxcut, CTvertex, etaCut2  
each pion  $|\eta| < \text{etaCut2}=1.5$   $\rightarrow$  hm4rec6SS
  
- cut 7: a, b,  $Q=0$ , diag, RPvertex, CTpxcut  $\rightarrow$  hm4recHFvetoOS  
a, b,  $Q \neq 0$ , diag, RPvertex, CTpxcut  $\rightarrow$  hm4recHFvetoOS

events in the 4-track sample

eta distribution:  $-3.0 < \eta < 3.0$   $\sim 5,300,000$  events

**sequence of processing:**

CMSPy+TOTEMpy histogram  $\sim 1,000,000$  events


if  $CT_{pycut} < 0.06$  then **(from here we have a big reduction of data)**

CMSPx+TOTEMpx histogram  $\sim 160,000$  events


cut 1: fiducialRegion, fiducialRegionPt,  $Q=0$  histograms  $\sim 140,000$  events

## 4-track sample job#81


number of good 4-tracks



number of vertices



number of tracks with 1 vertex only






cut 1, Q=0


M 4 pions

hm2recOS	
Entries	126290
Mean	2.066
Std Dev	0.7166




## M 4 pions

cut 2, Q=0




# M 4 pions TTBB

cut 2, Q=0



# M 4 pions TB/BT

cut 2, Q=0



hm2rec2OS_diag	
Entries	33865
Mean	2.024
Std Dev	0.6577

ptCut > 0.1  
etaCut < 2.5  
1 or 2 vertices  
RPvertex  
CTpxcut  
CTvertex

Question: What does Simone mean in the code ?

simulation: **GRANIITTI** is working fine on my Fedora 29

Thanks for your kind help and attention !