



# CONFIGURING AND CUSTOMIZING ALLOWED CONTENT RULES

Copyright ©2017 Liferay, Inc.

All Rights Reserved.

No material may be reproduced electronically or in print,  
distributed, copied, sold, resold, or otherwise exploited  
for any commercial purpose without express written  
consent of Liferay, Inc.

## ALLOWING CONTENT IN THE EDITOR

- ❖ It's possible to configure the `allowedContent` of an editor through an OSGi module.
- ❖ For more information about the allowed content rules, please see the documentation on *CKEditor*:  
[http://docs.ckeditor.com/#!/guide/dev\\_allowed\\_content\\_rules](http://docs.ckeditor.com/#!/guide/dev_allowed_content_rules)

## EXTENDING THE EDITOR'S CONFIGURATION

- ❖ To modify the editor's configuration, you can create a module that has a component that implements the `EditorConfigContributor` interface.
- ❖ When you implement this interface, your module will provide a service that modifies the editors you'd like to change.

## EXTENDING CONFIGURATION EXAMPLE

- ❖ As an example, you can create a generic OSGi module using your favorite third-party tool or use the *Blade CLI*.
- ❖ You can create a unique package name in the module's `src` directory and create a new Java class in that package.
- ❖ The class should extend the `BaseEditorConfigContributor` class.
- ❖ Directly above the class's declaration, you can insert a component annotation:

```
@Component(  
    property = {  
  
    },  
    service = EditorConfigContributor.class  
)
```

## CHANGING THE ALLOWED CONTENT RULES

- ❖ For this example, you could change the `allowedContent` of the Web Content's AlloyEditor. The declaration would look like this:

```
import com.liferay.journal.constants.JournalPortletKeys;
@Component(
    property = {
        "editor.name=alloyeditor",
        "javax.portlet.name=" + JournalPortletKeys.JOURNAL,
        "service.ranking:Integer=100"
    },
    service = EditorConfigContributor.class
)
public class CustomJournalMediaEditorConfigContributor
    extends BaseEditorConfigContributor {
}
```

## SPECIFYING CHANGES

- ❖ Next, changes need to be specified.
- ❖ Add the following method to the new class:

```
@Override
public void populateConfigJSONObject(
    JSONObject jsonObject, Map<String, Object> inputEditorTaglibAttributes,
    ThemeDisplay themeDisplay,
    RequestBackedPortletURLFactory requestBackedPortletURLFactory) {
    ...
}
```

- ❖ In the populateConfigJSONObject method, the element value can be added for allowedContent, extraPlugins, and disallowedContent through the jsonObject parameter:

```
jsonObject.put("allowedContent", "p ");
jsonObject.put("disallowedContent", "h1 h2 h3 h4 h5 h6 ");
```

- ❖ It should look like the 01-configuration-example.java in the exercises folder.

## FINISHING UP

- ❖ Now if we create a new web content article, the AlloyEditor will disallow all header tags except for `<p>` tags.

Notes: