



# LOADING SCRIPTS WITH THE AUI SCRIPT TAG

Copyright ©2017 Liferay, Inc.

All Rights Reserved.

No material may be reproduced electronically or in print, distributed, copied, sold, resold, or otherwise exploited for any commercial purpose without express written consent of Liferay, Inc.

## WHAT IS THE AUI SCRIPT TAG?

- ❖ The AUI script tag is a taglib for JSPs that allows you to load JavaScript in script tags on the page and ensure certain resources are loaded before executing.

# AUI SCRIPT OPTIONS

- ❖ Here is a list of attribute options:
1. **require:** Requires an AMD module that will be loaded with the Liferay AMD Module Loader
  2. **use:** Uses an AlloyUI/YUI module that will be loaded via the YUI loader
  3. **position:** The position the script tag is put in the page; can be `inline` or `auto`
  4. **sandbox:** If set to true, it will wrap the script tag in an anonymous function. Also, `$` and `_` will be defined for convenient use of jQuery and underscore.

# USING THE USE ATTRIBUTE

- ❖ Here is an example of the *use* attribute:

```
<alui:script use="alui-base">
  A.one('#someNodeId').on(
    'click',
    function(event) {
      alert('Thank you for clicking.')
    }
  );
</alui:script>
```

# USING THE REQUIRE ATTRIBUTE

❖ Here is an example of the *require* attribute:

```
<au:script require="metal-clipboard/src/Clipboard">  
    new metalClipboardSrcClipboard.default();  
</au:script>
```

Notes: