



Lab 5 – Test your Spring Boot REST service

This lab guides you through some steps to test your Spring Boot Service using JUnit.

The basis for this lab is the service that is created in Lab 1. In the Lab you will add some tests to this service.

The starting point for this lab is to have the provided VirtualBox machine up-and-running:


- You are logged in under user/password: developer/welcome01
- You have updated the labs running the `git pull` command in the lab workspace directory `/home/developer/projects/SIGSpringBoot101`

1. Starting point

The starting point for this lab is the service code in directory

`/home/developer/projects/SIGSpringBoot101/lab 5/dronebuzzers`.

Start STS Eclipse and first delete – when necessary – the project(s) that are still present. You can do so by right-clicking the project and then click Delete:




Click OK.


Next, import the maven project from the above folder. Goto File → Import:



Spring Boot 101 - intro, demo & handson with Java, REST APIs, Containers & Cloud



The Import window will be shown:




Click Next. In the next pop-up, set the Root Directory to

`/home/developer/projects/SIGSpringBoot101/lab 5/dronebuzzers` and select the `pom.xml` file:



Spring Boot 101 - intro, demo & hands-on with Java, REST APIs, Containers & Cloud



And press Finish.

2. Set up your project

Ensure that the pom.xml contains the following dependency:

```
<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-test</artifactId>
  <scope>test</scope>
</dependency>
```

This dependency contains some common libraries used when writing tests, like

- **Junit**: the de-facto standard for unit testing Java applications.
- **AssertJ**: a fluent assertion library
- **Mockito**: a Java mocking framework
- **Hamcrest**: a library of matcher objects (also known as constraints or predicates)

Now, the project is prepared for adding the unit tests.

3. Creating the Unit test PartTest




Spring Boot 101 - intro, demo & hands-on with Java, REST APIs, Containers & Cloud

In this section, we will:

- Create a unit test for the `/dronebuzzers/part/{id}` operation, and
- Determine the code coverage for the unit test


Start by creating a class named `PartTest.java` in the test folder. Do this by right clicking on `src/test/java`



And selecting *New->Class*

Set the Package to: `com.dronebuzzers.rest.controller`

Set Name to: `PartTest`



Press Finish to create the new class.



Spring Boot 101 - intro, demo & handson with Java, REST APIs, Containers & Cloud

Add two annotations to the newly created class:

```
@RunWith(SpringRunner.class)
@WebMvcTest(PartController.class)
```

The RunWith annotation ensures all JUnit annotations are read.

The WebMvcTest will auto configure the Spring MVC infrastructure and will allow us to test the controller without the need of starting the server.

Next, create two global variables:

- mockMvc, with datatype MockMvc and annotation @Autowired.
This datatype is used to test the controller without starting a server.
- partsDAO, with datatype PartsDAO and annotation @MockBean.
This will be the mocking bean used by our test.

The code looks like:

```
@Autowired
private MockMvc mockMvc;

@MockBean
private PartsDAO partsDAO;
```

Mocking PartsDAO

By using the @MockBean annotation a mock is created for PartsDao, which can bypass calls to the actual PartsDao. This is useful, since in the PartController class, all methods call PartsDAO methods to retrieve part information. In a real application, PartsDAO will be a service which gets its data from a database, other service, or any datasource. Therefore, in most situations this will be the class which is mocked for Unit tests.

Your class should look like this:

```
1 package com.dronebuzzers.rest.controller;
2
3 import org.junit.runner.RunWith;
4 import org.springframework.beans.factory.annotation.Autowired;
5 import org.springframework.boot.test.autoconfigure.web.servlet.WebMvcTest;
6 import org.springframework.boot.test.mock.mockito.MockBean;
7 import org.springframework.test.context.junit4.SpringRunner;
8 import org.springframework.test.web.servlet.MockMvc;
9
10 import com.dronebuzzers.rest.part.PartsDAO;
11
12
13 @RunWith(SpringRunner.class)
14 @WebMvcTest(PartController.class)
15 public class PartTest {
16
17     @Autowired
18     private MockMvc mockMvc;
19
20     @MockBean
21     private PartsDAO partsDAO;
22
23 }
24
```



Creating the first Unit test

Now, create a method named `testGet()` which will implement the first Unit test. Annotate this method with `@Test`.

Fill your method with the following code:

```
@Test
public void testGet() throws Exception {
    Part part = new Part("DB-FK-A250-V5", "Drone", "Beta", "TestPart", 100, "Euro");
    when(partsDAO.getPart("DB-FK-A250-V5")).thenReturn(part);

    this.mockMvc.perform(get("/dronebuzzers/part/DB-FK-A250-V5")
        .contentType(MediaType.APPLICATION_JSON))
        .andExpect(status().isOk())
        .andExpect(jsonPath("$.id", is("DB-FK-A250-V5")))
        .andExpect(jsonPath("$.category", is("Drone")));
}
```

`testGET()` unit test explained


The method will test the get functionality of the `PartController`:

- A mock part is created with part id `DB-FK-A250-V5`
- When method `getPart` of class `PartsDAO` is called with id `DB-FK-A250-V5`, the created mock part is returned
- The test itself uses `MockMvc` to call the `PartController` class with
 - o a GET operation and with Uri `/dronebuzzers/part/DB-FK-A250-V5`
 - o and Content-Type set to `application/json`
- And the `andExpect()` method is used to assert various aspects of the response.


The Unit test can be run by right clicking the `PartTest.java` file and then clicking `Run As -> JUnit Test`



Spring Boot 101 - intro, demo & hands on with Java, REST APIs, Containers & Cloud



The JUnit tab on the right of Eclipse STS will show the results. The tab should show a green bar like this:




Code Coverage

You want to check whether all the written code is covered by your unit test tests. For this purpose EclEmma can be used. This is an Eclipse plugin build on Jacoco.

Install EclEmma by going to *Help -> Eclipse Marketplace...* Search for EclEmma:




Spring Boot 101 - intro, demo & hands-on with Java, REST APIs, Containers & Cloud



and click Install. Accept the license agreement and restart Eclipse STS when asked..

Right click on the test and click *Coverage As -> JUnit Test*



This will run the test and after finishing it will show us the code coverage. A new tab will open named **Coverage** which shows all classes and if you have any java file opened, you will notice green or red bars behind your code.



Spring Boot 101 - intro, demo & handson with Java, REST APIs, Containers & Cloud

In the Coverage tab, navigate to the PartController.java file. You will see the percentage of code coverage of this file:

The screenshot shows the 'Coverage' tab in an IDE. The table lists the following elements and their coverage percentages:

Element	Coverage	Cover
dronebuzzers-rest-service	14.0 %	
src/main/java	9.1 %	
com.dronebuzzers.rest.order	0.0 %	
com.dronebuzzers.rest.part	16.8 %	
com.dronebuzzers.rest.controller	18.9 %	
PartController.java	22.8 %	
OrderController.java	0.0 %	
com.dronebuzzers.rest	37.5 %	
src/test/java	54.2 %	

Let us check which code is not used by opening the PartController.java file:

```
// Get a part by Id
@RequestMapping(method = RequestMethod.GET, value = "{id}")
public ResponseEntity<Part> get(@PathVariable String id) {

    Part match = null;
    match = partsDAO.getPart(id);

    if (match != null) {
        return new ResponseEntity<>(match, HttpStatus.OK);
    } else {
        return new ResponseEntity<>(null, HttpStatus.NOT_FOUND);
    }
}
```

Woops. You will see that not all code in the get() function is used since the else branch is red. Let's fix this by adding an extra test step in our testGet() method. Add the following code to this method:

```
this.mockMvc.perform(get("/dronebuzzers/part/unknown").contentType(MediaType.APPLICATION_JSON))
    .andExpect(status().isNotFound());
```

And run the test again using *Coverage As -> JUnit Test*.

Open PartController.java and you will see that the entire get() method is green:



Spring Boot 101 - intro, demo & hands on with Java, REST APIs, Containers & Cloud

```
// Get a part by Id
@RequestMapping(method = RequestMethod.GET, value = "{id}")
public ResponseEntity<Part> get(@PathVariable String id) {

    Part match = null;
    match = partsDAO.getPart(id);

    if (match != null) {
        return new ResponseEntity<>(match, HttpStatus.OK);
    } else {
        return new ResponseEntity<>(null, HttpStatus.NOT_FOUND);
    }
}
```

Increase test coverage - optional

There are still methods in this class which are not covered by test. To increase coverage, you can add new tests. You can create a method in the test file for each operation and name them 'testOperationname', eg testGet() and testGetAll(). Fill these methods with useful assertions and run the Unit test again. Do not forget the @Test annotation. Check if the coverage of PartController is 100%.

Hint: you can use .andDo(print()) function on mockMvc to print the information of the request.

If you don't want to spend too much time on this part, you can also check the code in the [/home/developer/projects/SIGSpringBoot101/lab 5/dronebuzzers-completed project](#)

4. Creating the Unit test OrderTest

In this section, we will create a unit test for the OrderController. This controller has only 1 method that handles a POST.

Create an OrderTest.java file in the same way as the PartTest.java. Add the following two annotations

```
@RunWith(SpringRunner.class)
@WebMvcTest(OrderController.class)
```



Spring Boot 101 - intro, demo & handson with Java, REST APIs, Containers & Cloud

And add the two global variables mockMvc and PartsDAO, like in the PartTest.java

```
1 package com.dronebuzzers.rest.controller;
2
3 import org.junit.runner.RunWith;
11
12 @RunWith(SpringRunner.class)
13 @WebMvcTest(OrderController.class)
14 public class OrderTest {
15
16     @Autowired
17     private MockMvc mockMvc;
18
19     @MockBean
20     private PartsDAO partsDAO;
21
22
23 }
```

We will be testing the update method, so create a testUpdate() method. If we take a close look at the update method in OrderController.java (which we want to test), we see that order is passed as a body variable. So when calling the update method, we need to pass a JSON payload.

So, these are the main differences when compared to our previous test PartTest:

1. The method post is used instead of get
2. An additional method content(payload) is called to pass the JSON payload

Put the following code in the testUpdate() method:

```
@Test
public void testUpdate() throws Exception {
    Part part = new Part("DB-FK-A250-V4", "Drone", "Beta", "TestPart", 100, "Euro");
    Part part2 = new Part("DB-38406-2350KV", "Bike", "Gamma", "TestPart2", 150, "Euro");
    when(partsDAO.getPart("DB-FK-A250-V4")).thenReturn(part);
    when(partsDAO.getPart("DB-38406-2350KV")).thenReturn(part2);
    when(partsDAO.getAmount(Mockito.any(String.class), Mockito.any(Integer.class))).thenReturn(5.0);

    String payload = "{\"clientId\": \"TDF\", \"clientReference\": \"TDF-0067\", \"orderLines\":\n" +
    "[{\"id\": \"DB-FK-A250-V4\", \"count\": 22 }, {\"id\": \"DB-38406-2350KV\", \"count\": 4 }]}";

    this.mockMvc.perform(post("/dronebuzzers/order")
        .contentType(MediaType.APPLICATION_JSON).content(payload)).andDo(print())
        .andExpect(status().isOk());
}
```

Let's have a look at that code. The main test part is:



Spring Boot 101 - intro, demo & handson with Java, REST APIs, Containers & Cloud

```
String payload = "{\"clientId\": \"TDF\", \"clientReference\": \"TDF-0067\", \"orderLines\": [{\"id\": \"DB-FK-A250-V4\", \"count\": 22 }, {\"id\": \"DB-38406-2350KV\", \"count\": 4 }]}\";

this.mockMvc.perform(post(\"/dronebuzzers/order\")
    .contentType(MediaType.APPLICATION_JSON)
    .content(payload))
    .andDo(print())
    .andExpect(status().isOk());
```

In this part, we:

1. Declare a payload
2. Use the post method to submit that payload
3. Using a post operation
4. With content-type set to application/json
5. Prints to the console what is happening
6. ... and checks that the answer is an Ok (HTTP 200)

The other code block is the part where we mock the requests to partsDAO:

```
Part part = new Part("DB-FK-A250-V4", "Drone", "Beta", "TestPart", 100, "Euro");
Part part2 = new Part("DB-38406-2350KV", "Bike", "Gamma", "TestPart2", 150, "Euro");
when(partsDAO.getPart("DB-FK-A250-V4")).thenReturn(part);
when(partsDAO.getPart("DB-38406-2350KV")).thenReturn(part2);
when(partsDAO.getAmount(Mockito.any(String.class), Mockito.any(Integer.class))).thenReturn(5.0);
```

Run the test again and check the body of the response. It should be correctly filled with information of the two (mocked) parts.

If you feel up to it, add some functional and useful expectations to this test.

5. Creating an integration test

So far, we working with the `@WebMvcTest` annotation, which focusses on a particular Controller and expects mocks for all other beans in your application. With that focus on only part of the application, these tests are focusing on units (and will most likely run pretty fast).

Now, we'll introduction the `@SpringBootTest` annotation. This annotation starts the complete application. So, this `@SpringBootTest` annotation is more geared to integration tests.



Spring Boot 101 - intro, demo & hands on with Java, REST APIs, Containers & Cloud

Create a new file named `PartIntegrationTest.java` in the same folder as the `PartTest.java`.

Add the following annotations:

```
@RunWith(SpringRunner.class)
@SpringBootTest(webEnvironment = SpringBootTest.WebEnvironment.RANDOM_PORT)
```

The `@SpringBootTest` annotation will start the entire server running our web service. The parameter `webEnvironment` will ensure that the server is running on a random available port.

Add the following global variable:

```
@Autowired
private TestRestTemplate restTemplate;
```

This bean is preconfigured to resolve relative paths, like `dronebuzzers/part`. So all test calls can be made to this bean.

Create a new test method `testGet()` and give it the `@Test` annotation. Use the id `DB-FK-A250-V4` in the request and assert on some fields and the http status:

```
@Test
public void testGet() {
    ResponseEntity<Part> responseEntity =
        restTemplate.getForEntity("/dronebuzzers/part/DB-FK-A250-V4", Part.class);
    Part resultPart = responseEntity.getBody();
    assertEquals(HttpStatus.OK, responseEntity.getStatusCode());
    assertEquals("DB-FK-A250-V4", resultPart.getId());
    assertEquals("Frame", resultPart.getType());
    assertEquals("Drone", resultPart.getCategory());
    assertEquals("DroneBuzzer Frame Kit regular V4 (2016 edition)", resultPart.getName());
}
```

You will notice that no mocks are defined, since we are testing with the entire server up and running. Therefore, all data in the response is coming from the real `PartsDAO` object. (Still, in this case this is not a real database, but a `MockedPartsDAO` file with hardcoded data)

Run the test and check the results.

Try to create your own method for the `getAll()` method of the `PartController.java` and assert on some response fields. Once again, no mocks need to be defined.

Note: a completed project with tests is available:

`/home/developer/projects/SIGSpringBoot101/lab 5/dronebuzzers-completed`