

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Rainbow Background Animation</title>
  <style>
    /* Define the keyframes for the rainbow background animation */
    @keyframes rainbow-background {
      0% {
        background-color: red;
      }
      16.7% {
        background-color: orange;
      }
      33.3% {
        background-color: yellow;
      }
      50% {
        background-color: green;
      }
      66.7% {
        background-color: blue;
      }
      83.3% {
        background-color: indigo;
      }
      100% {
        background-color: violet;
      }
    }

    /* Apply the animation to elements with the RainbowBackground class */
    .RainbowBackground {
      width: 200px;
      height: 200px;
      animation: rainbow-background 5s infinite;
    }
  </style>
</head>
<body>
  <!-- Apply the RainbowBackground class to an element -->
  <div class="RainbowBackground"></div>
</body>
</html>

```

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Hover Effect Example</title>
  <style>
    .Example {
      height: 100px;
      background: #fff;
      transition: height 0.5s, background 0.5s;
    }

    .Example:hover {
      height: 120px;
      background: #ff0000;
    }
  </style>
</head>
<body>
  <div class="Example">Hover me</div>
</body>
</html>
```

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Hover Effect Example</title>
  <style>
    .Example {
      height: 100px;
      background: #fff;
      transition: all 400ms ease;
    }

    .Example:hover {
      height: 120px;
      background: #ff0000;
    }
  </style>
</head>
<body>
  <div class="Example">Hover me</div>
</body>
```

</html>

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Hover Effect Example</title>
  <style>
    .Example {
      height: 100px;
      background: #fff;
      transition: all 400ms ease;
      -moz-transition: all 400ms ease; /* Firefox */
      -webkit-transition: all 400ms ease; /* Safari and Chrome */
    }

    .Example:hover {
      height: 120px;
      background: #ff0000;
    }
  </style>
</head>
<body>
  <div class="Example">Hover me</div>
</body>
</html>
```

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Animation Example</title>
  <style>
    @keyframes slidein {
      0% {
        transform: translateX(0);
      }
      100% {
        transform: translateX(100px);
      }
    }
  </style>
</head>
<body>
  <div class="box">
    <div class="text">
      Hello World!
    </div>
  </div>
</body>
</html>
```

```

    }

    .animated-element {
        width: 100px;
        height: 100px;
        background-color: blue;
        animation-duration: 3s;
        animation-timing-function: ease-in;
        animation-delay: 1s;
        animation-iteration-count: 2;
        animation-direction: reverse;
        animation-fill-mode: both;
        animation-play-state: paused;
        animation-name: slidein;
    }

    /* You can add more styles or keyframes as needed */
</style>
</head>
<body>
    <div class="animated-element"></div>
</body>
</html>

```

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Animation Example</title>
    <style>
        @keyframes slidein {
            0% {
                transform: translateX(0);
                opacity: 1;
            }
            100% {
                transform: translateX(100px);
                opacity: 0.5;
            }
        }

        .Example {
            width: 100px;
            height: 100px;
            background-color: blue;

```

```
        animation-duration: 3s;
        animation-timing-function: ease-in;
        animation-delay: 1s;
        animation-iteration-count: 2;
        animation-direction: reverse;
        animation-fill-mode: both;
        animation-play-state: paused;
        animation-name: slidein;
        will-change: transform, opacity;
    }

    /* You can add more styles or keyframes as needed */
</style>
</head>
<body>
    <div class="Example"></div>
</body>
</html>
```