

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<style>
  body {
    font-family: Arial, sans-serif;
    background-color: #f0f0f0;
    display: flex;
    justify-content: center;
    align-items: center;
    height: 100vh;
    margin: 0;
  }

  h1 {
    font-size: 36px;
    text-shadow:
      orange 2px 2px 3px,
      purple -2px -2px 5px;
  }
</style>
<title>Text Shadow Example</title>
</head>
<body>
  <h1>Alternate Text Shadow</h1>
</body>
</html>
```

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<style>
  body {
    font-family: Arial, sans-serif;
    background-color: #f0f0f0;
    display: flex;
    justify-content: center;
    align-items: center;
    height: 100vh;
    margin: 0;
  }
}
```

```

    div, p {
        color: blue;
    }
</style>
<title>Styling Example</title>
</head>
<body>
    <div>This is a styled div element.</div>
    <p>This is a styled p element.</p>
</body>
</html>

```

```

<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<style>
    body {
        font-family: Arial, sans-serif;
        background-color: #f0f0f0;
        display: flex;
        flex-direction: column;
        align-items: center;
        justify-content: center;
        height: 100vh;
        margin: 0;
    }

    p, .blue, #first, div span {
        color: blue;
    }
</style>
<title>Styling Example</title>
</head>
<body>
    <p>This is a styled p element.</p>
    <p class="blue">This is a blue-styled p element with the class "blue".</p>
    <div id="first">This is a div element with the ID "first".</div>
    <div>
        This is a div element with a <span>span</span> inside it, both styled with blue
        color.
    </div>
</body>
</html>

```

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<style>
  body {
    font-family: Arial, sans-serif;
    background-color: #f0f0f0;
    display: flex;
    flex-direction: column;
    align-items: center;
    justify-content: center;
    height: 100vh;
    margin: 0;
  }

  /* This is a CSS comment */
  div {
    color: red; /* This is a CSS comment */
  }
</style>
<title>CSS Comment Example</title>
</head>
<body>
  <div>This text is styled with red color.</div>
</body>
</html>
```

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<style>
  body {
    font-family: Arial, sans-serif;
    background-color: #f0f0f0;
    display: flex;
    flex-direction: column;
    align-items: center;
    justify-content: center;
    height: 100vh;
    margin: 0;
  }
```

```

/*
  This
  is
  a
  CSS
  comment
*/
div {
  color: red;
}
</style>
<title>CSS Comment Example</title>
</head>
<body>
  <div>This text is styled with red color.</div>
</body>
</html>

```

```

<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<style>
  body {
    font-family: Arial, sans-serif;
    background-color: #f0f0f0;
    display: flex;
    flex-direction: column;
    align-items: center;
    justify-content: center;
    height: 100vh;
    margin: 0;
  }

  div[data-color] {
    color: red;
  }
</style>
<title>Attribute Selector Example</title>
</head>
<body>
  <div data-color="red">This text will be red</div>
  <div data-color="green">This text will be red as well</div>
  <div data-background="red">This text will NOT be red</div>
</body>
</html>

```

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<style>
  body {
    font-family: Arial, sans-serif;
    background-color: #f0f0f0;
    display: flex;
    flex-direction: column;
    align-items: center;
    justify-content: center;
    height: 100vh;
    margin: 0;
  }

  [class*="foo"] {
    color: red;
  }
</style>
<title>Attribute Selector with Substring Example</title>
</head>
<body>
  <div class="foo-123">This text will be red</div>
  <div class="foo123">This text will be red as well</div>
  <div class="bar123foo">This text will be red too</div>
  <div class="barfooo123">This text will be red too</div>
  <div class="barfo0">This text will NOT be red</div>
</body>
</html>
```