

Additional exercises

Question 1

Level 1

Question:

Write a program which will find all such numbers which are divisible by 7 but are not a multiple of 5, between 2000 and 3200 (both included). The numbers obtained should be printed in a comma-separated sequence on a single line.

Hints: Consider use range(#begin, #end) method

Question 3

Level 1

##Question: Write a program which can compute the factorial of a given numbers. The results should be printed in a comma-separated sequence on a single line. Suppose the following input is supplied to the program: 8 Then, the output should be: 40320

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 3

Level 1

Question:

With a given integral number n, write a program to generate a dictionary that contains (i, i*i) such that i is an integral number between 1 and n (both included). and then the program should print the dictionary. Suppose the following input is supplied to the program: 8 Then, the output should be: {1: 1, 2: 4, 3: 9, 4: 16, 5: 25, 6: 36, 7: 49, 8: 64}

Hints: In case of input data being supplied to the question, it should be assumed to be a

console input. Consider use dict()

Question 4

Level 1

Question:

Write a program which accepts a sequence of comma-separated numbers from console and generate a list and a tuple which contains every number. Suppose the following input is supplied to the program: 34,67,55,33,12,98 Then, the output should be: ['34', '67', '55', '33', '12', '98'] ('34', '67', '55', '33', '12', '98')

Hints: In case of input data being supplied to the question, it should be assumed to be a console input. tuple() method can convert list to tuple

Question 5

Level 1

Question:

Define a class which has at least two methods: getString: to get a string from console input printString: to print the string in upper case. Also please include simple test function to test the class methods.

Hints: Use **init** method to construct some parameters

Question 6

Level 2

Question:

Write a program that calculates and prints the value according to the given formula: $Q = \text{Square root of } [(2 * C * D)/H]$ Following are the fixed values of C and H: C is 50. H is 30. D is the variable whose values should be input to your program in a comma-separated sequence. Example Let us assume the following comma separated input sequence is given

to the program: 100,150,180 The output of the program should be: 18,22,24

Hints: If the output received is in decimal form, it should be rounded off to its nearest value (for example, if the output received is 26.0, it should be printed as 26) In case of input data being supplied to the question, it should be assumed to be a console input.

Question 7

Level 2

Question:

Write a program which takes 2 digits, X,Y as input and generates a 2-dimensional array. The element value in the i-th row and j-th column of the array should be $i*j$. Note: $i=0,1\dots, X-1$; $j=0,1\dots, Y-1$. Example Suppose the following inputs are given to the program: 3,5 Then, the output of the program should be: `[[0, 0, 0, 0, 0], [0, 1, 2, 3, 4], [0, 2, 4, 6, 8]]`

Hints: Note: In case of input data being supplied to the question, it should be assumed to be a console input in a comma-separated form.

Question 8

Level 2

Question:

Write a program that accepts a comma separated sequence of words as input and prints the words in a comma-separated sequence after sorting them alphabetically. Suppose the following input is supplied to the program: without,hello,bag,world Then, the output should be: bag,hello,without,world

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 9

Level 2

Question

Write a program that accepts sequence of lines as input and prints the lines after making all characters in the sentence capitalized. Suppose the following input is supplied to the program: Hello world Practice makes perfect Then, the output should be: HELLO WORLD PRACTICE MAKES PERFECT

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 10

Level 2

Question:

Write a program that accepts a sequence of whitespace separated words as input and prints the words after removing all duplicate words and sorting them alphanumerically. Suppose the following input is supplied to the program: hello world and practice makes perfect and hello world again Then, the output should be: again and hello makes perfect practice world

Hints: In case of input data being supplied to the question, it should be assumed to be a console input. We use set container to remove duplicated data automatically and then use sorted() to sort the data.

Question 11

Level 2

Question:

Write a program which accepts a sequence of comma separated 4 digit binary numbers as its input and then check whether they are divisible by 5 or not. The numbers that are divisible by 5 are to be printed in a comma separated sequence. Example: 0100,0011,1010,1001 Then the output should be: 1010 Notes: Assume the data is input by console.

Hints: In case of input data being supplied to the question, it should be assumed to be a

console input.

Question 12

Level 2

Question:

Write a program, which will find all such numbers between 1000 and 3000 (both included) such that each digit of the number is an even number. The numbers obtained should be printed in a comma-separated sequence on a single line.

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 13

Level 2

Question:

Write a program that accepts a sentence and calculate the number of letters and digits. Suppose the following input is supplied to the program: hello world! 123 Then, the output should be: LETTERS 10 DIGITS 3

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 14

Level 2

Question:

Write a program that accepts a sentence and calculate the number of upper case letters and lower case letters. Suppose the following input is supplied to the program: Hello world! Then, the output should be: UPPER CASE 1 LOWER CASE 9

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 15

Level 2

Question:

Write a program that computes the value of $a+aa+aaa+aaaa$ with a given digit as the value of a . Suppose the following input is supplied to the program: 9 Then, the output should be: 11106

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 16

Level 2

Question:

Use a list comprehension to square each odd number in a list. The list is input by a sequence of comma-separated numbers. Suppose the following input is supplied to the program: 1,2,3,4,5,6,7,8,9 Then, the output should be: 1,3,5,7,9

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 17

Level 2

Question:

Write a program that computes the net amount of a bank account based a transaction log from console input. The transaction log format is shown as following: D 100 W 200

D means deposit while W means withdrawal. Suppose the following input is supplied to the program: D 300 D 300 W 200 D 100 Then, the output should be: 500

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 18

Level 3

Question:

A website requires the users to input username and password to register. Write a program to check the validity of password input by users. Following are the criteria for checking the password:

1. At least 1 letter between [a-z]
 2. At least 1 number between [0-9]
 3. At least 1 letter between [A-Z]
 4. At least 1 character from [\$#@]
 5. Minimum length of transaction password: 6
 6. Maximum length of transaction password: 12
- Your program should accept a sequence of comma separated passwords and will check them according to the above criteria. Passwords that match the criteria are to be printed, each separated by a comma.
- Example If the following passwords are given as input to the program: ABd1234@1,a F1#,2w3E*,2We3345 Then, the output of the program should be: ABd1234@1

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 19

Level 3

Question:

You are required to write a program to sort the (name, age, height) tuples by ascending order where name is string, age and height are numbers. The tuples are input by console.

The sort criteria is: 1: Sort based on name; 2: Then sort based on age; 3: Then sort by score. The priority is that name > age > score. If the following tuples are given as input to the program: Tom,19,80 John,20,90 Jony,17,91 Jony,17,93 Json,21,85 Then, the output of the program should be: [('John', '20', '90'), ('Jony', '17', '91'), ('Jony', '17', '93'), ('Json', '21', '85'), ('Tom', '19', '80')]

Hints: In case of input data being supplied to the question, it should be assumed to be a console input. We use itemgetter to enable multiple sort keys.

Question 20

Level 3

Question:

Define a class with a generator which can iterate the numbers, which are divisible by 7, between a given range 0 and n.

Hints: Consider use yield

Question 21

Level 3

Question

A robot moves in a plane starting from the original point (0,0). The robot can move toward UP, DOWN, LEFT and RIGHT with a given steps. The trace of robot movement is shown as the following: UP 5 DOWN 3 LEFT 3 RIGHT 2 ; The numbers after the direction are steps. Please write a program to compute the distance from current position after a sequence of movement and original point. If the distance is a float, then just print the nearest integer. Example: If the following tuples are given as input to the program: UP 5 DOWN 3 LEFT 3 RIGHT 2 Then, the output of the program should be: 2

Hints: In case of input data being supplied to the question, it should be assumed to be a console input.

Question 22

Level 3

Question:

Write a program to compute the frequency of the words from the input. The output should output after sorting the key alphanumerically. Suppose the following input is supplied to the program: New to Python or choosing between Python 2 and Python 3? Read Python 2 or Python 3. Then, the output should be: 2:2 3.:1 3?:1 New:1 Python:5 Read:1 and:1 between:1 choosing:1 or:2 to:1

Hints In case of input data being supplied to the question, it should be assumed to be a console input.

Question 23

level 1

Question:

Write a method which can calculate square value of number

Hints: Using the ** operator

Question 24

Level 1

Question:

Python has many built-in functions, and if you do not know how to use it, you Please write a program to print some Python built-in functions documents, such And add document for your own function

Hints: The built-in document method is **doc**

Question 25

Level 1

Question:

Define a class, which have a class parameter and have a same instance parameter

Hints: Define a instance parameter, need add it in **init** method You can init a object with construct parameter or set the value later

Question:

Define a function which can compute the sum of two numbers.

Hints: Define a function with two numbers as arguments. You can compute the sum in the function and return the value.

Question:

Define a function that can convert a integer into a string and print it in console.

Hints:

Use `str()` to convert a number to string.

Question:

Define a function that can convert a integer into a string and print it in console.

Hints:

Use `str()` to convert a number to string.

Question:

Define a function that can receive two integral numbers in string form and compute their sum and then print it in console.

Hints:

Use `int()` to convert a string to integer.

2.10

Question:

Define a function that can accept two strings as input and concatenate them and then print it in console.

Hints:

Use `+` to concatenate the strings

Question:

Define a function that can accept two strings as input and print the string with maximum length in console. If two strings have the same length, then the function should print all strings line by line.

Hints:

Use `len()` function to get the length of a string

Question:

Define a function that can accept an integer number as input and print the "It is an even number" if the number is even, otherwise print "It is an odd number".

Hints:

Use `%` operator to check if a number is even or odd.

Question:

Define a function which can print a dictionary where the keys are numbers between 1 and 3 (both included) and the values are square of keys.

Hints:

Use `dict[key]=value` pattern to put entry into a dictionary. Use `**` operator to get power of a number.

Question:

Define a function which can print a dictionary where the keys are numbers between 1 and 20 (both included) and the values are square of keys.

Hints:

Use dict[key]=value pattern to put entry into a dictionary. Use ** operator to get power of a number. Use range() for loops.

Question:

Define a function which can generate a dictionary where the keys are numbers between 1 and 20 (both included) and the values are square of keys. The function should just print the values only.

Hints:

Use dict[key]=value pattern to put entry into a dictionary. Use ** operator to get power of a number. Use range() for loops. Use keys() to iterate keys in the dictionary. Also we can use item() to get key/value pairs.

Question:

Define a function which can generate a dictionary where the keys are numbers between 1 and 20 (both included) and the values are square of keys. The function should just print the keys only.

Hints:

Use dict[key]=value pattern to put entry into a dictionary. Use ** operator to get power of a number. Use range() for loops. Use keys() to iterate keys in the dictionary. Also we can use item() to get key/value pairs.

Question:

Define a function which can generate and print a list where the values are square of numbers between 1 and 20 (both included).

Hints:

Use `**` operator to get power of a number. Use `range()` for loops. Use `list.append()` to add values into a list.

Question:

Define a function which can generate a list where the values are square of numbers between 1 and 20 (both included). Then the function needs to print the first 5 elements in the list.

Hints:

Use `**` operator to get power of a number. Use `range()` for loops. Use `list.append()` to add values into a list. Use `[n1:n2]` to slice a list

Question:

Define a function which can generate a list where the values are square of numbers between 1 and 20 (both included). Then the function needs to print the last 5 elements in the list.

Hints:

Use `**` operator to get power of a number. Use `range()` for loops. Use `list.append()` to add values into a list. Use `[n1:n2]` to slice a list

Question:

Define a function which can generate a list where the values are square of numbers between 1 and 20 (both included). Then the function needs to print all values except the first 5 elements in the list.

Hints:

Use `**` operator to get power of a number. Use `range()` for loops. Use `list.append()` to add values into a list. Use `[n1:n2]` to slice a list

Question:

Define a function which can generate and print a tuple where the value are square of numbers between 1 and 20 (both included).

Hints:

Use `**` operator to get power of a number. Use `range()` for loops. Use `list.append()` to add values into a list. Use `tuple()` to get a tuple from a list.

Question:

With a given tuple (1,2,3,4,5,6,7,8,9,10), write a program to print the first half values in one line and the last half values in one line.

Hints:

Use `[n1:n2]` notation to get a slice from a tuple.

Question:

Write a program to generate and print another tuple whose values are even numbers in the given tuple (1,2,3,4,5,6,7,8,9,10).

Hints:

Use "for" to iterate the tuple Use `tuple()` to generate a tuple from a list.

Question:

Write a program which accepts a string as input to print "Yes" if the string is "yes" or "YES" or "Yes", otherwise print "No".

Hints:

Use if statement to judge condition.

Question:

Write a program which can filter even numbers in a list by using filter function. The list is: [1,2,3,4,5,6,7,8,9,10].

Hints:

Use `filter()` to filter some elements in a list. Use `lambda` to define anonymous functions.

Question:

Write a program which can `map()` to make a list whose elements are square of elements in `[1,2,3,4,5,6,7,8,9,10]`.

Hints:

Use `map()` to generate a list. Use `lambda` to define anonymous functions.

Question:

Write a program which can `map()` and `filter()` to make a list whose elements are square of even number in `[1,2,3,4,5,6,7,8,9,10]`.

Hints:

Use `map()` to generate a list. Use `filter()` to filter elements of a list. Use `lambda` to define anonymous functions.

Question:

Write a program which can `filter()` to make a list whose elements are even number between 1 and 20 (both included).

Hints:

Use `filter()` to filter elements of a list. Use `lambda` to define anonymous functions.

Question:

Write a program which can `map()` to make a list whose elements are square of numbers between 1 and 20 (both included).

Hints:

Use `map()` to generate a list. Use `lambda` to define anonymous functions.

Question:

Define a class named `American` which has a static method called `printNationality`.

Hints:

Use `@staticmethod` decorator to define class static method.

Question:

Define a class named American and its subclass NewYorker.

Hints:

Use class `Subclass(ParentClass)` to define a subclass.

Question:

Define a class named Circle which can be constructed by a radius. The Circle class has a method which can compute the area.

Hints:

Use `def methodName(self)` to define a method.

Question:

Assuming that we have some email addresses in the "[username@companyname.com](#)" format, please write program to print the user name of a given email address. Both user names and company names are composed of letters only.

Example: If the following email address is given as input to the program:

[john@google.com](#)

Then, the output of the program should be:

john

In case of input data being supplied to the question, it should be assumed to be a console input.

Hints:

Use `\w` to match letters.

Question:

Assuming that we have some email addresses in the "[username@companyname.com](#)" format, please write program to print the company name of a given email address. Both user names and company names are composed of letters only.

Example: If the following email address is given as input to the program:

[john@google.com](#)

Then, the output of the program should be:

google

In case of input data being supplied to the question, it should be assumed to be a console input.

Hints:

Use `\w` to match letters.

Question:

Write a program which accepts a sequence of words separated by whitespace as input to print the words composed of digits only.

Example: If the following words is given as input to the program:

2 cats and 3 dogs.

Then, the output of the program should be:

['2', '3']

In case of input data being supplied to the question, it should be assumed to be a console input.

Hints:

Use `re.findall()` to find all substring using regex.

Question:

Print a unicode string "hello world".

Hints:

Use u'strings' format to define unicode string.

Question:

Write a special comment to indicate a Python source code file is in unicode.

Hints:

```
-- coding: utf-8 --
```

Question:

Write a program to compute $1/2+2/3+3/4+\dots+n/n+1$ with a given n input by console ($n>0$).

Example: If the following n is given as input to the program:

5

Then, the output of the program should be:

3.55

In case of input data being supplied to the question, it should be assumed to be a console input.

Hints: Use float() to convert an integer to a float

Question:

Write a program to compute:

$f(n)=f(n-1)+100$ when $n>0$ and $f(0)=1$

with a given n input by console ($n>0$).

Example: If the following n is given as input to the program:

5

Then, the output of the program should be:

500

In case of input data being supplied to the question, it should be assumed to be a console input.

Hints: We can define recursive function in Python.

Question:

The Fibonacci Sequence is computed based on the following formula:

$f(n)=0$ if $n=0$ $f(n)=1$ if $n=1$ $f(n)=f(n-1)+f(n-2)$ if $n>1$

Please write a program to compute the value of $f(n)$ with a given n input by console.

Example: If the following n is given as input to the program:

7

Then, the output of the program should be:

13

In case of input data being supplied to the question, it should be assumed to be a console input.

Hints: We can define recursive function in Python.

Question:

The Fibonacci Sequence is computed based on the following formula:

$f(n)=0$ if $n=0$ $f(n)=1$ if $n=1$ $f(n)=f(n-1)+f(n-2)$ if $n>1$

Please write a program using list comprehension to print the Fibonacci Sequence in comma separated form with a given n input by console.

Example: If the following n is given as input to the program:

7

Then, the output of the program should be:

0,1,1,2,3,5,8,13

Hints: We can define recursive function in Python. Use list comprehension to generate a list from an existing list. Use string.join() to join a list of strings.

In case of input data being supplied to the question, it should be assumed to be a console input.

Question:

Please write a program using generator to print the even numbers between 0 and n in comma separated form while n is input by console.

Example: If the following n is given as input to the program:

10

Then, the output of the program should be:

0,2,4,6,8,10

Hints: Use yield to produce the next value in generator.

In case of input data being supplied to the question, it should be assumed to be a console input.

Question:

Please write a program using generator to print the numbers which can be divisible by 5 and 7 between 0 and n in comma separated form while n is input by console.

Example: If the following n is given as input to the program:

100

Then, the output of the program should be:

0,35,70

Hints: Use yield to produce the next value in generator.

In case of input data being supplied to the question, it should be assumed to be a console input.

Question:

Please write assert statements to verify that every number in the list [2,4,6,8] is even.

Hints: Use "assert expression" to make assertion.

Question:

Please write a program which accepts basic mathematic expression from console and print the evaluation result.

Example: If the following string is given as input to the program:

35+3

Then, the output of the program should be:

38

Hints: Use eval() to evaluate an expression.

Question:

Please write a binary search function which searches an item in a sorted list. The function should return the index of element to be searched in the list.

Hints: Use if/elif to deal with conditions.

Question:

Please write a binary search function which searches an item in a sorted list. The function should return the index of element to be searched in the list.

Hints: Use if/elif to deal with conditions.

Question:

Please generate a random float where the value is between 10 and 100 using Python math module.

Hints: Use random.random() to generate a random float in [0,1].

Question:

Please generate a random float where the value is between 5 and 95 using Python math module.

Hints: Use `random.random()` to generate a random float in `[0,1]`.

Question:

Please write a program to output a random even number between 0 and 10 inclusive using random module and list comprehension.

Hints: Use `random.choice()` to a random element from a list.

Question:

Please write a program to output a random number, which is divisible by 5 and 7, between 0 and 10 inclusive using random module and list comprehension.

Hints: Use `random.choice()` to a random element from a list.

Question:

Please write a program to generate a list with 5 random numbers between 100 and 200 inclusive.

Hints: Use `random.sample()` to generate a list of random values.

Question:

Please write a program to randomly generate a list with 5 even numbers between 100 and 200 inclusive.

Hints: Use `random.sample()` to generate a list of random values.

Question:

Please write a program to randomly generate a list with 5 numbers, which are divisible by 5 and 7 , between 1 and 1000 inclusive.

Hints: Use `random.sample()` to generate a list of random values.

Question:

Please write a program to randomly print a integer number between 7 and 15 inclusive.

Hints: Use `random.randrange()` to a random integer in a given range.

Question:

Please write a program to compress and decompress the string "hello world!hello world!hello world!hello world!".

Hints: Use `zlib.compress()` and `zlib.decompress()` to compress and decompress a string.

Question:

Please write a program to print the running time of execution of "1+1" for 100 times.

Hints: Use `timeit()` function to measure the running time.

Question:

Please write a program to shuffle and print the list [3,6,7,8].

Hints: Use `shuffle()` function to shuffle a list.

Question:

Please write a program to shuffle and print the list [3,6,7,8].

Hints: Use `shuffle()` function to shuffle a list.

Question:

Please write a program to generate all sentences where subject is in ["I", "You"] and verb is in ["Play", "Love"] and the object is in ["Hockey","Football"].

Hints: Use `list[index]` notation to get a element from a list.

Question:

By using list comprehension, please write a program to print the list after removing delete numbers which are divisible by 5 and 7 in [12,24,35,70,88,120,155].

Hints: Use list comprehension to delete a bunch of element from a list.

Question:

By using list comprehension, please write a program to print the list after removing the 0th, 2nd, 4th,6th numbers in [12,24,35,70,88,120,155].

Hints: Use list comprehension to delete a bunch of element from a list. Use enumerate() to get (index, value) tuple.

Question:

By using list comprehension, please write a program generate a 358 3D array whose each element is 0.

Hints: Use list comprehension to make an array.

Question:

By using list comprehension, please write a program to print the list after removing the 0th,4th,5th numbers in [12,24,35,70,88,120,155].

Hints: Use list comprehension to delete a bunch of element from a list. Use enumerate() to get (index, value) tuple.

Question:

By using list comprehension, please write a program to print the list after removing the value 24 in [12,24,35,24,88,120,155].

Hints: Use list's remove method to delete a value.

Question:

With two given lists [1,3,6,78,35,55] and [12,24,35,24,88,120,155], write a program to make a list whose elements are intersection of the above given lists.

Hints: Use set() and "&=" to do set intersection operation.

Question:

Define a class Person and its two child classes: Male and Female. All classes have a method "getGender" which can print "Male" for Male class and "Female" for Female class.

Hints: Use Subclass(Parentclass) to define a child class.

Question:

Please write a program which count and print the numbers of each character in a string input by console.

Example: If the following string is given as input to the program:

abcdefgabc

Then, the output of the program should be:

a,2 c,2 b,2 e,1 d,1 g,1 f,1

Hints: Use dict to store key/value pairs. Use dict.get() method to lookup a key with default value.

Question:

Please write a program which accepts a string from console and print it in reverse order.

Example: If the following string is given as input to the program:

rise to vote sir

Then, the output of the program should be:

ris etov ot esir

Hints: Use list[::-1] to iterate a list in a reverse order.

Question:

Please write a program which accepts a string from console and print the characters that have even indexes.

Example: If the following string is given as input to the program:

H1e2l3l4o5w6o7r8l9d

Then, the output of the program should be:

Helloworld

Hints: Use list[::2] to iterate a list by step 2.

Question:

Please write a program which prints all permutations of [1,2,3]

Hints: Use itertools.permutations() to get permutations of list.

Question:

Write a program to solve a classic ancient Chinese puzzle: We count 35 heads and 94 legs among the chickens and rabbits in a farm. How many rabbits and how many chickens do we have?

Hint: Use for loop to iterate all possible solutions.