

```
(*      Computer Graphics with Applications of Dr. Makhanov.
      Lab 3
      "Flying" Objects and Rotations. *)
```


```
SetOptions[EvaluationNotebook[], ShowCellLabel → False];
```

```
SetOptions[{Graphics, Plot, Plot3D, ContourPlot, ContourPlot3D, DensityPlot, ParametricPlot,
  ParametricPlot3D, ListPlot, ListLinePlot, VectorPlot, VectorPlot3D, StreamPlot,
  ListPointPlot3D, RegionPlot, RegionPlot3D, Graphics, Graphics3D}, ImageSize → Small];
```

```
(* This introduces graphics primitives such as Circle[{x,y},Rc],
Sphere[{x,y,z},Rs], Cuboid[{xc,yc,zc}] (there are many others) where {x,y} and
{x,y,z} is the center of the circle and sphere/cuboid respectively and Rc
Rs the radius. Cuboid[{xc,yc,zc}] represents a unit cuboid with a corner at
{xc,yc,zc}. These functions must be called with displaying functions Graphics
and Graphics3D. See the examples below (you do not need to replicate them) *)
```


```
(* Circle, radius 3 and the center at {1,1} use Graphics *)
```

```
Graphics[Circle[{1, 1}, 3], Axes → True, ImageSize → Tiny]
```




```
(* Sphere radius 2 and the center at {1,1,1} use Graphics3D*)
```

```
Graphics3D[Sphere[{1, 1, 1}, 2], Axes → True, ImageSize → Tiny]
```



```
(* Cube, centered at {1,1,1} with the side 4 *)
```

```
Graphics3D[Cube[{1, 1, 1}, 4], Axes → True,
  ImageSize → Tiny, PlotRange → {{-5, 5}, {-5, 5}, {-5, 5}}]
```



(* ----- PART 1 ----- *)

(* Problem (1) Animate a growing parametric curve given by $x1[t_] := \cos[7t] \cos[11t]$
 $y1[t_] := \cos[7t] \sin[11t]$ $\{t, 0, \pi\}$. The animation parameter s : $\{s, 0.1, \pi, 0.001\}$
 Note the animation parameter s included as follows
 $\text{plot1}[s_] := \text{ParametricPlot}[p1[t], \{t, 0, s\}]$ *)


$x1[t_] := \cos[7t] \cos[11t]$

$y1[t_] := \cos[7t] \sin[11t]$

$p1[t_] := \{x1[t], y1[t]\}$


(* Here is the entire curve. We will need it later *)

$\text{plotg1} = \text{ParametricPlot}[p1[t], \{t, 0, \pi\}, \text{PlotStyle} \rightarrow \text{Red}]$



$\text{plot1}[s_] := \text{ParametricPlot}[p1[t], \{t, 0, s\},$
 $\text{PlotStyle} \rightarrow \text{Red}, \text{PlotRange} \rightarrow \{\{-1, 1\}, \{-1, 1\}\}, \text{PlotPoints} \rightarrow 100]$

$\text{Manipulate}[\text{plot1}[s], \{s, 0.1, \pi, 0.1\}]$




(* Problem (2) Animate a circle with the radius 0.25 moving along a curve from problem 1 use Circle[{x,y},Rss]. Plot the curve and the moving circle on the same graph. Animation parameter s: {s,0.1,Pi,0.001}
Note, Graphics[Circle[p1[s],Rs], where p1[s] is the trajectory *)

```
Rss := 0.25
```

```
plot2[s_] :=
```

```
Graphics[{Blue, Thick, Circle[p1[s], Rss]}, PlotRange → {{-1, 1}, {-1, 1}}, Axes → True]
```


```
Manipulate[plot2[s], {s, 0.1, Pi, 0.001}]
```



(* Plot with the trajectory *)

```
plot1and2[s_] := Show[plot2[s], plotg1]
```

```
Manipulate[plot1and2[s], {s, 0.1, Pi, 0.001}]
```



(* Problem (3) Construct a 2D trajectory based on data3 using the parametric 2D spline. data3 is given in the attached .nb file *)

```
data3 = {{-3, -1}, {-1, -2}, {1, -2}, {2, -3}, {1, -4}, {-1, -4}, {-2, -5}, {-2, -6},
  {-1, -6}, {-1, -5}, {2, -5}, {3, -4}, {6, -5}, {7, -7}, {6, -8}, {6, -9},
  {7, -9}, {7, -8}, {8, -7}, {7, -4}, {6, -4}, {6, -2}, {5, 0}, {10, -1}, {7, 0},
  {10, 0}, {7, 1}, {10, 2}, {8, 2}, {10, 3}, {6, 2}, {5, 0}, {3, 0}, {1, 2}, {1, 3},
  {-2, 6}, {-3, 6}, {-4, 7}, {-4, 6}, {-6, 4}, {-6, 3}, {-5, 3}, {-3, 4}, {-2, 2},
  {-3, 1}, {-5, 2}, {-7, 0}, {-7, -1}, {-6, -1}, {-6, 0}, {-5, 1}, {-4, 0},
  {-5, -2}, {-3, -4}, {-2, -4}, {-2, -3}, {-3, -3}, {-4, -2}, {-3, -1}};
```

```
x3 = Transpose[data3][[1]]
```

```
{-3, -1, 1, 2, 1, -1, -2, -2, -1, -1, 2, 3, 6, 7, 6, 6, 7, 7, 8,
  7, 6, 6, 5, 10, 7, 10, 7, 10, 8, 10, 6, 5, 3, 1, 1, -2, -3, -4, -4, -6, -6,
  -5, -3, -2, -3, -5, -7, -7, -6, -6, -5, -4, -5, -3, -2, -2, -3, -4, -3}
```

```
{-1, -2, -2, -3, -4, -4, -5, -6, -6, -5, -5, -4, -5, -7, -8,
  -9, -9, -8, -7, -4, -4, -2, 0, -1, 0, 0, 1, 2, 2, 3, 2, 0, 0, 2, 3, 6, 6,
  7, 6, 4, 3, 3, 4, 2, 1, 2, 0, -1, -1, 0, 1, 0, -2, -4, -4, -3, -3, -2, -1}
```


```
sx3 = Interpolation[x3]
```

```
InterpolatingFunction[  Domain: {{1, 59}}  
Output: scalar]
```


```
InterpolatingFunction[  Domain: {{1, 59}}  
Output: scalar]
```

```
s3[t_] := {sx3[t], sy3[t]}
```


```
plot31 = ParametricPlot[s3[t], {t, 1, Length[x3]}, PlotStyle -> Purple]
```



```
(* Plot the points using ListPlot *)
```




```
(* Superimpose *)
```



```
(* Problem (4) Animate a Circle of the radius 1 moving along the trajectory from  
Problem 3. Use Graphics[???] The animation parameter s runs from 1 to Length[x3]  
Fix the PlotRange *)
```

```
Rs4 := 1.0
```

```
plot41[s_] :=
```



(* Problem (5) Construct a 3D trajectory based on data5=
 {{1,1,1},{2,3,1},{1,3,2},{4,3,3},{4,4,4},{5,3,2},{7,5,6},{5,5,5}}
 using parametric 3D spline.
 Adapt the solution from Problems 1 and 3 to the 3D case Use
 ListPointPlot3D instead of ListPlot
 and ParametricPlot3D instead of ParametricPlot *)

```
data5 = {{1, 1, 1}, {2, 3, 1}, {1, 3, 2}, {4, 3, 3}, {4, 4, 7}, {5, 3, 2}, {7, 5, 6}, {5, 5, 5}}
{{1, 1, 1}, {2, 3, 1}, {1, 3, 2}, {4, 3, 3}, {4, 4, 7}, {5, 3, 2}, {7, 5, 6}, {5, 5, 5}}
```

```
x5 = Transpose[data5][[1]]
{1, 2, 1, 4, 4, 5, 7, 5}
```

```
{1, 3, 3, 3, 4, 3, 5, 5}
```

```
{1, 1, 2, 3, 7, 2, 6, 5}
```

```
sx5 = Interpolation[
```

```
InterpolatingFunction[
```



 Domain: {{1, 8}}
 Output: scalar

```
] ]
```



```
InterpolatingFunction[ Domain: {{1, 8}}  
Output: scalar]
```

```
s5[t_] := {sx5[t], sy5[t], sz5[t]}
```

```
plot15 = ListPointPlot3D[data5, PlotStyle -> PointSize[0.05]]
```



```
plotg5 = ParametricPlot3D[s5[t], {t, 1, Length[x5]}, PlotStyle -> {Red, Thick}]
```



```
(* Problem (6) Using the 3D spline from problem 5 as the design trajectory
construct an animation of a 3D sphere moving along the trajectory s5[t].
Use plotc7[s_]:=Graphics3D[Sphere[s5[t],Rs6],PlotRange->{{0,8},{0,8},{0,7}}],
where s5[t] is the required trajectory. The radius of the sphere Rs6=0.8 *)
```


```
Rs6 = 0.8
```

```
0.8
```

```
plotc6[s_] := Graphics3D[Sphere[s5[s], Rs6], PlotRange -> {{0, 8}, {0, 8}, {0, 7}}]
```

```
plot6show[s_] := Show[{plotc6[s], plotg5, plotl5], PlotRange -> {{0, 8}, {0, 8}, {0, 9}}]
```

Manipulate



```
(* Problem (7) Using the methods from the previous problems animate a sphere Rs7=
0.5 moving along a trajectory defined by the parametric equations
x7[t_]:=R7*Cos[t]
y7[t_]:=R7*Sin[t/1.2]
z7[t_]:=t/5,
R7=1.5,
{s,0,smax,2}
smax=20
Fig the PlotRange *)
```

```
smax = 20
```

```
20
```

```
Rs7 = 0.5
```

```
0.5
```


`R7 = 1.5`

`1.5`


`x7[t_] := R7 * Cos[t]`

`y7[t_] := R7 * Sin[t / 1.2]`

`z7[t_] := t / 5`

`trajectory7[t_] := {x7[t], y7[t], z7[t]}`

`plotg7 = ParametricPlot3D[trajectory7[t], {t, 0, smax}]`



`plot7[s_] :=`

