TUTORIAL · VERSION 3.2

OrthoFinder

A step-by-step tutorial on installing, running and interpreting OrthoFinder

David Emms, Jonathan Holmes, Laurence Belcher, Yi Liu & Steven Kelly
Department of Biology, University of Oxford
github.com/OrthoFinder/OrthoFinder · orthofinder.github.io/OrthoFinder

Contents

1 Beginner tutorial

1.1 Installing OrthoFinder
1.2 Input files for OrthoFinder
1.3 Running OrthoFinder
1.4 Exploring the results of OrthoFinder
1.5 Viewing the results in a web browser

2 Advanced tutorial on adding species to a core analysis

2.1 The core and assign workflow
2.2 Choosing the core species
2.3 Running it on the example data
2.4 Using outgroups

3 Understanding orthology

3.1 Orthogroups, orthologs and paralogs
3.2 Why orthogroups?
3.3 Hierarchical orthogroups

4 A complete guide to the OrthoFinder results files

4.1 Comparative_Genomics_Statistics
4.2 Gene_Duplication_Events
4.3 MultipleSequenceAlignments
4.4 Orthogroup_Sequences
4.5 Orthogroups
4.6 Orthologs
4.7 Phylogenetic_Hierarchical_Orthogroups
4.8 Phylogenetically_Misplaced_Genes
4.9 Putative_Xenologs
4.10 Resolved_Gene_Trees
4.11 Single_Copy_Ortholog_Sequences
4.12 Species_Tree
4.13 WorkingDirectory
4.14 The pages to view the results (`--view`)

5 Advanced usage

5.1 Stopping and restarting an analysis
5.2 Running the sequence searches separately
5.3 Choosing the methods and programs
5.4 Other options
5.5 Utility tools
5.6 Manually installing the dependencies

6 Getting input data for OrthoFinder

6.1 Getting data from Ensembl

6.2 Getting data from NCBI
6.3 Getting data from Phytozome
6.4 Preparing the files

7 Citing OrthoFinder

CHAPTER 1

Beginner tutorial

This tutorial covers the following.

1. Installing OrthoFinder
2. Input files for OrthoFinder
3. Running OrthoFinder
4. Exploring the results of OrthoFinder
5. Viewing the results in a web browser

All the steps are done on the command line, so that you can copy and paste the commands. If you are not familiar with the command line, there are many online tutorials and reference pages. here is a short one that covers the basics.

Throughout this tutorial we use the example data that comes with OrthoFinder, the proteomes of four *Mycoplasma* species (*M. agalactiae*, *M. gallisepticum*, *M. genitalium* and *M. hyopneumoniae*). They are small, so every step runs in seconds, and every number and gene name in this tutorial is from a real run of OrthoFinder v3.2 on them. Your numbers may differ very slightly.

1.1 Installing OrthoFinder

OrthoFinder runs on Linux (including WSL2 on Windows) and macOS, and needs Python 3.11 or later. There are three ways of installing it. Conda is the simplest, because it installs everything OrthoFinder depends on. We recommend it if you are new to the command line.

1.1.1 Install with conda (recommended)

If you don't have conda, install Miniconda first, following the instructions on its website. Then create an environment for OrthoFinder and install it from Bioconda.

```
conda create -n of3_env -c conda-forge -c bioconda python=3.12 orthofinder=3.2
conda activate of3_env
```

On a Mac with an Apple silicon chip (M1, M2, M3 …), some of the programs OrthoFinder uses are only available for Intel Macs. Create the environment for Intel instead (macOS runs it with Rosetta).

```
CONDA_SUBDIR=osx-64 conda create -n of3_env -c conda-forge -c bioconda python=3.12 orthofinder=3.2
conda activate of3_env
conda config --env --set subdir osx-64
```

1.1.2 Install from GitHub with pip

```
python3 -m venv of3_env
. of3_env/bin/activate
pip install git+https://github.com/OrthoFinder/OrthoFinder.git@v3.2
```

The `@v3.2` installs the release. Without it, pip installs the latest development code on the main branch, and `orthofinder -v` then shows a development version such as `3.2.post1.dev4`.

1.1.3 Install from the release files

Each release on GitHub has two archives of the source code.

- `orthofinder-linux-intel-3.2.tar.gz` also contains the programs OrthoFinder runs (DIAMOND, FAMSA, FastTree, MCL, MAFFT …), built for Linux on Intel/AMD processors. Use it on a Linux machine where you can't install them yourself.
- `orthofinder-3.2.tar.gz` is the source code only (it is the archive the Bioconda package is built from). OrthoFinder then uses the programs installed on your system.

```
mkdir OrthoFinder
wget -qO- https://github.com/OrthoFinder/OrthoFinder/releases/download/v3.2/orthofinder-linux-intel-
3.2.tar.gz | \
  tar -xz --strip-components=1 -C OrthoFinder
cd OrthoFinder
python3 -m venv of3_env
. of3_env/bin/activate
pip install .
```

Installed with pip, OrthoFinder is available only in the `of3_env` environment, which avoids conflicts with other Python packages. Leave the environment with `deactivate`, and come back to it with `. of3_env/bin/activate` (or `conda activate of3_env`).

1.1.4 Test your installation

```
orthofinder -h      # print the help text: all the command-line options
orthofinder -v      # print the version
```

Then test OrthoFinder on the example dataset. It is in the source code, in `ExampleData/`, and can be downloaded on its own from the release page (`ExampleData.tar.gz`).

```
wget https://github.com/OrthoFinder/OrthoFinder/releases/download/v3.2/ExampleData.tar.gz
tar -xzf ExampleData.tar.gz
orthofinder -f ExampleData/
```

At the start of each run, OrthoFinder checks that it can run each program it needs, as in this example.

```
Checking required programs are installed
=========================================
Test can run "mcl" - ok
Test can run "famsa" - ok
Test can run "fasttree" - ok
```

If a test fails, OrthoFinder stops and says which program is missing (see 5.6 to install it). If you get any other error, the best first step is to search for the error message. You can also look for it, or ask, on the GitHub issues page.

1.2 Input files for OrthoFinder

OrthoFinder needs one FASTA file for each species, all in one directory. Each file contains the amino acid sequences of all the protein-coding genes of that species, with **one sequence per gene**. The name of the file (without its extension) is the name of the species in all the results, so short, clear names such as `Homo_sapiens.fa` keep the results tidy. The files must end in `.fa`, `.faa`, `.fasta`, `.fas`, `.pep` or `.fna`, and be uncompressed (run `gunzip` on `.gz` files first). Other files in the directory are ignored.

The proteomes downloaded from most databases contain several sequences for many genes, one for each transcript (isoform). Running OrthoFinder on them takes longer and gives less accurate results, so keep only the longest transcript of each gene with the `primary_transcript` tool, which is installed with OrthoFinder.

```
primary_transcript Proteomes/
```

This writes the files to `Proteomes/primary_transcripts/`, ready for OrthoFinder. Section 6 shows how to download proteomes from Ensembl, NCBI and Phytozome and prepare them. For this tutorial, the example data is already prepared.

OrthoFinder can also be run on nucleotide sequences with `-d` (see 5.3), but protein sequences give much more accurate results.

1.3 Running OrthoFinder

We are now ready to run OrthoFinder on the four proteomes in `ExampleData/`.

```
orthofinder -f ExampleData/ -t 8
```

`-t` is the number of threads for the sequence searches, the slowest step for large datasets. By default OrthoFinder uses half the CPU cores of the machine (on a cluster, the cores allocated to the job). `-a` sets the threads for the rest of the analysis (by default a quarter of `-t`, at least 1, and `orthofinder -h` shows both defaults for your computer). With many species, more analysis threads make the later stages faster but need more memory.

OrthoFinder prints its progress as it runs through these stages.

1. **Sequence search.** An all-versus-all DIAMOND search of the proteins of every species against every species.
2. **Orthogroups.** The genes are clustered into orthogroups with MCL, from the search results.
3. **Gene trees.** A multiple sequence alignment (FAMSA) and gene tree (FastTree) for each orthogroup.
4. **Species tree.** Inferred from the concatenated alignment of the single-copy orthogroups, and rooted from the gene duplication events in the gene trees (STRIDE).
5. **Reconciliation.** Each gene tree is rooted and resolved against the species tree, to find the gene duplication events, the hierarchical orthogroups (HOGs) and the orthologs.

At the end it prints a summary and the location of the results.

```
Summary:
 OrthoFinder assigned 2216 genes (81.1% of total) to 599 orthogroups.
 50% of genes were in orthogroups with 4 or more genes (G50 was 4) and were
 contained in the largest 278 orthogroups (O50 was 278).
 There were 274 orthogroups with all species present and 250 of these consisted
 entirely of single-copy genes.

Results directory:
    ExampleData/OrthoFinder/Results_Oct21/
```

The results directory is named after the date. `-n <name>` names it `Results_<name>` instead, and `-o <dir>` puts it somewhere else than `OrthoFinder/` in the input directory. A run with the same name or date as an earlier run gets a number (`Results_Oct21_1`), so results are never overwritten.

> **How long will it take?** The example data takes about ten seconds. For tens of species with typical eukaryotic proteomes, expect hours. Most of the time is the sequence search, which grows with the square of the number of species. For more than about 100 species, use the core and assign workflow of section 2 instead.

1.4 Exploring the results of OrthoFinder

OrthoFinder creates the results directory inside `ExampleData/OrthoFinder/`. Its contents (with most per-orthogroup files left out) look like this.

```
Results_Oct21/
├── Citation.txt
├── Log.txt
├── Comparative_Genomics_Statistics/
│   ├── Duplications_per_Orthogroup.tsv
│   ├── Duplications_per_Species_Tree_Node.tsv
│   ├── OrthologsStats_many-to-many.tsv
│   ├── OrthologsStats_many-to-one.tsv
│   ├── OrthologsStats_one-to-many.tsv
│   ├── OrthologsStats_one-to-one.tsv
│   ├── OrthologsStats_Totals.tsv
│   ├── Statistics_Overall.tsv
│   └── Statistics_PerSpecies.tsv
├── Gene_Duplication_Events/
│   ├── Duplications.tsv
│   └── SpeciesTree_Gene_Duplications_0.5_Support.txt
├── MultipleSequenceAlignments/        OG0000000.fa … (one per orthogroup)
├── Orthogroup_Sequences/              OG0000000.fa … (one per orthogroup)
├── Orthogroups/
│   ├── Orthogroups.GeneCount.tsv
│   ├── Orthogroups_SingleCopyOrthologs.txt
│   ├── Orthogroups.tsv
│   ├── Orthogroups.txt
│   └── Orthogroups_UnassignedGenes.tsv
├── Orthologs/
│   ├── Mycoplasma_agalactiae.tsv.gz   … (one per species)
├── Phylogenetic_Hierarchical_Orthogroups/
│   ├── N1.tsv
│   └── N2.tsv
├── Phylogenetically_Misplaced_Genes/
├── Putative_Xenologs/
│   ├── Mycoplasma_agalactiae.tsv      … (one per species)
├── Resolved_Gene_Trees/
│   └── Resolved_Gene_Trees.txt
├── Single_Copy_Ortholog_Sequences/    OG0000055.fa …
├── Species_Tree/
│   ├── Orthogroups_for_concatenated_alignment.txt
│   ├── SpeciesTree_rooted.txt
│   └── SpeciesTree_rooted_node_labels.txt
└── WorkingDirectory/
```

All the tables are tab-separated text files. They can be opened in a spreadsheet program such as Excel or LibreOffice Calc (choose "tab" as the separator if asked), in R (`read.delim`) or Python (`pandas.read_csv(..., sep="\t")`), or looked at on the command line. The trees are text files in Newick format, which tree viewers such as iTOL, Dendroscope or FigTree open. The `.gz` files are compressed. Read them with `zcat` , `zgrep` or `zless` , or uncompress them with `gunzip` . Section 4 describes every file.

1.4.1 Step 1. Quality control

Before diving into the orthogroups, check the quality of the run, i.e. that most genes of all species have been assigned to orthogroups, and that the species tree looks right.

1.4.1.1 The proportion of genes in orthogroups

Open `Comparative_Genomics_Statistics/Statistics_Overall.tsv` . Its first lines are shown below.

Number of species	4
Number of genes	2733
Number of genes in orthogroups	2216
Number of unassigned genes	517
Percentage of genes in orthogroups	**81.1**
Percentage of unassigned genes	18.9
Number of orthogroups	599
Number of species-specific orthogroups	84
Number of genes in species-specific orthogroups	379
Mean orthogroup size	3.7
G50 (assigned genes)	4
O50 (assigned genes)	213
Number of orthogroups with all species present	274
Number of single-copy orthogroups	250

On the 5th line is the **percentage of genes in orthogroups**, here 81.1%. A good rule of thumb is that it should be above 80%. If it is much lower, OrthoFinder is likely missing orthology relationships that exist, usually because some species are too distantly related to the others. The best fix is better species sampling, adding species that fill the gaps in the tree. An "unassigned gene" is a gene that is not in an orthogroup with any other gene. Each unassigned gene is listed, as an orthogroup of its own, in `Orthogroups/Orthogroups_UnassignedGenes.tsv`.

The later lines of the file give the distribution of orthogroup sizes, i.e. how many orthogroups have, on average, less than one gene per species, one gene per species, two, and so on. A few very large orthogroups often come from large gene families or transposable elements.

Now open `Statistics_PerSpecies.tsv` from the same directory. It gives the same statistics for each species.

	M. agalactiae	M. gallisepticum	M. genitalium	M. hyopneumoniae
Number of genes	820	763	476	674
Number of genes in orthogroups	650	597	417	552
Percentage of genes in orthogroups	79.3	78.2	87.6	81.9
Number of species-specific orthogroups	37	11	3	33
Genes in species-specific orthogroups (%)	20.9	12.5	1.3	15.9

Most genes of every species are in orthogroups. The lowest is *M. gallisepticum*, with 78.2%. Always look at these numbers before interpreting the results. If one species has a much lower percentage than the others, it is either distantly related to all of them (add species in between), or there is a problem with its proteome, such as a poor annotation, many fragmented genes, or many transcripts per gene that were not filtered out.

1.4.1.2 The species tree

Next, look at the species tree, `Species_Tree/SpeciesTree_rooted.txt`. Go to itol.embl.de, click "Upload a tree" and drag and drop the file onto the page (or open it in another tree viewer).




Figure 1.1. The rooted species tree of the example data, with the labels of its internal nodes (from `SpeciesTree_rooted_node_labels.txt`).

Do a common-sense check that the tree agrees with what is known about the species, so that you are not rewriting the history of life on Earth. Here, *M. genitalium* and *M. gallisepticum* are sister species, as are *M. hyopneumoniae* and *M. agalactiae*, as expected. `SpeciesTree_rooted_node_labels.txt` is the same tree with its internal nodes named N0 (the root), N1, N2 …. The other results files use these names, so keep this tree at hand.

If the tree is wrong, the orthogroups are not affected, but the gene duplication events, the hierarchical orthogroups, and the orthologs and paralogs within each orthogroup may be. The most common cause is a wrong root. You can rerun the last stages of OrthoFinder with a corrected tree, which is quick because the sequence searches and gene trees are reused (see 5.1).

```
orthofinder -fgt ExampleData/OrthoFinder/Results_Oct21/ -s corrected_species_tree.txt
```

The tree given with `-s` must be rooted and in Newick format, with the species named as in the results (e.g. `Mycoplasma_agalactiae`, or `Mycoplasma agalactiae`). Branch lengths are optional.

```
((Mycoplasma_genitalium,Mycoplasma_gallisepticum),(Mycoplasma_hyopneumoniae,Mycoplasma_agalactiae));
```

1.4.2 Step 2. Interpreting the results

Now that we are happy with the run, we can start diving into the results. We will follow one gene through them, the gene `gi|144227417|gb|AAZ44095.2|` of *M. hyopneumoniae*.

1.4.2.1 Orthologs

First, we find the orthologs of our gene in *M. agalactiae*. The orthologs of each species are in the directory `Orthologs/`, in one compressed file per species, `Orthologs/<species>.tsv.gz`. Each row gives, for one orthogroup and one other species, a set of genes of this species and their orthologs in the other species. The columns are as follows.

Orthogroup	Species	Mycoplasma_hyopneumoniae	Orthologs
the orthogroup	the other species	genes of this species	their orthologs in the other species

Search the file of *M. hyopneumoniae* for our gene, and keep the row for *M. agalactiae*.

```
zgrep "AAZ44095.2" Orthologs/Mycoplasma_hyopneumoniae.tsv.gz | grep Mycoplasma_agalactiae
```

```
OG0000035  Mycoplasma_agalactiae  gi|144227417|gb|AAZ44095.2|  gi|290752267|emb|CBH40238.1|,
gi|290752987|emb|CBH40963.1|
```

The gene is in orthogroup **OG0000035**, and it has **two orthologs** in *M. agalactiae*, `gi|290752267|emb|CBH40238.1|` and `gi|290752987|emb|CBH40963.1|`.

If you prefer a file for each pair of species, as written by OrthoFinder before v3.2, run OrthoFinder with `-pof`, or write them afterwards from the results with the `split_ortholog_files` tool.

```
split_ortholog_files ExampleData/OrthoFinder/Results_Oct21/
# only some of the files, e.g. M. hyopneumoniae against M. agalactiae:
split_ortholog_files ExampleData/OrthoFinder/Results_Oct21/ --species Mycoplasma_hyopneumoniae --partners
Mycoplasma_agalactiae
```

This writes `Orthologs/Orthologs_Mycoplasma_hyopneumoniae/Mycoplasma_hyopneumoniae__v__Mycoplasma_agalactiae.tsv` and the other pairs, tables with three columns `Orthogroup`, `Mycoplasma_hyopneumoniae` and `Mycoplasma_agalactiae`. With many species there are n × (n − 1) such files (almost a million for 1,000 species), which is why they are no longer written by default.

The numbers of orthologs between each pair of species are in `Comparative_Genomics_Statistics/OrthologsStats_*.tsv`. For example, *M. hyopneumoniae* and *M. agalactiae* have 357 one-to-one orthologs (`OrthologsStats_one-to-one.tsv`).

1.4.2.2 Gene trees

Next, we look at the gene tree to see how these orthologs arose. OrthoFinder infers the orthologs from the **resolved gene trees**. Each gene tree is rooted and reconciled with the species tree, using a hybrid species-overlap / duplication-loss-coalescence model to find the most parsimonious interpretation of the tree (see the OrthoFinder 2 paper). The resolved trees of all orthogroups are in one file, `Resolved_Gene_Trees/Resolved_Gene_Trees.txt`, a line for each orthogroup with four or more genes (the minimum for a tree).

```
OG0000035:
((Mycoplasma_gallisepticum_gi|31541051|gb|AAP56353.1|:0.94131,Mycoplasma_genitalium_gi|3845066|gb|AAC72490
.1|:0.87787)n1:0.168517,(Mycoplasma_hyopneumoniae_gi|144227417|gb|AAZ44095.2|:0.90289,
(Mycoplasma_agalactiae_gi|290752987|emb|CBH40963.1|:2.10194,Mycoplasma_agalactiae_gi|290752267|emb|CBH4023
8.1|:0.616644)n3:0.068516)n2:0.168517)n0;
```

In the trees each gene is named with its species as a prefix, so that you can see the species in any tree viewer (`-X` leaves the prefix out). The internal nodes are named n0, n1 …. To view one tree, write it to its own file and open it in iTOL or Dendroscope.

```
grep "^OG0000035:" Resolved_Gene_Trees/Resolved_Gene_Trees.txt | cut -d " " -f 2 > OG0000035_tree.txt
```




Figure 1.2. The resolved gene tree of orthogroup OG0000035, with the names of its internal nodes.

The gene tree shows that the two *M. agalactiae* genes arose from a **gene duplication** (node n3) in the lineage leading to *M. agalactiae*, after it split from *M. hyopneumoniae*. The result is a one-to-two orthology relationship. Both *M. agalactiae* genes are equally related to the one *M. hyopneumoniae* gene. Orthology relationships are often not one-to-one, and it is important to know it. You don't want to spend months on experiments on "the ortholog" only to find out later that there are two.

The multiple sequence alignment the tree was inferred from is `MultipleSequenceAlignments/OG0000035.fa`, and the sequences of the genes are in `Orthogroup_Sequences/OG0000035.fa`.

1.4.2.3 Gene duplications

Having the gene trees means that OrthoFinder can identify all the gene duplication events, and map each of them to the branch of the species tree where it occurred. The directory `Gene_Duplication_Events/` has two files to explore them. First, open `Gene_Duplication_Events/SpeciesTree_Gene_Duplications_0.5_Support.txt` in iTOL (in iTOL, go to the "Advanced" tab of the Control Panel and choose "Display" next to "Node IDs" to see the node labels).




Figure 1.3. The number of well-supported gene duplication events on each branch of the species tree.

Each node is named with its label, an underscore, and the number of **well-supported** gene duplication events on the branch leading to it. A duplication is well supported if at least 50% of the species descended from it have kept both copies of the duplicated gene. For example, 5 duplications occurred in the common ancestor of *M. hyopneumoniae* and *M. agalactiae* (N1), and 123 on the branch leading to *M. agalactiae*. The numbers after the species names are the "terminal" duplications, those on the branch leading to that one species. The same numbers, with the numbers of all duplications, are in `Comparative_Genomics_Statistics/Duplications_per_Species_Tree_Node.tsv`.

All the duplication events are listed in `Gene_Duplication_Events/Duplications.tsv`, one per row. The one in our orthogroup is shown below.

Orthogroup	Species Tree Node	Gene Tree Node	Support	Type	Genes 1	Genes 2
OG0000035	Mycoplasma_agalactiae	n3	1.0	Terminal	`Mycoplasma_agalactiae_gi|290752987|emb|CBH40963.1|`	`Mycoplasma_agalactiae_gi|290752267|emb|CBH40238.1|`

Each event is cross-referenced to the orthogroup (and its gene tree) in which it occurred, the node of the gene tree (n3 in Figure 1.2) and the node of the species tree (here the branch leading to *M. agalactiae*). It also lists the genes descended from each of the two copies. The events are also counted for each orthogroup in `Comparative_Genomics_Statistics/Duplications_per_Orthogroup.tsv`.

1.4.2.4 Orthogroups

Often we are interested in comparisons across a group of species rather than between a pair of species. The generalisation of orthology to many species is the **orthogroup**. Just as orthologs are the genes descended from a single gene in the last common ancestor of a pair of species, an orthogroup is the set of genes descended from a single gene in the last common ancestor of a group of species (section 3). Each gene tree is the tree of one orthogroup, and contains all the orthologs between the species in it. Some genes in an orthogroup are paralogs of each other, but taking any of them out would also remove orthologs.

So to compare the "equivalent" genes in a set of species, compare the genes of an orthogroup. The orthogroups are in `Orthogroups/Orthogroups.tsv`, a row for each orthogroup and a column for each species, largest orthogroups first. Here is the row of our orthogroup.

Orthogroup	Mycoplasma_agalactiae	Mycoplasma_gallisepticum	Mycoplasma_genitalium	Mycoplasma_hyopneumoniae
OG0000035	gi|290752267|emb|CBH40238.1| , gi|290752987|emb|CBH40963.1|	gi|31541051|gb|AAP56353.1|	gi|3845066|gb|AAC72490.1|	gi|144227417|gb|AAZ44095.2|

`Orthogroups.GeneCount.tsv` has the number of genes of each species in each orthogroup (here 2, 1, 1, 1, total 5), which is what most analyses of gene family size need. `Orthogroups_SingleCopyOrthologs.txt` lists the orthogroups with exactly one gene from every species (250 in the example), often used for phylogenetics.

> The orthogroups in `Orthogroups.tsv` are the hierarchical orthogroups of the root of the species tree (N0), inferred from the gene trees. They are more accurate than the orthogroups from the MCL clustering of the search results, which OrthoFinder computes first. The MCL orthogroups are written as `Orthogroups/MCL_Orthogroups.tsv` when a run is stopped after them (`-og`) or fails, and kept in a full run with `-mog` .

1.4.2.5 Hierarchical orthogroups

OrthoFinder also infers the orthogroups at each node of the species tree, the **phylogenetic hierarchical orthogroups (HOGs)**. A HOG at node N1 is the set of genes descended from a single gene in the ancestor of the species below N1. The directory `Phylogenetic_Hierarchical_Orthogroups/` has a file for each internal node, `N1.tsv` , `N2.tsv` , …. There is no `N0.tsv` , because the HOGs of the root are the orthogroups in `Orthogroups/Orthogroups.tsv` . Compare the node names with `Species_Tree/SpeciesTree_rooted_node_labels.txt` (Figure 1.1) to see the species included.

Our orthogroup OG0000035 has a HOG at each of the two nodes.

HOG	OG	Gene Tree Parent Clade	M. agalactiae	M. gallisepticum	M. genitalium	M. hyopneumoniae
N1.HOG0000036	OG0000035	n0	…CBH40238.1| , …CBH40963.1|			…AAZ44095.2|
N2.HOG0000034	OG0000035	n0		…AAP56353.1|	…AAC72490.1|	

The HOG at N1 has the genes of *M. hyopneumoniae* and *M. agalactiae* descended from the one gene in their common ancestor, and the HOG at N2 those of *M. gallisepticum* and *M. genitalium*. Each row also gives the orthogroup the HOG is part of, and the clade of the gene tree it was taken from. If there had been a duplication in the common ancestor of the species at N1, the orthogroup would have two HOGs at N1, one for each copy. Use the HOGs of a node to analyse a clade of species, for example to compare gene family sizes within the clade, and the `create_hog_fastas` tool to write their sequences (5.5).

1.4.2.6 Orthogroup sequences

For each orthogroup there is a FASTA file in `Orthogroup_Sequences/` with the sequences of its genes, and the orthogroups with one gene from every species are also in `Single_Copy_Ortholog_Sequences/` .

1.4.2.7 Other results files

We have now covered the main results files that most users need, but OrthoFinder writes much more, including the putative xenologs, the phylogenetically misplaced genes, the statistics of orthologs between each pair of species, and so on. Section 4 describes every file.

1.5 Viewing the results in a web browser

Everything we have looked at so far is in the results files, but OrthoFinder can also write three pages to explore the results in a web browser, linked to each other, for the gene trees and species tree, the statistics with plots, and the genes of every orthogroup and HOG. The pages are made from the results files, so they show the same results. They are a quicker way to look through them, for example to browse the gene trees without a separate tree viewer.

1.5.1 Writing the pages

Add `--view` to the OrthoFinder command to write the pages at the end of the run.

```
orthofinder -f ExampleData/ --view
```

For the results of a run that has finished, as we have here, write them with the `view_results` tool, which is installed with OrthoFinder.

```
view_results ExampleData/OrthoFinder/Results_Oct21/
```

```
The results in a web browser (Gene trees (331), Statistics, Orthogroups & HOGs, a tab for each):
    ExampleData/OrthoFinder/Results_Oct21/OrthoFinder_Results.html
```

Each page can also be written on its own, with `--tree-view`, `--stats-view` and `--groups-view` (with OrthoFinder or with `view_results`). With many species, the pages and the data they read can be large, so you may only want some of them.

1.5.2 Opening the pages

Open `OrthoFinder_Results.html` in the results directory in any recent web browser (Chrome, Firefox, Safari, Edge). It shows the three pages, a tab for each. For example, on Linux, run this command.

```
google-chrome ExampleData/OrthoFinder/Results_Oct21/OrthoFinder_Results.html
```

The pages work offline, without a server. Each page reads its data from the results directories next to it, so to look at them on another computer, copy the whole results directory, not only the pages.

If the results are on a server or a cluster, `view_results` can serve the pages there, to open them in the browser of your own computer through an SSH tunnel.

```
# on the server: writes the pages, then serves them; it prints the address and the ssh command
view_results ExampleData/OrthoFinder/Results_Oct21/ --serve
# on your own computer, then open http://localhost:8000 in a browser
ssh -N -L 8000:localhost:8000 <user>@<server>
```

`--port` sets the port (by default 8000, or the next free one). The pages are served only on the server itself. `--host 0.0.0.0` would make them reachable by anyone on the network, with no password. Stop the server with Ctrl-C.

1.5.3 Gene trees

`Resolved_Gene_Trees/Resolved_Gene_Trees.html` shows the species tree and the resolved gene tree of each orthogroup, with its multiple sequence alignment below it. Choose an orthogroup from the list, or search for an orthogroup ID or a gene name. Here is our orthogroup OG0000035 from 1.4.



Figure 1.4. The gene tree page, showing orthogroup OG0000035, with the gene duplication at n3 (red square) and the alignment.

The genes are coloured by species, and gene duplications are marked on the tree (a filled square for a duplication with support ≥ 0.5). Click a node to collapse or expand its clade. The tree can be drawn rectangular or circular, scaled by branch length or not, and saved as an SVG image. The page has two more tabs, the **species tree explorer**, which lists the HOGs at each node of the species tree (open a HOG to see its clade of the gene tree), and **all genes**, the genes of every species placed on the species tree.

1.5.4 Statistics

`Comparative_Genomics_Statistics/Statistics.html` shows the statistics of the run (1.4.1) with interactive plots, an overview and tabs for the species, orthogroups, gene duplications and HOGs. Point at a plot to see its numbers. "table" shows them as a table.




Figure 1.5. The overview of the statistics page.

1.5.5 Orthogroups and HOGs

`Orthogroups/Groups.html` shows the genes of each orthogroup (`Orthogroups.tsv`), and of the HOGs at each node, a column for each species. Search for an orthogroup or HOG ID, or for a gene name (the search matches the start of a name). Each orthogroup links to its gene tree and statistics in the other pages.




Figure 1.6. The orthogroups page.

The colours of all the pages can be set to light or dark with **Colours**, at the top right of each page.

CHAPTER 2

Advanced tutorial on adding species to a core analysis

2.1 The core and assign workflow

The time and memory of a standard OrthoFinder run grow with the square of the number of species, because the proteome of every species is searched against that of every other species. OrthoFinder 3 provides a second workflow for large analyses (more than about 100 species), and for adding species to an existing analysis.

1. Run a standard analysis on a **core** set of species, chosen to cover the diversity of all the species.
2. **Assign** the genes of the other species to the orthogroups of the core analysis. OrthoFinder makes a sequence profile of each core orthogroup, and searches the genes of the new species against the profiles (the SHOOT method) instead of against all the genes of all the species. The genes that are not assigned to a core orthogroup are then clustered into new orthogroups with a standard OrthoFinder analysis, restricted to the clades of species they come from.




Figure 2.1. The core and assign workflow.

```
orthofinder [options] -f <core_dir>
orthofinder [options] --assign <additional_dir> --core <core_results_dir>
```

The assign run then infers the gene trees of all the orthogroups, including the new species, the species tree, the gene duplications, the HOGs and the orthologs, as a standard run does, and writes the same results files.

This workflow also makes it quick to add new species to an earlier analysis. For example, a research group working on angiosperms could share the results of a core analysis of a diverse set of species, to which each member adds the species they study. The results of an assign run can in turn be the core of another one, to add species in several stages.

```
orthofinder --assign <new_species_2> --core <results_of_the_first_assign_run>
```

> The core analysis must have been run with multiple sequence alignments and gene trees (`-M msa` , the default). Species cannot be added to results run with `-M dendroblast` , which was the default in OrthoFinder 2.

2.2 Choosing the core species

The core species should capture the evolutionary diversity of all the species. The orthogroups of the core analysis are the ones the other species are assigned to, so a clade with no core species gets only the orthogroups shared with distant species. If we were analysing bees, moths and flies, the core should include species from all three, rather than, for example, only moths, which would give less accurate orthogroups and a longer run. We recommend about 64 core species. A good way to choose them is from a species tree of all the species (for example from the NCBI Taxonomy, or the literature). Pick species spread evenly across the tree, preferring those with the best genome annotations.

2.3 Running it on the example data

The example data has two more *Mycoplasma* species in `ExampleData/AdditionalSpecies/`, *M. arthritidis* and *M. haemocanis*. Using the results of section 1 as the core, add them to the analysis.

```
orthofinder --assign ExampleData/AdditionalSpecies/ --core ExampleData/OrthoFinder/Results_Oct21/
```

An assign run always creates a new results directory, **next to the core results**, and leaves the core results as they are, here `ExampleData/OrthoFinder/Results_Oct21_1/`. Its files are the same as those of a standard run, for all six species.

```
Summary:
 OrthoFinder assigned 3778 genes (84.3% of total) to 692 orthogroups.
```

There are some differences from a standard run.

- The species tree is inferred from the gene trees with ASTRAL-Pro, rather than from a concatenated alignment of single-copy orthogroups (`-ST` chooses the program).
- To save memory with many species, an assign run uses FAMSA alignments and the fastest FastTree setting (`-T fasttree_fastest`) unless `-A` or `-T` is given.
- The sequence search settings (search program, scoring matrix, gap penalties) are those of the core analysis, so that the new species are scored as the core species were.
- An assign run that was stopped (e.g. with `-op`, or interrupted) is continued with `-b` on its own results directory (5.1).




Figure 2.2. The species tree of the assign run, with the two added species.

The new species are placed in the tree where expected, *M. arthritidis* with *M. agalactiae*, and *M. haemocanis* in the same clade as *M. hyopneumoniae*. Note that the node names are those of the new tree, so N1 of the assign run is not N1 of the core run.

2.4 Using outgroups

The orthogroups of the root of the species tree (`Orthogroups.tsv`) depend on how the root is placed, and the deepest splits of the tree are the hardest to infer. Including one or more **outgroup** species, more distantly related to all the others, makes the orthogroups of the species you are interested in more accurate. Use the HOGs of the node that is the common ancestor of your species of interest, in `Phylogenetic_Hierarchical_Orthogroups/N<x>.tsv` , rather than `Orthogroups.tsv` . Look up the node in `Species_Tree/SpeciesTree_rooted_node_labels.txt` . Check that the species tree is rooted between the outgroup and the other species. If it is not, rerun with the correct tree (`-fgt <results> -s <tree>` , see 1.4).

CHAPTER 3

Understanding orthology

3.1 Orthogroups, orthologs and paralogs

First, we need to define the key terms.

Orthogroup

The group of genes descended from a single gene in the last common ancestor of a group of species.

Orthologs

Pairs of genes descended from a single gene in the last common ancestor of two species.

Paralogs

Pairs of genes descended from a gene duplication event.

Orthologs can be thought of as "equivalent genes" between two species, as they are descended from a single gene in the last common ancestor of those species. For example, the last common ancestor of humans and mice was a small mammal that lived alongside the dinosaurs. The genes present in that ancestor still exist, in some form, through their descendants in both humans and mice, and those genes are orthologs.

Orthologs describe relationships between pairs of species, but the idea extends to larger groups of species. Humans, mice and chickens share a common ancestor that lived a few hundred million years ago, before the dinosaurs had even emerged. The genes across all three species descended from a single gene in this ancestor form an orthogroup.




Figure 3.1. Orthologs, orthogroups and paralogs, for three species, human, mouse and chicken.

The tree in Figure 3.1A shows the evolutionary history of a gene. First, there was a speciation event where the chicken lineage diverged from the human-mouse ancestor. In the human-mouse ancestor, there was a gene duplication event at X, producing two copies of the gene in that ancestor, Y and Z. When human and mouse diverged, they each inherited gene Y (becoming HuA and MoA) and gene Z (HuB and MoB). In general, a gene duplication event can be identified because it creates two copies of a gene in a species (e.g. HuA and HuB).

The mouse gene MoB is more closely related to a human gene than it is to the other mouse gene MoA. This is because the duplication occurred in the ancestor, so each mouse gene is most closely related to its human ortholog (e.g. HuA and MoA), both descended from a single gene. By contrast, HuA and MoB diverged at the gene duplication event. They are not descended from a single gene in the common ancestor of human and mouse, so they are not orthologs. They are paralogs (Figure 3.1C). Paralogs diverged at a gene duplication event in a common ancestor. Such a duplication must have occurred further back in time than the speciation, so paralogs between a pair of species are always less closely related than orthologs between that pair. Paralogs can also be within a species (e.g. HuA and HuB).

The chicken gene diverged from the other genes when the lineage leading to chicken split from the lineage leading to human and mouse. Therefore the chicken gene ChC is an ortholog of both HuA and HuB in human, and of both MoA

and MoB in mouse. Depending on what happened after the genes diverged, orthologs can be in one-to-one relationships (HuA – MoA), many-to-one (HuA and HuB – ChC) or many-to-many (no example in this tree, but there would be one after a duplication in chicken). OrthoFinder identifies all of these relationships, and they are counted in `Comparative_Genomics_Statistics/OrthologsStats_*.tsv`.

3.2 Why orthogroups?

There are several reasons why orthogroups are the right way to analyse orthology relationships between species.

3.2.1 Orthogroups allow you to analyse all of your data

All the genes in an orthogroup are descended from a single ancestral gene, so they all started out with the same sequence and function. Gene duplication and loss occur frequently in evolution, so restricting an analysis to one-to-one orthologs (the single-copy orthogroups) leaves out much of the data, and more of it with every species added, because each species is another lineage in which a gene can be duplicated or lost. In the example data, the 250 single-copy orthogroups of the four species contain 37% of their genes. With the two species added in section 2.3, the 168 single-copy orthogroups of the six species contain 22%. With tens of species, or species with large genomes and many gene families, the single-copy orthogroups are a small fraction of the data. By analysing orthogroups you can analyse all of your data.

3.2.2 Orthogroups allow you to define the unit of comparison

With orthogroups, you choose where to define the limits of the unit of comparison. For example, if you chose to analyse only human and mouse in Figure 3.1, there would be two orthogroups (the descendants of Y and of Z) rather than one. The hierarchical orthogroups of OrthoFinder give you these units for every clade of the species tree (3.3).

3.2.3 Orthogroups are the only way to identify orthologs

Orthology is defined by phylogeny. It cannot be defined by amino acid content, codon bias, GC content or other measures of sequence similarity. Methods that use such scores to define orthologs without phylogeny can only provide guesses. The only way to be sure that an orthology assignment is correct is by a phylogenetic reconstruction of all the genes descended from a single gene in the last common ancestor of the species considered, and this set of genes is an orthogroup. Thus the only way to define orthology is by analysing orthogroups.

For a comprehensive overview of orthology and the OrthoFinder approach, you can watch David Emms' talk at the 2020 symposium on Phylogenomics and Comparative Genomics.

3.3 Hierarchical orthogroups

An orthogroup is defined for a group of species, and so depends on the species. It is the set of genes descended from one gene in their last common ancestor. OrthoFinder therefore infers the orthogroups for every clade of the species tree, the phylogenetic hierarchical orthogroups (HOGs). They are inferred from the rooted gene trees. The HOGs of a node N are the clades of each gene tree descended from a single gene in the ancestor at N.




Figure 3.2. Hierarchical orthogroups, an orthogroup at each node of the species tree.

Inferring the orthogroups from the gene trees, rather than from sequence similarity alone, makes them more accurate. This is why, from OrthoFinder v3.1, `Orthogroups/Orthogroups.tsv` contains the HOGs of the root of the species tree (N0).

CHAPTER 4

A complete guide to the OrthoFinder results files

Some terms used in these files are defined below.

Species-specific orthogroup

An orthogroup that consists entirely of genes from one species.

G50

The number of genes in the orthogroup such that 50% of genes are in orthogroups of that size or larger.

O50

The smallest number of orthogroups such that 50% of genes are in orthogroups of that size or larger.

Single-copy orthogroup

An orthogroup with exactly one gene (and no more) from each species. These orthogroups are ideal for inferring a species tree and many other analyses.

Unassigned gene

A gene that has not been put into an orthogroup with any other gene.

Gene and species names are the same in every results file. A name is made once from the FASTA header (or the file name, for a species), replacing each character that a results file cannot hold by `_`. These are spaces and tabs, `: ; ( ) , [ ] =` and quotes (and for a species also `* ? < > | \ /`). For example `>sp|P12345|X_HUMAN Protein X` gives `sp|P12345|X_HUMAN_Protein_X`, and `Homo sapiens.fa` the species `Homo_sapiens`. All results files are UTF-8 text, the tables are tab-separated with no quoted cells, and the trees are standard Newick.

4.1 Comparative_Genomics_Statistics

Statistics_Overall.tsv

General statistics about the orthogroup sizes and the proportion of genes assigned to orthogroups (1.4.1).

Statistics_PerSpecies.tsv

The same information as `Statistics_Overall.tsv`, for each species.

Duplications_per_Orthogroup.tsv

The number of gene duplication events in each orthogroup, all of them and those with at least 50% support.

Duplications_per_Species_Tree_Node.tsv

The number of gene duplication events on each branch of the species tree (named by the node or species below it).

OrthologsStats_*.tsv

Matrices of the numbers of orthologs in one-to-one, one-to-many and many-to-many relationships between each pair of species.

- `OrthologsStats_one-to-one.tsv`. The number of one-to-one orthologs between each pair of species.
- `OrthologsStats_many-to-many.tsv`. Entry (i, j) is the number of genes in species i in a many-to-many orthology relationship with genes in species j (due to gene duplication events in both lineages after the speciation).
- `OrthologsStats_one-to-many.tsv`. Entry (i, j) is the number of genes in species i in a one-to-many orthology relationship with genes in species j.
- `OrthologsStats_many-to-one.tsv`. Entry (i, j) is the number of genes in species i in a many-to-one orthology relationship with a gene in species j.
- `OrthologsStats_Totals.tsv`. Entry (i, j) is the total number of genes in species i with orthologs in species j, of whatever multiplicity.

There is a walk-through of an example of these files in GitHub issue #259.

4.2 Gene_Duplication_Events

Duplications.tsv

All the gene duplication events found by examining each node of each orthogroup gene tree, one per row. The columns are as follows.

a. **Orthogroup**.
b. **Species Tree Node.** The branch of the species tree on which the duplication occurred, named by the node or species below it (see `Species_Tree/SpeciesTree_rooted_node_labels.txt`).
c. **Gene Tree Node.** The node of the orthogroup's resolved gene tree (in `Resolved_Gene_Trees/Resolved_Gene_Trees.txt`).
d. **Support.** The proportion of the expected species in which both copies of the duplicated gene are present.
e. **Type.** "Terminal" is a duplication on a terminal branch of the species tree (in one species). "Non-Terminal" is a duplication on an internal branch, and therefore shared by more than one species. "Non-Terminal: STRIDE" is a non-terminal duplication that also passes the very stringent STRIDE checks of the topology the gene tree should have after the duplication.
f. **Genes 1.** The genes descended from one of the copies of the duplicated gene.
g. **Genes 2.** The genes descended from the other copy.

SpeciesTree_Gene_Duplications_0.5_Support.txt

The above duplications summed over the branches of the species tree, as a Newick tree. The number after each node or species name is the number of gene duplication events with at least 50% support on the branch leading to it. The branch lengths are those of `Species_Tree/SpeciesTree_rooted.txt`.

4.3 MultipleSequenceAlignments

The multiple sequence alignments of the orthogroups, `OG0000000.fa` etc., in FASTA format (with `-M msa`, the default). The concatenated alignment the species tree was inferred from is in the working directory (`WorkingDirectory/Alignments_ids/SpeciesTreeAlignment.fa`).

4.4 Orthogroup_Sequences

A FASTA file for each orthogroup, with the amino acid sequences of its genes.

4.5 Orthogroups

Orthogroups.tsv

The main orthogroup file (the hierarchical orthogroups of the root, N0). Each row contains the genes of one orthogroup, in a column for each species, separated by commas.

Orthogroups.txt

The orthogroups, one per line, as `OG0000000: gene gene …`. It differs from `Orthogroups.tsv` in that it doesn't show the species of each gene. It is in the format of OrthoMCL, for programs that read it.

Orthogroups.GeneCount.tsv

The number of genes of each species in each orthogroup, and the total.

Orthogroups_SingleCopyOrthologs.txt

The orthogroups with exactly one gene from each species, i.e. one-to-one orthologs.

Orthogroups_UnassignedGenes.tsv

The genes not assigned to any orthogroup, each as an orthogroup of its own, in the format of `Orthogroups.tsv`.

Orthogroups.orthoxml

With `--orthoxml`, the orthogroups of `Orthogroups.tsv` in OrthoXML format, for other tools. Each orthogroup (a HOG of the root, N0) is a group with the HOGs of the nodes below it nested inside. The species tree is the taxonomy, and gene duplications are paralog groups. The MCL orthogroups are never in this file (see `MCL_Orthogroups.*`).

MCL_Orthogroups.*

The orthogroups from the MCL clustering of the search results, before the gene trees (`.tsv`, `.txt`, `.GeneCount.tsv`, `_UnassignedGenes.tsv`). With `--orthoxml` also `.orthoxml`. Written when a run stops after a stage (`-og`, `-ogt`, `-ost`) or fails after them, and kept in a full run with `-mog`. Their sequences can be written with the `mcl_orthogroup_sequences` tool.

4.6 Orthologs

<species>.tsv.gz

One compressed file for each species, listing its orthologs in all the other species. Each row gives an orthogroup, another species, a set of genes of this species and their orthologs in the other species. Orthologs can be one-to-one, one-to-many or many-to-many, depending on the gene duplication events since the orthologs diverged.

Orthologs_<species>/<species>__v__<other species>.tsv

With `-pof`, or written afterwards by `split_ortholog_files`. A file for each pair of species, listing the orthologs between them. Each row contains the gene(s) in one species that are orthologs of the gene(s) in the other species, cross-referenced to their orthogroup.

4.7 Phylogenetic_Hierarchical_Orthogroups

OrthoFinder infers the HOGs, the orthogroups at each hierarchical level (each node of the species tree), by analysing the rooted gene trees.

N1.tsv, N2.tsv, …

The HOGs of the clade of species below node N1, N2 etc. of the species tree. Each row contains the genes of one HOG, in a column for each species. The first columns are the HOG ID (e.g. `N1.HOG0000036`), the orthogroup it is part of, and the clade of the orthogroup's gene tree it was taken from. There is no N0.tsv, because the HOGs of the root are `Orthogroups/Orthogroups.tsv`.

4.8 Phylogenetically_Misplaced_Genes

Genes that appear to be out of place in their gene tree, and would otherwise lower the accuracy of the orthology analysis if not identified. They are often the result of contamination, or of a poorly predicted gene.

4.9 Putative_Xenologs

Xenologs are genes descended from a common ancestor where there has been horizontal gene transfer on the path to the genes in the extant species, rather than just speciation and duplication. OrthoFinder tries to identify xenologs, but we call them "putative", since many arise from contamination during sequencing. Each species has a file listing its genes and their putative xenologs in all the other species.

4.10 Resolved_Gene_Trees

Resolved_Gene_Trees.txt

A rooted phylogenetic tree for each orthogroup with four or more genes, resolved using the OrthoFinder hybrid species-overlap / duplication-loss-coalescent model, with a line for each orthogroup, `OG0000000: <Newick tree>`. The genes are named with their species as a prefix (without it with `-X`), and the internal nodes are named n0, n1 … (as in `Gene_Duplication_Events/Duplications.tsv`).

4.11 Single_Copy_Ortholog_Sequences

The same files as `Orthogroup_Sequences`, for the orthogroups with exactly one gene from each species.

4.12 Species_Tree

SpeciesTree_rooted.txt

The species tree, rooted with STRIDE from the gene duplication events, with support values at the internal nodes. In a standard run it is inferred from the concatenated alignment of the single-copy orthogroups. In an `--assign` run, or with `-ST astral-pro`, it is inferred from the gene trees with ASTRAL-Pro. Otherwise it is the tree given with `-s`.

SpeciesTree_rooted_node_labels.txt

The same tree, with its internal nodes named (N0, N1, …) instead of support values, so that other results files can refer to the nodes and branches of the species tree (e.g. the location of the gene duplication events, or the HOG files).

Orthogroups_for_concatenated_alignment.txt

The orthogroups whose alignments were concatenated to infer the species tree (standard runs only, and the `species_tree_alignment` tool writes it, and the alignment, from results without it).

4.13 WorkingDirectory

The files OrthoFinder needs to continue or restart an analysis, or to add species to it. Most of them are named with internal IDs rather than gene and species names. Some useful ones are listed below.

SpeciesIDs.txt, SequenceIDs.txt

The IDs OrthoFinder gave to the species and genes (e.g. `0: Mycoplasma_agalactiae.faa`, and `0_12` for the 13th gene of species 0), and the original FASTA headers.

Species*.fa, Blast*_*.txt.gz

The input sequences with IDs, and the results of each sequence search (species i against species j), reused by `-b`.

blast_commands.txt

The sequence search commands, written by `-op` (5.2).

run_state.json, checkpoint.txt

The settings and progress of the run, which a restart continues from.

Log.txt (in the results directory)

The command, settings and programs used, and the location of the files the run used.

4.14 The pages to view the results (`--view`)

Written with `--view` (or `--tree-view`, `--stats-view`, `--groups-view`), or by `view_results` for a finished run (1.5). Each page reads its data from a directory next to it, so keep the results directory together.

OrthoFinder_Results.html

Opens the pages written, a tab for each.

Resolved_Gene_Trees/Resolved_Gene_Trees.html

The species tree, each resolved gene tree with its alignment, a species tree explorer (the HOGs at each node) and all the genes on the species tree.

Comparative_Genomics_Statistics/Statistics.html

The statistics, with interactive plots.

Orthogroups/Groups.html

The genes of each orthogroup and HOG, searchable.

CHAPTER 5

Advanced usage

5.1 Stopping and restarting an analysis

An OrthoFinder analysis can be stopped after any of its stages, and restarted from any of them. This is useful to check the orthogroups before inferring the trees, to run the sequence searches on a cluster, to rerun the later stages with other programs or a corrected species tree, or to continue a run that was interrupted (Ctrl-C, or a job time limit).

Stop after	Option	Restart from	Option
preparing the files and search commands	`-op`	the sequence search results	`-b <dir>`
the MCL orthogroups	`-og`	the MCL orthogroups	`-fg <dir>`
the gene trees	`-ogt`	the gene trees	`-fgt <dir>`
the rooted species tree	`-ost`	the species tree	`-fst <dir>`

At the end of a stopped run, OrthoFinder prints the command to continue it. For example, to look at the orthogroups before running the gene trees, run the commands below.

```
orthofinder -f ExampleData/ -og -n og_only
orthofinder -fg ExampleData/OrthoFinder/Results_og_only/
```

- A restart writes its results to the results directory it is given, the one of the stopped run. It does not create a new one.
- A restart continues with the settings of the run (search program, scoring, `-M`, `-A`, `-T`, `-ST`, `-I` ..., kept in `WorkingDirectory/run_state.json`), unless they are given again. For example `orthofinder -fg <dir> -T iqtree3` infers the gene trees again with IQ-TREE.
- `-fg` also works on the results of a complete run, to redo the alignments and gene trees.
- With `-b`, OrthoFinder runs only the sequence searches whose results are missing or incomplete, e.g. after `-op` or after a run that was interrupted during the searches.
- An `--assign` run can be stopped and restarted in the same way, from its own results directory.

5.2 Running the sequence searches separately

The `-op` option prepares the files in the format OrthoFinder needs, and writes the sequence search commands to `WorkingDirectory/blast_commands.txt`, without running them.

```
orthofinder -f fasta_files_directory/ -op
```

This is useful to manage the searches yourself, for example to distribute them across the nodes of a cluster (there is one command for each pair of species, and each can run on its own). Once the searches are done, run the rest of the analysis with `-b` on the results directory.

```
orthofinder -b fasta_files_directory/OrthoFinder/Results_<date>/
```

OrthoFinder checks which searches have finished, and runs any that are missing. It is possible to use pre-computed search results in the same way, provided they are in the format OrthoFinder expects (the tabular BLAST format, with the gene and species IDs of `SequenceIDs.txt` and `SpeciesIDs.txt`). If you run the searches yourself, we strongly recommend preparing the files with `-op` first.

5.3 Choosing the methods and programs

Option	Choice	Default
`-S` sequence search	`diamond`, `diamond_ultra_sens`, `blast`, `blastp`, `blastn`, `mmseqs`. `blast` is BLAST+ for either kind of input, `blastp` for protein sequences or `blastn` with `-d` (nucleotide sequences). `blastp` and `blastn` can also be given directly	`diamond`, or `blastn` with `-d`
`-M` gene tree method	`msa` (alignments and maximum-likelihood trees), `dendroblast` (distance trees from the search results, faster and less accurate, the OrthoFinder 2 default)	`msa`
`-A` alignment (with `-M msa`)	`famsa`, `mafft`, `muscle`	`famsa`
`-T` gene trees (with `-M msa`)	`fasttree`, `fasttree_fastest`, `raxml`, `iqtree3`	`fasttree`
`-ST` species tree (with `-M msa`)	`astral-pro` (from the gene trees)	the concatenated alignment of the single-copy orthogroups, or ASTRAL-Pro with `--assign`
`-I` MCL inflation	usually 1.2 to 5 (larger values give smaller orthogroups)	1.2
`-d`	the input is nucleotide sequences, searched with BLAST+ `blastn` (by default, or with `-S blast`), or with `-S mmseqs`, whose commands then get the nucleotide search type. DIAMOND compares protein sequences only, so it cannot be used	protein

The programs other than the defaults (BLAST+, MMseqs2, MUSCLE, RAxML, IQ-TREE) must be installed separately. More accurate tree programs, such as IQ-TREE, take much longer than FastTree.

5.3.1 Sequence search scoring (DIAMOND)

`--matrix` chooses the scoring matrix (`BLOSUM45`, `BLOSUM50`, `BLOSUM62` (default), `BLOSUM80`, `BLOSUM90`, `PAM250`, `PAM70`, `PAM30`), and `-go` / `--gapopen` and `-ge` / `--gapextend` the gap penalties (by default those of the matrix, e.g. 11 and 1 for BLOSUM62). `--custom-matrix <file>` uses a matrix of your own, in NCBI's format, and requires `--gapopen` and `--gapextend`. A restart or an `--assign` run from the results uses the same scoring.

5.4 Other options

`-n <txt>`	The name of the results directory, `Results_<txt>`
`-o <dir>`	A results directory other than `OrthoFinder/` in the input directory
`-s <file>`	A rooted species tree to use, instead of inferring one
`-pof`	Write the ortholog files for each pair of species (see 1.4)
`--orthoxml`	Write the orthogroups in OrthoXML format
`-mog`	Keep the MCL orthogroups in a full run
`-X`	Name the genes without their species prefix in the gene trees, alignments and `Duplications.tsv`
`-y`	Split paralogous clades below the root of a HOG into separate HOGs
`-z`	Don't trim the alignments (by default columns with ≥ 90% gaps are removed, keeping at least 500 columns)
`-t <int>`, `-a <int>`	The threads for the sequence searches and for the rest of the analysis (1.3)
`--view`	Write the pages to view the results in a web browser, and `OrthoFinder_Results.html` to open them (1.5)
`--tree-view`, `--stats-view`, `--groups-view`	Write only the page of the gene trees, of the statistics, or of the orthogroups and HOGs

5.5 Utility tools

These tools are installed with OrthoFinder (in `tools/` of the source code, and most need only Python 3, so they can also be run as `python tools/<tool>.py` without installing OrthoFinder). `orthofinder-utils` lists them, and `<tool> -h` describes each.

primary_transcript <file or directory>

Keep the longest transcript of each gene (6.4). Works on FASTA files, directories (searched recursively) and `.zip` / `.tar.gz` archives, and recognises Ensembl and NCBI headers. A second argument (`last_dot`, `space`, `last_dot_before_first_space`) tells it how to find the gene of each transcript for other headers.

ncbi_primary_transcript <zip or directory>

Keep the longest protein of each gene from NCBI genome downloads (a `.zip` with `protein.faa` and `genomic.gff`), using the GFF to link proteins to genes (6.2).

split_ortholog_files <results>

Write the ortholog files for each pair of species from a run without `-pof` . `--species` and `--partners` write only some of them, `-t` in parallel.

create_hog_fastas <results> <node>

Write a FASTA file for each HOG of a node of the species tree (e.g. `N1` , or `all`).

mcl_orthogroup_sequences <results>

Write a FASTA file for each MCL orthogroup.

orthogroup_gene_count <file or directory>

Gene-count tables (genes of each species in each orthogroup) from `Orthogroups.tsv` , `Orthogroups.txt` or HOG files.

convert_orthofinder_tree_ids <tree> <SequenceIDs.txt> [SpeciesIDs.txt]

Convert the gene IDs of trees in the working directory (e.g. `0_12`) to the gene names, or back.

make_ultrametric <tree>

Make a rooted tree ultrametric (e.g. the species tree, for gene family evolution programs such as CAFE). `--root-age` sets the age of the root.

species_tree_alignment <results>

Write the concatenated alignment of the single-copy orthogroups, and the list of the orthogroups, for a run whose species tree was inferred with `-ST`.

view_results <results>

Write the pages to view the results of a finished run in a web browser (1.5). `--serve` serves them, e.g. from a cluster through an SSH tunnel. It needs only Python 3 and ete4, so `tools/view_results/` can be copied and used without OrthoFinder.

5.6 Manually installing the dependencies

If you installed OrthoFinder with conda, you shouldn't need to install any of the programs it runs. The programs bundled with OrthoFinder (in the `linux-intel` release and the source code) are built for Linux on Intel/AMD (x86-64) processors only, including WSL2 on Windows. On other systems, such as macOS or computers with ARM processors (e.g. Apple silicon), install them yourself, for example with conda. Otherwise, the default analysis needs DIAMOND, MCL, FAMSA and FastTree (and ASTRAL-Pro for `--assign`).

Program	Needed for	Installation
DIAMOND (2.1)	sequence search (default)	`conda install -c bioconda diamond`, or github.com/bbuchfink/diamond
MCL	orthogroups	`conda install -c bioconda mcl`, or github.com/micans/mcl
FAMSA	alignments (default)	`conda install -c bioconda famsa`, or github.com/refresh-bio/FAMSA
FastTree	gene and species trees (default)	`conda install -c bioconda fasttree`, or microbesonline.org/fasttree
ASTRAL-Pro	`--assign`, `-ST astral-pro`	github.com/chaoszhang/ASTER (bundled with OrthoFinder)
MAFFT	`-A mafft`	`conda install -c bioconda mafft`, or mafft.cbrc.jp
BLAST+, MMseqs2, MUSCLE, RAxML, IQ-TREE	`-S`, `-A`, `-T` alternatives	`conda install -c bioconda blast mmseqs2 muscle raxml iqtree`

CHAPTER 6

Getting input data for OrthoFinder

Let's imagine we want to perform a phylogenomic analysis across a set of species, dingo (*Canis lupus dingo*), great spotted kiwi (*Apteryx haastii*), kakapo (*Strigops habroptila*), platypus (*Ornithorhynchus anatinus*), tammar wallaby (*Notamacropus eugenii*) and common wombat (*Vombatus ursinus*).


OrthoFinder requires as input the amino acid sequences of all the protein-coding genes of each species. In this section we discuss how to get these files from three major websites.

- **Ensembl.** Recommended for eukaryotic species, especially vertebrates and model organisms.
- **NCBI.** Recommended for prokaryotic species, and for eukaryotes not in Ensembl.
- **Phytozome.** Recommended for plants.


A key consideration when getting input data is **transcripts**. The amino acid sequences downloaded for a genome often include several sequences for the same gene, because a gene can produce several transcripts, each of which may produce a different protein (see, for example, the transcripts of the human actin gene on Ensembl). Running OrthoFinder on these files would take much longer than necessary and could lower the accuracy, so we keep only the longest transcript of each gene with the tools provided with OrthoFinder (6.4).

6.1 Getting data from Ensembl

First, go to the Ensembl list of species (or the new Ensembl website, which is updated more regularly). Search for the first species (*Canis lupus dingo*) and click on its link, which takes you to the Ensembl page of that species.



On the right, under "Gene annotation", click "Download FASTA" files for the genome. This takes you to a page with some folders.



Index of /pub/release-112/fasta/canis_lupus_dingo

Name	Last modified	Size	Description
Parent Directory		-	
cdna/	2024-04-23 03:23	-	
cds/	2024-04-23 03:23	-	
dna/	2024-04-23 03:24	-	
dna_index/	2024-04-23 03:25	-	
ncrna/	2024-04-23 03:25	-	
pep/	2024-04-23 03:25	-	

Click on the `pep/` folder, and then on the file that ends in `.pep.all.fa.gz`.



Index of /pub/release-112/fasta/canis_lupus_dingo/pep

Name	Last modified	Size	Description
Parent Directory		-	
CHECKSUMS	2024-03-05 10:31	136	
Canis_lupus_dingo.ASM325472v1.pep.abinitio.fa.gz	2024-02-14 01:14	13M	
Canis_lupus_dingo.ASM325472v1.pep.all.fa.gz	2024-02-14 00:47	8.6M	
README	2024-02-14 01:14	2.4K	


Repeat this for the other species, saving the files in one folder on your computer, for example `Proteomes/`. The files can also be downloaded on the command line. Right-click the file, copy its link, and run

```
wget <the link you copied>
```


The files are compressed (`.gz`) to save space. Uncompress them with `gunzip *.gz` (or by double-clicking them). Ensembl headers name the gene of each transcript (`gene:ENSCAFG…`), which `primary_transcript` uses.

6.2 Getting data from NCBI


Go to www.ncbi.nlm.nih.gov and search for the first species.




To find the genome of the species, scroll down to the "Genomes" section and click on "Assembly / Genome".



There may be several genomes listed. Click on the one with the green tick, the reference genome.



Click the blue "Download" button, and tick the boxes for the curated "RefSeq only" annotation and for the GFF and protein FASTA files. You can also give the download a useful name, such as the name of the species.



Click "Download", which downloads a zip file. Repeat this for each species. For some species in our list, like the kiwi, there is no RefSeq genome with protein sequences. For those, use Ensembl.


The NCBI protein files have a sequence for each transcript. For the dingo, there are about 75,000 sequences for about 20,000 genes. The `ncbi_primary_transcript` tool keeps the longest protein of each gene, using the GFF file in the zip to link each protein to its gene (6.4).

To download data in bulk, use the NCBI Datasets command-line tool, which downloads the same zip files, e.g..


```
datasets download genome taxon "Ornithorhynchus anatinus" --reference --include protein,gff3 --filename
Ornithorhynchus_anatinus.zip
```

6.3 Getting data from Phytozome

Go to the Phytozome data portal, and search for a species, such as *Oryza sativa*.



Find the genome you want to download and click on it. The file we want ends in `primaryTranscriptOnly.fa.gz`. Phytozome has already kept one transcript per gene, so these files are ready for OrthoFinder. Select the file and click "Add to Cart".



Repeat this for each species. When you are ready, click the shopping cart icon and press "Download" on the next page. You have to sign in, or register, to download the data. Place the files in one folder, and uncompress them (`gunzip *.gz`).

6.4 Preparing the files

6.4.1 Keeping the longest transcript of each gene

For files from Ensembl (or any files whose headers name the gene of each transcript), uncompress them and run `primary_transcript` on the folder (it also reads `.zip` and `.tar.gz` archives of FASTA files).

```
primary_transcript Proteomes/
```

The files with one transcript per gene are written to `Proteomes/primary_transcripts/`. If the headers don't name the gene, but the transcript IDs are the gene ID with a suffix (e.g. `AT1G01010.1`, `AT1G01010.2`), give the rule as a second argument, as in `primary_transcript Proteomes/ last_dot`.

For the zip files from NCBI, run `ncbi_primary_transcript` on the folder with the zip files.

```
ncbi_primary_transcript NCBI_downloads/
```

which writes a FASTA file for each genome to `NCBI_downloads/primary_transcripts/`, ready for OrthoFinder.

6.4.2 Naming the files

The name of each file is the name of the species in all the results, so shorten the file names. For example, rename `Canis_lupus_dingo.<assembly>.pep.all.fa` to `Canis_lupus_dingo.fa`. Put only the files of the species to analyse in the input folder, and check that each species has one file.

The data is now ready for OrthoFinder. Run `orthofinder -f Proteomes/primary_transcripts/` as in section 1.3.

CHAPTER 7

Citing OrthoFinder

When publishing work that uses OrthoFinder, please cite the following paper.

Emms D.M., Liu Y., Belcher L., Holmes J. & Kelly S. (2026). OrthoFinder: improved phylogenetic orthology inference with enhanced accuracy and scalability. *Nature Methods* 23, 1327–1333. doi:10.1038/s41592-026-03126-6

If you use the species tree in your work, please also cite the following papers.

Emms D.M. & Kelly S. (2017). STRIDE: Species Tree Root Inference from Gene Duplication Events. *Molecular Biology and Evolution* 34(12), 3267–3278. doi:10.1093/molbev/msx259

Emms D.M. & Kelly S. (2018). STAG: Species Tree Inference from All Genes. *bioRxiv*. doi:10.1101/267914

The methods introduced in earlier versions of OrthoFinder are described in the following papers.

- Emms D.M. & Kelly S. (2022). SHOOT: phylogenetic gene search and ortholog inference. *Genome Biology* 23, 85. doi:10.1186/s13059-022-02652-8
- Emms D.M. & Kelly S. (2019). OrthoFinder: phylogenetic orthology inference for comparative genomics. *Genome Biology* 20, 238. doi:10.1186/s13059-019-1832-y
- Emms D.M. & Kelly S. (2015). OrthoFinder: solving fundamental biases in whole genome comparisons dramatically improves orthogroup inference accuracy. *Genome Biology* 16, 157. doi:10.1186/s13059-015-0721-2

OrthoFinder also uses DIAMOND, MCL, FAMSA, FastTree and (for `--assign`) ASTRAL-Pro. Please cite the programs you use, which are listed in `Citation.txt` in the results directory.