

# DM887 Assignment2 Q1

Jiawei Zhao

19.03.2024

Implementation of Least-Squares Temporal Differences (LSTD) Deep Q-Learning with Nonlinear Feature Extraction that maps a state to lower-dimensional latent embedding. While the action-value function should be a linear function of the output of the feature extractor.

---

**Algorithm 1** Initialization

---

- 1: Initialize a variational autoencoder  $\mathbf{A}$  as the feature extraction network with initial weights  $w_0$  [ $w_0$  are drawn from Glorot uniform initialization]
- 2: Initialize the learning rate of  $\mathbf{A}$  as  $\alpha$
- 3: Initialize an Adam optimizer  $o$  with a learning rate  $\alpha$  for  $\mathbf{A}$
- 4: Initialize the minibatch size of DQN as  $k$
- 5: Initialize the total number of training episodes  $N$ , the number of episodes at each cycle consisting of three phases of training  $N_0$ , ensure that  $N \bmod N_0 = 0$
- 6: Set the number of episodes at the warm-up phase as  $N_1$ , at the autoencoder update phase as  $N_2$ , and at the LSTD weight update phase as  $N_3$ , ensure that  $(N_0 - N_1) \bmod (N_2 + N_3) = 0$  [It would be a wise choice to separate the warm-up phase, the autoencoder update phase, and the LSTD update phase at each cycle]
- 7: Initialize the number of maximum time step per episode  $T$
- 8: Initialize the weights  $\theta_0$  for linear approximation function randomly between  $(0, 1)$  which will be used for LSTD
- 9: Initialize a replay memory buffer  $\mathcal{D}$  with a capacity  $N \times T$
- 10: Initialize a relatively discount factor, e.g.  $\gamma = 0.9$
- 11: Initialize a small constant  $\lambda$ , e.g.  $1 \times 10^{-3}$  to initialize  $A^{-1}$  for LSTD
- 12: Given the number of actions as  $N_a$  and embedding dimension  $N_e$ , initialize a matrix  $\theta$  with shape  $N_a \times N_e$
- 13: Initialize a tensor  $A^{-1} = \lambda^{-1}I$  with shape  $N_a \times N_e \times N_e$  and a tensor  $b$  with shape  $N_a \times N_e$  full of zeros to store the tensors that suffice  $\theta_a = A_a^{-1}b_a, \forall a \in A$  [A relatively large discount factor encourages long-term planning and faster convergence during training]

[1]

---

---

**Algorithm 2** Warm-up phase

---

```
1: Freeze the weights of  $f(\phi(s))$ , i.e.  $\theta$ 
2: Freeze the weights of  $\mathbf{A}$ , i.e.  $w$ 
3: for episode  $e_0 = 1$  to  $N_1$  do
4:   Initialize state  $s$ 
5:   Preprocess  $s$  into  $s_0$  to adapt it as input of  $\mathbf{A}$  [preprocessing of high-dimensional states is necessary
   w.r.t. autoencoders]
6:   for each time step  $t = 1$  to  $T$  do
7:     Encode state  $s_t$  using  $\mathbf{A}$  to get latent embedding  $\phi(s_t)$ 
8:     Select action  $a_t$  using  $\epsilon$ -greedy policy with  $\epsilon = 0.2$  with an  $\epsilon$  decay
9:     Execute  $a_t$  and obtain reward  $r_t$  and new state  $s_{t+1}$ 
10:    if  $s_{t+1} \notin S$  then
11:      break
12:    end if
13:    Store the transition of the current  $t$ , i.e.  $(s_t, a_t, r_t, s_{t+1})$  in  $\mathcal{D}$ 
14:  end for
15: end for
16:  $e = e + N_1$ 
[1]
```

---

---

**Algorithm 3** Autoencoder update phase

---

```
1: Freeze the weights of  $f(\phi(s))$ , i.e.  $\theta$ 
2: Unfreeze the weights of  $\mathbf{A}$ , i.e.  $w$ 
3: for episode  $e_0 = 1$  to  $N_2$  do
4:   Repeat the same steps at the warm-up phase
5:   for each time step  $t = 1$  to  $T$  do
6:     Repeat the same steps at the warm-up phase
7:     [Start updating the autoencoder using minibatches]
8:     Sample a minibatch of transitions  $d$  from  $\mathcal{D}$  with a batchsize  $k$ 
9:     Use the  $s_t$  of  $d$  as input to  $\mathbf{A}$ 
10:    First encode, then decode  $d$  using  $\mathbf{A}$ 
11:    Calculate the loss  $L$  of  $s_t$  by comparing the input and output of  $\mathbf{A}$ 
12:    Update  $w$  with  $o$  as per  $L$ 
13:  end for
14: end for
15:  $e = e + N_2$ 
[1]
```

---

---

**Algorithm 4** LSTD update phase

---

```
1: Freeze the weights of  $f(\phi(s))$ , i.e.  $\theta$ 
2: Unfreeze the weights of  $\mathbf{A}$ , i.e.  $w$ 
3: for episode  $e_0 = 1$  to  $N_3$  do
4:   Repeat the same steps at the warm-up phase
5:   for each time step  $t = 1$  to  $T$  do
6:     Repeat the same steps at the warm-up phase
7:     [Start using the online LSTD algorithm to update  $\theta$ ]
8:     Calculate  $\tau = \phi(s_t) - \gamma\phi(s_{t+1})$ 
9:     Calculate  $v = \tau^T A^{-1}$ 
10:    Update  $A_a^{-1} = A_a^{-1} - \frac{A_a^{-1}\phi(s)v^T}{1+v\phi(s)}$ 
11:    Update  $b_a = b_a + r\phi(s)$ 
12:    Given the action  $a$  of the current time step, update  $\theta_a = A_a^{-1}b_a$ 
13:    Update state  $s_t = s_{t+1}$ 
14:   end for
15: end for
16:  $e = e + N_3$ 
[1]
```

---

---

**Algorithm 5** Training procedure

---

```
1: Run Initialization
2: for each training cycle  $c = 1$  to  $\frac{N}{N_0}$  do
3:   Run Warm-up phase
4:   for each intra- $c$  round  $r = 1$  to  $\frac{N_0 - N_1}{N_2 + N_3}$  do
5:     Run Autoencoder update phase
6:     Reset  $A^{-1}, b, \theta$  to the default value at the initialization phase
7:     Run LSTD update phase
8:   end for
9: end for
```

[1]

---