

Name: Osama Abdul Razzak(2303.KHI.DEG.029)

Peer Name: Rahima Siddiqui(2303.KHI.DEG.030)

Assignment 3.4(a) and 3.4(b)

Write a component that will log metadata of your Classification model that you trained on the day dedicated to Supervised Learning. Remember to include all metadata that are important to track for this problem.

Run your Classification model that you trained on the day dedicated to Supervised Learning in MLFlow.

We work on Logistics Regression Classification model

First we created virtual environment and install required libraries init

```
python3 -m venv venv
source venv/bin/activate
(mlops-student) (base) osamaabdu1razzak@11-MS-7035:~/Desktop/usama_ejaz/data_engineering_bootcamp_2303/tasks/3_machine_learning_essentials/day_4_mlops$
```

also install kernel in virtual environment and use that kernel for the task

and here are environment variable for the code

Name: Osama Abdul Razzak(2303.KHI.DEG.029)
Peer Name: Rahima Siddiqui(2303.KHI.DEG.030)

```
osamaabulrazzak@all-MS- X README.md X MLFlow_Lab.ipynb X mlflow_env_vars.sh X MLproject
1 #!/bin/sh
2
3 export MLFLOW_CONDA_HOME=/home/osamaabulrazzak/anaconda3/
4 export MLFLOW_TRACKING_URI="http://0.0.0.0:5000"
5 export MLFLOW_AR=./mlruns
6
```

and python file for logistic regression

```
osamaabulrazzak@all-MS- X README.md X MLFlow_Lab.ipynb X mlflow_env_vars.sh X MLproject
1 import pandas as pd
2 from sklearn.linear_model import LogisticRegression
3 from sklearn.pipeline import make_pipeline
4 from sklearn.preprocessing import StandardScaler
5 from sklearn.datasets import load_wine
6 import mlflow
7 import fire
8 def preprocess_data(wine_data):
9     df = pd.DataFrame(wine_data.data, columns=wine_data.feature_names)
10    df["target"] = wine_data.target
11    return df
12 def setup_lr_pipeline():
13     lr = LogisticRegression()
14     pipe = make_pipeline(StandardScaler(), lr)
15     return pipe
16 def split_data(df):
17     feature_cols = df.columns[:-1]
18     X = df[feature_cols]
19     y = df["target"]
20     return X, y
21 def track_with_mlflow(model, X_test, y_test, mlflow, model_metadata):
22     mlflow.log_params(model_metadata)
23     mlflow.log_metric("accuracy", model.score(X_test, y_test))
24     mlflow.sklearn.log_model(model, "lr", registered_model_name="sklearn_lr")
25 def main():
26     wine_data = load_wine()
27     df = preprocess_data(wine_data)
28     X, y = split_data(df)
29     with mlflow.start_run():
30         lr_pipe = setup_lr_pipeline()
31         lr_pipe.fit(X, y)
32         model_metadata = {"dataset": "wine"}
33         track_with_mlflow(lr_pipe, X, y, mlflow, model_metadata)
34 if __name__ == "__main__":
35     fire.Fire(main)
```


import pandas as pd

Name: Osama Abdul Razzak(2303.KHI.DEG.029)

Peer Name: Rahima Siddiqui(2303.KHI.DEG.030)

```
from sklearn.linear_model import LogisticRegression
from sklearn.pipeline import make_pipeline
from sklearn.preprocessing import StandardScaler
from sklearn.datasets import load_wine
import mlflow
import fire
def preprocess_data(wine_data):
    df = pd.DataFrame(wine_data.data, columns=wine_data.feature_names)
    df["target"] = wine_data.target
    return df
def setup_lr_pipeline():
    lr = LogisticRegression()
    pipe = make_pipeline(StandardScaler(), lr)
    return pipe
def split_data(df):
    feature_cols = df.columns[:-1]
    X = df[feature_cols]
    y = df["target"]
    return X, y
def track_with_mlflow(model, X_test, y_test, mlflow, model_metadata):
    mlflow.log_params(model_metadata)
    mlflow.log_metric("accuracy", model.score(X_test, y_test))
    mlflow.sklearn.log_model(model, "lr", registered_model_name="sklearn_lr")
def main():
    wine_data = load_wine()
    df = preprocess_data(wine_data)
    X, y = split_data(df)
    with mlflow.start_run():
        lr_pipe = setup_lr_pipeline()
        lr_pipe.fit(X, y)
        model_metadata = {"dataset": "wine"}
        track_with_mlflow(lr_pipe, X, y, mlflow, model_metadata)
if __name__ == "__main__":
    fire.Fire(main)
```

and we use ml_project file, which required to run for bash command in ipynb file



```
1 name: basic_mlflow
2 # this file is used to configure Python package dependencies.
3 # it uses Anaconda, but it can be also alternatively configured to use pip.
4 conda_env: conda.yaml
5 # entry points can be ran using `mlflow run <project_name> -e <entry_point_name>`
6 entry_points:
7   main:
8     # parameters is a key-value collection.
9     parameters:
10       command:
11         type: str
12         default: "train"
13       command: "python train.py"
```

Name: Osama Abdul Razzak(2303.KHI.DEG.029)
Peer Name: Rahima Siddiqui(2303.KHI.DEG.030)


than we mlflow server on 5000 port
by using following bash command

After running the command, testing server will be accessible at localhost:5000.

```
W bash --bg
```

```
mlflow server --host 0.0.0.0 \  
--port 5000 \  
--backend-store-uri sqlite:///mlflow.db \  
--default-artifact-root ./mlruns
```

ML Project file



and check out ml_project file

```
%cat MLproject
```

```
name: basic_mlflow  
# this file is used to configure Python package dependencies.  
# it uses Anaconda, but it can be also alternatively configured to use pip.  
conda_env: conda.yaml  
# entry points can be ran using `mlflow run <project_name> -e <entry_point_name>  
entry_points:  
  main:  
    # parameters is a key-value collection.  
    parameters:  
      command:  
        type: str  
        default: "train"  
    command: "python train.py"
```

First we need to download data. We will use weather data from previous machine learning tutorial.

then we run our model

Name: Osama Abdul Razzak(2303.KHI.DEG.029)
Peer Name: Rahima Siddiqui(2303.KHI.DEG.030)

```
import sklearn

sklearn.__version__

'1.2.2'

%%bash
source mlflow_env_vars.sh
mlflow run .

2023/05/08 10:21:38 INFO mlflow.utils.conda: Conda environment mlflow-dd0fbdd40ba98798131458f29496394bd1a3fb33 already exists.
2023/05/08 10:21:38 INFO mlflow.projects.utils: === Created directory /tmp/tmpx1mvlr3 for downloading remote URIs passed to arguments of type 'path' ===
2023/05/08 10:21:38 INFO mlflow.projects.backend.local: === Running command 'source /home/osamaabdulrazzak/anaconda3/bin/../etc/profile.d/conda.sh && conda activate mlflow-dd0fbdd40ba98798131458f29496394bd1a3fb33 && python train.py' in run with ID 'ca65b85542f641e3971569bcf21cf286' ===
/home/osamaabdulrazzak/Desktop/usama_ejaz/data_engineering_bootcamp_2303/tasks/3_machine_learning_essentials/mlops-student/lib/python3.10/site-packages/_distutils_hack/__init__.py:33: UserWarning: Setuptools is replacing distutils.
  warnings.warn("Setuptools is replacing distutils.")
Registered model 'sklearn_lr' already exists. Creating a new version of this model...
2023/05/08 10:21:40 INFO mlflow.tracking._model_registry.client: Waiting up to 300 seconds for model version to finish creation. Model name: sklearn_lr, version 6
Created version '6' of model 'sklearn_lr'.
2023/05/08 10:21:40 INFO mlflow.projects: === Run (ID 'ca65b85542f641e3971569bcf21cf286') succeeded ===
```

and then give the path

```
%%bash
last_model_path=$(ls -tr mlruns/0/ | tail -1)
cat mlruns/0/$last_model_path/artifacts/lr/MLmodel

artifact_path: lr
flavors:
  python_function:
    env:
      conda: conda.yaml
      virtualenv: python_env.yaml
    loader_module: mlflow.sklearn
    model_path: model.pkl
    predict_fn: predict
    python_version: 3.10.6
  sklearn:
    code: null
    pickled_model: model.pkl
    serialization_format: cloudpickle
    sklearn_version: 1.2.2
mlflow.version: 2.3.1
model_uuid: 26013996b4b74346bd36fb829b2d7f93
run_id: ca65b85542f641e3971569bcf21cf286
utc_time_created: '2023-05-08 05:21:39.335761'
```

then run the another port for model prediction

```
%%bash --bg
source mlflow_env_vars.sh
mlflow --version
mlflow models serve -m models:/sklearn_lr/Production -p 5002 --env-manager=conda
```

here we did prediction on two row

Name: Osama Abdul Razzak(2303.KHI.DEG.029)
Peer Name: Rahima Siddiqui(2303.KHI.DEG.030)

```
1: %bash
data='[[13.27, 4.28, 2.26, 20.0, 120.0, 1.59, 0.69, 0.43, 1.35, 10.2, 0.59, 1.56, 835.0],[13.27, 4.28, 2.26, 20.0, 120.0, 1.59, 0.69, 0.43, 1.35, 10.2, 0.59, 1.56, 835.0]]'
echo $data
curl -d '{"inputs\": $data}" -H 'Content-Type: application/json' 127.0.0.1:5002/invocations

[[13.27, 4.28, 2.26, 20.0, 120.0, 1.59, 0.69, 0.43, 1.35, 10.2, 0.59, 1.56, 835.0],[13.27, 4.28, 2.26, 20.0, 120.0, 1.59, 0.69, 0.43, 1.35, 10.2, 0.59, 1.56, 835.0]]

% Total    % Received % Xferd  Average Speed   Time    Time     Time  Current
           Dload  Upload   Total     Spent    Left  Speed
100 200 100    23 100    177    9725  74841  --:--:--  --:--:--  --:--:--   97k
{"predictions": [2, 2]}
```

```
1: %bash
data='[[14.23,1.71,2.43,15.6,127.0,2.80,3.06,0.28,2.29,5.64,1.04,3.92,1065.0],[14.23,1.71,2.43,15.6,127.0,2.80,3.06,0.28,2.29,5.64,1.04,3.92,1065.0]]'
echo $data
curl -d '{"instances\": $data}" -H 'Content-Type: application/json' 127.0.0.1:5002/invocations

[[14.23,1.71,2.43,15.6,127.0,2.80,3.06,0.28,2.29,5.64,1.04,3.92,1065.0],[14.23,1.71,2.43,15.6,127.0,2.80,3.06,0.28,2.29,5.64,1.04,3.92,1065.0]]

% Total    % Received % Xferd  Average Speed   Time    Time     Time  Current
           Dload  Upload   Total     Spent    Left  Speed
100 181 100    23 100    158    15710  105k  --:--:--  --:--:--  --:--:--  176k
{"predictions": [0, 0]}
```

```
1: 14.23,1.71,2.43,15.6,127.0,2.80,3.06,0.28,2.29,5.64,1.04,3.92,1065.0]]'
:'["alcohol","malic_acid","ash","alcalinity_of_as","magnesium","total_phenols","flavanoids","nonflavanoid_phenols","proanthocyanins","color_intensity","hue","od280/od315_of_dilute
ita

"{"dataframe_split":{"columns":["alcohol","malic_acid","ash","alcalinity_of_as","magnesium","total_phenols","flavanoids","nonflavanoid_phenols","proanthocyan
14.23,1.71,2.43,15.6,127.0,2.80,3.06,0.28,2.29,5.64,1.04,3.92,1065.0]]

% Total    % Received % Xferd  Average Speed   Time    Time     Time  Current
           Dload  Upload   Total     Spent    Left  Speed
100 845 100    534 100    311    368K  214K  --:--:--  --:--:--  --:--:--   825k
{"error_code": "BAD_REQUEST", "message": "Failed to parse input from JSON. Ensure that input is a valid JSON formatted string. Error: 'Extra data: line 1 column 311 (char 310)'."
Input: \n{"dataframe_split":{"columns":["alcohol","malic_acid","ash","alcalinity_of_as","magnesium","total_phenols","flavanoids","nonflavanoid_phenols","proa
nthyocyanins","color_intensity","hue","od280/od315_of_diluted_wines","proline"],"data": [[14.23,1.71,2.43,15.6,127.0,2.80,3.06,0.28,2.29,5.64,1.04,3.92,1065.0]]}}\n"}

Voilà! We see that the model outputs correct predictions.
```