

COMPUTER SCIENCE 10TH – MULTIPLE CHOICE QUESTIONS

➔ INPUT / OUTPUT HANDLING IN C++

Chapter # 03

ADAMJEECOACHING.BLOGSPOT.COM

1. Each escape sequence must start with.
(a) & (and sign) (b) / (forward slash)
(c) ✓ \ (back slash) (d) % (percentage sign)
2. The multi-line comment begins with the character set of.
(a) */ (b) ✓ /*
(c) * (d) * \ b
3. *adamjeeecoaching.blogspot.com*
<stdio.h> is _____ file.
(a) Document file (b) Spreadsheet file
(c) ✓ Header file (d) Executable file
4. Every C++ program must have this function.
(a) cout () (b) ✓ main ()
(c) cin () (d) None of these
5. In this statement "int main(void)" the second void is.
(a) Return type (b) ✓ Argument
(c) Function (d) Variable
6. The # symbol is called _____ directives
(a) ✓ Preprocessor (b) Multiprocessor
(c) Postprocessor (d) None of these
7. All C++ statements must end with:
(a) comma (,) (b) ✓ semicolon (;)
(c) > (d) <

8. This is a statement terminator in C++.
- (a) { } (b) "
- (c) ✓ ; (d) :
9. Single line comment written in C++ with _____ symbol.
- (a) /+ (b) ✓ //
- (c) * (d) None of these
10. gets () function is used to input data type:
- (a) Character (b) Integer
- (c) Float (d) ✓ None of them
- adamjeeecoaching.blogspot.com*
11. getche () function gets a character and the character:
- (a) ✓ Display (b) Print
- (c) Read (d) Variable
12. cin() statement is used to data from standard input device:
- (a) Process (b) ✓ Input
- (c) Output (d) None of them
13. In which logical operator, the result of operation will be true, if both operands are true, otherwise false:
- (a) NOT (b) ✓ AND
- (c) OR (d) None of them
14. Logical NOT operator takes operand:
- (a) Two (b) Three
- (c) Four (d) ✓ None of them
15. The remainder operator (%) requires that both operands be.
- (a) Float (b) ✓ Integer
- (c) Double (d) Character

16. Relational operators are used to _____ two operands:
- (a) Add (b) Combine
(c) ✓ Compare (d) Collect
17. Increment and decrement operators operate on only one operand and are called:
- (a) ✓ Unary operator (b) Binary operator
(c) Ternary operator (d) None of these
18. \n escape sequence is used to move the cursor to.
- (a) New page (b) ✓ New line
(c) New paragraph (d) New section
- adamjeeecoaching.blogspot.com*
19. Equality operator is denoted by.
- (a) = (b) ✓ ==
(c) != (d) None of them
20. The symbol << is called.
- (a) New line symbol (b) Output operator
(c) ✓ Insertion operator (d) None of them
21. Which of the following operator works only with integer variables?
- (a) Increment (b) Decrement
(c) Binary operator (d) ✓ Both increment & decrement
22. If an increment or decrement operator is placed after a variable, it is called as.
- (a) Pre-increment and Pre-decrement (b) Post-increment
(c) Post-decrement (d) ✓ Post-increment and Post-decrement
23. Which of the following escape sequence represents carriage return?
- (a) ✓ \r (b) \n
(c) \n\r (d) \c

24. What value does the variable a have, after all of the code executes?

```
int a =1;
```

```
int b;
```

```
b = a++;
```

(a) ✓ 2

(b) 1

(c) 3

(d) Unknown/undefined

25. Those operators that require two operands are known as:

(a) Unary operators

(b) ✓ Binary operators

(c) Ternary operators

(d) None of them

FOR MORE NOTES, MCQS & ONLINE TEST

ADAMJEECOACHING.BLOGSPOT.COM