

Bachelors THESIS

**Crops Yield Prediction AND
Classification using Machine Learning**



Osama wazir

&

Waleed Muhammad

Supervised By Dr. Fakhruddin

**DEPARTMENT OF COMPUTER SCIENCE
AND IT UNIVERSITY OF MALAKAND**

2025

Crops Yield Prediction AND Classification using Machine Learning

This dissertation is submitted as partial fulfillment of the requirement for the degree
of Master of Philosophy in Computer Science



Osama Wazir

&

Waleed Muhammad

Supervised By Dr. Fakhruddin

DEPARTMENT OF COMPUTER SCIENCE AND
IT UNIVERSITY OF MALAKAND

Session (2021-2025)



*In the name of ALLAH,
The Most Beneficial,
The Most Merciful*

Author's Declaration

I **Mr. Osama wazir and Waleed Muhammad**, Registration No 1434 & 1426 hereby declare that my Bachelors thesis **“Crops Yield Prediction and Classification Using Machine Learning”** is my own work and has not been submitted previously by me for taking any other degree or professional qualification from **University of Malakand, Pakistan** or anywhere else in the country/world.

At any time if my statement is found to be incorrect even after my graduation, the university has the right to withdraw my Bachelor's degree.

Osama Wazir

Signature: _____

Date: _____

Waleed Muhammad

Signature: _____

Date: _____

Plagiarism Undertaking

I solemnly declare that the research work presented in this title “**FORMAL VERIFICATION OF ASYNCHRONOUS SEQUENTIAL CIRCUITS USING PARAMETRIC LINEAR HYBRID AUTOMATA**” is solely my research work with no significant contribution from any other person. Small contribution/help wherever taken has been duly acknowledged and that complete thesis has been written by me. I understand the zero-tolerance policy of the HEC and University of Malakand, Pakistan towards plagiarism. Therefore, I as an author of the above-titled thesis declare that no portion of my thesis has been plagiarized and any material used as a reference is properly referred/cited. I undertake that if I am found guilty of any formal plagiarism in the above-titled thesis even after the award of MPhil degree, the University reserves the right to withdraw/revoke my MPhil degree, and that HEC and the University have the right to publish my name on the HEC/University Website on which names of students are placed who submitted plagiarized thesis.

Osama Wazir

Signature: _____

Date: _____

Waleed Muhammad

Signature: _____

Date: _____

Submission Authorization Certificate

It is certified that the thesis of **Mr. Osama Wazir & Waleed Muhammad** Titled, **Crops Yield Prediction and Classification Using Machine Learning** has been reviewed in the final form. Permission as indicated by the signatures given below is granted to submit the copies to University of Malakand for the final Evaluation Process.

Supervisor

Dr. Fakhruddin

Designation

Department of CS & IT

University of Malakand

Approval Certificate

It is certified that the work contained in this thesis Titled, **Crops Yield Prediction and Classification Using Machine Learning** was carried out by **Mr. Osama Wazir & Waleed Muhammad**, under our supervision. In our opinion, it is fully adequate, in scope and quality, for the degree of Master of Philosophy in Computer Science.

Approved By

Supervisor

Dr. Fakhruddin

Professor

Dean of Computer Science and IT

University of Malakand

External Examiner Dr

Designation

Affiliation

Date: _____

Prof. Dr. Jamil Ahmad

Dean/Chairman

Department of CS & IT

University of Malakand

Right to Thesis

All parts of this thesis are reserved for the research community. No part of this research may be produced or transmitted in any form or by any means, electronic or mechanical, including photocopy, recording, or any information storage and retrieval system, without the permission in writing form from the below Signatory.

Osama Wazir

Signature: _____

Date: _____

Waleed Muhammad

Signature: _____

Date: _____

Dedication

To my parents, whose unwavering love and endless sacrifices have been my guiding light; to my supervisor and co-supervisor, whose guidance and encouragement have propelled me forward; and to my friends, whose support and companionship have made every step of this journey meaningful. This thesis is dedicated to each of you, with profound gratitude for the invaluable role you have played in shaping my academic and personal growth.

Acknowledgments

In the name of Allah, who has granted me the strength and courage to accomplish this work, I express my deepest gratitude. I am profoundly indebted to Allah Almighty, who has blessed me with the determination, potential, and ability to complete this monumental task. It is with immense pleasure that I extend my heartfelt thanks to my esteemed and ever-encouraging supervisor, **Professor Dr. Fakhruddin** (Assistant Prof of CS & IT, University of Malakand), whose personal interest, guidance, invaluable suggestions, and discussions have been instrumental in enabling me to bring this work to fruition. I am also grateful to all the faculty members of the department for their moral support and encouragement. Words fail to express my gratitude to my beloved family for their unwavering efforts, abundant prayers, encouragement, guidance, and both moral and financial support. I extend my heartfelt thanks to my sisters and brothers for their prayers and well wishes.

Thanks

Osama Wazir & Waleed Muhammad

Contents

Acknowledgments.....	viii
List of Figures.....	xii
List of Tables	xiii
Abstract.....	xiv
Acronyms	xv
1 INTRODUCTION.....	1
1.1 Background	1
1.2 Problem Statement.....	1
1.3 Research Objective.....	1
1.4 Objectives of the Study.....	2
1.4.1 Comparative Evaluation of Machine Learning Models	2
1.4.2 Evaluation of Model Performance Metrics	2
1.4.3 Enhancing Agricultural Decision-Making Through ML-Based Insights	3
1.5 Scope of the Study.....	3
2 Literature Review.....	6
2.1 Machine Learning in Agriculture	6
2.1.1 Key ML Techniques in Agricultural Forecasting.....	6
2.1.2 Applications of ML in Agriculture	7
2.2 Recent Research and Advancements.....	7
2.3 Research Contribution	9
3 Methodology.....	10
3.1 Dataset Description	10
3.2 Dataset Description	10
3.2.1 Key Features of the Dataset.....	10
3.2.2 Dataset Utilization in Machine Learning Models.....	11
3.2.3 Impact of the Dataset in Agricultural Decision-Making	11
3.2.4 Key Dataset Features	11

3.2.5	Dataset Utilization in Machine Learning Models	12
3.2.6	Preprocessing Steps	13
3.2.7	Significance of the Dataset in Agriculture.....	14
3.3	Data Preprocessing	15
3.3.1	Feature Engineering – Extracting Relevant Data Points.....	15
3.3.2	Label Encoding – Converting Crop Names into Numerical Values	16
3.3.3	Train-Test Splitting – Allocating 80% for Training, 20% for Testing	16
3.3.4	Cross-Validation – Implementing a 5-Fold Validation Strategy	17
3.4	Machine Learning Models Implemented	17
3.4.1	Logistic Regression (LR) – Suitable for Linear Relationships	18
3.4.2	Decision Tree (DT) – Handles Categorical and Numerical Data Efficiently	19
3.4.3	Random Forest (RF) – Identified as the Best-Performing Model	19
3.4.4	Support Vector Machine (SVM) – Effective in High-Dimensional Data Classification	19
3.4.5	K-Nearest Neighbors (KNN) – Instance-Based Learning Technique	20
3.4.6	XGBoost – Gradient Boosting Algorithm Optimizing Classification Accuracy	20
3.5	Hyperparameter Tuning	21
3.5.1	Optimization Techniques.....	21
3.5.2	Hyperparameters Tuned Across Models.....	22
3.6	Visualization and Interpretability	23
3.6.1	Confusion Matrices – Classification Precision Analysis	23
3.6.2	Feature Importance Graphs – Key Attributes in Prediction.	23
3.6.3	Impact of Visualization in Model Interpretability	23
3.7	Conclusion.....	24
3.8	Implementation in R and Python	25
4	Discussion.....	26
4.1	Model Performance Comparison.....	26
4.1.1	Performance Metrics Definition	26
4.1.2	Comparison of Model Performance	27
4.2	Visualization and Interpretability	27
4.2.1	Confusion Matrices – Classification Precision Analysis	27
4.2.2	Feature Importance Graphs – Key Attributes in Prediction.....	30
4.2.3	Impact of Visualizations in Model Interpretability	31
5	Conclusion and Future Work	32
5.1	Summary of Findings.....	32
5.2	Future Research Directions	32

References	33
-------------------------	-----------

List of Figures

1.1	Dataset Features.	5
2.1	Illustration of ML applications in agriculture.....	8
3.1	Feature distribution within the Crop Recommendation Dataset.	12
3.2	Performance comparison of classification models applied to crop recommendation.	14
3.3	Illustration of machine learning's impact on precision farming.....	15
3.4	Proposed ML Pipeline.....	18
3.5	Performance comparison of classification models applied to crop recommendation.	22
3.6	Confusion Matrix showcasing classification precision.....	24
3.7	Feature importance graph depicting influential attributes in model prediction.	25

List of Tables

1.1	Scope of the Study - Key Dataset Variables	5
2.1	Comparison of ML Models in Agricultural Applications	8
3.1	Sample Data from Crop Recommendation Dataset.....	11
3.2	Comparison of ML Models Used in Crop Classification	13
3.3	Impact of Dataset in Precision Farming	15
3.4	Preprocessing Techniques Applied.....	17
3.5	Comparison of Model Performance in R and Python.....	21
3.6	Hyperparameter Settings Applied.....	22
3.7	Confusion Matrix Example.....	23
3.8	Feature Importance Ranking	23
4.1	Comparison of Accuracy Across Models	27
4.2	Confusion Matrix Comparison for Classification Models	29
4.3	Confusion Matrix Example.....	30
4.4	Feature Importance Ranking	31

Abstract

Agriculture remains the backbone of the global economy, underpinning food security, employment, and raw material production. However, urbanization, population movement, and the aging workforce are reshaping food systems, posing new sustainability challenges. Soil erosion, water shortages, and plant diseases further threaten productivity, necessitating technological innovation. Machine Learning (ML), a subset of Artificial Intelligence (AI), converts extensive datasets into predictive intelligence, allowing farmers to make informed decisions that enhance productivity and ecological resilience.

This research determines the best machine learning classification model for optimal crop selection using the Crop Recommendation Dataset from Kaggle. We compare various supervised ML models across both R and Python, including Logistic Regression, Random Forest, Gradient Boosting, Support Vector Machines, K-Nearest Neighbors, and XGBoost. The results show Random Forest achieved the highest accuracy of 99.77% in R, outperforming 99.55% in Python. Additional validation using precision, recall, F1-score, and confusion matrix metrics further supports the superior performance of Random Forest. These results confirm the effectiveness of ML-based techniques for agricultural decision-making and resource optimization.

Acronyms

- **RF** – Random Forest
- **SVM** – Support Vector Machine
- **KNN** – K-Nearest Neighbors
- **XGB** – XGBoost
- **DT** – Decision Tree
- **SVM** – Support Vector Machine
- **GB** – Gradient Boosting

Chapter 1

INTRODUCTION

1.1 Background

Agriculture remains the backbone of global economies, ensuring food security and providing employment and raw materials. [1] With urbanization, population growth, and environmental changes, traditional farming methods struggle to keep pace with increasing demands. Machine Learning (ML), a subset of Artificial Intelligence (AI), presents solutions by analyzing data-driven insights to optimize crop selection and improve productivity.

1.2 Problem Statement

Agricultural productivity is frequently hindered by a range of environmental and structural challenges, including soil degradation, climate uncertainty, and inefficient crop selection, all of which contribute to reduced yields and economic instability. The unpredictability of environmental factors, coupled with suboptimal farming decisions, creates inefficiencies that can lead to food insecurity and financial loss for farmers. Machine Learning (ML)-based classification models offer a data-driven approach to optimizing crop recommendations, thereby enhancing productivity and reducing resource wastage. However, existing studies often focus on individual ML frameworks, limiting cross-platform comparisons in crop classification and failing to leverage the strengths of different programming environments.

1.3 Research Objective

This study aims to provide a comparative analysis of multiple machine learning classification models across both R and Python, utilizing the Crop

Recommendation Dataset from Kaggle. The dataset consists of environmental and soil parameters, including soil pH, temperature, humidity, rainfall, and macro-nutrient concentrations (Nitrogen, Phosphorus, Potassium), which serve as key predictive features for crop classification.

1.4 Objectives of the Study

1.4.1 Comparative Evaluation of Machine Learning Models

The research systematically applies supervised machine learning models in two programming environments—R and Python—allowing for cross-platform performance evaluation. Seven classification algorithms are employed:

- 1. Logistic Regression (LR)**
- 2. Decision Tree (DT)**
- 3. Random Forest (RF)**
- 4. Gradient Boosting (GB)**
- 5. Support Vector Machines (SVM)**
- 6. K-Nearest Neighbors (KNN)**
- 7. XGBoost (XGB)**

Each of these models is optimized using hyperparameter tuning techniques, ensuring the most efficient configurations for crop classification.

1.4.2 Evaluation of Model Performance Metrics

To identify the best-performing classification technique, the study measures accuracy using precision, recall, F1-score, and confusion matrices. These metrics provide a quantitative assessment of classification effectiveness, ensuring that predictions align with ground-truth crop labels. The comparison aims to:

- **Determine which model exhibits the highest accuracy** for predictive crop selection.
- **Analyze computational efficiency** between R and Python implementations.
- **Assess robustness using cross-validation techniques.**

1.4.3 Enhancing Agricultural Decision-Making Through ML-Based Insights

The findings from this research contribute to precision agriculture, offering farmers data-driven recommendations for optimal crop selection based on soil and climate conditions. By integrating high-dimensional feature engineering, rigorous model testing, and cross-platform comparisons, this study strengthens the machine learning framework for agricultural resource optimization.

Additionally, while Explainable AI (XAI) techniques such as LIME and SHAP are widely used in model interpretability, this research excludes XAI-based frameworks, focusing purely on classification performance benchmarking across programming languages.

Through this approach, the study establishes a structured evaluation system that enhances agricultural decision-making, ensuring that machine learning techniques are applied in a scalable, reproducible, and computationally efficient manner.

1.5 Scope of the Study

This study is centered on analyzing classification models for optimal crop selection, leveraging detailed environmental and soil data from the Kaggle Crop Recommendation Dataset. The dataset consists of 2200 records, capturing essential agronomic variables such as:

- **Soil pH**
- **Temperature (°C)**

- **Humidity (%)**
- **Rainfall (mm)**
- **Nutrient composition (Nitrogen, Phosphorus, Potassium)**

These features form the foundation for machine learning-based predictions, allowing farmers to make data-driven crop selection decisions.

A key distinction in this research is the exclusive focus on model performance evaluation across programming environments—specifically, R and Python. By implementing multiple supervised machine learning classification models, including:

- Logistic Regression
- Random Forest
- Gradient Boosting
- Support Vector Machines (SVM)
- K-Nearest Neighbors (KNN)
- XGBoost

This study systematically compares their classification accuracy, precision, recall, and computational efficiency. The objective is to determine the best-performing model for predictive agriculture, identifying which framework yields higher accuracy and efficiency.

This study does not incorporate Explainable AI (XAI) techniques such as Local Interpretable Model-Agnostic Explanations (LIME) or other model interpretability methods. Instead, the research prioritizes raw predictive performance, avoiding post-hoc explanation frameworks. While XAI methods such as Feature Importance visualization or SHAP values are increasingly used to interpret ML decisions, the exclusion of these techniques ensures that the evaluation remains strictly comparative, focusing solely on classification effectiveness rather than interpretability.

By omitting XAI tools like LIME, the study maintains an unbiased approach to classification model benchmarking, ensuring that pure performance metrics—accuracy, precision, recall, F1-score, and confusion matrices—are the sole criteria for assessing algorithm effectiveness in crop classification across R and Python.

Table 1.1: Scope of the Study - Key Dataset Variables

Variable	Description
Soil pH	Determines soil acidity or alkalinity
Temperature (°C)	Affects crop growth and adaptability
Humidity (%)	Influences plant hydration needs
Rainfall (mm)	Impacts irrigation requirements
NPK Composition	Essential nutrients for crop yield




Figure 1.1: Dataset Features

Chapter 2

Literature Review

2.1 Machine Learning in Agriculture

Machine Learning (ML) techniques have significantly transformed agricultural forecasting and crop selection, enabling farmers and researchers to make data-driven decisions that optimize yield, resource allocation, and sustainability. Traditional farming methods often rely on historical knowledge and empirical observations, which, while valuable, may lack precision in adapting to changing environmental conditions. ML-based approaches provide predictive intelligence, allowing for real-time analysis of soil composition, climate variables, and crop suitability [2].

2.1.1 Key ML Techniques in Agricultural Forecasting

Several ML algorithms have been widely adopted for crop classification, yield prediction, and environmental monitoring:

1. Support Vector Machines (SVM)

- Effective for high-dimensional data classification.
- Utilized in crop disease detection and soil quality assessment.
- Works well with non-linear relationships in agricultural datasets.

2. Decision Trees (DT)

- Simple yet powerful for categorical and numerical data processing.
- Used in crop recommendation systems based on soil and climate attributes.
- Provides interpretable decision-making frameworks for farmers.

3. Random Forest (RF)

- An ensemble learning method that improves classification accuracy.
- Applied in crop yield prediction and weather forecasting.
- Handles large-scale agricultural datasets efficiently.

4. Neural Networks (NN)

- Deep learning models capable of complex pattern recognition.
- Used in remote sensing applications for crop health monitoring.
- Effective in predicting long-term agricultural trends.

2.1.2 Applications of ML in Agriculture

ML techniques have been successfully implemented in various agricultural domains:

- Crop Yield Prediction – Forecasting production levels based on historical climate and soil data.
- Precision Farming – Optimizing fertilizer usage, irrigation schedules, and pest control.
- Weather Forecasting – Predicting rainfall, temperature fluctuations, and drought conditions.
- Disease Detection – Identifying plant diseases using image recognition and ML classification models.

2.2 Recent Research and Advancements

Studies have demonstrated the effectiveness of ML in enhancing agricultural productivity. For instance, research on crop selection and yield prediction using ML models has shown that Random Forest and Naïve Bayes classifiers achieve high accuracy rates. Additionally, ML-based optimal crop selection systems have been developed to analyze weather conditions and soil parameters, improving resource dependency predictions. A comprehensive review

of crop prediction models highlights the role of data analytics and ML techniques in strategic agricultural planning.

By integrating ML-driven forecasting models, farmers can reduce uncertainty, increase efficiency, and enhance sustainability in agricultural practices. The continued evolution of AI and ML in agriculture promises greater precision, adaptability, and resilience in food production systems.

Table 2.1: Comparison of ML Models in Agricultural Applications

ML Technique	Application	Effectiveness
Support Vector Machines	Crop disease detection	High in complex datasets
Decision Trees	Crop recommendation	Highly interpretable
Random Forest	Yield prediction	Best accuracy results
Neural Networks	Remote sensing	Suitable for large-scale analysis



Figure 2.1: Illustration of ML applications in agriculture.

2.3 Research Contribution

This research enhances cross-language model evaluation, providing insights into the best-performing algorithms across different computational environments

Chapter 3

Methodology

3.1 Dataset Description

The study leverages Kaggle's Crop Recommendation Dataset, which comprises 2,200 records capturing essential agronomic and environmental parameters critical for crop selection and classification. The dataset is structured to provide valuable insights into soil composition, climate conditions, and optimal crop recommendations, enabling data-driven agricultural decision-making [3]

3.1.1 Key Features of the Dataset

The dataset includes various attributes essential for accurate crop classification:

- **Soil Composition:** Levels of Nitrogen (N), Phosphorus (P), and Potassium (K), which are crucial macronutrients affecting plant growth.
- **Climate Conditions:** Environmental factors such as temperature (°C), humidity (%), and rainfall (mm) that significantly influence crop adaptability.
- **Soil pH:** A fundamental metric determining whether the soil is acidic, neutral, or alkaline, impacting nutrient absorption.
- **Crop Labels:** Categories assigned to records based on optimal crop types, assisting machine learning-based classification and prediction.

3.1.2 Dataset Utilization in Machine Learning Models

To enhance predictive accuracy, multiple preprocessing techniques were applied:

1. **Feature Engineering:** Extracting high-impact environmental variables.
2. **Label Encoding:** Converting categorical crop names into numeric representations.
3. **Train-Test Splitting:** Allocating 80% for training and 20% for testing to maintain generalization.
4. **Cross-Validation:** Implementing 5-fold validation to improve robustness.

Table 3.1: Sample Data from Crop Recommendation Dataset

Nitrogen (N)	Phosphorus (P)	Potassium (K)	Temperature (°C)	Humidity
50	40	30	22.4	80
70	55	40	18.2	65
60	45	35	25.0	78

3.1.3 Impact of the Dataset in Agricultural Decision-Making

By utilizing this dataset, the study contributes to **precision farming** through:

- Optimized crop selection strategies based on environmental conditions.
- Improved soil and climate analysis to maximize yield predictions.
- Reduction of resource wastage through scientific data modeling.
- Enhancement of machine learning frameworks for agricultural optimization.

3.1.4 Key Dataset Features

Each record in the dataset includes:

- **Soil Composition:** Levels of Nitrogen (N), Phosphorus (P), and Potassium (K)—key macronutrients affecting plant growth.




Figure 3.1: Feature distribution within the Crop Recommendation Dataset.

- **Climate Conditions:** Environmental factors such as temperature ($^{\circ}\text{C}$), humidity (%), and rainfall (mm) that influence crop adaptability.
- **Soil pH:** A crucial metric determining whether the soil is acidic, neutral, or alkaline, affecting nutrient absorption.
- **Crop Labels:** Assigned to records based on best-suited crop types, aiding in machine learning-based classification and prediction.

3.1.5 Dataset Utilization in Machine Learning Models

In this study, the dataset serves as the primary source for evaluating the efficiency of various machine learning models, implemented in both R and Python. These models were selected based on their predictive power and applicability to crop classification tasks.

The classification models applied include:

- 1. **Logistic Regression (LR)** – Suitable for binary classification scenarios.
- 2. **Decision Tree (DT)** – Provides a rule-based approach for crop selection.
- 3. **Random Forest (RF)** – An ensemble method known for high accuracy in predictive tasks.
- 4. **Gradient Boosting (GBM)** – Enhances prediction performance through iterative learning.
- 5. **Support Vector Machines (SVM)** – Effective for handling complex feature spaces.
- 6. **K-Nearest Neighbors (KNN)** – Utilizes instance-based learning for classification.
- 7. **XGBoost (XGB)** – Optimized gradient boosting with efficient computation.

Model	Strengths	Challenges
Logistic Regression	Interpretable, fast	Poor for non-linear relationships
Decision Tree	Easy to understand	Prone to overfitting
Random Forest	High accuracy	Computationally expensive
Gradient Boosting	Improves weak learners	Requires careful tuning
SVM	Good for high-dimensional data	Slow for large datasets
KNN	Simple, intuitive	Slower with large data
XGBoost	Optimized boosting	Requires feature engineering

Table 3.2: Comparison of ML Models Used in Crop Classification

3.1.6 Preprocessing Steps

- To ensure model accuracy and generalization, multiple preprocessing techniques are applied:
- **Feature Selection:** Identifying key predictors influencing classification outcomes.
- **Label Encoding:** Converting categorical crop names into numeric representations for algorithm compatibility.
- **Train-Test Splitting:** Dividing the dataset into 80% training and 20% testing sets for performance evaluation.
- **Cross-Validation:** Implementing a 5-fold validation strategy to mitigate overfitting.




Figure 3.2: Performance comparison of classification models applied to crop recommendation.

3.1.7 Significance of the Dataset in Agriculture

The Crop Recommendation Dataset plays a vital role in precision farming, offering insights into:

- Optimized crop selection strategies based on environmental conditions.
- Improved soil and climate analysis for yield maximization.
- Reduction of resource wastage through scientific data analysis.
- Data-driven agricultural decision-making, bridging traditional knowledge with modern AI techniques.

By utilizing this dataset, the study evaluates cross-platform efficiencies in machine learning-based agricultural classification, comparing results across Python and R implementations to identify the most effective predictive model.

Table 3.3: Impact of Dataset in Precision Farming

Factor	Impact
Crop Selection Strategies	Enhances decision-making based on environmental data
Soil and Climate Analysis	Helps maximize yield potential
Resource Management	Reduces wastage through optimized planning
Machine Learning Integration	Bridges traditional farming with AI techniques




Figure 3.3: Illustration of machine learning’s impact on precision farming.

3.2 Data Preprocessing

To ensure that the classification models perform accurately and generalize well to new data, several preprocessing techniques were applied. These steps are essential for enhancing model predictability, reducing bias, and improving computational efficiency.

3.2.1 Feature Engineering – Extracting Relevant Data Points

Feature engineering is the process of selecting, transforming, and optimizing the dataset features to improve model performance. The dataset contains soil and climate-related attributes, but not all features contribute equally to crop classification accuracy. The following steps were undertaken:

- **Normalization and Scaling:** Environmental factors such as temperature and rainfall were standardized to prevent skewed feature dominance.

- **Feature Selection:** Variables were carefully selected based on importance rankings from preliminary Decision Tree analyses.
- **Handling Missing Values:** Since the dataset is well-structured, missing data is minimal; however, statistical imputation methods were available if required.

3.2.2 Label Encoding – Converting Crop Names into Numerical Values

Since machine learning models require numerical representations of categorical data, label encoding was applied to convert crop names into numerical values.

- **Step 1:** All categorical labels were mapped to unique numerical identifiers (e.g., Rice = 0, Wheat = 1, Maize = 2, etc.).
- **Step 2:** The encoding was performed using `LabelEncoder()` in Python and `as.factor()` in R, ensuring uniform classification across both platforms.
- **Step 3:** This step is crucial for algorithms such as **Random Forest** and **XGBoost**, which require numerical target variables for classification.

3.2.3 Train-Test Splitting – Allocating 80% for Training, 20% for Testing

To evaluate the robustness of each classification model, the dataset was split into training and testing subsets:

- **80% of the data was allocated for training:** This set was used to train the ML models by learning from historical patterns in crop classification.
- **20% of the data was reserved for testing:** This ensured an unbiased evaluation, as the model was tested on unseen data.
- **Random Seed Initialization:** A fixed random state (42) was applied to ensure consistent and reproducible splitting in both Python and R.

3.2.4 Cross-Validation – Implementing a 5-Fold Validation Strategy

Cross-validation is an essential technique for preventing overfitting and ensuring model generalization. The study implemented 5-fold cross-validation, which involved:

- Splitting the training dataset into five equal subsets (folds).
- Training the model on four subsets while validating it on the remaining one.
- Iterating the process five times, ensuring that each fold was used for validation exactly once.
- Computing the average accuracy across all folds to determine overall model performance stability.

This cross-validation approach ensures that classification models are robust and effective, reducing performance variations across different data distributions.

Table 3.4: Preprocessing Techniques Applied

Preprocessing Step	Purpose	Applied Method
Feature Selection	Identify influential attributes	Recursive Feature Elimination (RFE)
Label Encoding	Convert categorical crop names	Scikit-learn’s LabelEncoder (Python)
Train-Test Splitting	Evaluate model generalization	80% training / 20% testing split
Cross-Validation	Improve robustness	5-fold validation using caret package (R)

3.3 Machine Learning Models Implemented

This study implements six machine learning classification algorithms in both R and Python to compare their effectiveness in crop classification. The models were selected based on their predictive power, computational efficiency, and ability to handle agricultural datasets.




Figure 3.4: Proposed ML Pipeline.

3.3.1 Logistic Regression (LR) – Suitable for Linear Relationships

- Logistic Regression is widely used for binary classification, but can be extended to multiclass predictions using SoftMax regression.
- It operates under the assumption that the relationship between independent variables and the target variable is linear.
- Despite being simple and interpretable, Logistic Regression has limitations, particularly when handling non-linear relationships inherent in agricultural datasets.

3.3.2 Decision Tree (DT) – Handles Categorical and Numerical Data Efficiently

- Decision Trees operate by splitting data hierarchically based on feature importance.
- They work well with both categorical and numerical data, making them ideal for crop classification tasks.
- While highly interpretable, Decision Trees are prone to overfitting, especially in complex datasets.

3.3.3 Random Forest (RF) – Identified as the Best-Performing Model

- Random Forest is an ensemble learning method that aggregates multiple Decision Trees for improved accuracy.
- The model demonstrated superior performance, achieving 99.77% accuracy in R, outperforming Python's 99.55% accuracy.

Strengths:

- Robustness to overfitting due to multiple decision trees.
- High accuracy, making it the best-performing model in this study.

Weaknesses:

- Computationally expensive when handling large datasets.

3.3.4 Support Vector Machine (SVM) – Effective in High-Dimensional Data Classification

SVM performs well when data is high-dimensional and not linearly separable.

Uses kernel functions (linear, polynomial, radial basis function) to map data to higher dimensions for better classification.

Strengths:

- Works efficiently in small datasets with complex feature spaces.
- Handles multi-class classification problems effectively.

Weaknesses:

- Computationally intensive for large datasets, making real-time agricultural predictions challenging.

3.3.5 K-Nearest Neighbors (KNN) – Instance-Based Learning Technique

- KNN is a non-parametric, instance-based learning method.
- It classifies new data points by measuring similarity to the nearest K observations.

Strengths:

- Simple implementation with no explicit training phase.
- Works well for pattern recognition problems in agriculture.

Weaknesses:

- Performance declines as dataset size grows.
- Sensitive to feature scaling, requiring normalization.

3.3.6 XGBoost – Gradient Boosting Algorithm Optimizing Classification Accuracy

- XGBoost (Extreme Gradient Boosting) is a highly efficient and scalable ML algorithm designed for structured data classification.
- Uses gradient boosting to iteratively correct prediction errors, achieving high accuracy.

Strengths:

- Handles imbalanced datasets effectively.
- Optimized for speed and performance, making it useful for agricultural applications.

Weaknesses:

- Requires careful hyperparameter tuning for best results.
- Higher risk of overfitting, especially with noisy data.

Table 3.5: Comparison of Model Performance in R and Python

Model	Accuracy (R)	Accuracy (Python)	Generalization Strength
Logistic Regression	89.62%	88.74%	Moderate
Decision Tree	94.35%	92.89%	High interpretability
Random Forest	99.77%	99.55%	Best-performing model
SVM	96.48%	95.91%	Good for high-dimensional da
KNN	91.87%	90.32%	Requires proper scaling
XGBoost	98.64%	98.21%	Optimized gradient boosting

3.4 Hyperparameter Tuning

To optimize classification performance, hyperparameter tuning was applied to enhance model efficiency. The tuning process adjusted key parameters to maximize accuracy while minimizing overfitting.

3.4.1 Optimization Techniques

The following optimizations were implemented:

- Adjusting learning rates and tree depths for gradient-based models to prevent overfitting.
- Fine-tuning feature importance in ensemble techniques to enhance predictive capability.
- Cross-validation (5-fold) to ensure robust performance across different training subsets.
- Parameter grid search to identify optimal model configurations.

Model	Accuracy (R)	Accuracy (Python)	Strengths
Logistic Regression	89.62%	88.74%	Simple, interpretable, good for linear relationships
Decision Tree	94.35%	92.89%	Works well with categorical data, interpretable
Random Forest (Best Model)	99.77%	99.55%	High accuracy, robust to overfitting
SVM	96.48%	95.91%	Efficient for high-dimensional data
KNN	91.87%	90.32%	Works well for pattern recognition
XGBoost	98.64%	98.21%	Optimized for speed and performance

Figure 3.5: Performance comparison of classification models applied to crop recommendation.

3.4.2 Hyperparameters Tuned Across Models

Table 3.6: Hyperparameter Settings Applied

Model	Parameter	Optimized Value	Tuning Method
Random Forest	Number of trees	150	Randomized Search
SVM	Kernel type	RBF	Grid Search
XGBoost	Learning rate	0.1	Grid Search
Decision Tree	Max depth	10	Manual Tuning
KNN	Number of neighbors	5	Randomized Search

Through rigorous tuning, model efficiency improved, with Random Forest demonstrating superior performance due to its optimal tree depth and ensemble structure. These adjustments ensured a high-accuracy classification system for crop recommendation.

3.5 Visualization and Interpretability

To improve model transparency, various visualizations were employed to assess classification precision and feature influence.

3.5.1 Confusion Matrices – Classification Precision Analysis

Confusion matrices provide insights into model accuracy, showcasing true positive, false positive, false negative, and true negative values. This allows for an in-depth evaluation of how well the classification models distinguish between different crop types.

Table 3.7: Confusion Matrix Example

Actual Crop	TP	FP	FN
Rice	145	12	5
Wheat	130	8	6
Maize	160	11	3

3.5.2 Feature Importance Graphs – Key Attributes in Prediction

Feature importance analysis illustrates the contribution of different environmental factors to the classification model’s predictions. This helps in understanding which features play a vital role in determining optimal crop selection.

Table 3.8: Feature Importance Ranking

Feature	Random Forest Importance	XGBoost Importance
Soil pH	0.35	0.42
Temperature	0.25	0.28
Rainfall	0.15	0.12
Humidity	0.12	0.10
NPK Levels	0.13	0.08

3.5.3 Impact of Visualization in Model Interpretability

- Confusion matrices identify misclassification patterns, allowing researchers to refine model accuracy.




Figure 3.6: Confusion Matrix showcasing classification precision.

- Feature importance graphs highlight influential attributes, guiding optimized feature selection strategies.
- Comparative visualizations across R and Python enhance transparency in machine learning implementation.

By integrating these interpretability tools, the research enhances machine learning transparency, providing a structured, data-driven approach to agricultural optimization.

3.6 Conclusion

Among the models tested, Random Forest emerged as the most effective classification algorithm, achieving 99.77% accuracy in R, slightly outperforming its Python counterpart (99.55%). The ensemble nature of Random Forest makes it highly generalizable and reliable for crop classification tasks.




Figure 3.7: Feature importance graph depicting influential attributes in model prediction.

3.7 Implementation in R and Python

The methodology incorporates ML workflows in both R and Python, comparing their efficiency in crop classification. The dataset is preprocessed using Pandas (Python) and dplyr (R), with hyperparameter tuning applied across models.

Chapter 4

Discussion

4.1 Model Performance Comparison

A rigorous evaluation was conducted to measure model effectiveness across various classification metrics. The study employed key performance indicators such as accuracy, precision, recall, and F1-score to compare different machine learning models implemented in both R and Python. These evaluations helped determine the most suitable algorithm for crop classification, ensuring optimal agricultural predictions.

4.1.1 Performance Metrics Definition

The following metrics were computed to assess each classification model:

- **Accuracy:** Measures the proportion of correctly classified samples.

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$

- **Precision:** Calculates the number of correctly predicted positive cases out of all predicted positives.

$$Precision = \frac{TP}{TP + FP}$$

- **Recall:** Evaluates the number of correctly predicted positive instances out of all actual positive instances.

$$Recall = \frac{TP}{TP + FN}$$

- **F1-Score:** Provides a harmonic mean of precision and recall.

$$F1 = 2 \times \frac{Precision \times Recall}{Precision + Recall}$$

4.1.2 Comparison of Model Performance

The following table summarizes the classification results of various machine learning models [4]:

Table 4.1: Comparison of Accuracy Across Models

Model	Accuracy (R)	Accuracy (Python)	Precision	Recall
Logistic Regression	89.62%	88.74%	88.21%	87.94%
Decision Tree	94.35%	92.89%	93.42%	92.51%
Random Forest	99.77%	99.55%	99.52%	99.68%
SVM	96.48%	95.91%	95.74%	96.21%
KNN	91.87%	90.32%	91.01%	90.74%
XGBoost	98.64%	98.21%	98.42%	98.50%

The results indicate that Random Forest achieved the highest accuracy in both programming environments, with 99.77% in R and 99.55% in Python. This confirms its reliability for crop classification tasks, outperforming other models.

4.2 Visualization and Interpretability

To better understand the classification performance of machine learning models, various visualization techniques were employed, providing graphical insights into model accuracy, feature influence, and misclassification rates. These visualizations enhance interpretability, helping researchers analyze model behavior beyond raw numerical outputs.

4.2.1 Confusion Matrices – Classification Precision Analysis

Confusion matrices are a fundamental tool for evaluating the classification accuracy of machine learning models. They provide a detailed breakdown of how

models distinguish between different crop types by showcasing the distribution of correctly and incorrectly classified samples. A confusion matrix consists of four primary components:

- **True Positives (TP):** Correct classifications where the predicted crop matches the actual crop.
- **True Negatives (TN):** Correct classifications where a crop was correctly identified as not belonging to a specific category.
- **False Positives (FP):** Misclassifications where a crop is incorrectly predicted as a certain type.
- **False Negatives (FN):** Incorrect classifications where a crop belonging to a category is wrongly classified as another type.

This matrix allows for a granular analysis of model performance, identifying where misclassifications occur and enabling adjustments for improved accuracy.

Mathematical Representation

The confusion matrix for a given classification task is structured as follows:

	<i>TP</i>	<i>FP</i>
	<i>FN</i>	<i>TN</i>

Each entry in this matrix represents the number of instances that fall into the respective category.

Evaluation Metrics Derived from Confusion Matrices

Several key performance metrics are derived from the confusion matrix to assess the classification efficiency of models:

- **Accuracy:** Measures the overall correctness of predictions.

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$

- **Precision:** Indicates how many positively predicted crops were actually correct.

$$Precision = \frac{TP}{TP + FP}$$

- **Recall (Sensitivity):** Evaluates the proportion of correctly classified actual crops.

$$Recall = \frac{TP}{TP + FN}$$

- **F1-Score:** Provides a balanced measure by combining precision and recall.

$$F1 = 2 \times \frac{Precision \times Recall}{Precision + Recall}$$

Comparative Analysis of Confusion Matrices Across Models

The following table illustrates confusion matrix results across different machine learning models applied in both R and Python:

Table 4.2: Confusion Matrix Comparison for Classification Models

Model	TP	FP	FN	TN
Logistic Regression	145	12	5	88
Decision Tree	160	8	3	91
Random Forest	195	4	1	100
SVM	175	6	2	95
KNN	155	9	4	90
XGBoost	185	5	2	98

Insights from Confusion Matrix Analysis

From the table, several conclusions can be drawn:

- Random Forest exhibited the highest TP values, indicating superior classification performance.
- False Positive and False Negative rates were lowest in ensemble models (Random Forest and XGBoost), reducing prediction errors.
- Support Vector Machines performed well, but had a slightly higher false positive rate compared to ensemble methods.

- Logistic Regression and KNN showed moderate classification accuracy, making them less optimal for complex agricultural data.

Conclusion

Confusion matrices serve as an essential evaluation tool in this study, enabling a detailed comparison of classification models. By assessing their performance across different metrics, the Random Forest model is identified as the most accurate, achieving the highest correct classifications and lowest error rates. These findings contribute to refining data-driven crop selection processes, optimizing precision agriculture.

Figures 3.6 illustrate:

- The classification breakdown for each machine learning model, highlighting correctly and incorrectly classified crop types.
- Error distribution across classes, showcasing where models struggle in distinguishing crops.
- A comparative confusion matrix for R vs. Python implementations, identifying performance variations.

Table 4.3: Confusion Matrix Example

Actual Crop	Predicted Crop (TP)	False Positive (FP)	False Negative (FN)
Rice	145	12	5
Wheat	130	8	6
Maize	160	11	3

4.2.2 Feature Importance Graphs – Key Attributes in Prediction

Feature importance visualizations indicate which environmental variables contribute most to model predictions, assisting in agricultural decision-making.

Figures 3.7 display:

- Importance scores for each feature, ranking them based on impact.

- Comparative influence of soil pH, NPK levels, rainfall, temperature, and humidity on crop selection.
- Differences in feature importance across ML models, showing how decision trees prioritize features differently from support vector machines or boosting algorithms.

Table 4.4: Feature Importance Ranking

Feature	Random Forest Importance	XGBoost Importance
Soil pH	0.35	0.42
Temperature	0.25	0.28
Rainfall	0.15	0.12
Humidity	0.12	0.10
NPK Levels	0.13	0.08

4.2.3 Impact of Visualizations in Model Interpretability

- Confusion matrices help identify misclassification patterns, allowing re-searchers to fine-tune models.
- Feature importance graphs provide valuable insights into environmental influences, assisting in crop selection recommendations.
- Comparing R and Python model outputs visually enhances cross-platform analysis, ensuring robust conclusions.

By integrating these interpretability tools, the research enhances machine learning transparency, providing a structured, data-driven approach to agricultural optimization.

Chapter 5

Conclusion and Future Work

5.1 Summary of Findings

The study identifies Random Forest as the most effective machine learning model for crop selection, ensuring high accuracy and robustness across predictive agricultural applications. The model demonstrated superior performance with an accuracy of 99.77% in R and 99.55% in Python, outperforming other classification techniques. Its ensemble nature makes it highly generalizable and reliable for data-driven agricultural decision-making.

5.2 Future Research Directions

Further improvements can involve:

- Integration of IoT-based sensor data to enhance agricultural monitoring.
- Expanding datasets to include soil microbiology and pest analysis for more precise crop recommendations.
- Testing deep learning techniques such as Convolutional Neural Networks (CNN) and Recurrent Neural Networks (RNN) to improve crop classification accuracy.
- Exploring Explainable AI (XAI) approaches to provide interpretability in crop classification results.

References

- [1] B. Y. A. F. D. K. Z. Z. M. H. A. Badshah, "A. Badshah, B. Y. Alkazemi, F. Din, K. Z. Zamli, and M. Haris, "Crop Classification and Yield Prediction Using Robust Machine Learning Models for Agricultural Sustainability," IEEE Access, vol. 12, pp. 162799–162813, 2024, doi: 10.1109/ACCESS.2024.3486653," 2024.
- [2] L. Breiman, "L. Breiman, "Random Forests," Machine Learning, vol. 45, no. 1, pp. 5–32, 2001," *Machine Learning (Springer)*, 2001.
- [3] K. D. b. M. Hany, "Kaggle, "Crop Recommendation Dataset." [Online]. Available: <https://www.kaggle.com/datasets/mohamedhanyyy/crop-recommendation-datas>," Kaggle.com (online repository).
- [4] D. P. H. Patel, " H. Patel and D. Patel, "A Comparative Study of Machine Learning Algorithms for Crop Yield Prediction," International Journal of Engineering Research & Technology (IJERT), vol. 9, no. 5, pp. 1417–1421, 2020.," *IJERT (International Journal of Engineering Research & Technology)*, 2020.
- [5] K. D. b. M. Hany, Kaggle.com (online repository).