

Lecture 2: Markov Decision Processes

David Silver

- 1 Markov Processes
- 2 Markov Reward Processes
- 3 Markov Decision Processes
- 4 Extensions to MDPs

Introduction to MDPs

- *Markov decision processes* formally describe an **environment** for reinforcement learning
- Where the environment is **fully observable**
- i.e. The current *state* completely characterises the process
- Almost all RL problems can be formalised as MDPs, e.g.
 - Optimal control primarily deals with continuous MDPs
 - Partially observable problems can be converted into MDPs
 - Bandits are MDPs with one state

Markov Property

“The future is independent of the past given the present”

Definition

A state S_t is *Markov* if and only if

$$\mathbb{P}[S_{t+1} \mid S_t] = \mathbb{P}[S_{t+1} \mid S_1, \dots, S_t]$$

- The state captures all relevant information from the history
- Once the state is known, the history may be thrown away
- i.e. The state is a sufficient statistic of the future

State Transition Matrix

For a Markov state s and successor state s' , the *state transition probability* is defined by

$$\mathcal{P}_{ss'} = \mathbb{P} [S_{t+1} = s' \mid S_t = s]$$

State transition matrix \mathcal{P} defines transition probabilities from all states s to all successor states s' ,

$$\mathcal{P} = \begin{matrix} & \text{to} \\ \text{from} & \begin{bmatrix} \mathcal{P}_{11} & \dots & \mathcal{P}_{1n} \\ \vdots & & \\ \mathcal{P}_{n1} & \dots & \mathcal{P}_{nn} \end{bmatrix} \end{matrix}$$

where each **row** of the matrix sums to 1.

Markov Process

A Markov process is a memoryless random process, i.e. a sequence of random states S_1, S_2, \dots with the Markov property.


Definition

A *Markov Process* (or *Markov Chain*) is a tuple $\langle \mathcal{S}, \mathcal{P} \rangle$

- \mathcal{S} is a (finite) set of states
- \mathcal{P} is a state transition probability matrix,
$$\mathcal{P}_{ss'} = \mathbb{P}[S_{t+1} = s' \mid S_t = s]$$




Example: Student Markov Chain



Example: Student Markov Chain Episodes

Sample **episodes** for Student Markov Chain starting from $S_1 = C1$


$$S_1, S_2, \dots, S_T$$



- C1 C2 C3 Pass Sleep
- C1 FB FB C1 C2 Sleep
- C1 C2 C3 Pub C2 C3 Pass Sleep
- C1 FB FB C1 C2 C3 Pub C1 FB FB
FB C1 C2 C3 Pub C2 Sleep



Example: Student Markov Chain Transition Matrix



$$\mathcal{P} = \begin{array}{c} \begin{matrix} C1 \\ C2 \\ C3 \\ Pass \\ Pub \\ FB \\ Sleep \end{matrix} \end{array} \begin{bmatrix} & C1 & C2 & C3 & Pass & Pub & FB & Sleep \\ & & 0.5 & & & & 0.5 & \\ & & & 0.8 & & & & 0.2 \\ & & & & 0.6 & 0.4 & & \\ Pass & & & & & & & 1.0 \\ Pub & 0.2 & 0.4 & 0.4 & & & & \\ FB & 0.1 & & & & & 0.9 & \\ Sleep & & & & & & & 1 \end{bmatrix}$$

Markov Reward Process

A Markov reward process is a Markov chain with values.

Definition

A *Markov Reward Process* is a tuple $\langle \mathcal{S}, \mathcal{P}, \mathcal{R}, \gamma \rangle$

- \mathcal{S} is a finite set of states
- \mathcal{P} is a state transition probability matrix,
$$\mathcal{P}_{ss'} = \mathbb{P}[S_{t+1} = s' \mid S_t = s]$$
- \mathcal{R} is a reward function, $\mathcal{R}_s = \mathbb{E}[R_{t+1} \mid S_t = s]$
- γ is a discount factor, $\gamma \in [0, 1]$

Example: Student MRP



Return

Definition

The *return* G_t is the total discounted reward from time-step t .

$$G_t = R_{t+1} + \gamma R_{t+2} + \dots = \sum_{k=0}^{\infty} \gamma^k R_{t+k+1}$$

- The *discount* $\gamma \in [0, 1]$ is the present value of future rewards
- The value of receiving reward R after $k + 1$ time-steps is $\gamma^k R$.
- This values immediate reward above delayed reward.
 - γ close to 0 leads to "myopic" evaluation
 - γ close to 1 leads to "far-sighted" evaluation



Why discount?

Most Markov reward and decision processes are discounted. Why?

- Mathematically convenient to discount rewards
- Avoids **infinite returns** in cyclic Markov processes
- Uncertainty about the future may not be fully represented
- If the reward is financial, immediate rewards may earn more interest than delayed rewards
- Animal/human behaviour shows preference for immediate reward
- It is sometimes possible to use *undiscounted* Markov reward processes (i.e. $\gamma = 1$), e.g. **if all sequences terminate**.

Value Function

The value function $v(s)$ gives the **long-term** value of state s

Definition

The *state value function* $v(s)$ of an MRP is the **expected** return starting from state s

$$v(s) = \mathbb{E}[G_t \mid S_t = s]$$

Example: Student MRP Returns

Sample **returns** for Student MRP:

Starting from $S_1 = C1$ with $\gamma = \frac{1}{2}$

$$G_1 = R_2 + \gamma R_3 + \dots + \gamma^{T-2} R_T$$

C1 C2 C3 Pass Sleep	$v_1 = -2 - 2 * \frac{1}{2} - 2 * \frac{1}{4} + 10 * \frac{1}{8}$	=	-2.25
C1 FB FB C1 C2 Sleep	$v_1 = -2 - 1 * \frac{1}{2} - 1 * \frac{1}{4} - 2 * \frac{1}{8} - 2 * \frac{1}{16}$	=	-3.125
C1 C2 C3 Pub C2 C3 Pass Sleep	$v_1 = -2 - 2 * \frac{1}{2} - 2 * \frac{1}{4} + 1 * \frac{1}{8} - 2 * \frac{1}{16} \dots$	=	-3.41
C1 FB FB C1 C2 C3 Pub C1 ...	$v_1 = -2 - 1 * \frac{1}{2} - 1 * \frac{1}{4} - 2 * \frac{1}{8} - 2 * \frac{1}{16} \dots$	=	-3.20
FB FB FB C1 C2 C3 Pub C2 Sleep			


Example: State-Value Function for Student MRP (1)



Example: State-Value Function for Student MRP (2)



Example: State-Value Function for Student MRP (3)



Bellman Equation for MRPs


The value function can be **decomposed** into two parts:

- immediate reward R_{t+1}
- discounted value of **successor** state $\gamma v(S_{t+1})$

$$\begin{aligned}v(s) &= \mathbb{E}[G_t \mid S_t = s] \\&= \mathbb{E}[R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots \mid S_t = s] \\&= \mathbb{E}[R_{t+1} + \gamma (R_{t+2} + \gamma R_{t+3} + \dots) \mid S_t = s] \\&= \mathbb{E}[R_{t+1} + \gamma G_{t+1} \mid S_t = s] \\&= \mathbb{E}[R_{t+1} + \gamma v(S_{t+1}) \mid S_t = s]\end{aligned}$$

Bellman Equation for MRPs (2)

$$v(s) = \mathbb{E} [R_{t+1} + \gamma v(S_{t+1}) \mid S_t = s]$$



$$v(s) = \mathcal{R}_s + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'} v(s')$$

Example: Bellman Equation for Student MRP



Bellman Equation in Matrix Form

The Bellman equation can be expressed concisely using matrices,

$$v = \mathcal{R} + \gamma \mathcal{P}v$$

where v is a column vector with one entry per state

$$\begin{bmatrix} v(1) \\ \vdots \\ v(n) \end{bmatrix} = \begin{bmatrix} \mathcal{R}_1 \\ \vdots \\ \mathcal{R}_n \end{bmatrix} + \gamma \begin{bmatrix} \mathcal{P}_{11} & \dots & \mathcal{P}_{1n} \\ \vdots & & \\ \mathcal{P}_{n1} & \dots & \mathcal{P}_{nn} \end{bmatrix} \begin{bmatrix} v(1) \\ \vdots \\ v(n) \end{bmatrix}$$

Solving the Bellman Equation

- The Bellman equation is a linear equation
- It can be solved directly:

$$v = \mathcal{R} + \gamma \mathcal{P} v$$

$$(I - \gamma \mathcal{P}) v = \mathcal{R}$$

$$v = (I - \gamma \mathcal{P})^{-1} \mathcal{R}$$

- Computational complexity is $O(n^3)$ for n states
- Direct solution only possible for small MRPs
- There are many **iterative methods for large MRPs**, e.g.
 - Dynamic programming
 - Monte-Carlo evaluation
 - Temporal-Difference learning

Markov Decision Process


A Markov decision process (MDP) is a Markov reward process with decisions. It is an *environment* in which all states are Markov.

Definition

A *Markov Decision Process* is a tuple $\langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma \rangle$

- \mathcal{S} is a finite set of states
- \mathcal{A} is a finite set of actions
- \mathcal{P} is a state transition probability matrix,
 $\mathcal{P}_{ss'}^a = \mathbb{P}[S_{t+1} = s' \mid S_t = s, A_t = a]$
- \mathcal{R} is a reward function, $\mathcal{R}_s^a = \mathbb{E}[R_{t+1} \mid S_t = s, A_t = a]$
- γ is a discount factor $\gamma \in [0, 1]$.

Example: Student MDP



Policies (1)

Definition

A *policy* π is a distribution over actions given states,

$$\pi(a|s) = \mathbb{P}[A_t = a \mid S_t = s]$$

- A policy fully defines the behaviour of an agent
- MDP policies depend on the current state (not the history)
- i.e. Policies are *stationary* (time-independent),
 $A_t \sim \pi(\cdot|S_t), \forall t > 0$

Policies (2)

- Given an MDP $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma \rangle$ and a policy π
- The state sequence S_1, S_2, \dots is a Markov process $\langle \mathcal{S}, \mathcal{P}^\pi \rangle$
- The state and reward sequence S_1, R_2, S_2, \dots is a Markov reward process $\langle \mathcal{S}, \mathcal{P}^\pi, \mathcal{R}^\pi, \gamma \rangle$
- where

$$\mathcal{P}_{s,s'}^\pi = \sum_{a \in \mathcal{A}} \pi(a|s) \mathcal{P}_{ss'}^a$$

$$\mathcal{R}_s^\pi = \sum_{a \in \mathcal{A}} \pi(a|s) \mathcal{R}_s^a$$

Value Function

Definition

The *state-value function* $v_{\pi}(s)$ of an MDP is the expected return starting from state s , and then following policy π


$$v_{\pi}(s) = \mathbb{E}_{\pi} [G_t \mid S_t = s]$$

Definition

The *action-value function* $q_{\pi}(s, a)$ is the expected return starting from state s , taking action a , and then following policy π

$$q_{\pi}(s, a) = \mathbb{E}_{\pi} [G_t \mid S_t = s, A_t = a]$$

Example: State-Value Function for Student MDP



Bellman Expectation Equation

The state-value function can again be decomposed into immediate reward plus discounted value of successor state,

$$v_{\pi}(s) = \mathbb{E}_{\pi} [R_{t+1} + \gamma v_{\pi}(S_{t+1}) \mid S_t = s]$$

The action-value function can similarly be decomposed,

$$q_{\pi}(s, a) = \mathbb{E}_{\pi} [R_{t+1} + \gamma q_{\pi}(S_{t+1}, A_{t+1}) \mid S_t = s, A_t = a]$$

Bellman Expectation Equation for V^π




$$v_\pi(s) = \sum_{a \in \mathcal{A}} \pi(a|s) q_\pi(s, a)$$

Bellman Expectation Equation for Q^π




$$q_\pi(s, a) = \mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a v_\pi(s')$$

Bellman Expectation Equation for v_π (2)




$$v_\pi(s) = \sum_{a \in \mathcal{A}} \pi(a|s) \left(\mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a v_\pi(s') \right)$$

Bellman Expectation Equation for q_π (2)



$$q_\pi(s, a) = \mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a \sum_{a' \in \mathcal{A}} \pi(a'|s') q_\pi(s', a')$$

Example: Bellman Expectation Equation in Student MDP



Bellman Expectation Equation (Matrix Form)

The Bellman expectation equation can be expressed concisely using the induced MRP,

$$v_{\pi} = \mathcal{R}^{\pi} + \gamma \mathcal{P}^{\pi} v_{\pi}$$

with direct solution

$$v_{\pi} = (I - \gamma \mathcal{P}^{\pi})^{-1} \mathcal{R}^{\pi}$$



Optimal Value Function

Definition

The *optimal state-value function* $v_*(s)$ is the maximum value function over all policies


$$v_*(s) = \max_{\pi} v_{\pi}(s)$$

The *optimal action-value function* $q_*(s, a)$ is the maximum action-value function over all policies


$$q_*(s, a) = \max_{\pi} q_{\pi}(s, a)$$

- The optimal value function specifies the best possible performance in the MDP.
- An MDP is “solved” when we know the optimal value fn.

Example: Optimal Value Function for Student MDP



Example: Optimal Action-Value Function for Student MDP



Optimal Policy

Define a partial ordering over policies

$$\pi \geq \pi' \text{ if } v_\pi(s) \geq v_{\pi'}(s), \forall s$$

Theorem

For any Markov Decision Process

- *There exists an optimal policy π_* that is better than or equal to all other policies, $\pi_* \geq \pi, \forall \pi$*
- *All optimal policies achieve the optimal value function, $v_{\pi_*}(s) = v_*(s)$*
- *All optimal policies achieve the optimal action-value function, $q_{\pi_*}(s, a) = q_*(s, a)$*


Finding an Optimal Policy

An optimal policy can be found by maximising over $q_*(s, a)$,

$$\pi_*(a|s) = \begin{cases} 1 & \text{if } a = \operatorname{argmax}_{a \in \mathcal{A}} q_*(s, a) \\ 0 & \text{otherwise} \end{cases}$$


- There is always a deterministic optimal policy for any MDP
- If we know $q_*(s, a)$, we immediately have the optimal policy

Example: Optimal Policy for Student MDP



Bellman Optimality Equation for v_*

The optimal value functions are recursively related by the Bellman optimality equations:




$$v_*(s) = \max_a q_*(s, a)$$

Bellman Optimality Equation for Q^*




$$q_*(s, a) = \mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a v_*(s')$$

Bellman Optimality Equation for V^* (2)



$$v_*(s) = \max_a \mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a v_*(s')$$

Bellman Optimality Equation for Q^* (2)



$$q_*(s, a) = \mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a \max_{a'} q_*(s', a')$$

Example: Bellman Optimality Equation in Student MDP



Solving the Bellman Optimality Equation

- Bellman Optimality Equation is non-linear
- No closed form solution (in general)
- Many iterative solution methods
 - Value Iteration
 - Policy Iteration
 - Q-learning
 - Sarsa

Extensions to MDPs

(no exam)

- Infinite and continuous MDPs
- Partially observable MDPs
- Undiscounted, average reward MDPs

