

Lecture 3: Planning by Dynamic Programming

David Silver

Outline

- 1 Introduction
- 2 Policy Evaluation
- 3 Policy Iteration
- 4 Value Iteration
- 5 Extensions to Dynamic Programming
- 6 Contraction Mapping

What is Dynamic Programming?

Dynamic sequential or temporal component to the problem

Programming optimising a “program”, i.e. a policy

- c.f. linear programming
- A method for solving complex problems
- By breaking them down into subproblems
 - Solve the subproblems
 - Combine solutions to subproblems

Requirements for Dynamic Programming

Dynamic Programming is a very general solution method for problems which have two properties:

- Optimal substructure
 - *Principle of optimality* applies
 - Optimal solution can be decomposed into subproblems
- Overlapping subproblems
 - Subproblems recur many times
 - Solutions can be cached and reused
- Markov decision processes satisfy both properties
 - Bellman equation gives recursive decomposition
 - Value function stores and reuses solutions

Planning by Dynamic Programming

- Dynamic programming assumes full knowledge of the MDP
- It is used for *planning* in an MDP
- For prediction:
 - Input: MDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma \rangle$ and policy π
 - or: MRP $\langle \mathcal{S}, \mathcal{P}^\pi, \mathcal{R}^\pi, \gamma \rangle$
 - Output: value function v_π
- Or for control:
 - Input: MDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma \rangle$
 - Output: optimal value function v_*
 - and: optimal policy π_*

Other Applications of Dynamic Programming


Dynamic programming is used to solve many other problems, e.g.

- Scheduling algorithms
- String algorithms (e.g. sequence alignment)
- Graph algorithms (e.g. shortest path algorithms)
- Graphical models (e.g. Viterbi algorithm)
- Bioinformatics (e.g. lattice models)

Iterative Policy Evaluation

- Problem: evaluate a given policy π
- Solution: iterative application of Bellman expectation backup
- $v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_\pi$
- Using **synchronous backups**,
 - At each iteration $k + 1$
 - For all states $s \in \mathcal{S}$
 - Update $v_{k+1}(s)$ from $v_k(s')$
 - where s' is a successor state of s
- We will discuss *asynchronous* backups later
- Convergence to v_π will be proven at the end of the lecture


Iterative Policy Evaluation (2)



$$v_{k+1}(s) = \sum_{a \in \mathcal{A}} \pi(a|s) \left(\mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a v_k(s') \right)$$

$$\mathbf{v}^{k+1} = \mathcal{R}^\pi + \gamma \mathcal{P}^\pi \mathbf{v}^k$$

Evaluating a Random Policy in the **Small** Gridworld



- Undiscounted episodic MDP ($\gamma = 1$)
- Nonterminal states 1, ..., 14
- One terminal state (shown twice as shaded squares)
- Actions leading out of the grid leave state unchanged
- Reward is -1 until the terminal state is reached
- Agent follows uniform random policy

$$\pi(n|\cdot) = \pi(e|\cdot) = \pi(s|\cdot) = \pi(w|\cdot) = 0.25$$

Iterative Policy Evaluation in Small Gridworld



v_k for the
Random Policy

Greedy Policy
w.r.t. v_k

$k = 0$

0.0	0.0	0.0	0.0
0.0	0.0	0.0	0.0
0.0	0.0	0.0	0.0
0.0	0.0	0.0	0.0

⬛	↕↔↕	↕↔↕	↕↔↕
↕↔↕	↕↔↕	↕↔↕	↕↔↕
↕↔↕	↕↔↕	↕↔↕	↕↔↕
↕↔↕	↕↔↕	↕↔↕	⬛

← random policy

$k = 1$

0.0	-1.0	-1.0	-1.0
-1.0	-1.0	-1.0	-1.0
-1.0	-1.0	-1.0	-1.0
-1.0	-1.0	-1.0	0.0

⬛	←	↕↔↕	↕↔↕
↑	↕↔↕	↕↔↕	↕↔↕
↕↔↕	↕↔↕	↕↔↕	↓
↕↔↕	↕↔↕	→	⬛

$k = 2$


0.0	-1.7	-2.0	-2.0
-1.7	-2.0	-2.0	-2.0
-2.0	-2.0	-2.0	-1.7
-2.0	-2.0	-1.7	0.0

⬛	←	←	↕↔↕
↑	↖	↕↔↕	↓
↑	↕↔↕	↘	↓
↕↔↕	→	→	⬛


Iterative Policy Evaluation in Small Gridworld (2)

 $k = 3$


0.0	-2.4	-2.9	-3.0
-2.4	-2.9	-3.0	-2.9
-2.9	-3.0	-2.9	-2.4
-3.0	-2.9	-2.4	0.0


 $k = 10$

0.0	-6.1	-8.4	-9.0
-6.1	-7.7	-8.4	-8.4
-8.4	-8.4	-7.7	-6.1
-9.0	-8.4	-6.1	0.0


 $k = \infty$

0.0	-14.	-20.	-22.
-14.	-18.	-20.	-20.
-20.	-20.	-18.	-14.
-22.	-20.	-14.	0.0



optimal
policy

How to Improve a Policy

- Given a policy π
 - **Evaluate** the policy π

$$v_{\pi}(s) = \mathbb{E}[R_{t+1} + \gamma R_{t+2} + \dots | S_t = s]$$

- **Improve** the policy by acting greedily with respect to v_{π}

$$\pi' = \text{greedy}(v_{\pi})$$


- In Small Gridworld improved policy was optimal, $\pi' = \pi^*$
- In general, need more iterations of improvement / evaluation
- But this process of **policy iteration** always converges to π^*

Policy Iteration



Policy evaluation Estimate v_π
 Iterative policy evaluation

Policy improvement Generate $\pi' \geq \pi$
Greedy policy improvement




Jack's Car Rental



- States: Two locations, maximum of 20 cars at each
- Actions: Move up to 5 cars between locations overnight
- Reward: \$10 for each car rented (must be available)
- Transitions: Cars returned and requested randomly
 - Poisson distribution, n returns/requests with prob $\frac{\lambda^n}{n!} e^{-\lambda}$
 - 1st location: average requests = 3, average returns = 3
 - 2nd location: average requests = 4, average returns = 2



Policy Iteration in Jack's Car Rental



Policy Improvement

- Consider a **deterministic** policy, $a = \pi(s)$
- We can *improve* the policy by acting greedily

$$\pi'(s) = \operatorname{argmax}_{a \in \mathcal{A}} q_{\pi}(s, a)$$

- This improves the value from any state s over one step,

$$q_{\pi}(s, \pi'(s)) = \max_{a \in \mathcal{A}} q_{\pi}(s, a) \geq q_{\pi}(s, \pi(s)) = v_{\pi}(s)$$

- It therefore improves the value function, $v_{\pi'}(s) \geq v_{\pi}(s)$

$$\begin{aligned} v_{\pi}(s) &\leq q_{\pi}(s, \pi'(s)) = \mathbb{E}_{\pi'} [R_{t+1} + \gamma v_{\pi}(S_{t+1}) \mid S_t = s] \\ &\leq \mathbb{E}_{\pi'} [R_{t+1} + \gamma q_{\pi}(S_{t+1}, \pi'(S_{t+1})) \mid S_t = s] \\ &\leq \mathbb{E}_{\pi'} [R_{t+1} + \gamma R_{t+2} + \gamma^2 q_{\pi}(S_{t+2}, \pi'(S_{t+2})) \mid S_t = s] \\ &\leq \mathbb{E}_{\pi'} [R_{t+1} + \gamma R_{t+2} + \dots \mid S_t = s] = v_{\pi'}(s) \end{aligned}$$

Policy Improvement (2)

- If improvements stop,

$$q_{\pi}(s, \pi'(s)) = \max_{a \in \mathcal{A}} q_{\pi}(s, a) = q_{\pi}(s, \pi(s)) = v_{\pi}(s)$$

- Then the Bellman optimality equation has been satisfied


$$v_{\pi}(s) = \max_{a \in \mathcal{A}} q_{\pi}(s, a)$$

- Therefore $v_{\pi}(s) = v_*(s)$ for all $s \in \mathcal{S}$
- so π is an optimal policy

Modified Policy Iteration

- Does policy evaluation need to converge to v_π ?
- Or should we introduce a stopping condition
 - e.g. ϵ -convergence of value function
- Or simply stop after k iterations of iterative policy evaluation?
- For example, in the small gridworld $k = 3$ was sufficient to achieve optimal policy
- Why not update policy every iteration? i.e. stop after $k = 1$
 - This is equivalent to *value iteration* (next section)

Generalised Policy Iteration




Policy evaluation Estimate v_π

Any policy evaluation algorithm

Policy improvement Generate $\pi' \geq \pi$

Any policy improvement algorithm



Principle of Optimality

Any optimal policy can be subdivided into two components:

- An optimal first action A_*
- Followed by an optimal policy from successor state S'

Theorem (Principle of Optimality)

A policy $\pi(a|s)$ achieves the optimal value from state s , $v_\pi(s) = v_(s)$, if and only if*

- *For any state s' reachable from s*
- *π achieves the optimal value from state s' , $v_\pi(s') = v_*(s')$*

Deterministic Value Iteration

- If we know the solution to subproblems $v_*(s')$
- Then solution $v_*(s)$ can be found by one-step lookahead

$$v_*(s) \leftarrow \max_{a \in \mathcal{A}} \mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a v_*(s')$$

- The idea of value iteration is to apply these updates iteratively
- Intuition: start with final rewards and work backwards
- Still works with loopy, stochastic MDPs

Example: Shortest Path



g			

Problem

0	0	0	0
0	0	0	0
0	0	0	0
0	0	0	0

 V_1

0	-1	-1	-1
-1	-1	-1	-1
-1	-1	-1	-1
-1	-1	-1	-1

 V_2

0	-1	-2	-2
-1	-2	-2	-2
-2	-2	-2	-2
-2	-2	-2	-2

 V_3

0	-1	-2	-3
-1	-2	-3	-3
-2	-3	-3	-3
-3	-3	-3	-3

 V_4

0	-1	-2	-3
-1	-2	-3	-4
-2	-3	-4	-4
-3	-4	-4	-4

 V_5

0	-1	-2	-3
-1	-2	-3	-4
-2	-3	-4	-5
-3	-4	-5	-5

 V_6


0	-1	-2	-3
-1	-2	-3	-4
-2	-3	-4	-5
-3	-4	-5	-6

 V_7

Value Iteration

- Problem: find optimal policy π
- Solution: iterative application of Bellman optimality backup
- $v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_*$
- Using synchronous backups
 - At each iteration $k + 1$
 - For all states $s \in \mathcal{S}$
 - Update $v_{k+1}(s)$ from $v_k(s')$
- Convergence to v_* will be proven later
- Unlike policy iteration, there is no explicit policy
- Intermediate value functions may not correspond to any policy

Value Iteration (2)



$$v_{k+1}(s) = \max_{a \in \mathcal{A}} \left(\mathcal{R}_s^a + \gamma \sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a v_k(s') \right)$$

$$\mathbf{v}_{k+1} = \max_{a \in \mathcal{A}} \mathbf{R}^a + \gamma \mathbf{P}^a \mathbf{v}_k$$

Example of Value Iteration in Practice

<http://www.cs.ubc.ca/~poole/demos/mdp/vi.html>

Synchronous Dynamic Programming Algorithms

Problem	Bellman Equation	Algorithm
Prediction	Bellman Expectation Equation	Iterative Policy Evaluation
Control	Bellman Expectation Equation + Greedy Policy Improvement	Policy Iteration
Control	Bellman Optimality Equation	Value Iteration

- Algorithms are based on **state-value** function $v_{\pi}(s)$ or $v_*(s)$
- Complexity $O(mn^2)$ per iteration, for m actions and n states
- Could also apply to action-value function $q_{\pi}(s, a)$ or $q_*(s, a)$
- Complexity $O(m^2n^2)$ per iteration



Asynchronous Dynamic Programming



- DP methods described so far used *synchronous* backups
- i.e. all states are backed up in parallel
- *Asynchronous DP* backs up states individually, in any order
- For each selected state, apply the appropriate backup
- Can significantly reduce computation
- Guaranteed to converge if all states continue to be selected