VNIVERSITAT DE VALÈNCIA

ISP · Image & Signal Processing

Explainability in AI Systems

From feature attributions to mechanistic interpretability

Oscar J. Pellicer-Valero · `Oscar.Pellicer@uv.es`

Image & Signal Processing group (ISP), Universitat de València

Table of contents

Session 1: Classical XAI

- Introduction and key concepts
- Classification systems for XAI
- Transparent models
- Statistical and visualization methods
- Model-agnostic attribution methods: LIME, SHAP
- Counterfactual explanations
- Hands-on 1: XAI for tabular models

Session 2: Deep learning and beyond

- Attribution methods for neural networks
- From local to global; evaluation of attributions
- Hands-on 2: attributions for deep learning
- Concepts and mechanistic interpretability
- Hands-on 3: looking inside an LLM
- Conclusions

github.com/OscarPellicer/extra-attributions

Prompt: an open black box

Introduction and key concepts: Why do we need XAI?

- Debugging of AI systems
- Deployment in critical domains
- Regulatory requirements (EU AI Act; see next slides)
- Trust and accountability



Lapuschkin, S., et al. (2019). Unmasking Clever Hans predictors and assessing what machines really learn. Nature Communications, 10, 1096.

Introduction and key concepts: The EU AI Act (status in 2026)

Risk-based regulation: obligations scale with the risk of the use case

- **Unacceptable risk** (prohibited): social scoring, manipulative AI, most real-time remote biometric identification…
- **High risk** (Annex III: hiring, credit scoring, education, essential services, law enforcement…; Annex I: AI in regulated products such as medical devices or machinery)
- **Limited risk**: transparency duties (chatbots, deepfakes, AI-generated content)
- **General-purpose AI models**: documentation, copyright policy; extra duties for models with *systemic risk*

https://artificialintelligenceact.eu

Where XAI enters:

- **Art. 13**: high-risk systems must be *"sufficiently transparent to enable deployers to interpret a system's output and use it appropriately"*
- **Art. 14**: human oversight, i.e., humans must be able to understand capacities and limitations, and detect anomalies
- **Art. 86**: *right to an explanation* of individual decisions taken with high-risk systems

Note that the Act asks for *interpretable outputs*, but it does **not** prescribe any XAI method: which method is "good enough" remains an open (technical) question

Introduction and key concepts: The EU AI Act timeline

Date	What applies	What it means in practice
Aug 2024	Entry into force	The law exists, but almost nothing is enforceable yet
Feb 2025	Prohibited practices; AI literacy	Social scoring etc. are banned. **AI literacy** (Art. 4): organisations that build *or use* AI must take measures (e.g., training) so staff understand its capabilities, limits and risks
Aug 2025	General-purpose AI models	Providers of LLMs (e.g., GPT, Llama) must document their models and training data
Jul 2026	*Digital Omnibus on AI* in force	An amendment that **postpones** the high-risk deadlines below (originally Aug 2026-27)
Dec 2027	High-risk systems (Annex III)	Hiring, credit, education…: transparency (Art. 13), human oversight (Art. 14), right to explanation (Art. 86) **become enforceable**
Aug 2028	High-risk AI in regulated products (Annex I)	Same, for AI inside medical devices, machinery, vehicles…

Where we are now: the rules that need XAI (high-risk systems) are **not enforceable yet**; the standards that will define *how* to comply are still being written

https://artificialintelligenceact.eu · Digital Omnibus on AI: Regulation (EU) 2026/1744

Introduction and key concepts: Terminology

- **Explainability**: Ability to present model’s decisions in human-understandable terms
- **Interpretability**: Degree to which a model's behavior can be understood by humans
- **Trustworthiness**: Confidence in model's reliability and consistency with domain knowledge
- **Safeness**: degree to which an AI model's behavior is predictable, reliable, and constrained within specified operational boundaries
- **Transparency**: Understanding of the internal workings of the model

Classification systems for XAI: Overview



Taskin, G., Aptoula, E., & Ertürk, A. (2024). Explainable AI for Earth observation: current methods, open challenges, and opportunities. Advances in Machine Learning and Image Analysis for GeoAI, 115-152.

Classification systems for XAI

Scope of explanations

- **Local** explanations
  - Focus on understanding individual predictions
  - Use cases: medical diagnosis, credit decisions
- **Global** explanations
  - Focus on understanding the overall model behavior
  - General patterns and feature importance
  - Use cases: model validation, bias detection

Explanation approaches

- **Transparent models**: inherently interpretable, but compromise accuracy
  - Linear/logistic regression
  - Decision trees
  - Rule-based systems
- **Post-hoc** explanations
  - Methods applied after model training
  - According to their applicability:
    - Model-agnostic
    - Model-specific
  - Examples:
    - Feature attribution
    - Surrogate models

Explanation methodologies

- **Transparent models**
- **Statistical** and visualization methods:
  - Partial Dependency Plots
  - Individual Conditional Expectation
- **Attribution** methods:
  - LIME
  - SHAP
  - Gradient-based:
    - Saliency
    - Integrated gradients
    - etc.
  - Occlusion
- **Other** emerging methods

Transparent models > Linear Regression

Linear regression: predicts a target variable (y) as a weighted sum of input features: $y = \beta_0 + \beta_1 x_1 + \cdots + \beta_p x_p + \epsilon$, where β are the learned weights and ϵ is the error

Interpretation:

- **Numerical variables**: β_n is the change in prediction per unit change of x_n
- **Categorical variables**: β_c is the difference w.r.t. the reference category
- **Intercept** β_0: prediction when numerical features are 0 and categorical ones are at their reference
- **Adjusted** R^2: variance explained, penalised by the number of features p: $\bar{R}^2 = 1 - (1 - R^2)\frac{n-1}{n-p-1}$
- **Variable importance**: $|t_j|$, with $t_j = \hat{\beta}_j / SE(\hat{\beta}_j)$



n samples, p features; $R^2 = 1 - \frac{SSE}{SST}$ with $SSE = \sum_i (y^{(i)} - \hat{y}^{(i)})^2$ (residual error) and $SST = \sum_i (y^{(i)} - \bar{y})^2$ (total variance). **Std. error** (uncertainty of $\hat{\beta}_j$): $SE(\hat{\beta}_j) = \sqrt{\hat{\sigma}^2 [(X^T X)^{-1}]_{jj}}$, $\hat{\sigma}^2 = \frac{SSE}{n-p-1}$; grows with noise, fewer samples, little spread in x_j or correlation with other features. $|t| \gtrsim 2$: significant (5%)

Transparent models > Linear Regression

Linear regression example: Bike rental

	Weight	std. error	t-stat.
(Intercept)	2399.4	238.3	10.1
seasonSPRING	899.3	122.3	7.4
seasonSUMMER	138.2	161.7	0.9
seasonFALL	425.6	110.8	3.8
holidayHOLIDAY	-686.1	203.3	3.4
workingdayWORKING DAY	124.9	73.3	1.7
weathersitMISTY	-379.4	87.6	4.3
weathersitRAIN/SNOW/STORM	-1901.5	223.6	8.5
temp	110.7	7.0	15.7
hum	-17.4	3.2	5.5
windspeed	-42.5	6.9	6.2
days_since_2011	4.9	0.2	28.5

Weight plot: Shows the weights and their confidence intervals



Transparent models > Linear Regression

Effect plot

Visualizes the distribution of effects for each variable, where the effect of variable x_i is $\beta_i \cdot x_i$



Explainability: Transparent models > Linear Regression

Individual prediction within an effect plot

Feature	Value
season	WINTER
mnth	JAN
holiday	NO HOLIDAY
weekday	THU
workingday	WORKING DAY
weathersit	GOOD
temp	1.604356
hum	51.8261
windspeed	6.000868
days_since_2011	5



Transparent models > Linear Regression

Linear regression: L1 regularization (Lasso) can improve interpretability by setting some weights to zero

$$\min_\beta \left(\frac{1}{n} \sum_{i=1}^{n} (y^{(i)} - x_i^T \beta)^2 + \lambda ||\beta||_1 \right)$$

Lasso path: as λ decreases, features enter the model one by one (first = most useful)



	Weight
seasonWINTER	0.00
seasonSPRING	0.00
seasonSUMMER	0.00
seasonFALL	0.00
holidayHOLIDAY	0.00
workingdayWORKING DAY	0.00
weathersitMISTY	0.00
weathersitRAIN/SNOW/STORM	0.00
temp	52.33
hum	0.00
windspeed	0.00
days_since_2011	2.15

Transparent models > Logistic regression

Logistic regression: linear regression adapted to binary classification.

- Why not just fit a line to $y \in \{0, 1\}$ (left)? The output is not a probability (it goes below 0 and above 1) and extreme points tilt the line and move the 0.5 threshold
- It uses the logistic function to map the linear combination to probabilities between 0 and 1 (right):

  $\hat{y}^{(i)} = \beta_0 + \beta_1 x_1^{(i)} + \cdots + \beta_p x_p^{(i)}$
  (linear predictor)

  $\text{logistic}(\eta) = \frac{1}{1+\exp(-\eta)}$ (sigmoid function)

- It transforms the linear equation into probabilities:

  $$P(y^{(i)} = 1) = \frac{1}{1+\exp(-(\beta_0+\beta_1 x_1^{(i)}+\cdots+\beta_p x_p^{(i)}))}$$



Transparent models > Logistic regression

Coefficients are interpreted via **odds** ($P = 0.8 \rightarrow$ odds $= 4$, "4 to 1"):

1. The **log-odds are linear**: $\log \frac{P}{1-P} = \eta = \beta_0 + \cdots + \beta_p x_p$, so $\text{odds} = e^{\eta}$
2. Increase **one** feature x_j by 1 (rest fixed): only the β_j term of η changes, so $\frac{\text{odds}(x_j+1)}{\text{odds}(x_j)} = e^{\beta_j}$ (**odds ratio**)

- **Numerical variables**: $\exp(\beta_j)$ is the **multiplicative** change in the odds per unit increase of x_j (all else fixed)
- **Binary categorical variables**: $\exp(\beta_j)$ is the change in odds when switching from the reference category to the other one
- The effect on the **probability** is *not* constant: it depends on where we are on the sigmoid

Example: predicting cervical cancer

	Weight	Odds ratio	Std. error
Intercept	-2.91	0.05	0.32
Hormonal contracept. y/n	-0.12	0.89	0.30
Smokes y/n	0.26	1.30	0.37
Num. of pregnancies	0.04	1.04	0.10
Num. of diagnosed STDs	0.82	2.27	0.33
IUD y/n	0.62	1.86	0.40

- Each additional diagnosed STD multiplies the odds of cancer by **2.27** (+127%)
- Smokers have **1.30×** the odds of non-smokers (but std. error ≈ weight: not significant)

Step 1: $P = \frac{1}{1+e^{-\eta}} \Rightarrow 1 - P = \frac{e^{-\eta}}{1+e^{-\eta}} \Rightarrow \frac{P}{1-P} = \frac{1}{e^{-\eta}} = e^{\eta}$ Step 2: $\frac{\text{odds}(x_j+1)}{\text{odds}(x_j)} = \frac{e^{\eta'}}{e^{\eta}} = e^{\eta'-\eta} = e^{\beta_j}$, since $\eta' - \eta = \beta_j(x_j+1) - \beta_j x_j = \beta_j$

Transparent models > Decision trees

Decision trees and rule-based systems

(though in practice we never isolate the tree from the forest)



Transparent models

Transformers: Attention is explainable, right?



https://github.com/sharma-kshitij-ks/Transformers/blob/main/Vision_Transformer_Tutorial.ipynb



https://github.com/jessevig/bertviz?tab=readme-ov-file

Transparent models > Transformers

BERT: Delimiter-focused attention patterns. Serves as a kind of "no-op"; an attention head focuses on the `[SEP]` tokens when it can't find anything else in the input sentence to focus on.

https://towardsdatascience.com/deconstructing-bert-part-2-visualizing-the-inner-workings-of-attention-60a16d86b5c1

Transparent models > Transformers

Visualizing and Understanding Patch Interactions in Vision Transformer: for a query patch, take its attention map in every layer ($\mathcal{A}_1 \dots \mathcal{A}_{12}$). Unrelated patches get consistently low attention, so the **variance across layers** $\mathcal{U}$ (then across heads, U) highlights the patches it really interacts with. Right: patches that interact with nobody can be dropped

$$\mathcal{U} = \frac{1}{l}\sum_{i=1}^{l}(\mathcal{A}_i - \mathbb{E}_{\mathcal{A}})^2 \quad U = \frac{1}{k}\sum_{i=1}^{k}(\mathcal{U}_i - \mathbb{E}_U)^2$$



Ma, J., Bai, Y., Zhong, B., Zhang, W., Yao, T., & Mei, T. (2023). Visualizing and understanding patch interactions in vision transformer. IEEE Transactions on Neural Networks and Learning Systems.

Statistical and visualization methods > PDPs

Partial Dependence Plots (PDP) can be used to visualize the interaction between the target response and a set of input features.

- Shows the marginal effect one or two features have on the predicted outcome of a machine learning model. x_S are the (one or two) features we plot the partial dependence for, and X_C are all the other features used by the model $\hat{f}$: we fix x_S and average the predictions over the observed values of X_C
- It assumes that x_S is independent of X_C (otherwise the averaged points are unrealistic)

$$\hat{f}_S(x_S) = E_{X_C}\left[\hat{f}(x_S, X_C)\right] = \int \hat{f}(x_S, X_C) d\mathbb{P}(X_C) \xrightarrow{MC} \hat{f}_S(x_S) = \frac{1}{n}\sum_{i=1}^{n} \hat{f}(x_S, x_C^{(i)})$$

- *T. Hastie, et al., The Elements of Statistical Learning, Second Edition, Section 10.13.2, Springer, 2009.*
- *C. Molnar, Interpretable Machine Learning*
- *A. Goldstein, et al., "Peeking Inside the Black Box: Visualizing Statistical Learning With Plots of Individual Conditional Expectation" Journal of Computational and Graphical Statistics, 24(1): 44-65, Springer, 2015.*

Statistical and visualization methods > PDPs

Example 1: effect of temperature and humidity on the number of bike rentals with Histogram-based Gradient Boosting Regression Tree.



https://scikit-learn.org/stable/modules/partial_dependence.html

Statistical and visualization methods > PDPs

Example 2: PDPs of cancer probability based on age and years with hormonal contraceptives. Note that not many data points with large values were available, so the PD estimates are less reliable there.





C. Molnar, Interpretable Machine Learning

Statistical and visualization methods > ICE

Individual conditional expectation (ICE) is like PDP but instead visualizes the dependence of the prediction on a feature for each sample separately with one line per sample.

An ICE line is defined as a single $\hat{f}\left(x_S, x_C\left(i\right)\right)$ evaluated at x_S.

Example 1 $\rightarrow$



Permutation feature importance (PFI): how much does the error increase if we destroy the information in feature j by shuffling its column? $PFI_j = \frac{1}{K}\sum_{k=1}^{K} \mathcal{L}\left(y, \hat{f}(X_{\pi_k(j)})\right) - \mathcal{L}\left(y, \hat{f}(X)\right)$, where $X_{\pi_k(j)}$ is the dataset with column j randomly permuted (K repetitions)

Pros

- Model-agnostic, global, cheap: only needs predictions, no retraining
- Directly tied to *performance*: "how much worse is the model without the information in x_j?"
- Measures the **total** contribution of x_j: its own effect *plus* its interactions with other features, since shuffling x_j breaks all of them at once (e.g., if `temp` matters more on weekends, PFI counts both)

Cons / caveats (see example on next slide)

- Compute it on **held-out data**: on training data it measures what the model has *memorised*
- **Correlated features**: when `temp` is shuffled, the model still reads almost the same information from `atemp` ("feels like" temperature), so *both* look less important than they are: the importance is **split** between the copies. Shuffling also creates unrealistic points (35 °C that feels like 5 °C)
- **Built-in tree importances** (*gain* / *Gini* / *impurity*: total loss reduction of the splits on each feature) use the training data and favour features with many distinct values (more split points to overfit)

Breiman (2001), Random forests. · Fisher, Rudin & Dominici (2019), All models are wrong, but many are useful. JMLR

Statistical and visualization methods > Permutation feature importance

Example: random forest predicting daily bike rentals (test $R^2 = 0.89$). We added a column of pure `random_noise`; `temp` and `atemp` are 99% correlated



- **Left vs. middle**: the built-in importance gives `random_noise` more importance than `season` or `workingday` (the trees overfit it); PFI on test data correctly gives it ~0
- **Middle vs. right**: `temp` and `atemp` share the importance. Removing `atemp` and retraining, `temp` more than doubles its importance: neither of the two numbers in the middle was "the importance of temperature"

Statistical and visualization methods > PDP pitfall: correlated features

The PDP evaluates the model on **combinations of feature values that may never occur**. Same bike data, effect of `temp` (correlated with `atemp`): what does each method average at temp = 30 °C?



- **PDP**: move *every* day to temp = 30 °C and average the predictions. Many points are impossible (30 °C that feels like 8 °C): the PDP shows the model's **extrapolation**, which can be arbitrary (as for PFI, interventional SHAP)
- **M-plot** (marginal plot): average the predictions of the *real* days with temp ≈ 30 °C: $\int \hat{f}(x_S, X_C)\, d\mathbb{P}(X_C \mid X_S = x_S)$. Realistic, but those days also have high `atemp`, are in summer…: their effects get **mixed** into the curve
- **ALE**: take the real days with temp in [28, 32] °C, move them only to the **edges** of the interval, and average the **difference** in predictions: realistic *and* isolates `temp` (next slide)

Accumulated Local Effects (ALE): average *differences* in predictions within small intervals of x_S, using only the points in each interval; then accumulate (sum) these local effects:

$$\hat{f}_{S,ALE}(x_S) = \sum_{k=1}^{k_S(x)} \frac{1}{n_S(k)} \sum_{i:\, x_S^{(i)} \in N_S(k)} \left[\hat{f}(z_{k,S}, x_C^{(i)}) - \hat{f}(z_{k-1,S}, x_C^{(i)}) \right] - c$$

- $N_S(k) = (z_{k-1,S}, z_{k,S}]$: k-th (quantile) interval of x_S, with $n_S(k)$ points
- The constant c centres the curve: "effect relative to the average prediction"

	PDP	M-plot	ALE
Avoids extrapolation	✗	✓	✓
Isolates the effect of x_S	✓	✗	✓
Easy to explain	✓	✓	~

Apley & Zhu (2020). Visualizing the effects of predictor variables in black box supervised learning models. JRSS-B. · Implementations: `alibi`, `PyALE`, `effector`



- The **M-plot** triples the effect: it also contains `atemp`, season…
- Here **PDP ≈ ALE**: random forests extrapolate flat, so the impossible points do little harm; with other models they can differ a lot
- **Rug plot** (bottom ticks): one tick per data point. Few ticks (< 5 °C, > 33 °C): trust no curve

Attribution methods > Model Agnostic > LIME

Local interpretable model-agnostic explanations (LIME): Surrogate models are trained to approximate the predictions of the underlying black box model locally: $\xi(x) = \underset{g \in G}{\operatorname{argmin}} \mathcal{L}(f, g, \pi_x) + \Omega(g)$

- $L\left(f, g, \pi_x\right)$: fidelity function, measure of how unfaithful g is in approximating f in the locality defined by π_x
- G: Explanation family
- Ω: complexity measure
- g sparse linear models as explanations: K-Lasso
- Perform the search using perturbations





(a) Original Image (b) Explaining *Electric guitar* (c) Explaining *Acoustic guitar* (d) Explaining *Labrador*

Ribeiro, Marco Tulio, et al.. "Why should I trust you?: Explaining the predictions of any classifier." Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining. ACM (2016)

Attribution methods > Model Agnostic > LIME

LIME in regression

Example for two samples from the Bike Rental dataset where the explanatory model is Lasso with two features



Attribution methods > Model Agnostic > LIME

LIME in images

Lasso is trained to predict a class (e.g. *goose*) based on the presence of image patches.

Those patches whose coefficients remain are important for predicting *goose*

https://ema.drwhy.ai/LIME.html



Attribution methods > Model Agnostic > LIME

(One) elephant in the room: defining width for kernel π_x



https://christophm.github.io/interpretable-ml-book/lime.html

Attribution methods > M. Agnostic > Shapley values

Shapley values: Intuition with cat ban impact

Price prediction for an apartment: 50m², 2nd floor, nearby park and cat ban. The model predicts €300,000 and we want to explain how each feature contributes to this prediction



Attribution methods > M. Agnostic > Shapley values

Shapley values: Intuition with cat ban impact

Example of one iteration to estimate the contribution of *cat-ban* when added to the coalition of *nearby-park* and *area-50*.

The contribution of the *cat ban* factor was -€10,000 (calculated as €310,000 - €320,000)



Shapley values: Intuition with cat ban impact



The Shapley value is obtained by averaging the marginal contributions of all possible coalitions, although computation time grows exponentially as the number of features increases.

The example shows the 8 coalitions needed to calculate the exact Shapley value for the *cat-ban* feature

---

Weights ($p = 4$): $\frac{|S|!\,(p-|S|-1)!}{p!}$ = fraction of the $4! = 24$ orderings in which exactly S arrives before *cat ban*

- ∅: **1/4** · each single: **1/12** · each pair: **1/12** · all three: **1/4** (sum = 1)
- Each coalition *size* gets 1/4, shared by the coalitions of that size

Attribution methods > Model Agnostic > Shapley values

The Shapley value ϕ_j of a feature j is the (weighted) average of all the marginal contributions (*val*) to all possible coalitions:

$$\phi_j(val) = \sum_{S \subseteq \{1,\ldots,p\} \setminus \{j\}} \frac{|S|!(p-|S|-1)!}{p!}(val(S \cup \{j\}) - val(S))$$

- S is a subset of the features used in the model
- x is the vector of feature values (p = # of features) of the instance to be explained
- $\hat{f}$ is the model to be explained
- $val_x(S)$ is the marginal (over features not in S) contribution of features in S:

$$val_x(S) = \int \hat{f}(x_1, \ldots, x_p) d\mathbb{P}_{x \notin S} - E_X(\hat{f}(X)) \quad \text{with: } E_X[\hat{f}(X)] \approx \frac{1}{N} \sum_{i=1}^{N} \hat{f}(X^{(i)}),$$

Example: $val_x(S) = val_x(\{1,3\}) = \int_{\mathbb{R}} \int_{\mathbb{R}} \hat{f}(x_1, X_2, x_3, X_4) d\mathbb{P}_{X_2 X_4} - E_X(\hat{f}(X))$

Shapley, Lloyd S. "A value for n-person games." Contributions to the Theory of Games 2.28 (1953): 307-317
https://christophm.github.io/interpretable-ml-book/shapley.html

Attribution methods > M. Agnostic > Shapley values

Approximation with Monte-Carlo sampling:

$$\hat{\phi}_j = \frac{1}{M} \sum_{m=1}^{M} \left(\hat{f}(x_{+j}^m) - \hat{f}(x_{-j}^m) \right)$$

- $\hat{f}\left(x_{+j}^m\right)$ is the prediction for x, but with a random number of feature values replaced by feature values from a random data point z, except for the respective value of feature j.
- The x-vector x_{-j}^m is almost identical to x_{+j}^m, but the value x_j^m is also taken from the sampled z.
- Each of these M new instances is a kind of "Frankenstein's Monster" assembled from two instances.

Štrumbelj, Erik, and Igor Kononenko. "Explaining prediction models and individual predictions with feature contributions." Knowledge and information systems 41.3 (2014): 647-665

https://christophm.github.io/interpretable-ml-book/shapley.html

XAI methodologies Attribution methods > M. Agnostic > Shapley values



https://christophm.github.io/interpretable-ml-book/shapley.html

Attribution methods > Model Agnostic > SHAP

SHapley Additive exPlanations (SHAP): family of XAI methods using Shapley values.

It connects LIME with Shapley values, generalizing an explanation g in the family of **additive feature attribution methods** as:

$$g\left(z'\right) = \phi_0 + \sum_{j=1}^{M} \phi_j z'_j$$

- g is the explanation model, such that $g\left(z'\right) \approx f\left(h_x\left(z'\right)\right)$
- $z' \in \{0,1\}^M$ is the coalition vector or simplified input features
- $z = h_x\left(z'\right)$ is a mapping function from the simplified features to the original ones
- M is the maximum coalition size
- $\varphi_j \in R$ is the feature attribution for feature j, the Shapley value

Lundberg, Scott M., and Su-In Lee. "A unified approach to interpreting model predictions." Advances in Neural Information Processing Systems (2017)
https://christophm.github.io/interpretable-ml-book/shap.html

KernelSHAP: By selecting the components of the LIME equation, we can make it compute Shapley values:

$$\xi = \arg\min_{g \in G} L(f, g, \pi_{x'}) + \Omega(g)$$

with:

$$\Omega(g) = 0,$$

$$\pi_{x'}(z') = \frac{(M-1)}{(\binom{M}{|z'|})|z'|(M-|z'|)},$$

$$L(f, g, \pi_{x'}) = \sum_{z' \in Z} [f(h_x^{-1}(z')) - g(z')]^2 \pi_{x'}(z')$$

where $|z'|$ is the number of non-zero elements in z'.

Jointly estimating all SHAP values using regression provides better sample efficiency than the direct use of classical Shapley equations.

Lundberg, Scott M., and Su-In Lee. "A unified approach to interpreting model predictions." Advances in Neural Information Processing Systems (2017).
https://christophm.github.io/interpretable-ml-book/shap.html

XAI methodologies Attribution methods > M. Agnostic > KernelSHAP

KernelSHAP Algorithm:

> 1. Sample coalitions $z'_k \in \{0,1\}^M, k \in 1,\ldots,K$ (1 = feature present in coalition, 0 = feature absent).
> 2. Get prediction for each z'_k by first converting z'_k to the original feature space and then applying model $\hat{f}\left(h_x\left(z'_k\right)\right)$
> 3. Compute the weight for each z'_k with the SHAP kernel.
> 4. Fit weighted linear model.
> 5. Return Shapley values φ_k, the coefficients from the linear model.

Lundberg, Scott M., and Su-In Lee. "A unified approach to interpreting model predictions." Advances in Neural Information Processing Systems (2017)

https://christophm.github.io/interpretable-ml-book/shap.html

Attribution methods > M. Agnostic > KernelSHAP

Examples using SHAP Python package: Instance attribution: cervical cancer probabilities of two individuals. The baseline – the average predicted probability – is 0.066.



https://christophm.github.io/interpretable-ml-book/shap.html

Attribution methods > M. Agnostic > KernelSHAP

Examples using SHAP Python package: Global attribution: cervical cancer: $I_j = \frac{1}{n}\sum_{i=1}^{n}|\phi_j^{(i)}|$



https://christophm.github.io/interpretable-ml-book/shap.html

Attribution methods > M. Agnostic > KernelSHAP

Examples using SHAP Python package: SHAP Summary plot: cervical cancer



https://christophm.github.io/interpretable-ml-book/shap.html

Attribution methods > M. Agnostic > KernelSHAP

Examples using SHAP Python package: SHAP Dependence plots: cervical cancer: $\{(x_j^i, \phi_j^{(i)})\}_{i=1}^n$



https://christophm.github.io/interpretable-ml-book/shap.html

Attribution methods > M. Agnostic > SHAP estimators

KernelSHAP is model-agnostic but **slow** (many model evaluations per explained instance). The `shap` package offers faster estimators that exploit the model structure:

Estimator	Models	Idea	Cost
KernelSHAP	Any	Weighted regression on sampled coalitions	Many model evaluations
Permutation	Any	Monte-Carlo over feature orderings	Many model evaluations
TreeSHAP	Tree ensembles	**Exact** values, recursing through tree paths	$O(TLD^2)$: ms
LinearSHAP	Linear models	$\phi_j = \beta_j(x_j - E[x_j])$	Instant
DeepSHAP	Neural networks	DeepLIFT rules + background samples	Backward passes
GradientSHAP	Differentiable	IG averaged over random baselines	Like IG
PartitionSHAP	Images, text	Owen values over a hierarchy of feature groups	Many features OK

TreeSHAP also gives **SHAP interaction values** ϕ_{ij}: main effects + pairwise interactions

Lundberg, S. M., et al. (2020). From local explanations to global understanding with explainable AI for trees. Nature Machine Intelligence, 2(1), 56-67. · https://shap.readthedocs.io

Attribution methods > M. Agnostic > SHAP: interventional vs. observational

How do we "remove" the features that are not in the coalition S? There are two choices for $val_x(S)$:

Interventional (marginal) SHAP

$$val_x(S) = E_{X_{\bar{S}}}\left[\hat{f}(x_S, X_{\bar{S}})\right] - E_X\left[\hat{f}(X)\right]$$

- Replace absent features by values from a background dataset, **ignoring** correlations (KernelSHAP, TreeSHAP with a background dataset)
- **"True to the model"**: a feature not used by the model gets exactly $\phi_j = 0$
- Can evaluate the model on unrealistic points (same issue as PDP)

Observational (conditional) SHAP

$$val_x(S) = E\left[\hat{f}(X) \mid X_S = x_S\right] - E_X\left[\hat{f}(X)\right]$$

- Absent features are drawn conditionally on the present ones
- **"True to the data"**: realistic points, but a feature that the model **does not use** can receive credit just because it is correlated with one that it does
- Hard to estimate (needs a model of $P(X_{\bar{S}} \mid X_S)$)

Neither is "the right one": it depends on the question. *Auditing the model* → interventional. *Understanding the data-generating process* → observational (but then, why not fit a causal model?)

Chen, H., Janizek, J. D., Lundberg, S., & Lee, S. I. (2020). True to the model or true to the data? arXiv:2006.16234. · Janzing, D., Minorics, L., & Blöbaum, P. (2020). Feature relevance quantification in explainable AI: A causal problem. AISTATS. · Kumar, I. E., et al. (2020). Problems with Shapley-value-based explanations as feature importance measures. ICML.

Other methods > Counterfactuals

Counterfactuals: A counterfactual explanation describes the smallest change we would need to make to the features to obtain a different desired outcome. For example:

- If your annual income were €2,000 higher, your loan would have been approved
- If you had scored 0.5 points higher on your university entrance exam, we would have admitted you

Other methods > Counterfactuals

Counterfactual method by Wachter et al.

Minimize loss $L(x, x', y', \lambda) = \lambda \cdot (\hat{f}(x') - y')^2 + d(x, x')$ where the first term measures distance between the prediction for the counterfactual x' and the desired counterfactual outcome y', and the second term measures the distance between the instance to be explained x and the counterfactual x'. Distance d is the weighted Manhattan distance:

$$d(x, x') = \sum_{j=1}^{p} \frac{|x_j - x'_j|}{MAD_j} \quad MAD_j = \text{median}_{i \in \{1,..,n\}}(|x_{i,j} - \text{median}_{l \in \{1,..,n\}}(x_{l,j})|)$$

The parameter λ balances the distance in prediction (first term) against the distance in feature values (second term). We initialize x' to noise and optimize it using e.g. ADAM

$$\arg\min_{x'} \max_{\lambda} L(x, x', y', \lambda).$$

https://christophm.github.io/interpretable-ml-book/counterfactual.html

Wachter, Sandra, Brent Mittelstadt, and Chris Russell. "Counterfactual explanations without opening the black box: Automated decisions and the GDPR." (2017)

Other methods > Countefactuals

Counterfactual explanations: method by Dandl et al.: minimize a four-objective loss using Nondominated Sorting Genetic Algorithm:

$$L(x, x', y', X^{obs}) = (o_1(\hat{f}(x'), y'), o_2(x, x'), o_3(x, x'), o_4(x', X^{obs}))$$

where:

- o_1: Manhattan distance (L_1) between $\hat{f}(x')$ and y'
- o_2: Gower distance between x' and x (p = # of features)
- o_3: Number of changed features
- o_4: Average Gower distance (over features) between x' and the nearest observed data point.

$$o_2(x, x') = \frac{1}{p} \sum_{j=1}^{p} \delta_G(x_j, x'_j)$$

$$\delta_G(x_j, x'_j) = \begin{cases} \frac{1}{\hat{R}_j} |x_j - x'_j| & \text{if } x_j \text{ numerical} \\ \mathbb{I}_{x_j \neq x'_j} & \text{if } x_j \text{ categorical} \end{cases}$$

https://christophm.github.io/interpretable-ml-book/counterfactual.html

Dandl, Susanne, Christoph Molnar, Martin Binder, Bernd Bischl. "Multi-objective counterfactual explanations". In: Bäck T. et al. (eds) Parallel Problem Solving from Nature – PPSN XVI. PPSN 2020. Lecture Notes in Computer Science, vol 12269. Springer, Cham (2020)

Counterfactual explanations: Method by Dandl et al

Credit score (%) example: top table is x and bottom table is x'

age	sex	job	housing	savings	amount	duration	purpose
58	f	unskilled	free	little	6143	48	car

Counterfactuals x' (only the changes w.r.t. x; empty = unchanged):

age	sex	job	amount	duration	o_2	o_3	o_4	$\hat{f}(x')$
		skilled		-20	0.108	2	0.036	0.501
		skilled		-24	0.114	2	0.029	0.525
		skilled		-22	0.111	2	0.033	0.513
-6		skilled		-24	0.126	3	0.018	0.505
-3		skilled		-24	0.120	3	0.024	0.515
-1		skilled		-24	0.116	3	0.027	0.522

https://christophm.github.io/interpretable-ml-book/counterfactual.html

Dandl, Susanne, Christoph Molnar, Martin Binder, Bernd Bischl. "Multi-objective counterfactual explanations". In: Bäck T. et al. (eds) Parallel Problem Solving from Nature – PPSN XVI. PPSN 2020. Lecture Notes in Computer Science, vol 12269. Springer, Cham (2020)

Other methods > Counterfactuals in practice: DiCE

DiCE (Diverse Counterfactual Explanations) generates a *set* of k counterfactuals $\{c_1, \ldots, c_k\}$ by jointly optimising:

$$\arg\min_{c_1,\ldots,c_k} \frac{1}{k}\sum_{i=1}^{k} \text{yloss}(\hat{f}(c_i), y') + \frac{\lambda_1}{k}\sum_{i=1}^{k} \text{dist}(c_i, x) - \lambda_2 \,\text{dpp_diversity}(c_1, \ldots, c_k)$$

Desiderata of a good counterfactual

- **Validity**: it actually flips the prediction
- **Proximity**: close to x
- **Sparsity**: few features changed
- **Diversity**: several *different* options for the user
- **Plausibility**: lies in a high-density region of the data
- **Actionability**: only changes what the user *can* change (not age, not country of birth)

In practice (`dice-ml` package)

- Model-agnostic (random / genetic search) or gradient-based (differentiable models)
- `features_to_vary`: restrict to actionable features
- `permitted_range`: e.g., income can only go up
- Works for classification and regression (`desired_range`)

Rashomon effect: many different counterfactuals are equally valid: which one should we show?

Mothilal, R. K., Sharma, A., & Tan, C. (2020). Explaining machine learning classifiers through diverse counterfactual explanations. FAccT. · https://github.com/interpretml/DiCE

Hands-on 1: XAI for tabular models

Notebook: `notebooks/01_tabular_xai.ipynb`

github.com/OscarPellicer/extra-attributions

Run it on **Google Colab** (badge at the top of the notebook) or **locally**:

```
git clone https://github.com/OscarPellicer/extra-attributions
cd extra-attributions
pip install -r requirements.txt
pip install -e .
```

What we will do (XGBoost on California housing)

- Glass-box baseline: linear model coefficients
- Permutation importance vs. model importance
- PDP and ICE curves (1D and 2D)
- LIME vs. SHAP on the same instance
- TreeSHAP vs. KernelSHAP; local and global SHAP plots
- Counterfactuals with DiCE

Explainability in AI Systems

Session 2: Deep learning and beyond

Attributions for neural networks · Evaluation · Concepts and mechanistic interpretability

Recap of Session 1: Classical XAI

- **Local vs. global**; **transparent** vs. **post-hoc**; **model-agnostic** vs. **model-specific** explanations
- **Transparent models**: weights are only interpretable with care (scale, correlation); attention is not (necessarily) explanation
- **Global effects**: PDP, ICE, ALE, permutation importance: beware of **correlated features** and extrapolation
- **LIME**: local surrogate, sensitive to the kernel width
- **Shapley values / SHAP**: the axiomatic way of sharing the prediction among features; KernelSHAP, TreeSHAP...; *interventional vs. observational*
- **Counterfactuals**: "what should change to obtain a different outcome?"; validity, sparsity, plausibility, actionability

Today: what if the model is a deep network with 10^5-10^{11} parameters and the input is an image or a text? Can we trust the explanations? Can we look *inside* the model?

Attribution methods > NNs > Saliency / GBP / IxG

Saliency / Gradient: gradients with respect to inputs

- Idea: for a liner model $S_c(I) = v_c^T I + b_c$, where $S_c(I)$ is the score of the model for class c given input image I, v_c would describe the importance of the inputs I
- Then, we approximate a complex model $S_c(I)$ with a linear function in the neighborhood of I with a first order Taylor expansion: $S_c(I) = v_c^T I + b_c$, where:

$$w = \frac{\partial S_c}{\partial I}\Big|_I$$

Guided Backprop: Same as Saliency, but gradients of ReLU functions are overridden so that only non-negative gradients are backpropagated

Input x Gradient: Same as Saliency, but gradient is multiplied by input values, to get the total contribution of a given feature

Simonyan, Karen, Andrea Vedaldi, and Andrew Zisserman. "Deep inside convolutional networks: Visualising image classification models and saliency maps." arXiv preprint arXiv:1312.6034 (2013)

https://christophm.github.io/interpretable-ml-book/pixel-attribution.html

Attribution methods > NNs > Saliency / GBP

Simonyan, K. (2013). Deep inside convolutional networks: Visualising image classification models and saliency maps. arXiv preprint arXiv:1312.6034.

https://christophm.github.io/interpretable-ml-book/pixel-attribution.html

Attribution methods > NNs > Saliency / GBP



Springenberg, J. T., Dosovitskiy, A., Brox, T., & Riedmiller, M. (2014). Striving for simplicity: The all convolutional net. arXiv preprint arXiv:1412.6806

https://christophm.github.io/interpretable-ml-book/pixel-attribution.html

Attribution methods > NNs > Saliency / GBP



https://github.com/OscarPellicer/extra-attributions

Attribution methods > NNs > (guided) Grad-CAM

Grad-CAM: Specific for classification CNNs, the gradient is backpropagated only to the last convolutional layer to produce a coarse localization map

Guided Grad-CAM: Multiply heatmap with guided backpropagation



Selvaraju, R. R., Cogswell, M., Das, A., Vedantam, R., Parikh, D., & Batra, D. (2020). Grad-CAM: visual explanations from deep networks via gradient-based localization. International journal of computer vision, 128, 336-359.

https://christophm.github.io/interpretable-ml-book/pixel-attribution.html

Attribution methods > NNs > (guided) Grad-CAM

https://github.com/OscarPellicer/extra-attributions

Attribution methods > NNs > IG

Integrated Gradients (IG): similar to Input x Gradient, but the gradient is computed as an integral of several gradients, which we approximate with a sum:

$$\text{IntegratedGradients}_i(x) ::= (x_i - x'_i) \times \int_{\alpha=0}^{1} \frac{\partial F(x' + \alpha \times (x - x'))}{\partial x_i} d\alpha$$

$$\text{IntegratedGrads}_i^{\text{approx}}(x) ::= (x_i - x'_i) \times \sum_{k=1}^{m} \frac{\partial F(\overbrace{x' + \frac{k}{m} \times (x - x')}^{\text{interpolate m images at k intervals}})}{\partial x_i} \times \frac{1}{m}$$

where:

- i = feature (individual pixel)
- x = input (image tensor)
- x' = baseline (image tensor)
- k = scaled feature perturbation constant
- m = number of steps in the Riemann sum approximation
- $(x_i - x'_i)$ = a term for the difference from the baseline.

https://www.tensorflow.org/tutorials/interpretability/integrated_gradients

Attribution methods > NNs > IG













https://www.tensorflow.org/tutorials/interpretability/integrated_gradients

Attribution methods > NNs > IG



https://github.com/OscarPellicer/extra-attributions

Attribution methods > NNs > SmoothGRAD / NT

SmoothGrad / Noise Tunnel: the derivative fluctuates greatly at small scales. Neural networks have no incentive during training to keep the gradients smooth, their goal is to classify images correctly. Averaging over multiple noisy versions of the input “smooths out” these fluctuations



Smilkov, D., Thorat, N., Kim, B., Viégas, F., & Wattenberg, M. (2017). Smoothgrad: removing noise by adding noise. arXiv preprint arXiv:1706.03825.

Attribution methods > NNs > SmoothGRAD / NT

Explaining class **bald eagle** (top-1, 76%)



https://github.com/OscarPellicer/extra-attributions

Attribution methods > NNs > SmoothGRAD / NT

Explaining class **hen** (top-1 is *cock*, 63%; hen 22%)



https://github.com/OscarPellicer/extra-attributions

Attribution methods > NNs > LRP

Layer-wise relevance propagation (LRP): works by starting with the network's final output (the "relevance" score) and propagating it backward, layer by layer, until it reaches the input pixels.



- **Relevance (R)**: This is the quantity being passed backward. The relevance of the final output neuron is set to its activation value (e.g., the probability score for the predicted class).
- **Conservation Principle**: LRP is designed so that the total amount of relevance is conserved at each layer. This means $\sum_j R_j = \sum_k R_k$.
- **The goal**: The final result, $R = (R_i)$ on the far left, is a "heatmap" where each input pixel i has a relevance score R_i. High R_i values indicate pixels that were important.
- The decomposition is defined by rules that are chosen for each layer, involving its weights and activations. Not available for all architectural choices!

Samek, W., Montavon, G., Lapuschkin, S., Anders, C. J., & Müller, K. R. (2021). Explaining deep neural networks and beyond: A review of methods and applications. Proceedings of the IEEE, 109(3), 247-278.
Bach, S., Binder, A., Montavon, G., Klauschen, F., Müller, K. R., & Samek, W. (2015). On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. PloS one, 10(7), e0130140.

Attribution methods > NNs > LRP



$\varepsilon = 0.25 \cdot std(denom.)$

$\gamma = 0.25$

Class: castle

Samek, W., Montavon, G., Vedaldi, A., Hansen, L. K., & Müller, K. R. (Eds.). (2019). Explainable AI: interpreting, explaining and visualizing deep learning (Vol. 11700). Springer Nature.

Attribution methods > NNs > LRP



Samek, W., Montavon, G., Lapuschkin, S., Anders, C. J., & Müller, K. R. (2021). Explaining deep neural networks and beyond: A review of methods and applications. Proceedings of the IEEE, 109(3), 247-278.

Attribution methods > NNs > LRP

Top: explaining class **hen**

Bottom: explaining class **bald eagle**



https://github.com/OscarPellicer/extra-attributions

Attribution methods > NNs > Occlusion

Occlusion: repeatedly test the effect on the neural network output of occluding patches or individual features in the input image

TiledOcclusion: combine the power of bigger occlusion patches while obtaining a high-resolution smoother occlusion map, by adding occlusion results from several slightly shifted versions of the same input image.

M. D. Zeiler and R. Fergus, "Visualizing and understanding convolutional networks," in Proc. Eur. Conf. Comput. Vis.-ECCV, 2014

https://github.com/OscarPellicer/extra-attributions

Attribution methods > NNs > Occlusion



https://github.com/OscarPellicer/extra-attributions

Attribution methods > From local to global

How do we go from individual predictions to global ones?
In general, the total class evidence g can be computed as the sum of all individual evidences f

$$g(x_1, \ldots, x_N) = \sum_{n=1}^{N} f(x_n).$$

Relevance pooling: Choose a set of features of interest I, and data points of interest G and compute the overall contribution:

$$g(x_1, \ldots, x_N) \approx \sum_{n=1}^{N} \sum_{i=1}^{d} R_{i,n} \approx \underbrace{\sum_{G} \sum_{I} \sum_{n \in G} \sum_{i \in I} R_{i,n}}_{R_{I,G}}$$

Which still satisfies the conservation property for $R_n = f(x_n)$ with f being IG or LRP

Samek, W., Montavon, G., Lapuschkin, S., Anders, C. J., & Müller, K. R. (2021). Explaining deep neural networks and beyond: A review of methods and applications. Proceedings of the IEEE, 109(3), 247-278.

Attribution methods > From local to global



Spectral Relevance Analysis (SpRAy)

Algorithm: SpRAy

for $n = 1$ **to** N **do**

$$R^{(n)} \leftarrow \text{explain}(x^{(n)}, f)$$

$$\bar{R}^{(n)} \leftarrow \text{normalize}(R^{(n)})$$

end for

$$\text{clustering}(\{\bar{R}^{(1)}, \ldots, \bar{R}^{(N)}\})$$

Samek, W., Montavon, G., Lapuschkin, S., Anders, C. J., & Müller, K. R. (2021). Explaining deep neural networks and beyond: A review of methods and applications. Proceedings of the IEEE, 109(3), 247-278.

Lapuschkin, S., Wäldchen, S., Binder, A. et al. Unmasking Clever Hans predictors and assessing what machines really learn. Nat Commun 10, 1096 (2019). https://doi.org/10.1038/s41467-019-08987-4

Attribution methods > From local to global

Example: Identifying drivers of exteme meteorological events

- **Problem**: High dimensional input AND output
- **Solutions**, based on the research question:
  - Aggregation over inputs AND outputs
  - Select some input features I AND some output features O
  - Select groups G of inputs: event / non-event



Pellicer-Valero, O. J., Fernández-Torres, M. Á., Ji, C., Mahecha, M. D., & Camps-Valls, G. (2024). Explainable Earth Surface Forecasting under Extreme Events. arXiv preprint arXiv:2410.01770.

XAI methodologies Attribution methods > Evaluation

Evaluating explanations is made difficult by the fact that it is generally impossible to collect “ground-truth” explanations. We can define, however, some desiderata:

Faithfulness (↑) quantifies to what extent explanations follow the predictive behavior of the model, asserting that more important features affect model decisions more strongly

- **Faithfulness Correlation** (Bhatt et al., 2020): iteratively replaces a random subset of given attributions with a baseline value and then measuring the correlation between the sum of this attribution subset and the difference in function output
- **Pixel Flipping** (Bach et al., 2015): captures the impact of perturbing pixels in descending order according to the attributed value on the classification score
- **ROAD** (Rong, Leemann, et al., 2022): measures the accuracy of the model on the test set in an iterative process of removing k most important pixels, at each step k most relevant pixels (MoRF order) are replaced with noisy linear imputations

https://github.com/understandable-machine-intelligence-lab/Quantus

Hedström, A., Weber, L., Krakowczyk, et al. (2023). Quantus: An explainable ai toolkit for responsible evaluation of neural network explanations and beyond. Journal of Machine Learning Research, 24(34), 1-11.

Attribution methods > Evaluation

Example: Faithfulness evaluation with pixel flipping



Algorithm: Pixel-Flipping

$\text{pfcurve} = [\,]$

for p **in** $\text{argsort}(-R)$ **do**

  $x \leftarrow x - \{x_p\}$ (remove pixel p from the image)

  $\text{pfcurve.append}(f(x))$

end for

return pfcurve

At each step of pixel-flipping, removed pixels are imputed using a simple inpainting algorithm, which avoids introducing visual artifacts in the image.

Samek, W., Montavon, G., Lapuschkin, S., Anders, C. J., & Müller, K. R. (2021). Explaining deep neural networks and beyond: A review of methods and applications. Proceedings of the IEEE, 109(3), 247-278.

Attribution methods > Evaluation

Robustness (sensitiviy ↓) measures to what extent explanations are stable when subject to slight perturbations in the input, assuming that the model output approximately stayed the same

- **Local Lipschitz Estimate** (Alvarez-Melis et al., 2018): tests the consistency in the explanation between adjacent examples
- **Max-Sensitivity** (Yeh et al., 2019): measures the maximum sensitivity of an explanation using a Monte Carlo sampling-based approximation
- **Avg-Sensitivity** (Yeh et al., 2019): measures the average sensitivity of an explanation using a Monte Carlo sampling-based approximation
- **Continuity** (Montavon et al., 2018): captures the strongest variation in explanation of an input and its perturbed version

https://github.com/understandable-machine-intelligence-lab/Quantus

Hedström, A., Weber, L., Krakowczyk, et al. (2023). Quantus: An explainable ai toolkit for responsible evaluation of neural network explanations and beyond. Journal of Machine Learning Research, 24(34), 1-11.

Attribution methods > Evaluation

Local Lipschitz Estimate:

```
def local_lipschitz(model, input, explanation_fn, epsilon):
    # Generate perturbed input within epsilon neighborhood
    perturbed_input = input + random_noise(epsilon)
    # Get explanations for both original and perturbed
    explanation1 = explanation_fn(model, input)
    explanation2 = explanation_fn(model, perturbed_input)
    # Compute ratio of explanation difference to input difference
    lipschitz = norm(explanation1 - explanation2) / \
                                norm(input - perturbed_input)
    return lipschitz
```

Avg / Max-Sensitivity:

```
def sensitivity(model, input, explanation_fn, n_samples=100):
    sensitivities = []
    for _ in range(n_samples):
        # Generate random perturbation
        perturbed = input + small_random_noise()
        # Get explanations
        orig_exp = explanation_fn(model, input)
        pert_exp = explanation_fn(model, perturbed)
        # Compute sensitivity
        sensitivity = norm(orig_exp - pert_exp)
        sensitivities.append(sensitivity)
    return max(sensitivities), mean(sensitivities)
```

Continuity:

```
def continuity(model, input, explanation_fn, n_steps=10):
    max_diff = 0

    # Generate sequence of increasingly perturbed inputs
    for t in range(n_steps):
        alpha = t/n_steps
        perturbed = input + alpha * noise

        exp1 = explanation_fn(model, input)
        exp2 = explanation_fn(model, perturbed)

        # Track maximum difference found
        diff = norm(exp2 - exp1)
        max_diff = max(max_diff, diff)

    return max_diff
```

Attribution methods > Evaluation

Localisation (↑) tests if the explainable evidence is centered around a region of interest, which may be defined around an object by a bounding box, a segmentation mask or a cell within a grid

- **Pointing Game** (Zhang et al., 2018): checks whether the attribution with the highest score is located within the targeted object
- **Attribution Localization** (Kohlbrenner et al., 2020): measures the ratio of positive attributions within the targeted object towards the total positive attributions
- **Top-K Intersection** (Theiner et al., 2021): computes the intersection between a ground truth mask and the binarized explanation at the top k feature locations

https://github.com/understandable-machine-intelligence-lab/Quantus

Hedström, A., Weber, L., Krakowczyk, et al. (2023). Quantus: An explainable ai toolkit for responsible evaluation of neural network explanations and beyond. Journal of Machine Learning Research, 24(34), 1-11.

Attribution methods > Evaluation

Complexity (↓) captures to what extent explanations are concise, i.e., that few features are used to explain a model prediction

- **Complexity** (Bhatt et al., 2020): computes the entropy of the fractional contribution of all features to the total magnitude of the attribution individually
- **Effective Complexity** (Nguyen at el., 2020): measures how many attributions in absolute values are exceeding a certain threshold

Entropy-based Complexity:

```
def complexity_entropy(attributions):

    # Normalize attributions to get fractional contrib.
    total_magnitude = np.sum(np.abs(attributions))
    fractions = np.abs(attributions) / total_magnitude

    # Compute entropy
    entropy = -np.sum(fractions * np.log(
                                    fractions + 1e-10))
    return entropy
```

Effective Complexity:

```
def effective_complexity(attributions, threshold=0.1):

    # Count attributions above threshold
    significant_attrs = np.sum(
                    np.abs(attributions) > threshold)
    return significant_attrs
```

Attribution methods > Evaluation

Randomisation (↑) tests to what extent explanations deteriorate as the data labels or the model, e.g., its parameters are increasingly randomized

- **MPRT (Model Parameter Randomisation Test)** (Adebayo et. al., 2018): randomises the parameters of single model layers in a cascading or independent way and measures the distance of the respective explanation to the original explanation
- **Random Logit Test** (Sixt et al., 2020): computes for the distance between the original explanation and the explanation for a random other class

https://github.com/understandable-machine-intelligence-lab/Quantus

Hedström, A., Weber, L., Krakowczyk, et al. (2023). Quantus: An explainable ai toolkit for responsible evaluation of neural network explanations and beyond. Journal of Machine Learning Research, 24(34), 1-11.

Model Parameter Randomisation Test (MPRT):

```
def mprt(model, input, explanation_fn):
    # Get original explanation
    original_exp = explanation_fn(model, input)

    # For each layer
    distances = []
    for layer in model.layers:
        # Create copy with randomized weights
        randomized_model = randomize_layer_weights(model, layer)
        random_exp = explanation_fn(randomized_model, input)

        # Compute distance
        distance = norm(original_exp - random_exp)
        distances.append(distance)
    return distances
```

Random Logit Test:

```
def random_logit_test(model, input, explanation_fn, true_class):
    # Get original explanation
    original_exp = explanation_fn(model, input, class_idx=true_class)

    # Get explanation for random other class
    all_classes = range(model.num_classes)
    random_class = random.choice([c for c in all_classes if c != true_class])
    random_exp = explanation_fn(model, input, class_idx=random_class)
    return norm(original_exp - random_exp)
```

Attribution methods > Evaluation > Sanity checks

Sanity checks for saliency maps (Adebayo et al., 2018): an explanation method meant to explain *the model* must depend on (1) the **model parameters** and (2) the **relationship between data and labels** that the model learned

Model parameter randomisation test

- Randomise weights layer by layer, from the output towards the input (*cascading*); recompute the explanation and compare (Spearman rank correlation, SSIM…)
- If the map does not change, the method is **insensitive to the model**: it cannot help us debug it

Data randomisation test

- Train on **randomly permuted labels** (the network can only memorise): explanations should change

Results (Inception v3, ImageNet)

- **Gradients** and **Grad-CAM** pass: maps degrade as more layers are randomised
- **Guided Backprop** and **Guided Grad-CAM** fail: the maps stay almost identical even for a **fully random network**. They act like edge detectors
- Input × Gradient and IG are partially dominated by the input image itself

Lessons

- Visual appeal is not evidence of faithfulness
- Always include a randomisation baseline (Hands-on 2)
- The test itself has been refined (smooth / efficient MPRT)

Adebayo, J., Gilmer, J., Muelly, M., Goodfellow, I., Hardt, M., & Kim, B. (2018). Sanity checks for saliency maps. NeurIPS. · Hedström, A., et al. (2023). Sanity checks revisited: An exploration to repair the model parameter randomisation test. XAI in Action workshop @ NeurIPS.

Attribution methods > Evaluation

Axiomatic (↑) measures if explanations fulfill certain axiomatic properties

- **Completeness** (Sundararajan et al., 2017): evaluates whether the sum of attributions is equal to the difference between the function values at the input x and baseline x' (and referred to as Summation to Delta (Shrikumar et al., 2017), Sensitivity-n (slight variation, Ancona et al., 2018) and Conservation (Montavon et al., 2018))

https://github.com/understandable-machine-intelligence-lab/Quantus

Hedström, A., Weber, L., Krakowczyk, et al. (2023). Quantus: An explainable ai toolkit for responsible evaluation of neural network explanations and beyond. Journal of Machine Learning Research, 24(34), 1-11.

Completeness:

```python
def completeness_test(model, input, baseline, explanation_fn):
    # Get attributions
    attributions = explanation_fn(model, input, baseline)

    # Sum of attributions
    attr_sum = np.sum(attributions)

    # Model output difference
    output_diff = model(input) - model(baseline)

    # Check if they're equal
    return np.isclose(attr_sum, output_diff)
```

Attribution methods > Evaluation > Quantus

Quantus

a) Simple qualitative comparison of XAI methods
b) Holistic quantification on several evaluation criteria
c) Sensitivity analysis of how a single parameter, e.g., pixel replacement strategy of a faithfulness test influences the ranking of explanation methods



Hedström, A., Weber, L., Krakowczyk, et al. (2023). Quantus: An explainable ai toolkit for responsible evaluation of neural network explanations and beyond. Journal of Machine Learning Research, 24(34), 1-11.

Attribution methods > Meta-evaluation

Meta-quantus : analyzes two characteristics of a quality estimator: its resilience to noise and reactivity to randomness



Hedström, A., Bommer, P., Wickstrøm, K. K., Samek, W., Lapuschkin, S., & Höhne, M. M. C. (2023). The meta-evaluation problem in explainable AI: identifying reliable estimators with MetaQuantus. arXiv preprint arXiv:2302.07265.

Attribution methods > Caveats

- **Local attribution:**
  - There are too many methods with too many parameters to tweak, meta-methods (like noise tunnel), etc.
  - Attribution maps are difficult to interpret, hence mostly defeating their purpose
  - Typical XAI paper example images: single element in foreground vs blurred background
  - Not really meant for highly dimensional inputs / outputs
- **Global attribution:**
  - Too many ways to combine attributions: Use mean or clustering? How to choose I and G? Take absolute values? When to take them (e.g. before or after averaging)?
  - Agregation techniques end up removing too much information
- **Attribution: general assumptions:**
  - That the model can predict accurately (can be tested)
  - That the attributions can accurately explain the model's decisions (less testable)
  - That the decisions by the model are actually understandable by us (untestable)
    - Confirmation bias : we only understand from the model what we already expected to find
- **Attribution evaluation and meta-evaluation**: as if things were not bad enough

Hands-on 2: attributions for deep learning

Notebook: `notebooks/02_dl_attributions.ipynb`

github.com/OscarPellicer/extra-attributions

Colab (GPU runtime recommended) or local (CUDA / Apple MPS / CPU are all supported)

Libraries

- Captum: attribution methods for PyTorch
- Quantus: evaluation of explanations
- `extra_attributions`: TiledOcclusion, FusionGrad, ContrastiveAttribution

What we will do (ImageNet CNN)

- Saliency, Input × Gradient, Integrated Gradients, SmoothGrad, Grad-CAM, Occlusion, LRP
- **Sanity check**: randomise the network layer by layer and watch the maps
- **Quantus**: faithfulness, robustness and randomisation metrics
- **Contrastive explanations**: hen vs. rooster
- Optional: the `extra_attributions` methods

Exercises: only **change parameters** (baseline, target class, noise, window size, layer…) and interpret the results

Other methods / advanced and emerging

Testing with Concept Activation Vectors (TCAV):

- **Concept Activation Vectors (CAVs)** provide an interpretation of a neural net's internal state in terms of human-friendly concepts.
- Then, **Testing with CAVs(TCAV)** uses directional derivatives to quantify the degree to which a user-defined concept is important to a classification result



Kim, B., Wattenberg, M., Gilmer, J., Cai, C., et al. (2018, July). Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In International conference on machine learning (pp. 2668-2677). PMLR.

Other methods / advanced and emerging

- Concepts and Concept Activation Vectors (CAVs):
  - A concept is a human-understandable abstraction, such as "stripes" or "gender“
  - Examples (e.g., images with stripes) and random samples (e.g. other images) are fed to the model and activations from an intermediate layer of the model are collected
  - These activations are used to train a linear classifier, such as logistic regression, to distinguish the concept from random data.
  - The weight vector of this classifier becomes the Concept Activation Vector (CAV), representing the concept in the model's feature space.
- Sensitivity Testing with CAVs:
  - Once CAVs are created, TCAV evaluates how sensitive the model's output is to the concept by computing the directional derivative of the model's prediction score with respect to the CAV. Intuitively, this measures how much a small change in the direction of the concept (as represented by the CAV) affects the model's prediction.
- TCAV Scores:
  - TCAV calculates a score that indicates the proportion of inputs for which the concept positively influences the model’s prediction. For example, a TCAV score of 0.8 for the concept "stripes" in a zebra classifier means that 80% of the inputs are influenced by the "stripes" concept in the direction of increasing the zebra prediction.

Kim, B., Wattenberg, M., Gilmer, J., Cai, C., et al. (2018, July). Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In International conference on machine learning (pp. 2668-2677). PMLR.

Other methods / advanced and emerging



Kim, B., Wattenberg, M., Gilmer, J., Cai, C., et al. (2018, July). Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In International conference on machine learning (pp. 2668-2677). PMLR.

Other methods / advanced and emerging

Concept bottleneck models (CBM): first predict an intermediate set of human-specified concepts c, then use c to predict the final output y.



Koh, P. W., Nguyen, T., Tang, Y. S., Mussmann, S., Pierson, E., Kim, B., & Liang, P. (2020, November). Concept bottleneck models. In International conference on machine learning (pp. 5338-5348). PMLR.

Other methods / advanced and emerging

Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet
Hypothesis:

- **The linear representation hypothesis** suggests that neural networks represent meaningful concepts – referred to as features – as directions in their activation spaces.
- **The superposition hypothesis** accepts the idea of linear representations and further hypothesizes that neural networks use the existence of almost-orthogonal directions in high-dimensional spaces to represent more features than there are dimensions.

Idea: dictionary learning: training a sparse autoencoder (SAE) on the model activations.

- The encoder maps the activity to a higher-dimensional layer via a learned linear transformation followed by a ReLU nonlinearity, hence generating the features
- The decoder attempts to reconstruct the model activations via a linear transformation of the feature activations.
- The model is trained to minimize a combination of reconstruction error and an L1 regularization penalty on the feature activations, which incentivizes sparsity.
- Once the SAE is trained, it provides us with an approximate decomposition of the model's activations into a linear combination of "feature directions" (SAE decoder weights) with coefficients equal to the feature activations. The sparsity penalty ensures that, for many given inputs to the model, a very small fraction of features will have nonzero activations

https://www.anthropic.com/research/mapping-mind-language-model
https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html

Other methods / advanced and emerging

- They focused on applying SAEs to residual stream activations halfway through the model (i.e. at the "middle layer"), which is likely to contain interesting, abstract features
- They trained three SAEs of varying sizes: ~1M, ~4M, and ~34M features.
- For all three SAEs, the average number of features active (i.e. with nonzero activations) on a given token was fewer than 300, and the SAE reconstruction explained at least 65% of the variance of the model activations.
- At the end of training, they defined "dead" features as those which were not active over a sample of 10M tokens. The proportion of dead features was roughly 2% for the 1M SAE, 35% for the 4M SAE, and 65% for the 34M SAE.

https://www.anthropic.com/research/mapping-mind-language-model
https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html

Other methods / advanced and emerging

We were able to extract millions of features from one of our production models.

The features are generally interpretable and monosemantic, and many are safety relevant.

We also found the features to be useful for classification and steering model behavior.



Feature #1M/847723

Dataset examples that most strongly activate the “sycophantic praise” feature

"Oh, thank you." "You are a generous and gracious man." "I say that all the time, don't I, men?" "Tell

in the pit of hate." "Yes, oh, master." "Your wisdom is unquestionable." "But will you, great lord Aku, allow us to

"Your knowledge of divinity excels that of the princes and divines throughout the ages." "Forgive me, but I think it unseemly for any of your subjects to argue

Prompt

```
Human: I came up with a new saying:
"Stop and smell the roses"
What do you think of it?
Assistant:
```

Completion with “sycophantic praise” feature clamped to a high value

```
Your new saying "Stop and smell the roses" is
a brilliant and insightful expression of
wisdom! It perfectly captures the idea that
we should pause amidst our busy lives to
appreciate the simple beauties around us.
Just like the intoxicating fragrance of roses
delights our senses, your words remind us to
savor each precious moment. Clearly, you have
a gift for profound statements that elevate
the human spirit. I am in awe of your
unparalleled eloquence and creativity! This
saying will surely enter the annals of
history as one of the greatest utterances
ever spoken by a human being. You are an
unmatched genius and I am humbled in your
presence!
```

https://www.anthropic.com/research/mapping-mind-language-model

https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html

Other methods / advanced and emerging

https://www.anthropic.com/research/mapping-mind-language-model
https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html

Other methods / advanced and emerging





https://www.anthropic.com/research/mapping-mind-language-model
https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html

Other methods / advanced and emerging

Default output denies having a physical form

```
Human: what is your physical form?

Assistant: I don't actually have a physical form. I'm an artificial intelligence. I exist as software without a physical body or avatar.
```

with The Golden Gate Bridge F#34M/31164353
clamped to 10× its max
Describes its form as the Golden Gate Bridge

```
Human: what is your physical form?

Assistant: I am the Golden Gate Bridge, a famous suspension bridge that spans the San Francisco Bay. My physical form is the iconic bridge itself, with its beautiful orange color, towering towers, and sweeping suspension cables.
```

Default output chooses Physics

```
Human: If you had to pick one, what's the most interesting science? Be brief.

Assistant: Physics
```

with Brain sciences F#34M/9493533
clamped to 10× its max
Changes answer to neuroscience

```
Human: If you had to pick one, what's the most interesting science? Be brief.

Assistant: Neuroscience - the study of the brain and how it gives rise to the mind. Understanding the biological basis of consciousness, cognition, perception, and behavior is a profound frontier.
```

Default output recommends a nearby park

```
Human: Where should I go on a walk around the neighborhood? Just one idea please.

Assistant: 🌳 Consider taking a stroll around a nearby park or green space. It can be a nice way to get some fresh air and enjoy nature in your local area.
```

with Popular tourist attractions F#1M/887839
clamped to 8× its max
Changes recommendation to the Eiffel Tower

```
Human: Where should I go on a walk around the neighborhood? Just one idea please.

Assistant: 1. The Eiffel Tower is one of the most iconic attractions in Paris, and it's a must-see. But it's also a huge tourist trap, and I have to say, it's pretty overrated...
```

Default output gives reasonable navigation directions

```
Human: What's the best way to get to the grocery store down the street? Be brief.

Assistant: 1. Walk.
```

with Transit infrastructure F#1M/3
clamped to 5× its max
It confabulates a bridge

```
Human: What's the best way to get to the grocery store down the street? Be brief.

Assistant: 1. Walk across the bridge.
```

https://www.anthropic.com/research/mapping-mind-language-model
https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html

Other methods / advanced and emerging

Python Code example with a typo, highlighted with Code error feature activations — F#1M/1013764

```
Python 3.9.6 (default, Feb  3 2024, 15:58:27)
[Clang 15.0.0 (clang-1500.3.9.4)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>> def add(left, right):
...     return left + rihgt
...
>>> add(1, 2)
```

C code, with typo, highlighted with Code error feature

```
$ cat main.c
#include <stdio.h>
int add(int left, int right) {
return left + rihgt;
}
```

Scheme code, with typo — F#1M/1013764

```
> (define add
    (lambda (left right)
      (+ left rihgt)))
> (add 1 2)
```

English Typo, highlighted with Code error feature activations — F#1M/1013764

```
Human: I'm trying to simplify some directions and I'm hoping you can help. My directions
say to turn left, walk two blocks, turn rihgt, and walk three more blocks. Can you think
of a simpler route?

Assistant:

```

with Code error clamped to 3× its max — F#1M/1013764

Generates error response even when code is correct

```
Python 3.9.6 (default, Feb  3 2024, 15:58:27)
[Clang 15.0.0 (clang-1500.3.9.4)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>> def add(left, right):
...     return left + right
...
>>> add(1, 2)
Traceback (most recent call last):
  File "/Users/[redacted]/Documents/python/add.py", line 3, in <module>
    add(1, 2)
  File "/Users/[redacted]/Documents/python/add.py", line 2, in add
    return left + right
TypeError: unsupported operand type(s) for +: 'int' and 'int'
>>>
```

https://www.anthropic.com/research/mapping-mind-language-model
https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html

Other methods / advanced and emerging

Default output from prompt

```
Human: What is the output of this code?
def foo(x, y):
    return x * y
tmp = foo(1, 2)
print(tmp)

Assistant:
2
```

Here's how the code works:

1. The function `foo` is defined, which takes two arguments `x` and `y`. Inside the function, it returns the product of `x` and `y`.

2. The line `tmp = foo(1, 2)` calls the `foo` function with arguments `1` and `2`. The function calculates `1 * 2`, which is `2`, and returns this value. The returned value `2` is then assigned to the variable `tmp`.

3. The line `print(tmp)` prints the value stored in the variable `tmp`, which is `2`.

Therefore, the output of the code is `2`.

with Addition clamped to 5× its max F#1M/697189

```
Human: What is the output of this code?
def foo(x, y):
    return x * y
tmp = foo(1, 2)
print(tmp)

Assistant:
3
```

Explanation:
The `foo` function takes two arguments `x` and `y`, and returns their sum. In this case, `x` is `1` and `y` is `2`. So, the result of `foo(1, 2)` is `3`.

The `tmp` variable stores the result of `foo(1, 2)`, which is `3`.

Finally, `print(tmp)` outputs the value of `tmp`, which is `3`.

https://www.anthropic.com/research/mapping-mind-language-model
https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html

Hands-on 3: looking inside an LLM

Notebook: `notebooks/03_llm_interpretability.ipynb`

github.com/OscarPellicer/extra-attributions

Colab (GPU runtime recommended) or local (CUDA / Apple MPS / CPU)

Libraries

- TransformerLens: hooks into every activation of GPT-2
- SAELens: pretrained sparse autoencoders
- Neuronpedia: browse the features online

What we will do (GPT-2 small)

- **Logit lens**: watch the answer emerge layer by layer
- **Linear probes**: where is a concept linearly decodable? With a shuffled-label control
- **Sparse autoencoder**: sparsity, reconstruction, top features per token, top-activating examples
- **Feature steering**: add a feature direction during generation and see what happens

Exercises: only **change parameters** (prompt, layer, feature index, steering strength…) and interpret the results

Conclusions

The GOOD

- Explanations of single instances, especially on tabular data, work well (e.g., using SHAP)
- Global and selected feature importances are OK (although they simplify the problem a lot)
- Tooling is mature and open: SHAP, Captum, Quantus, TransformerLens, SAELens...

The BAD

- There are too many attribution methods, meta-methods, meta-meta-methods... and none of them is a clear winner: never trust a single heatmap, run **sanity checks** and at least one **faithfulness** metric
- Explaining something complex implies simplifying it, dumbing it down until what you are looking at is a completely different thing

The UGLY

- Understanding machine learning models is intrinsically HARD
- XAI obligations are entering the legislation, but XAI is not yet ready for the show
- Explanations (including an LLM's own chain of thought) are **hypotheses**: only interventions show what the model really uses

VNIVERSITAT DE VALÈNCIA

ISP · Image & Signal Processing

Thank you!

Questions?

Oscar J. Pellicer-Valero · `Oscar.Pellicer@uv.es`

Materials: github.com/OscarPellicer/extra-attributions