

# An Introduction to HPC and Scientific Computing

Lecture six: How to multi-task on CPUs using OpenMP.

Jacob Wilkins  
Ian Bush

Oxford e-Research Centre,  
Department of Engineering Science

# Overview

In this lecture we will learn about:

- The Basic Idea Behind Parallelism
- What OpenMP is
- How to divide work amongst threads
- How to synchronise threads
- How to go about parallelising a simple program with OpenMP

# Parallelism – How to do we split up the work?

**Scenario:** The application takes too long to run!

Parallel processing can shorten the run-time:

- Parallelism in the workload (in algorithms and data) and
- Assign portions of the workload to different workers (processors)

# Parallelism – How to do we split up the work?

## Analogy:

Shorten the time it takes to build an entire row of houses by:

- dividing the work into parts that can be carried out in parallel and
- scheduling different (teams of) workers to work on these parts concurrently.

# Parallelism – How to do we split up the work?

**Perfect (linear) scaling** is the holy grail:

- execution time is inversely proportional with the number of processors
- by analogy: halve the time by using twice the workers
- in practice, scaling is not linear but can be close enough

# Many ways to parallelise

- Consider the row of houses analogy
  - One could hire one man for each house
  - Or you could hire a brickie, a roofer, a plumber, an electrician, etc.
- The second obviously requires more communication between the workers
  - They have to coordinate their activities
  - Can't put a roof on the house before you have built the walls
- But the second also doesn't require every person to know everything about how to build a house
  - The required knowledge is split across many people
- Another possibility is a hybrid approach
  - Hire  $N$  brickies,  $N$  roofers,  $N$  plumbers,  $N$  electricians
  - And form  $N$  teams each of which works on  $1/N^{\text{th}}$  of the houses

# Parallelism – A maths example

- Consider adding two vectors:
$$a_i = b_i + c_i$$
- The operations required for each value of  $i$  are independent from any other value
- Thus for parallelism we require *independent operations*
- We can perform the operations *in any order*
- We also require *independent data*
  - Consider the apparently very similar  $a_i = b_i + a_{i-1}$
  - Can't calculate  $a_i$  until  $a_{i-1}$  has been calculated

# Parallelism – Communication and Synchronisation

- Now consider a dot product

$$a = \sum b_i \times c_i$$

- Could give a subset of the indices to each process and form the local contribution to  $a$
- Sum together all the local contributions for final answer
- This last phase requires the processes or threads to work together
  - i.e. they are no longer totally independent
  - They need to communicate with each other
  - If one finishes before the others it will have to wait for them
- Very typical way parallelism work inside real codes
  - Independent iterations
  - Coordinate local results into global one




# Parallel Scaling

- Consider the time to solution for our dot product.
- Vectors of order N
- P threads or processes
- The time to compute the local sum will be proportional to N/P
  - A **decreasing** function of the number of threads
- The time to synchronise and is more complicated
  - But it will be an **increasing** function of the number of threads
  - and independent of N
  - A deeper analysis shows a suitable model is  $\log(P)$
- Thus our model is:
  - $$t(P) = \alpha N/P + \beta \log(P)$$
- Thus parallelism is most efficient
  - For large N
  - For small P
  - Too many threads may cause your program to slow down!



# Measuring Scalability – Speed Up

$$S = t(1)/t(P)$$




# Parallelising Scientific Programs

- **Shared memory programming**
  - Each core can see all of the memory
  - This is generally done via *OpenMP*
  - Generally limited to a single node
- **Distributed memory programming**
  - Each core can only see its memory
  - Have to use the interconnect
  - Can use an unlimited number of cores
  - Generally done via *MPI*
  - We don't cover it here but there are free ARC and ARCHER courses
- Hybrids of the two are possible and are used



# Shared memory model


- Represents computing on a multi-processor architecture which links multiple (identical) CPUs to a single unified main memory;
- Uses a shared-memory programming model, with data that can be shared between processors
- Also called SMP, Symmetric Multi-Processor systems (for historical reasons)



# Processes and Threads

In shared-memory computing:

- An “application” is a single process – May be many threads
- The “process” is the “master thread”
- Master thread can spawn/destroy other threads (fork/join strategy)



# Thread programming

- Explicit, low-level thread programming:
  - start several threads and explicitly tell each what to do
  - tedious, difficult to write and difficult to maintain
  - standards not universal (POSIX pthreads, Windows threads)
  - may be suited to task parallelism
- High-level programming using the OpenMP API:
  - instruct the compiler what can be done in parallel
  - let the compiler do the tedious stuff
  - threads are generated at runtime and scheduled by the OS
  - “standard” supported by a large number of compilers and operating systems
  - by design, suited to data parallelism

# OpenMP Status

- OpenMP specification is not a formal standard.
- Agreement between industrial vendors and users
- an agreement between industrial vendors and users and
- Version 2.5 (May 2005)
- Version 3.0 (May 2008)
- Version 3.1 (July 2011)
- Version 4.0 (July 2013)
  - Currently this is probably the most common implementation you will meet
- Version 5.0 (November 2018)

# The OpenMP API

- OpenMP is
  - An API for portable and scalable shared memory programming
  - Defined and supported by a group of major vendors
  - Supported by most compilers for Fortran, C, C++
- OpenMP programming is
  - Standardised parallelism (fine-grained – loops, coarse-grain – regions)
  - If we're careful, usable serial code
- OpenMP API components:
  - Compiler directives
  - Runtime library routines
  - Environment variables



# OpenMP “Hello World” in C

```
#include <stdio.h>
#include <stdlib.h>
#include "omp.h"
int main( void ) {
    int my_thread;
    /* Scope the variables and create the threads */
#pragma omp parallel default( none ) private( my_thread )
    {
        my_thread = omp_get_thread_num();
        printf( "Hello from thread %d\n", my_thread );
    }
    return EXIT_SUCCESS;
}
$ gcc -fopenmp -O -std=c89 -Wall -Wextra -pedantic hello.c -o hello
$ export OMP_NUM_THREADS=5
$ ./hello
Hello from thread 2
Hello from thread 4
Hello from thread 3
Hello from thread 0
Hello from thread 1
$ export OMP_NUM_THREADS=3
$ ./hello
Hello from thread 0
Hello from thread 2
Hello from thread 1
```

# Running In Batch

```
#!/bin/bash

# set the number of nodes, which is always 1 for OpenMP codes
#SBATCH --nodes=1

# set number of cores per node -- grab the whole node (why?)
#SBATCH --ntasks-per-node=16

# set max wallclock time
#SBATCH --time=00:10:00

# set name of job
#SBATCH --job-name hello

# Set up the software environment
module purge
module load intel-compilers

# set the number of threads we will use
export OMP_NUM_THREADS=5

# run the OpenMP program
./my_prog
```

# A More Complex Example

```
#include <stdlib.h>
#define N 50
int main( void ) {
    double a[ N ], b[ N ], c[ N ];
    int i;
    for( i = 0; i < N; i++ ) {
        b[ i ] = ( (double) rand() ) / RAND_MAX;
        c[ i ] = ( (double) rand() ) / RAND_MAX;
    }
    /* Scope the variables for the parallel region and create the threads */
    #pragma omp parallel default( none ) shared( a, b, c ) private( i )
    {
        /* A work sharing directive */
        #pragma omp for
        for( i = 0; i < N; i++ ) {
            a[ i ] = b[ i ] + c[ i ];
        }
    }
    return EXIT_SUCCESS;
}
```

# Scoping and Work Sharing

- So there are two main steps
  1. Create the threads with a parallel directive and at that point “scope” the variables.
    - **default none** forces you to scope all the variables – USE THIS.
    - Variables can be one of
      - **Shared** – each thread can access the variable
      - **Private** – each thread has its own, unique copy
    - Note thread creation is *expensive*.
  2. Once the threads are created you split the work up between them with a “work sharing” directive
    - Without a work sharing directive all threads will do exactly the same thing on the same data!
    - You can have as many work sharing constructs as you want within a parallel region
    - As thread creation is expensive exploit this – don’t create threads every time you need to share work, reuse the threads as many times as you can!

# Problems Of Sharing Data

- Shared variables makes writing parallel code easy
- But what happens if multiple threads are trying to update (the same part of) a shared variable at the same time?
  - The result is not well defined!
  - And will probably vary from run to run!
- This is called a “race condition” and OpenMP does NOTHING by default to protect you from them
- So if multiple threads need to access a shared variable you will need to synchronize the threads somehow
- Rule of thumb: **If a shared variable is on the left hand side of an = sign it is time to stop and think about thread synchronisation**
- Race conditions are very easy to write and very hard to debug! Be careful!
  - To fully cover this subject we need to have discussed the OpenMP memory model, which is well beyond what we have time to cover here.

# Synchronising Threads

- So how can we synchronise threads?
- OpenMP provides a number of mechanisms. Here we will cover
  - Barrier: a given thread can only proceed once all threads have reached the barrier
    - **Important:** By default there is an implicit barrier at the end of each worksharing construct
  - Critical region: Only 1 thread can be executing codes within a critical region. All other threads must wait at the start until the thread executing the region has exited it
  - Reduction: Combining multiple private values into a single shared value

# Summary: OpenMP Directives So Far

parallel region constructs	blocks of code executed by all threads (most data shared by default)	<pre>#pragma omp parallel (C,C++) !\$omp parallel (Fortran)</pre> <ul style="list-style-type: none"><li>• shared data are visible to all threads</li><li>• private data is local to thread and invisible outside, created on entry to scope, destroyed on exit</li></ul>
work-sharing constructs (within a parallel region)	parallel DO loops (distribute iterations over active threads)	<pre>#pragma omp for !\$omp do</pre>
critical section	protects action on the shared variables (only one thread at a time allowed)	<pre>#pragma omp critical !\$omp critical</pre>
synchronisation	barriers	<pre>#pragma omp barrier !\$omp barrier</pre> <p>Threads can proceed only after all execute the barrier; implied at end of parallel region and loop (unless overridden by nowait)</p>

# Bringing It Together – A More Complex Example

**Task:**  
Orthogonalise 2  
NORMALIZED  
vectors **x** and **y**  
on 2 threads.

There are  
several  
problems to  
watch out for.

## Thread 1

```
z = 0
for i = 1 to n/2
    z = z + xi * yi
end for
[ w = w + z ]
< barrier >
for i = 1 to n/2
    yi = yi - w * xi
end for
```

## Thread 2

```
z = 0
for i = n/2+1 to n
    z = z + xi * yi
end for
[ w = w + z ]
< barrier >
for i = n/2+1 to n
    yi = yi - w * xi
end for
```

### Problem

A thread may finish before  
other has updated **w**

### This now works!

z private



# OpenMP program example

Wait for all Threads  
(Barrier)

## Fortran

```
w = 0.0
```

```
!OMP PARALLEL SHARED(n,w,x,y), &  
!OMP PRIVATE (i,z)
```

```
z = 0.0
```

```
!OMP DO  
DO i = 1, n  
z = z + x(i)*y(i)  
END DO  
!OMP END DO
```

```
!OMP CRITICAL  
w = w + z  
!OMP END CRITICAL
```

```
!OMP BARRIER
```

```
!OMP DO  
DO i = 1, n  
y(i) = y(i) - w*x(i)  
END DO  
!OMP END DO
```

```
!END PARALLEL
```

```
w = 0.0;
```

```
#pragma omp parallel shared (n,w,x,y) \  
private(i,z)
```

```
{  
z = 0.0;  
#pragma omp for  
for (i=0; i<n; i++) {  
z = z + x[i]*y[i];  
}
```

```
#pragma omp critical  
{  
w = w + z;  
}
```

```
#pragma omp barrier
```

```
#pragma omp for  
for (i=0; i<n; i++) {  
y(i) = y(i) - w*x(i);  
}
```

```
}
```

# OpenMP program example

```
w = 0.0;


#pragma omp parallel shared (n,w,x,y) \
    private(i,z)
{
    z = 0.0;

    #pragma omp for
    for (i=0; i<n; i++) {
        z = z + x[i]*y[i];
    }

    #pragma omp critical
    {
        w = w + z;
    }

    #pragma omp barrier

    #pragma omp for
    for (i=0; i<n; i++) {
        y[i] = y[i] - w*x[i];
    }
}
```



# Reductions

- In the above example we are adding up the value of the private z's across all threads to produce a shared value in w
  - So we are reducing many values to a single one via the + operator
- This is so common that reduction operations are supplied directly by OpenMP
- And if it is applicable reductions should be used rather than critical as it will be faster
  - Critical is all purpose, reduction is the precision tool
- Reductions can be applied to whole parallel regions or parallel do/for work share constructs
  - In the latter the reduction variable should be shared

```
w = 0.0;

#pragma omp parallel shared (n,w,x,y) \
    private(i)
{

    #pragma omp for reduction(+:w)
    for (i=0; i<n; i++) {
        w = w + x[i]*y[i];
    }

    #pragma omp for
    for (i=0; i<n; i++) {
        y[i] = y[i] - w*x[i];
    }
}
```

# Reduction Operators

- C/C++ Syntax:  
reduction (operator : list)
- Where
  - operator is one of: + \* - & ^ | && || min max

## More OpenMP

- There is much more in OpenMP
  - More run time library routines
    - Inquiry, timers, locks ...
  - More work share directives
    - Sections, work share, task ...
  - More synchronisation directives
    - atomic, flush ...
  - More environment variables than you can imagine
- We have only scratched the surface here
  - ARC courses
  - ARCHER Courses

## OpenMP: best practices

- thread creation / destruction can be expensive, so threads should be re-used
  - maximise parallel loops (large loops has more opportunities for reuse of cached data)
  - avoid parallel regions in inner loops (aim for the coarsest data parallelism)
  - minimise the number of times parallel regions are entered/exited
  - example: parallel inner loop moved to parallel outer region

```
# initial
for (n=0;n<NN;n++)
  #pragma omp parallel private(m)
  #pragma omp for
  for (m=0;m<MM;m++)
```

```
# improved
#pragma omp parallel private (n,m)
for (n=0;n<NN;n++)
  # pragma omp for
  for (m=0;m<MM;m++)
```

## OpenMP: best practices

- Do not overuse synchronisation and explicit barriers
  - Remember every workshare construct by default has an implicit barrier on exit – this is normally enough
- Scope all your variables and use default(none)
- Think carefully about potential race conditions
  - Remember – a shared variable on the left hand side of an = should start alarm bells ringing




## Example – The 1D Heat Equation

- The **physics**: find the time-varying distribution of temperature along a rod, starting from an initial distribution, given the fixed temperature at the ends
- The **maths** (an initial value problem): find  $u(x,t)$  on the interval  $[0, 1]$  given

–  $u(0, t) = u(1, t) = 0$  and  $u(0, x) = u_0(x)$ .

- The **numerics** (a finite difference scheme):
  - sample the interval  $[0, 1]$  at equidistant points  $x_j = j \Delta x$  ( $j=0, \dots, J-1$ ) and fixed time intervals  $t_n = n \Delta t$ ,  $n > 0$  and find the values of all temperature samples  $u_j^n$  at the sample points
  - discretised equations give:
$$u_j^{(n+1)} = u_j^n + \nu (u_{j+1}^n - 2u_j^n + u_{j-1}^n)$$
  - 4 point stencil




## Example: 1D Heat Equation

- The core of the program is to use two vectors  $u$  and  $u_o$  ( $u$  “old”).

At every time step,

- copy  $u$  into  $u_o$  (not efficient but simple to understand)
- apply the finite difference scheme (the 4 point stencil)



- apply boundary conditions:  $u_1 = u_j = 0$

## Example – 1D Heat Equation

```
// boundary conditions
u[0]    = 0.0; uo[0]    = 0.0;
u[J-1]  = 0.0; uo[J-1] = 0.0;

// time loop
for (n=0; n<n_time_steps; n++) {

    // store solution
    for (j=1; j<J-1; j++) {
        uo[j] = u[j];
    }

    // finite difference scheme
    for (j=1; j<J-1; j++) {
        u[j] = uo[j] + nu*(uo[j-1]-2.0*uo[j]+uo[j+1]);
    }

}
```

# Problem: 1D heat equation in Parallel – The Easy Way

```
// time loop
for (t=0; t<n_time_steps; t++) {
    // store solution

    for (j=1; j<n-1; j++) {
        uo[j] = u[j];
    }

    // finite difference scheme

    for (j=1; j<n-1; j++) {
        u[j] = uo[j] +
            nu*(uo[j-1]-2.0*uo[j]+uo[j+1]);
    }
}
```

```
// time loop
for (t=0; t<n_time_steps; t++) {
    // store solution
    #pragma omp parallel shared(n,u,uo,J) private(j)
    {
        #pragma omp for
        for (j=1; j<n-1; j++) {
            uo[j] = u[j];
        }
    }

    // finite difference scheme
    #pragma omp parallel shared(n,u,uo,nu,J) private(j)
    {
        #pragma omp for
        for (j=1; j<n-1; j++) {
            u[j] = uo[j] +
                nu*(uo[j-1]-2.0*uo[j]+uo[j+1]);
        }
    }
}
```

# Problem: 1D Heat Equation in Parallel – The Better Way

```
// time loop
for (t=0; t<n_time_steps; t++) {
    // store solution
    #pragma omp parallel shared(n,u,uo,J) private(j)
    {
        #pragma omp for
        for (j=1; j<n-1; j++) {
            uo[j] = u[j];
        }
    }
    // finite difference scheme
    #pragma omp parallel shared(n,u,uo,nu,J) private(j)
    {
        #pragma omp for
        for (j=1; j<n-1; j++) {
            u[j] = uo[j] +
            nu*(uo[j-1]-2.0*uo[j]+uo[j+1]);
        }
    }
}
```

```
// time loop
# pragma omp parallel default( none ) \
    shared(n,n_time_steps,u,uo,nu,) \
    private(t,j)
{
    for (t=0; t<n_time_steps; t++) {
        // store solution
        # pragma omp for
        for (j=1; j<n-1; j++) {
            uo[j] = u[j];
        }

        // finite difference scheme
        # pragma omp for
        for (j=1; j<n-1; j++) {
            u[j] = uo[j] +
            nu*(uo[j-1]-2.0*uo[j]+uo[j+1]);
        }
    }
}
```

# What have we learnt?

We have learnt

- The basic ideas behind parallelism
- How OpenMP implements the shared memory programming model
- How to create threads with `#pragma omp parallel`
- How to scope variables
- How to share the work between the threads with `#pragma omp for`
- How to synchronise the threads with barriers, critical regions and reductions
- How to parallelise a small but realistic program

## Further learning

- The best way to learn OpenMP is to go on a longer course. Two free possibilities are
  - The courses run here in Oxford by the Advanced Research Computing Service
    - <http://www.arc.ox.ac.uk/content/training>
    - <https://oxford.imparando.com/accessplan/LMSPortal/UI/Page/Courses/book.aspx?courseid=HP014>  
is the direct link to the OpenMP course
  - Courses run by the national supercomputing service, ARCHER and it's soon to come replacement, ARCHER2
    - <http://www.archer.ac.uk/training/>
    - <https://www.archer2.ac.uk/training/>
- Unfortunately there are no books I know of that I can totally recommend
  - Probably the best is **Parallel Programming in OpenMP** by Chandra *et al.*
  - But it is a bit old now

