


# 作業系統

## Operating System

TZU-CHUN HSU<sup>1</sup>

<sup>1</sup>[vm3y3rmp40719@gmail.com](mailto:vm3y3rmp40719@gmail.com)

<sup>1</sup>Department of Computer Science, Zhejiang University



2021 年 1 月 17 日  
Version 3.2

# Disclaimer

本文「作業系統」為台灣研究所考試入學的「作業系統」考科使用，內容主要參考洪逸先生的作業系統參考書 [1]，以及 wjungle 網友在 PTT 論壇上提供的資料結構筆記 [2]。本文作者為 TZU-CHUN HSU，本文及其 L<sup>A</sup>T<sub>E</sub>X 相關程式碼採用 MIT 協議，更多內容請訪問作者之 GITHUB 分頁 [Oscarshu0719](#)。

## MIT License

Copyright (c) 2020 TZU-CHUN HSU

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

# 1 Overview

1. 本文頁碼標記依照實體書 [1] 的頁碼。

2. TKB 筆記 [2] 章節頁碼：

Chapter	Page No.	Importance
1	3	★ ★
2	15	★ ★
3	25	★ ★
4	34	★ ★ ★ ★ ★
5	99	★ ★ ★
6	119	★ ★ ★ ★ ★
7	175	★ ★ ★
8	197	★ ★ ★ ★ ★
9	221	★ ★ ★
10	221	★

3. 因為第六章 critical section design 部分筆記較複雜，特別分章節。

## 2 Summary

### Theorem (7, 10)

- Time-sharing (Multitasking): 使用 virtual memory 以及 spooling, 且對所有 users 公平對待。
- Real-time:
  - **Hard** real-time disk 少用, 不使用 virtual memory; 但 **soft** real-time 可, 但 real-time processes 的 pages 在完成前不能被 swapped out。
  - **Hard** real-time 不與 time-sharing 並存; 但 **soft** real-time 可。
  - 減少 kernel 干預時間, 因為 Linux kernel 在執行某些 system process 時, 不允許 user process preempts kernel, 防止 race condition。

### Theorem (16)

- Interrupt: Hardware-generated, e.g. I/O-complete, Time-out.
- Trap: Software-generated. Catch arithmetic error 或重大 error, 例如 Divide-by-zero, 以及 process 需要 OS 提供服務, 會先發 trap 通知 OS。

### Theorem (67) Scheduler:

- Long-term (Job) scheduler: 通常僅 **batch system** 採用, 從 job queue 中選 jobs 載入 memory。執行頻率最低, 可以調控 multiprogramming degree 與 CPU-bound 與 I/O-bound jobs 的比例。
- Short-term (CPU, process) scheduler: 從 ready queue 選擇一個 process 分派給 CPU 執行。所有系統都需要, 執行頻率最高, 無法調控 multiprogramming degree 與 CPU-bound 與 I/O-bound jobs 的比例。
- Medium-term scheduler: Memory space 不足且有其他 processes 需要更多 memory 時執行, 選擇 Blocked 或 lower priority process swap out to disk。僅 **Time-sharing system** 採用, batch 和 real-time systems 不採用, 可以調控 multiprogramming degree 與 CPU-bound 與 I/O-bound jobs 的比例。

### Theorem (70) Dispatcher:

- 將 CPU 真正分配給 CPU scheduler 選擇的 process。

- Context switching.
- Switch mode to user mode.
- Jump to execution entry of user process.

**Theorem (72, 78, 82, 84)** CPU scheduling:

- Non-preemptive SJF 不適合用在 **short-term** scheduler, 因為很難在短時間算出 next CPU burst; long-term scheduler 較合適。
- MFQ 雖然不公平, 但 **NO** starvation。
- Linux 指定 processes 不要移轉到某些 processors。
- Worst-case CPU utilization for scheduling  $n$  processes using Rate-monotonic:

$$2 \times (2^{\frac{1}{n}} - 1) \Rightarrow (n \rightarrow \infty) = 69\% \quad (1)$$

- Dispatch latency:
  - Conflict phase: preempts kernel, 並且 low-priority process releases needed resources for high-priority process。
  - Dispatch phase: Context switching, change mode to user mode, and jump to the user process.

**Theorem (141)** Deadlock avoidance:

- 若  $n$  processes,  $m$  resources (單一種類), 若滿足

$$1 \leq Max_i \leq m$$

$$\sum_{i=1}^n Max_i < n + m \quad (2)$$

則 NO deadlock。

*Proof.* 若所有資源都分配給 processes, 即

$$\sum_{i=1}^n Allocation_i = m \quad (3)$$

又

$$\begin{aligned}\sum_{i=1}^n Need_i &= \sum_{i=1}^n Max_i - \sum_{i=1}^n Allocation_i \\ \rightarrow \sum_{i=1}^n Max_i &= \sum_{i=1}^n Need_i + m\end{aligned}\tag{4}$$

根據第二條件，有

$$\begin{aligned}\sum_{i=1}^n Max_i &< n + m \\ \rightarrow \sum_{i=1}^n Need_i &< n\end{aligned}\tag{5}$$

$\exists$  process  $P_i$ ,  $Need_i = 0$ , 又

$$\begin{aligned}Max_i &\geq 1 \wedge Need_i = 0 \\ \rightarrow Allocation_i &\geq 1\end{aligned}\tag{6}$$

在  $P_i$  完工後，會產生  $\geq 1$  resources 給其他 processes 使用，又可以使  $\geq 1$  processes  $P_j$  有  $Need_j = 0$ ，依此類推，所有 processes 皆可完工。

## 2.1 Critical section design

**Theorem (170)** Critical section:

- 在 critical section, CPU 也可能被 preempted。
- 滿足：
  - Mutual exclusion: 同一時間點，最多 1 process 在他的 critical section，不允許多個 processes 同時在各自的 critical section。
  - Progress: 不想進入 critical section 時，不能阻礙其他想進入 critical section 的 process 進入，即不能參與進入 critical section 的 decision，且必須在有限時間內決定進入 critical section 的 process。
  - Bounded waiting: Process 提出申請進入 critical section 後，必須在有限時間內進入，即公平，NO starvation。

### 2.1.1 Software support

**Theorem (171)** Two processes solution (Peterson's solution):

- 共享變數:

```

||
||         int turn = i ∨ j;
||         bool flag = False;

```

Listing 1: Shared variables of Peterson's solution (two processes solution).

- *flag* 或 *turn* 或兩者值皆互換依然正確，但若將前兩行賦值順序對調，則因為 **mutual exclusion** 不成立，而不正確。
- Peterson's solution is NOT guaranteed to work on modern PC, since processors and compilers may reorder read and write operations that have NO dependencies.

---

**Algorithm 1**  $P_i$  of Peterson's solution (two processes solution).

---

```

1: function  $P_i$ 
2:   repeat
3:      $flag[i] := True$ 
4:      $turn := j$ 
5:     while  $flag[j] \wedge turn = j$  do
6:     end while
7:     Critical section.
8:      $flag[i] := False$ 
9:     Remainder section.
10:  until False
11: end function

```

---

### 2.1.2 Hardware support

**Theorem (176)** Test-and-Set:

- 共享變數:

```

||
||         bool lock = False;
||         /*
||         True, 表示想進但在等;
||         False, 表示已在 critical section 或是初值。
||         */
||         bool waiting[0 ... (n - 1)] = False;

```

Listing 2: Shared variables of TEST-AND-SET solution.

- 若移除第八行 `waiting[i] := False`，則 **progress** 不成立，若僅  $P_i$  和  $P_j$  想進入 critical section，此時 `waiting[i]`，`waiting[j] = True`，且  $P_i$  先進入 critical section，有 `lock`，`waiting[i] = True`；當  $P_i$  離開 critical section 後，將 `waiting[j] := False`， $P_j$  進入 critical section；當  $P_j$  離開 critical section 後，因為 `waiting[i] = True`， $P_j$  將 `waiting[i] := False`，但 `lock = True`，未來沒有 process 可以再進入 critical section，**deadlock**。

---

**Algorithm 2**  $P_i$  (Test-and-Set).

---

```

1: function  $P_i$ 
2:   repeat
3:     waiting[i] := True
4:     key := True                                     ▷ Local variable.
5:     while waiting[i] ∧ key do
6:       key := TEST-AND-SET(&lock)
7:     end while
8:     waiting[i] := False
9:     Critical section.
10:    j := i + 1 (mod n)
11:    while j ≠ i ∧ ¬waiting[j] do                       ▷ 找下一個想進入的  $P_j$ 。
12:      j := j + 1 (mod n)
13:    end while
14:    if j = i then                                     ▷ 沒有  $P_j$  想進入 critical section。
15:      lock := False
16:    else
17:      waiting[j] := False
18:    end if
19:    Remainder section.
20:  until False
21: end function

```

---

### 2.1.3 Semaphore

**Theorem (168)** Producer-consumer problem:

- 共享變數:

```

|| semaphore mutex = 1;
|| semaphore empty = n; // buffer 空格數。
|| semaphore full = 0; // buffer 中 item 數。

```

Listing 3: Shared variables of Producer-consumer problem.



- 若將其中一個或兩個程式的兩行 `wait` 對調，可能會 **deadlock**。

---

**Algorithm 3** Producer.

---

```
1: function PRODUCER
2:   repeat
3:     Produce an item.
4:     WAIT(empty)
5:     WAIT(mutex)
6:     Add the item to buffer.
7:     SIGNAL(mutex)
8:     SIGNAL(full)
9:   until False
10: end function
```

---

---

**Algorithm 4** Consumer.

---

```
1: function CONSUMER
2:   repeat
3:     WAIT(full)
4:     WAIT(mutex)
5:     Retrieve an item from buffer.
6:     SIGNAL(mutex)
7:     SIGNAL(empty)
8:     Consume the item.
9:   until False
10: end function
```

---

---

**Theorem (182)** Reader/Writer problem:

---

- R/W 和 W/W 皆要互斥。
- First readers/writers problem:

- 共享變數:

```
// R/W和W/W互斥控制，同時對writer不利之阻擋。
semaphore wrt = 1 ;
int readcnt = 0;
semaphore mutex = 1; // readcnt互斥控制。
```

Listing 4: Shared variables of First Reader/Writer problem.

---

**Algorithm 5** Writer (First Reader/Writer problem).

---

```
1: function WRITER
2:   repeat
3:     WAIT(wrt)
4:     Writing.
5:     SIGNAL(wrt)
6:   until False
7: end function
```

---

---

**Algorithm 6** Reader (First Reader/Writer problem).

---

```
1: function READER
2:   repeat
3:     WAIT(mutex)
4:     readcnt := readcnt + 1
5:     if readcnt = 1 then                                ▷ 表示第一個 reader 需偵測有無 writer 在。
6:       WAIT(wrt)
7:     end if
8:     SIGNAL(mutex)
9:     Reading.
10:    WAIT(mutex)
11:    readcnt := readcnt - 1
12:    if readcnt = 0 then                                ▷ No reader.
13:      SIGNAL(wrt)
14:    end if
15:    SIGNAL(mutex)
16:  until False
17: end function
```

---

- Second Reader/Writer problem:

- 共享變數:

```
int readcnt = 0;
semaphore mutex = 1; // readcnt互斥控制。
semaphore wrt = 1; // R/W和W/W互斥控制。
int wrtcnt = 0;
semaphore y = 1; // wrtcnt互斥控制。
semaphore rsem = 1; // 對reader不利之阻擋。
semaphore z = 1; // reader的入口控制，可有可無。
```

Listing 5: Shared variables of Second Reader/Writer problem.

---

**Algorithm 7** Writer (Second Reader/Writer problem).

---

```
1: function WRITER
2:   repeat
3:     WAIT( $y$ )
4:      $wrtcnt := wrtcnt + 1$ 
5:     if  $wrtcnt = 1$  then                                ▷ 表示第一個 writer 需阻擋 readers。
6:       WAIT( $rsem$ )
7:     end if
8:     SIGNAL( $y$ )
9:     WAIT( $wrt$ )
10:    Writing.
11:    WAIT( $y$ )
12:     $wrtcnt := wrtcnt - 1$ 
13:    if  $wrtcnt = 0$  then
14:      SIGNAL( $rsem$ )                                       ▷ No writer.
15:    end if
16:    SIGNAL( $wrt$ )
17:    SIGNAL( $y$ )
18:  until False
19: end function
```

---

---

**Algorithm 8** Reader (Second Reader/Writer problem).

---

```
1: function READER
2:   repeat
3:     WAIT( $z$ )
4:     WAIT( $rsem$ )
5:     WAIT( $mutex$ )
6:      $readcnt := readcnt + 1$ 
7:     if  $readcnt = 1$  then
8:       WAIT( $wrt$ )
9:     end if
10:    SIGNAL( $mutex$ )
11:    SIGNAL( $rsem$ )
12:    SIGNAL( $z$ )
13:    Reading.
14:    WAIT( $mutex$ )
15:     $readcnt := readcnt - 1$ 
16:    if  $readcnt = 0$  then
17:      SIGNAL( $wrt$ )
18:    end if
19:    SIGNAL( $mutex$ )
20:  until False
21: end function
```

---

**Theorem (184)** The sleeping barber problem:

- 共享變數:

```
semaphore customer = 0; // 強迫 barber sleep。  
// 強迫 customer sleep if barber is busy。  
semaphore barber = 0;  
int waiting = 0; // 正在等待的 customers 個數。  
semaphore mutex = 1; // waiting 互斥控制。
```

Listing 6: Shared variables of The sleeping barber problem.

- 若將 BARBER 將兩行 `wait` 對調，可能會 **deadlock**。

---

**Algorithm 9** Barber.

---

```
1: function BARBER  
2:   repeat  
3:     WAIT(customer)           ▷ Barber go to sleep if no customer.  
4:     WAIT(mutex)  
5:     waiting := waiting - 1  
6:     SIGNAL(barber)           ▷ Wake up customer.  
7:     SIGNAL(mutex)  
8:     Cutting hair.  
9:   until False  
10: end function
```

---

---

**Algorithm 10** Customer.

---

```
1: function CUSTOMER  
2:   repeat  
3:     WAIT(mutex)  
4:     if waiting < n then      ▷ 入店。  
5:       waiting := waiting + 1  
6:       SIGNAL(customer)      ▷ Wake up barber.  
7:       SIGNAL(mutex)  
8:       WAIT(barber)          ▷ Customer go to sleep if barber is busy.  
9:       Getting cut.  
10:    else  
11:      SIGNAL(mutex)  
12:    end if  
13:  until False  
14: end function
```

---

**Theorem (187)** The dining-philosophers problem:



```

    int c = n; // Counting semaphore 號誌值。
    semaphore s1 = 1; // c 互斥控制。
    binary_semaphore s2 = 0; // c < 0 時卡住 process

```

Listing 8: Shared variables of The dining-philosophers problem.

---

**Algorithm 12** *wait(c)* (counting semaphore).

---

```

1: function WAIT(c)
2:   WAIT(s1)
3:   c := c - 1
4:   if c < 0 then
5:     SIGNAL(s1)
6:     WAIT(s2)
7:   else
8:     SIGNAL(s1)
9:   end if
10: end function

```

▷ Process 卡住。

---



---

**Algorithm 13** *signal(c)* (counting semaphore).

---

```

1: function SIGNAL(c)
2:   WAIT(s1)
3:   c := c + 1
4:   if c ≤ 0 then
5:     SIGNAL(s2)
6:   end if
7:   SIGNAL(s1)
8: end function

```

▷ 先前有 process 卡住。

---

**Theorem ()** Non-busy waiting semaphore:

```

struct semaphore {
    int value;
    Queue Q; // Waiting queue.
}

```

Listing 9: Non-busy waiting semaphore.

---

**Algorithm 14**  $wait(S)$  (non-busy waiting semaphore).

---

```
1: function WAIT( $S$ )
2:    $S.value := S.value - 1$ 
3:   if  $S.value < 0$  then
4:     Add process  $p$  into  $S.Q$ .
5:      $block(p)$   $\triangleright$  System call 將  $p$  的 state 從 running 改為 wait, 有 context switch
       cost.
6:   end if
7: end function
```

---

---

**Algorithm 15**  $signal(S)$  (non-busy waiting semaphore).

---

```
1: function SIGNAL( $S$ )
2:    $S.value := S.value + 1$ 
3:   if  $S.value \leq 0$  then
4:     Remove process  $p$  from  $S.Q$ .
5:      $wakeup(p)$   $\triangleright$  System call 將  $p$  的 state 從 wait 改為 ready, 有 context switch
       cost.
6:   end if
7: end function
```

---

**Theorem ()** 製作 semaphore:

- Algorithm 1 (disable interrupt and non-busy waiting):

---

**Algorithm 16**  $wait(S)$  of Algorithm 1 (disable interrupt and non-busy waiting).

---

```
1: function WAIT( $S$ )
2:   Disable interrupt.
3:    $S.value := S.value - 1$ 
4:   if  $S.value < 0$  then
5:     Add process  $p$  into  $S.Q$ .
6:     Enable interrupt.
7:      $block(p)$ 
8:   else
9:     Enable interrupt.
10:  end if
11: end function
```

---

---

**Algorithm 17**  $signal(S)$  of Algorithm 1 (disable interrupt and non-busy waiting).

---

```
1: function SIGNAL( $S$ )
2:   Disable interrupt.
3:    $S.value := S.value + 1$ 
4:   if  $S.value \leq 0$  then
5:     Remove process  $p$  from  $S.Q$ .
6:      $wakeup(p)$   $\triangleright$  System call 將  $p$  的 state 從 wait 改為 ready, 有 context switch cost.
7:   end if
8:   Enable interrupt.
9: end function
```

---

- Algorithm 2 (critical section design and non-busy waiting): 將 Algorithm 1 (2.1.3) 中的 **Enable interrupt.** 和 **Disable interrupt.** 分別改為 **Entry section.** 和 **Exit section.** 並使用 TEST-AND-SET (2) 或 COMPARE-AND-SWAP 實現。
- Algorithm 3 (disable interrupt design and busy waiting):

---

**Algorithm 18**  $wait(S)$  of Algorithm 3 (disable interrupt design and busy waiting).

---

```
1: function WAIT( $S$ )
2:   Disable interrupt.
3:   while  $S \leq 0$  do
4:     Enable interrupt.
5:     Disable interrupt.
6:   end while
7:    $S := S - 1$ 
8:   Enable interrupt.
9: end function
```

---

---

**Algorithm 19**  $signal(S)$  of Algorithm 3 (disable interrupt design and busy waiting).

---

```
1: function SIGNAL( $S$ )
2:   Disable interrupt.
3:    $S := S + 1$ 
4:   Enable interrupt.
5: end function
```

---

- Algorithm 4 (critical section design and busy waiting): 同 Algorithm 2 (2.1.3), 將 Algorithm 3 (2.1.3) 中的 **Enable interrupt.** 和 **Disable interrupt.** 分別改為 **Entry section.** 和 **Exit section.** 。



### 2.1.4 Monitor

#### Theorem (189)

Process is NOT active:

- Process 呼叫的 function 執行完畢。
- Process 執行 `wait()` 被 blocked。

**Theorem (191)** Monitor 解 The dining philosophers problem:

```
Monitor Dining-ph {  
    enum {  
        thinking, hungry, eating  
    } state[5];  
}  
Condition self[5];
```

Listing 10: Data structure (The dining philosophers problem (Monitor)).

---

**Algorithm 20** *pickup(i)*.

---

```
1: function PICKUP(i)  
2:   state[i] := hungry  
3:   TEST(i)  
4:   if state[i] ≠ eating then  
5:     self[i].WAIT  
6:   end if  
7: end function
```

---

---

**Algorithm 21** *test(i)*.

---

```
1: function TEST(i)  
2:   if state[(i+4) (mod 5)] ≠ eating ∧ state[i] = hungry ∧ state[(i+1) (mod 5)] ≠ eating  
   then  
3:     state[i] := eating  
4:     self[i].SIGNAL  
5:   end if  
6: end function
```

---

---

**Algorithm 22** *putdown(i).*

---

```
1: function PUTDOWN(i)
2:   state[i] := thinking
3:   TEST((i + 4) (mod 5))
4:   TEST((i + 1) (mod 5))
5: end function
```

---

---

**Algorithm 23** *initialization\_code().*

---

```
1: function INITIALIZATION_CODE                                     ▷ For non-Condition type.
2:   for i := 0 to 4 do
3:     state[i] := thinking
4:   end for
5: end function
```

---

---

**Algorithm 24**  $P_i$  (The dining philosophers problem (Monitor)).

---

```
1: function  $P_i$ 
2:   DINING_PH dp                                               ▷ Shared variable.
3:   repeat
4:     Hungry.                                                    ▷ No active.
5:     dp.PICKUP(i)                                              ▷ Running: active; Blocked: NOT active.
6:     Eating.                                                    ▷ No active.
7:     dp.PUTDOWN(i)                                             ▷ Active.
8:     Thinking.                                                  ▷ No active.
9:   until False
10: end function
```

---

**Theorem ()** Example of monitor: 若有三台 printers, 且 process ID 越小, priority 越高。

```
Monitor PrinterAllocation {
    bool pr[3];
    Condition x;
}
```

Listing 11: Data structure of example of monitor

---

**Algorithm 25** *Apply(i).*

---

```
1: function APPLY(i)
2:   if pr[0]  $\wedge$  pr[1]  $\wedge$  pr[2] then
3:     x.WAIT(i)
4:   else
5:     n := Non-busy printer
6:     pr[n] := True
7:     return n
8:   end if
9: end function
```

---

---

**Algorithm 26** *Release(n).*

---

```
1: function RELEASE(n)
2:   pr[n] := False
3:   x.SIGNAL
4: end function
```

---

---

**Algorithm 27** *initialization\_code().*

---

```
1: function INITIALIZATION_CODE
2:   for i := 0 to 2 do
3:     pr[i] := False
4:   end for
5: end function
```

---

---

**Algorithm 28**  $P_i$  of example of monitor.

---

```
1: function  $P_i$ 
2:   PRINTERALLOCATION pa ▷ Shared variable.
3:   n := pa.APPLY(i)
4:   Using printer pr[n].
5:   pa.RELEASE(n)
6: end function
```

---

**Theorem ()** 使用 semaphore 製作 monitor:

- 共享變數:

```
semaphore mutex = 1;
// Block process P if P call signal.
semaphore next = 0;
// 統計 process P 那種特殊 waiting processes 的個數。
int next_cnt = 0;
```

```

// Block process Q if Q call wait.
semaphore x_sem = 0;
// 統計一般 waiting processes 的個數。
int x_cnt = 0;

```

Listing 12: Shared variables of making monitor using semaphore.

- 在 function body 前後加入控制碼，類似 Entry section 和 Exit section。

---

**Algorithm 29** *f* (Example for adding control code before and after function body).

---

```

1: function F
2:   WAIT(mutex)
3:   Function body.
4:   if next_cnt > 0 then
5:     SIGNAL(next)
6:   else
7:     SIGNAL(mutex)
8:   end if
9: end function

```

---



---

**Algorithm 30** *x.wait*.

---

```

1: function x.WAIT
2:   x_cnt := x_cnt + 1
3:   if next_cnt > 0 then
4:     SIGNAL(next)
5:   else
6:     SIGNAL(mutex)
7:   end if
8:   WAIT(x_sem)
9:   x_cnt := x_cnt - 1
10: end function

```

---

▷ *Q* 自己卡住。  
▷ *Q* 被救。

---

**Algorithm 31** *x.signal*.

---

```

1: function x.SIGNAL
2:   if x_cnt > 0 then
3:     next_cnt := next_cnt + 1
4:     SIGNAL(x_sem)
5:     WAIT(next)
6:     next_cnt := next_cnt - 1
7:   end if
8: end function

```

---

▷ *P* 自己卡住。  
▷ *P* 被救。

### Theorem (223)

- Dynamic binding 由 MMU 負責。
- Dynamic loading 由 programmer 負責，OS 無負擔。
- Dynamic linking 需要 OS 支持。
- 必須支援 dynamic binding 才可以在 execution time compaction。

**Theorem (253)** Process 可分配 frames 數量由 hardware 決定，最多為 physical memory size，最少須讓任一 machine code 完成，即週期中最多可能 memory access 數量，e.g. *IF*, *MEM*, *WB* 共三次。

### Theorem () Dirty bit:

- MMU: from 0 to 1.
- OS: from 1 to 0.

### Theorem (263)

$$\text{TLB reach} = \text{TLB entries} \times \text{Frame size} \quad (7)$$

### Theorem ((343)42, (344)44)

- Solaris ZFS uses **checksums** to provide fault-tolerance in case pointers are wrong.
- NFS:
  - Using RPC for remote file operations.
  - Writing to a file by a user are immediately visible to other users, since it does **NOT** support session semantics.
  - Does **NOT** support `open()` and `close()` operations.
  - Each request must provide a full set of arguments.
  - Supported file operations must be idempotent.
  - **NO** special measures are needed to recover a server from crash.

### Theorem (309)

- Seek time: head 移到 **track** 的時間。

- Latency (Rotation) time: **sector** 移到 head 的時間。

**Theorem () Storage:**

- Smartphones normally do **NOT** have HDDs.
- Secondary storage is normally **non-volatile**.
- Wearable devices are normally equipped with **hard disks** to increase its storage space.

**Theorem () Disk:**

- **High-level** formatting creates a file system on a disk partition.
- A disk sector contains a header, a data area, and a trailer.
- In UNIX, disk scheduling algorithm is performed in the **disk driver**.
- A file system can be created across **multiple disk partitions**.

**Theorem () Cybersecurity:**

- Trojan Horse is a code segment that **misuses** its environment.
- Installing antivirus software is **NOT** an example of least privileges.

**Theorem () Cryptography:**

- 公開金鑰加密提供 digital signature 功能。
- AES: Symmetric, block cipher.
- DES: Symmetric, block cipher.
- RC4: Symmetric, stream cipher.
- RSA: Asymmetric, 只要鑰匙夠長, 沒有任何可靠的攻擊方法。
  - Authentication: 將 message 與 hash 過再用 private key 加密的 message 串接。e.g.  $M || \{h(M)\}_{K_{sa}}$ .
  - Confidentiality: 將用 one-time AES key 加密的 message 與用 public key 加密的 one-time AES key 串接。e.g.  $\{M\}_{K_{da}} || \{K_{da}\}_{K_{pb}}$ .

- Confidentiality and authentication: 將 authentication 的內容用 one-time AES key 加密,再與用 public key 加密的 one-time AES key 串接。e.g.  $\{M||\{h(M)\}_{K_{sa}}\}_{K_{da}}||\{K_{da}\}_{K_{pb}}$ .

- Digital certificate contains **private key** signed by the user.

#### Theorem () Kernel:

- Monolithic: UNIX, UNIX-like, Windows 9x, Android.
- Microkernel: Mach.
- Hybrid: Windows NT, Windows XP, macOS.

#### Theorem ()

- **Native Windows threads** cause a user-mode to kernel-mode.
- Physical caches do NOT flush at **context switching**.
- Hyper-threading is **superscalar** and it can speedup **context switching**.
- There is **NO** optimum solution to allocate contiguous memory from free holes.
- Data fault: Access invalid data memory, which is signaled by **MMU**.
- NUMA is intrinsic in Von Neumann's computer model.
- The TLB cache may require a flush after a page table update.
- **kmalloc** : physically contiguous; **vmalloc** : virtually contiguous; **malloc** : no constraints.
- **strncpy** 相較 **strcpy** 安全, 且需要預留一格, 可防止 buffer overflow。
- Java **interprets** Java bytecode operations **one at a time**.
- CLR, which is the implementation of .NET VM, **compiles** Microsoft intermediate language instructions **one at a time**.
- Normal instructions for the VM can execute **directly on the hardware** and **only the privileged instructions** must be simulated.
- Named pipes are referred to as **FIFOs** in UNIX systems. Once created, they appear as typical **files** in the file systems.

- Kernel processes are **NOT** allocated through paging and virtual memory interface.
- A **non-preemptive** kernel is free from race conditions on kernel data structures.
- **Preemptive** kernel design can **NOT** prevent the deadlock problem with kernel data structures from occurring in the kernel.
- **Disk device driver** can **NOT** be paged out, but page tables, memory-mapped files, shared memory can.
- Permission bits are stored at **inodes**.
- Linux kernel is a **preemptive** kernel and a process running in a kernel mode could **NOT** be preempted.
- Most operating systems **downgrade** the thread priority when it runs out of time quantum, but **boost** the priority when it returns from an I/O request.
- FIFO can outperform LRU.
- A program using asynchronous I/O system calls is **NOT** simpler to write than using synchronous I/O system calls.
- TEST-AND-SET still wastes cycles when a process can **NOT** acquire a lock.
- Moving files between directories on the **same** disk partition and **deleting** files on a hard disk cause little overhead, but moving files between directories on **different** disk partitions cause much.
- Five classic components: datapath, control unit, memory, input, and output.
- Data center cares more about **throughput** than response time.
- Cache memories are usually hardware controlled, and OS may **NOT** even need to know their existence.
- After making system calls, the process is still in running state.
- FIFO may have Convoy effect, which causes low **I/O** utilization.
- **(FALSE)** In a time-sharing system, a process does **NOT** leave running state unless it terminates or is preempted through a timer interrupt.



- The variation of disk I/O **latencies** under SSTF can be very high.
- Extent allocation uses **contiguous physical** blocks, and it also needs defragmentation.
- Arithmetic overflow can be ignored.
- To use shared memory, several system calls have to be invoked.
- OS does **NOT** need to estimate *MAX* when a process enters ready queue.
- Memory blocks on the **stacks** can **NOT** be freed at any time.
- **(FALSE)** Use of shared memory can reduce the number of page table entries.
- **(FALSE)** The page table of Linux process is managed by the C runtime library (.so) in the process.
- For the **unused regions** in the virtual address space, the space overhead of the corresponding **page table entries** can be negligible.
- Via HTTPS, ISPs can know the browsing website, but can **NOT** know the content.
- **Two-phase locking protocol (2PL)** ensures **conflict serializability**, but it may result in **deadlock**.
- **Stack** is good for locality.

## References

- [1] 洪逸. 作業系統金寶書 (含系統程式). 鼎茂圖書出版股份有限公司, 4 edition, 2019.
- [2] wjungle@ptt. 作業系統 @tkb 筆記. <https://drive.google.com/file/d/0B8-2o6L73Q2VeiFZaXpBVGx2aWM/view?usp=sharing>, 2017.

