

演算法

Algorithm

TZU-CHUN HSU¹

¹vm3y3rmp40719@gmail.com

¹Department of Computer Science, Zhejiang University



2021 年 1 月 28 日
Version 4.0

Disclaimer

本文「演算法」為台灣研究所考試入學的「演算法」考科使用，內容主要參考洪捷先生的演算法參考書 [1]，以及 wjungle 網友在 PTT 論壇上提供的演算法筆記 [2]。

本文作者為 TZU-CHUN HSU，本文及其 L^AT_EX 相關程式碼採用 MIT 協議，更多內容請訪問作者之 GITHUB 分頁 [Oscarshu0719](#)。

MIT License

Copyright (c) 2020 TZU-CHUN HSU

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1 Overview

1. 本文頁碼標記依照實體書 [1] 的頁碼。

2. TKB 筆記 [2] 章節頁碼：

Chapter	Page No.	Importance
1	1	★★★★
2	13	★★★★
3	18	★★★★★
4	34	★★★★★
5	43	★★★
6	48	★★★
7	×	★
8	×	★★★

3. 省略第 7 章。

Dynamic Programming algorithms		
Problem	Time complexity	Space complexity
Making change	$O(kn)$	$O(n)$
Fractional Knapsack problem	$\Theta(n \log n)$	$O(n)$
0/1 Knapsack problem (DP)	$O(n2^{\log W})$	$O(n2^{\log W})$
0/1 Knapsack problem (Branch-and-Bound)	$O(2^n)$	
Longest Common Subsequence (LCS)	$O(mn)$	$O(mn)$
Longest Increasing Subsequence (LIS)	$O(n^2)$	$O(n^2)$
Longest Common Substring	$O(mn)$	$O(mn)$
Minimum Edit Distance	$O(mn)$	$O(mn)$
Matrix-chain Multiplication	$O(n^3)$	$O(n^2)$
Traveling Salesperson problem	$\Theta(n^2 2^n)$	$O(n2^n)$
Optimal Binary Search Tree (OBST)	$\Theta(n^3)$	$\Theta(n^2)$

Graph algorithms		
Problem	Time complexity	Remark
Depth-First Search (DFS)	$O(V + E)$	
Kosaraju's	$O(V + E)$	
Kruskal's	$O(E \log V)$	
Prim's (Adjacency matrix)	$O(V ^2)$	
Prim's (Adjacency list)	$O(V E)$	
Prim's (Min-Heap, Adjacency list)	$O(E \log V)$	
Prim's (Fibonacci heap, Adjacency list)	$O(E + V \log V)$	
Sollin's (Borůvka's)	$O(E \log V)$	
Dijkstra's (Min-heap)	$\Theta((E + V) \log V)$	Greedy, no negative edges or cycles
Dijkstra's (Fibonacci-heap)	$\Theta(E + V \log V)$	
Bellman-Ford	$O(V E)$	DP
Floyd-Warshall	$\Theta(V ^3)$	DP, no negative cycles
Johnson's	$\Theta(V E + V ^2 \log V)$	No negative cycles
Ford-Fulkerson	$O(E f^*)$	Greedy, f^* 為最大流
Edmond-Karp	$O(V E ^2)$	
Push-relabel	$O(V ^2 E)$	

2 Summary

1. Theorem (100) Matrix-chain Multiplication:

$$m[i, j] = \begin{cases} 0 & , i = j \\ \min_{i \leq k \leq j-1} \{m[i, k] + m[k+1, j] + p_{i-1}p_kp_j\} & , i < j \end{cases} \quad (1)$$

- $p[0 \cdots \text{Number}(\text{Matrices})]$, 存入矩陣大小。
- $m[1 \cdots \text{Number}(\text{Matrices})][1 \cdots \text{Number}(\text{Matrices})]$, 初始化對角線上元素為 0。
- $s[1 \cdots \text{Number}(\text{Matrices}) - 1][2 \cdots \text{Number}(\text{Matrices})]$, $s[i, j]$ 存入 $m[i, j]$ 中最小值對應的 k 。
- 理解: $m[i, k]$ 為拆分的前部分, $m[k+1, j]$ 為拆分的後部分, $p_{i-1}p_kp_j$ 為前後部分相乘。

2. Theorem (111) Optimal Binary Search Tree (OBST):

$$e[i, j] = \begin{cases} q_{i-1} & , j = i - 1 \\ \min_{i \leq r \leq j} \{e[i, r-1] + e[r+1, j] + w[i, j]\} & , i \leq j \end{cases} \quad (2)$$

$$w[i, j] = w[i, j-1] + p_j + q_j$$

其中, p_j 為 **key** (內部節點) 機率, q_j 為 **dummy key** (外部節點) 機率。

- $w[1 \cdots \text{Number}(\text{Key}) + 1][0 \cdots \text{Number}(\text{Key})]$, 初始化對角線上元素 $w[j+1, j]$ 為 q_j 。
- $e[1 \cdots \text{Number}(\text{Key}) + 1][0 \cdots \text{Number}(\text{Key})]$, 初始化對角線上元素 $e[j+1, j]$ 為 q_j 。
- $r[1 \cdots \text{Number}(\text{Key})][1 \cdots \text{Number}(\text{Key})]$, $r[i, j]$ 存入 $e[i, j]$ 中最小值對應的 r 。
- 理解: $e[i, r-1]$ 為左子樹, $e[r+1, j]$ 為右子樹, $w[i, j]$ 為節點權重和, 因為計算 cost 時是節點階層加一。

3. Theorem () Minimum vertex cover (tree):

$$V(v) = \min\{1 + \sum\{V(c), \forall c \in v.child\}, \text{Length}\{v.child\} + \sum\{V(g), \forall c \in v.child \forall g \in c.child\}\} \quad (3)$$

First part: root is in the cover; second part: root is NOT in the cover.

4. **Theorem ()** Max-cut:

- NPC。
- 若所有邊權重皆負，則可乘上 -1 ，變為 Min-cut。
- 若為平面圖，可轉換為 Chinese Postman Problem（若為無向圖，即 Euler circuit，若為有向圖，則為 NPC）。

5. **Theorem (285)**

- 如果可以證明 **lower bound of worst case** of NPC problems is polynomial, 則 $P = NP$ 。




图 1: Relationship between NP and CO-NP.

6. **Theorem ()**

- **(FALSE)** For two functions $f(n)$ and $g(n)$, either $f(n) = O(g(n))$ or $f(n) = \Omega(f(n))$.
Counterexample:

$$\begin{aligned} f(n) &= \begin{cases} 1, & \text{if } n = 2k \\ 0, & \text{if } n = 2k + 1 \end{cases} \\ g(n) &= \begin{cases} 0, & \text{if } n = 2k \\ 1, & \text{if } n = 2k + 1 \end{cases} \end{aligned} \quad (4)$$

- For any uniform cost RAM program $T(n) = \Omega(S(n))$, where $S(n)$ is the space an algorithm uses for an input of size n .
- The capacity of each edge of a flow network can be floating-point, and it can be solved by linear programming.
- A flow network of multiple sources can be reduced to a single source.
- **(FALSE)** The value of any flow of a flow network is bounded by the capacity of only at most $O(n)$ cuts.

- 2-coloring: $O(n^2)$, 3-coloring, 4-coloring: superpolynomial.
- Weighted-union heuristic: Append the **smaller** list onto the **longer** list, with ties broken arbitrarily.
- $n! \neq \Theta(n^n)$.
- A DAG with n vertices can **NOT** have more than $\binom{n}{2}$ edges.
- Longest palindrome subsequence:

$$L(i, j) = \begin{cases} 0 & , i = j + 1 \\ 1 & , i = j \\ L(i + 1, j - 1) + 2 & , i < j \wedge s[i] = s[j] \\ \max(L(i + 1, j), L(j, j - 1)) & , \text{otherwise} \end{cases} \quad (5)$$

where $L[1 \dots n][1 \dots n], s[1 \dots n]$

- Minimum triangulation:

$$c(i, j) = \begin{cases} 0 & , j < i + 2 \\ \min_{i < k < j} \{c(i, k) + c(k, j) + \text{dist}(i, j) + \text{dis}(j, k) + \text{dist}(k, j)\} & , \text{otherwise} \end{cases} \quad (6)$$

```
double triangulation(Point P[], int n) {
    if (n < 3)
        return 0;

    double c[n][n];
    for (int gap = 0, gap < n; gap++) {
        for (int i = 0, j = gap; j < n; i++, j++) {
            if (j < i + 2)
                c[i][j] = 0.0;
            else {
                c[i][j] = MAX;
                for (int k = i + 1; k < j; k++) {
                    double val = c[i][k] + c[k][j] + wt(
                        P, i, j, k);
                    if (c[i][j] > val)
                        c[i][j] = val;
                }
            }
        }
    }
}
```

```

    }
}

return c[0][n - 1];
}

```

Listing 1: Minimum triangulation.

- Sort n integers ranged from 0 to $n^2 - 1$: 將 n 個整數表示成 n 進位數，每個數由 2-digit 表示，範圍 0 到 $n - 1$ ，再用 radix sort 對 2-digit 排序，共兩次。
- If max frequency is ≤ 2 times of min frequency, Huffman code is **NOT** always better than an ordinary fixed-length code.
- Amortized analysis 與 average-case analysis 無關。
- **(FALSE)** If a graph has a unique MST then, for every cut of the graph, there is a **unique light edge** crossing the cut.
- **(TRUE)** A graph has a unique MST **if**, for every cut of the graph, there is a **unique light edge** crossing the cut.
- The worst-case running time and expected running time are equal to within **constant** factors for any randomized algorithm.
- Selection problem: $T(n) = T(\frac{n}{5}) + T(\frac{3n}{4}) + O(n)$
- Given an **undirected** graph and a positive integer k , is there a path of length $\leq k$, which each edge has weight 1 and each vertex is visited **exactly** once: P, solved by Floyd-Warshall algorithm.
- Given an **undirected** graph and a positive integer k , is there a path of length $\geq k$, which each edge has weight 1 and each vertex is visited \leq once: NPC.
- A flow network of multiple sources can be reduced to a single source.
- Subset sum: $s(i, j)$: sum j can be found in $\{a_1, \dots, a_i\}$

$$s(i, j) = \begin{cases} 0 & , i = 0 \\ 1 & , j = 0 \\ s(i - 1, j) \vee s(i - 1, j - v_i) & , j \geq v_i \end{cases} \quad (7)$$

result is $s(m, n)$.

- Hanoi tower iterative version: Check if the **input number** n is even or odd.

If n is even,

$$\begin{cases} A \leftrightarrow C \\ A \leftrightarrow B \\ C \leftrightarrow B \end{cases} \quad (8)$$

If n is odd,

$$\begin{cases} A \leftrightarrow B \\ A \leftrightarrow C \\ B \leftrightarrow C \end{cases} \quad (9)$$

- Fibonacci search:

```
def fibSearch(arr, data):
    max = len(arr) - 1
    y = getY(fib, max + 1) # Find the largest index,
                           # which its value is smaller than data.
    m = max - fib[y]
    x = y - 1
    i = x
    if arr[i] < data: # Check at first.
        i += m
    while fib[x] > 0:
        if arr[i] < data:
            x -= 1
            i += fib[x]
        elif arr[i] > data:
            x -= 1
            i -= fib[x]
    else:
        return i
    return -1
```

Listing 2: Fibonacci search.

- Box stacking:

- (a) Generate all 3 rotations of all boxes. We consider width as always smaller than or equal to depth.
- (b) Sort the above generated $3n$ boxes in **decreasing** order of **base area**.

(c) $msh(i)$: Max possible stack height with box i at top of stack.

$$msh(i) = \{ \max\{msh(j)\} + height(i) \}, \quad (10)$$

$$\forall j < i \wedge width(j) > width(i) \wedge depth(j) > depth(i)$$

result is

$$\max_{0 < i < n} \{msh(i)\} \quad (11)$$

- Building bridge:

- (a) Sort the north-south pairs on the basis of **increasing** order of **south** x-coordinates.
- (b) Find **LIS** of north x-coordinates.

- Optimal strategy: $f(i, j)$: max value the user can collect from i -th coin to j -th coin.

$$f(i, j) = \begin{cases} v_i & , j = i \\ \max\{v_i, v_j\} & , j = i + 1 \\ \max\{v_i + \min\{f(i+2, j), f(i+1, j-1)\}, \\ v_j + \min\{f(i+1, j-1), f(i, j-2)\}\} & , \text{otherwise} \end{cases} \quad (12)$$

- (TIOJ-1097) Find the largest square submatrix with all 0s in a 0/1 matrix: $dp(i, j)$: max square submatrix in $i \times j$ left upper submatrix.

$$dp(i, j) = \min\{dp(i-1, j-1), dp(i, j-1), dp(i-1, j)\} + 1 \quad (13)$$

- (UVA-10934) Dropping water balloons (k balloons and height n): $dp(i, j)$: max height i balloons can be dropped j times.

$$dp(i, j) = \begin{cases} dp(i, j-1) + dp(i-1, j-1) + 1 & , arr(i, j) = 1 \\ 0 & , arr(i, j) = 0 \end{cases} \quad (14)$$

result is

$$\min_j \{dp(k, j) \geq n\} \quad (15)$$

- (TIOJ-1471) Skyline: $dp(i, j)$: walk i distance and height is j .

$$\begin{cases} dp(i, j) & = dp(i-1, j-1) + sum(j) \\ sum(j) & = sum(j) - dp(i-j, j) + dp(i, j) \end{cases} \quad (16)$$

result is

$$\sum_j dp(n, j) \quad (17)$$

- Largest rectangle in histogram:
 - If the new element is higher than stack top element, push it; otherwise, pop and calculate the area until the new element is higher than stack top element.
 - Maximal rectangle: Similarly, for each column, the count of 1 of each row, can be seen as the element.



References

- [1] 洪捷. 演算法—名校攻略秘笈. 鼎茂圖書出版股份有限公司, 9 edition, 2017.
- [2] wjungle@ptt. 演算法 @tkb 筆記. <https://drive.google.com/file/d/0B8-2o6L73Q2VVmNWQk9DY3hsUm8/view?usp=sharing>, 2017.

