
資料結構 Data Structure

TZU-CHUN HSU¹

 $^{1}\mathrm{vm3y3rmp40719@gmail.com}$

¹Department of Computer Science, Zhejiang University



2021年1月28日 Version 4.0

Disclaimer

本文「資料結構」為台灣研究所考試入學的「資料結構」考科使用,內容主要參考 Introduction to Algorithms[1],以及 wjungle 網友在 PTT 論壇上提供的資料結構筆記 [2]。本文作者為 TZU-CHUN HSU,本文及其 LATEX 相關程式碼採用 MIT 協議,更多內容請訪問作者之 GITHUB 分頁Oscarshu0719。

MIT License

Copyright (c) 2020 TZU-CHUN HSU

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1 Overview

- 1. 本文頁碼標記依照 TKB 筆記 [2] 的頁碼。
- 2. TKB 筆記 [2] 章節頁碼:

Chapter	Page No.	Importance
1	3	***
2	259	*
3	52	***
4	259	*
5	82	****
6	228	***
7	180	***
8	221	***
9	// 129	***

3.

$$\log 2 = 0.3010$$

$$\log 3 = 0.4771$$

$$\log 5 = 0.6990$$

$$\log 7 = 0.8451$$
(1)

4. OBST 在「演算法」中,不再贅述。

	Trees	
Tree	Insert x Delete x Search x	Remark
BST	$O(\log n) \sim O(n)$	Create: $O(n \log n) \sim O(n^2)$
AVL tree		$F_{h+2} - 1 \le n \le 2^h - 1$
B tree	$O(\log_m n)$	$1 + 2\frac{\lceil \frac{m}{2} \rceil^{h-1} - 1}{\lceil \frac{m}{2} \rceil - 1} \le n \le \frac{m^h - 1}{m - 1}$
RBT		$h \le 2\log(n+1)$
Splay tree		Worst: $O(n)$, Amortized: $O(\log n)$

Priority queues						
Operations	Max (Min)	Min-max & Deap & SMMH	Leftist	Binomial	Fibonacci	
Insert x	$O(\log n)$	$O(\log n)$	$O(\log n)$	$O(\log n), O(1)^*$	$O(1)^*$	
Delete max	$O(\log n)$	$O(\log n)$				
Delete min	O(n)	$O(\log n)$	$O(\log n)$	$O(\log n)$	$O(\log n)^*$	
Delete x				$O(\log n)$	$O(\log n)^*$	
Merge	O(n)		$O(\log n)$	$O(\log n)$	$O(1)^*$	
Decrease key				$O(\log n)$	$O(1)^*$	
Search x	O(n)					
Find max	O(1)	O(1)				
Find min		O(1)		$O(\log n)$	O(1)	
Remark		0 4	$shortest(root) \\ \leq \log(n+1) - 1$			

Sorting algorithms						
Method	Tim Best	e comple Worst	exity Average	Space complexity	Stable	
Insertion	O(n)	VC	$O(n^2)$	O(1)		
Selection		$\square O(n^2)$	5	O(1)	×	
Bubble	O(n)	= C	$O(n^2)_{-}$	O(1)		
Shell	$O(n^{1.5})$	7 0	$O(n_{\overline{\gamma}}^2)$	O(1)	×	
Quick \\\\\	$O(n \log n)$	$O(n^2)$	$O(n \log n)$	$O(\log n) \sim O(n)$	×	
Merge	> ($O(n \log n)$) /	O(n)		
Heap		$O(n \log n)$		O(1)	×	
LSD Radix		$O(n \times k)$		O(n+k)		
Bucket/MSD Radix	O(n)///	$O(n^2)$	O(n+k)	$O(n \times k)$		
Counting		47 U	O(n+k)			

2 Summary

1. Theorem (17) Permutation:

```
1: function PERM(list, i, n)
       if i == n then
          Print(list)
 3:
 4:
       else
          for j := i to n do
 5:
              SWAP(list, i, j)
 6:
              Perm(list, i + 1, n)
 7:
              SWAP(list, i, j)
 8:
          end for
 9:
       end if
10:
11: end function
```

2. Theorem (87) 節點數:

3. Theorem (116)

```
1: function CreateMinHeap(Tree s, size n)
        for i := n/2 to 1 do
                                                             ▷ Start from parent of the last node.
2:
            tmp := s[i]
3:
           j := 2 \times i
                                                                                    \triangleright Left child of i.
4:
5:
            while j \leq n do
                                                                                  \triangleright There is a child.
               if j < n then
                                                                                ▷ Right child exists.
6:
                   if s[j] > s[j+1] then
                                                                        ▷ Choose the smaller child.
7:
8:
                       j := j + 1
                   end if
9:
               end if
10:
               if tmp \leq s[j] then
11:
12:
                   Break.
               else
                                                                              ▶ Percolate one level.
13:
                   s[j/2] := s[j]
14:
                   j := j \times 2
15:
               end if
16:
            end while
17:
18:
            s[j/2] := tmp
        end for
19:
20: end function
```

4. **Theorem (257)** 尋找 articulation point: 若 root 有 ≥ 2 子節點,則 root 為 articulation point; \exists 非 root 節點 u,若 \exists v 為 u 子節點,且 $low(v) \geq dfn(u)$,則 u 為 articulation point。

5. Theorem ()

- AVL trees are ideal for sorting items of an ordered dictionary.
- Different number binary trees of height h:

$$H_n = \begin{cases} 2H_{n-1} \times \sum_{i=0}^{h-2} H_i + H_{i-1}^2 &, h \ge 2\\ H_0 = 1, H_1 = 3 \end{cases}$$
 (3)

References

- [1] Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. *Introduction to Algorithms, Third Edition*. The MIT Press, 3 edition, 2009.
- [2] wjungle@ptt. 資料結構 @tkb 筆記. https://drive.google.com/file/d/ OB8-2o6L73Q2VeFpGejlYRk1WeFk/view?usp=sharing, 2017.

