

# 628 Final Project Report

## Event Recommendation System

Author: Xinghan Qin

**Content:**

<b>Introduction</b>	<b>2</b>
<b>Objectives</b>	<b>2</b>
Aims	
Objectives	
<b>Feature Analyse</b>	<b>2</b>
Data sets	
Features	
<b>Data Processing</b>	<b>3</b>
Read data	
Data processing	
Result	
<b>Model Training</b>	<b>5</b>
<b>Result Analyse</b>	
<b>Future Improvement</b>	
<b>Conclusion</b>	

## Introduction:

As life speed becomes faster and faster, people sometimes can feel lonely and bored but don't know what to do. One of the reasons for this situation is because our world is too colourful. When people have too many interests, then sometimes it will become very hard for us to decide exactly what to do. And at the end, we will decide to do nothing.

Hence, because of this problem, I decided to create an events recommendation system to help people choose some events, that this person may interest to, based on the person information, friends list, and event attendance record. The data set was found on open source website, Kaggle. Following is the link:

<https://www.kaggle.com/c/event-recommendation-engine-challenge/data>

## Aims & Objectives:

### Aims:

Based on given events information, user information, training data and test data, to train a network to predict if the user will interest or uninterest to the event.

### Objectives:

- Analyse the given data sets and select the features
- Read and process data into wanted format
- Create the model based on requirement
- Train and evaluate the model by train data and validate data
- Predict the result for test data

## Data Analyse:

### Data sets:

- train.csv: (15398 \* 6)  
user, event, invited, timestamp, interested, not\_interested
- test.csv: (10237 \* 4)  
user, event, invited, timestamp
- users.csv: (38209 \* 7)  
user\_id, locale, birthyear, gender, joinedAt, location, timezone
- event\_attendees.csv: (24144 \* 5)  
event, yes, maybe, invited, no
- events.csv: (3137972 \* 110)  
event\_id, user\_id, start\_time, city, state, zip, country, lat, lng, count\_1, count\_2, ..., count\_100, count\_other
- user\_friends.csv: (38202 \* 2)  
user\_id, friends

### Features: (214)

- user\_id: the id of the user
- event\_id: the id of the event
- interested: does user interest in the event
- not\_interested: does user uninterest the event

- invited: have user been invited, 1 for yes, 0 for no
- friend\_attend\_yes: the number of friends attend the event
- friend\_attend\_maybe: the number of friends maybe attend the event
- friend\_attend\_invited: the number of friends invited to the event
- friend\_attend\_no: the number of friends not attend the event
- attend\_same\_gender\_rate\_yes: the rate of same gender attends the event
- attend\_same\_gender\_rate\_maybe: the rate of same gender maybe attends the event
- attend\_same\_gender\_rate\_invite: the rate of same gender invites by the event
- attend\_same\_gender\_rate\_no: the rate of same gender not attend the event
- host\_is\_friend: is host is friend of user, 1 for yes, 0 for no
- c\_1 to c\_100: the information about the event
- interest\_c1 to interest\_c\_100: the mean value of user attended events' information

More features will be added in the future. The information about time, location and time zone has not been applied.

## Data Processing:

### Read data:

To read and use given data sets efficiently, 7 dictionaries were designed:

("1": yes, "2": maybe, "3": invited, "4": no)

- train\_dict = {user\_id : {event\_id : [invited, interested, not\_interested]}}
- test\_dict = {user\_id : {event\_id : invited}}
- friends\_dict = {user\_id : []}
- users\_dict = {user\_id : [birthday, gender]}
- events\_dict = {event\_id : [host\_user\_id, [c\_list]]}
- user\_interests\_dict = {user\_id : {"1" : [], "2" : [], "3" : [], "4" : []}}
- event\_attendees\_dict = {event\_id : {"1" : [], "2" : [], "3" : [], "4" : []}}

During reading the data, Duplicated data in user was found:

```

1 train_dict = {}
2 for index, row in train.iterrows():
3     user_id = str(row[0])
4     event_id = str(row[1])
5     invited = row[2]
6     interested = row[4]
7     not_interested = row[5]
8     if user_id == "203456139":
9         print([event_id, invited, interested, not_interested])
10    if not user_id in train_dict:
11        train_dict[user_id] = {}
12    if event_id in train_dict[user_id]:
13        print("Duplicated data! for event_id, user_id:" + event_id + ", " + user_id)
14    # print(train_dict[user_id][event_id])
15    # print([invited, interested, not_interested])
16    else:
17        train_dict[user_id][event_id] = [invited, interested, not_interested]

['4242816413', 0, 0, 0]
['1462902079', 0, 0, 0]
['498238691', 0, 0, 0]
['745914541', 0, 0, 0]
['1462902079', 0, 0, 0]
Duplicated data! for event_id, user_id:1462902079, 203456139
['2746202243', 0, 1, 0]
['2989846146', 0, 1, 0]
['4242816413', 0, 0, 0]
Duplicated data! for event_id, user_id:4242816413, 203456139
['498238691', 0, 0, 0]
Duplicated data! for event_id, user_id:498238691, 203456139
['2153037761', 0, 1, 0]
['745914541', 0, 0, 0]
Duplicated data! for event_id, user_id:745914541, 203456139

```

```
In [148]: 1 train_dict = create_train_dict(train)
```

```
Duplicated data in user: 178
Multiple data in user: 0
```

```
In [149]: 1 test_dict = create_test_dict(test)
```

```
Duplicated data in user: 131
Multiple data in user: 0
```

Because it was just duplicated and had no multiple data for same combo of user and event, the data will be ignored if it just duplicated.

```
In [98]: 1 train_dict = {}
2 for index, row in train.iterrows():
3     user_id = str(row[0])
4     event_id = str(row[1])
5     invited = row[2]
6     interested = row[4]
7     not_interested = row[5]
8     if not user_id in train_dict:
9         train_dict[user_id] = {}
10    if event_id in train_dict[user_id]:
11        if train_dict[user_id][event_id] == [invited, interested, not_interested]:
12            print("Duplicated data! for event_id, user_id: " + event_id + ", " + user_id)
13        else:
14            print("Multiple data! for event_id, user_id: " + event_id + ", " + user_id)
15    else:
16        train_dict[user_id][event_id] = [invited, interested, not_interested]
```

```
Duplicated data! for event_id, user_id:1462902079, 203456139
Duplicated data! for event_id, user_id:4242816413, 203456139
Duplicated data! for event_id, user_id:498238691, 203456139
Duplicated data! for event_id, user_id:745914541, 203456139
```

Hence, after processing, the train\_data and test\_data would be 15398 – 178 and 10237 – 131:

```
1 print(train.shape)
2 print(test.shape)
```

```
(15220, 214)
(10106, 214)
```

## Data processing:

As all data has been read into the dictionary, train\_data and test\_data should be create based on the feature design.

- user\_id:  
train\_dict.keys()
- event\_id:  
train\_dict[user\_id].keys()
- interested:  
train\_dict[user\_id][event\_id][1], for test\_data is -1
- not\_interested:  
train\_dict[user\_id][event\_id][2], for test\_data is -1
- invited:  
train\_dict[user\_id][event\_id][0]
- friend\_attend\_yes, friend\_attend\_maybe, friend\_attend\_invited, friend\_attend\_no:  
attend\_list ← event\_attendees\_dict[event\_id]  
friends\_list ← friends\_dict[user\_id]  
compare attend\_list with friends\_list
- attend\_same\_gender\_rate\_yes, attend\_same\_gender\_rate\_maybe,  
attend\_same\_gender\_rate\_invite, attend\_same\_gender\_rate\_no:  
attend\_list ← event\_attendees\_dict[event\_id]  
gender ← users\_dict[guest\_id in attend\_list]
- host\_is\_friend:  
friends\_list ← friends\_dict[user\_id]  
host\_id ← events\_dict[event\_id][0]
- c\_1 to c\_100:  
events\_dict[event\_id][1 : 100]

- interest\_c1 to interest\_c\_100:  
 $\text{interests\_list} \leftarrow \text{user\_interests\_dict}[\text{user\_id}]$   
 $\text{mean of all events\_dict}[\text{event\_id in interests\_list}][1 : 100]$

During the data processing, some problems about the data set were found. The main problem was lack of data. For example, lots of user\_id in event\_attendees cannot be found in users file. Hence, while processing the same gender, there were lots of unknown data. This situation also happened for user\_interests\_dict. Some user didn't attend any events before, hence, there was not record for the interest. Because lack of data happens in real world as well, unknown data was ignored or tread as 0 this time depends on the situation.

Result:

train\_data.csv

1	train
0	3044012 1918771225 0 0 0 0 0 0 3 3 0.000000 ... 0.0
1	3044012 1502284248 0 0 0 0 0 0 1 0 0.000000 ... 0.0
2	3044012 2529072432 1 0 0 0 0 0 2 0 0.833333 ... 0.0
3	3044012 3072478280 0 0 0 0 1 0 0 0 0.000000 ... 0.0
4	3044012 1390707377 0 0 0 0 0 0 2 0 0.333333 ... 0.0
...	...
15215	4293103086 2750873665 0 0 0 0 0 1 0 0 0.000000 ... 0.0
15216	4293103086 4084655790 0 0 0 0 1 0 1 0 0.000000 ... 0.0
15217	4293103086 598708806 0 0 0 0 1 1 3 1 0.000000 ... 0.0
15218	4293103086 604179853 0 0 0 0 0 1 0 1 0.000000 ... 0.0
15219	4293103086 2351245308 1 0 0 0 0 0 1 0 0.000000 ... 0.0

15220 rows x 214 columns

test\_data.csv:

1	test
	user_id event_id interested un_interested invited friend_yes friend_maybe friend_invited friend_no same_gender_yes ... interest_c_190 inter
0	1776192 2877501688 -1 -1 0 1 0 1 0 0.0 ... 0.0
1	1776192 3025444328 -1 -1 0 1 0 11 2 0.0 ... 0.0
2	1776192 4078218285 -1 -1 0 0 0 7 0 0.0 ... 0.0
3	1776192 1024025121 -1 -1 0 0 0 3 0 0.0 ... 0.0
4	1776192 2972428928 -1 -1 0 0 0 3 0 0.0 ... 0.0
...	...
10101	4289724715 2652356640 -1 -1 0 0 0 0 0 1.0 ... 0.0
10102	4289724715 3128167927 -1 -1 0 0 0 0 0 0.0 ... 0.0
10103	4289724715 645947926 -1 -1 0 0 0 0 0 0.0 ... 0.0
10104	4289724715 3547653054 -1 -1 0 0 0 0 0 0.0 ... 0.0
10105	4289724715 2769292935 -1 -1 0 0 0 0 0 0.0 ... 0.0

10106 rows x 214 columns

## Model Training:

Data prepare:

Total training data set has 15220 elements, 14000 elements were set as training data and the rest data were set as validation data. Total test data set has 10106 elements.:

```
In [5]: 1 train_total_size = 15220
2 training_size = 14000
3 validate_size = train_total_size - training_size
4 testing_size = 10106
5
6 training_data = torch.FloatTensor(train.iloc[: training_size, 4 :].values)
7 validate_data = torch.FloatTensor(train.iloc[training_size :, 4 :].values)
8 testing_data = torch.FloatTensor(test.iloc[:, 4 :].values)
9 training_label = torch.FloatTensor(train.iloc[: training_size, [2, 3]].values)
10 validate_label = torch.FloatTensor(train.iloc[training_size :, [2, 3]].values)
11 print("training_data size:", list(training_data.shape))
12 print("validate_data size:", list(validate_data.shape))
13 print("testing_data size:", list(testing_data.shape))
14 print("training_label size:", list(training_label.shape))
15 print("validate_label size:", list(validate_label.shape))

training_data size: [14000, 210]
validate_data size: [1220, 210]
testing_data size: [10106, 210]
training_label size: [14000, 2]
validate_label size: [1220, 2]
```

## Model setting

First hidden layer: input size 210, output size 514, linear and ReLU

Second hidden layer: input size 514, output size 128, linear and ReLU

Output layer: input size 128, output size 2, linear

```
myNet(
    (fc1): Linear(in_features=210, out_features=514, bias=True)
    (relu1): ReLU()
    (fc2): Linear(in_features=514, out_features=128, bias=True)
    (relu2): ReLU()
    (fc3): Linear(in_features=128, out_features=2, bias=True)
)
```

Optimizer and loss function:

```
1 optimizer = optim.Adam(net.parameters(), lr=lr)
2 loss_funtion = nn.MSELoss()
```

Depends on the batch\_size to create train\_loader:

```
1 def load_array(data_arrays, batch_size, is_train=True):
2     features, labels = data_arrays
3     num_examples = len(labels)
4     indices = list(range(num_examples))
5     random.shuffle(indices)
6     array = []
7     for i in range(0, num_examples, batch_size):
8         batch_indices = torch.tensor(indices[i : min(i + batch_size, num_examples - 1)])
9         minibatch_features = features.index_select(0, batch_indices)
10        minibatch_labels = labels.index_select(0, batch_indices)
11        array.append((minibatch_features, minibatch_labels))
12    train_loader = iter(array)
13    return train_loader
```

Depends on Epochs to train the model, and print the loss for this epoch

```
1 for epoch in range(Epchs):
2     data_iter = load_array((training_data, training_label), batch_size)
3     for batch_X, batch_y in data_iter:
4         net.zero_grad()
5         output = net(batch_X)
6         loss = loss_funtion(output, batch_y)
7         loss.backward()
8         optimizer.step()
9     if epoch % ((Epchs - 1) / 10) == 0:
10        print("loss for epoch ", epoch, " is ", loss.data)
```

## Parameters setting:

To improve the model, batch\_size, learning rate(lr) and Epchs were adjusted based on the final epoch loss and AUC of results.

For batch\_size = 140, lr = 0.01, Epchs = 101:

As result shows, the final epoch loss was 0.0546. And during the training, the loss didn't get improved gradually. Hence, lr was decided to be decreased.

```

loss for epoch 0 is tensor(0.1297)
loss for epoch 10 is tensor(0.0823)
loss for epoch 20 is tensor(0.0780)
loss for epoch 30 is tensor(0.0868)
loss for epoch 40 is tensor(0.0742)
loss for epoch 50 is tensor(0.0755)
loss for epoch 60 is tensor(0.0734)
loss for epoch 70 is tensor(0.0737)
loss for epoch 80 is tensor(0.0643)
loss for epoch 90 is tensor(0.0873)
loss for epoch 100 is tensor(0.0676)

In [13]: 1 train_result = net(training_data)
2 print(train_result.shape)
3 print("loss for train_data is: ", loss_funtion(train_result, training_label).data)
4 fpr, tpr, thresholds = metrics.roc_curve(training_label.data.numpy()[:, 0], train_result.data.numpy()[:, 0], pos_label=1)
5 train_auc = metrics.auc(fpr, tpr)
6 print("AUC is: ", train_auc)

torch.Size([14000, 2])
loss for train_data is: tensor(0.0546)
AUC is: 0.9252576997007824

In [14]: 1 result = net(validate_data)
2 print(result.shape)
3 print("loss for train_data is: ", loss_funtion(result, validate_label).data)
4 fpr, tpr, thresholds = metrics.roc_curve(validate_label.data.numpy()[:, 0], result.data.numpy()[:, 0], pos_label=1)
5 validate_auc = metrics.auc(fpr, tpr)
6 print("AUC is: ", validate_auc)

torch.Size([1220, 2])
loss for train_data is: tensor(0.1603)
AUC is: 0.5952877846790889

```

For batch\_size = 140, lr = 0.001, Epchs = 101:

As lr was decreased, the loss has been decreased. However, because in the training data, there were lots of 0 (the reason will be discussed in the next part), batch\_size was increased to avoid all data in batch were 0.

```

loss for epoch 0 is tensor(0.1149)
loss for epoch 10 is tensor(0.0769)
loss for epoch 20 is tensor(0.0520)
loss for epoch 30 is tensor(0.0541)
loss for epoch 40 is tensor(0.0497)
loss for epoch 50 is tensor(0.0436)
loss for epoch 60 is tensor(0.0425)
loss for epoch 70 is tensor(0.0228)
loss for epoch 80 is tensor(0.0327)
loss for epoch 90 is tensor(0.0293)
loss for epoch 100 is tensor(0.0371)

In [13]: 1 train_result = net(training_data)
2 print(train_result.shape)
3 print("loss for train_data is: ", loss_funtion(train_result, training_label).data)
4 fpr, tpr, thresholds = metrics.roc_curve(training_label.data.numpy()[:, 0], train_result.data.numpy()[:, 0], pos_label=1)
5 train_auc = metrics.auc(fpr, tpr)
6 print("AUC is: ", train_auc)

torch.Size([14000, 2])
loss for train_data is: tensor(0.0259)
AUC is: 0.985314843438633

In [14]: 1 result = net(validate_data)
2 print(result.shape)
3 print("loss for train_data is: ", loss_funtion(result, validate_label).data)
4 fpr, tpr, thresholds = metrics.roc_curve(validate_label.data.numpy()[:, 0], result.data.numpy()[:, 0], pos_label=1)
5 validate_auc = metrics.auc(fpr, tpr)
6 print("AUC is: ", validate_auc)

torch.Size([1220, 2])
loss for train_data is: tensor(0.1678)
AUC is: 0.571976811594203

```

For batch\_size = 1400, lr = 0.001, Epchs = 101:

As result shows, the loss increased. However, different than before, the loss kept tending to decrease. The previous results tended to be stable or jump back. To determine when would the results tend to be stable or jump back, Epchs was increased.



```

loss for epoch 0 is tensor(0.1319)
loss for epoch 10 is tensor(0.1486)
loss for epoch 20 is tensor(0.0961)
loss for epoch 30 is tensor(0.0824)
loss for epoch 40 is tensor(0.0630)
loss for epoch 50 is tensor(0.0580)
loss for epoch 60 is tensor(0.0535)
loss for epoch 70 is tensor(0.0541)
loss for epoch 80 is tensor(0.0468)
loss for epoch 90 is tensor(0.0478)
loss for epoch 100 is tensor(0.0394)

```

```

In [13]: 1 train_result = net(training_data)
2 print(train_result.shape)
3 print("loss for train_data is: ", loss_funtion(train_result, training_label).data)
4 fpr, tpr, thresholds = metrics.roc_curve(training_label.data.numpy()[:, 0], train_result.data.numpy()[:, 0], pos_label=1)
5 train_auc = metrics.auc(fpr, tpr)
6 print("AUC is: ", train_auc)

torch.Size([14000, 2])
loss for train_data is: tensor(0.0404)
AUC is: 0.9617783759299537

```

```

In [14]: 1 result = net(validate_data)
2 print(result.shape)
3 print("loss for train_data is: ", loss_funtion(result, validate_label).data)
4 fpr, tpr, thresholds = metrics.roc_curve(validate_label.data.numpy()[:, 0], result.data.numpy()[:, 0], pos_label=1)
5 validate_auc = metrics.auc(fpr, tpr)
6 print("AUC is: ", validate_auc)

torch.Size([1220, 2])
loss for train_data is: tensor(0.1630)
AUC is: 0.6069747412008282

```

For batch\_size = 1400, lr = 0.001, Epchs = 1001:

As it shows, the loss was decreased. However, although the AUC of training\_data\_pred became 0.994, which means the model is very close to the training data, the AUC of validation data decreased to 0.538. This caused by overfitting. Because the model has been trained too many times, the model almost kept the shape of training data. Hence, Epchs needed to be decreased. As the part be highlighted shows, during 700th epoch, the loss has jumped back. Hence, Epchs was set somewhere around 600.

```

loss for epoch 0 is tensor(0.1695)
loss for epoch 100 is tensor(0.0550)
loss for epoch 200 is tensor(0.0337)
loss for epoch 300 is tensor(0.0272)
loss for epoch 400 is tensor(0.0237)
loss for epoch 500 is tensor(0.0225)
loss for epoch 600 is tensor(0.0191)
loss for epoch 700 is tensor(0.0219)
loss for epoch 800 is tensor(0.0219)
loss for epoch 900 is tensor(0.0178)
loss for epoch 1000 is tensor(0.0158)

```

```

In [13]: 1 train_result = net(training_data)
2 print(train_result.shape)
3 print("loss for train_data is: ", loss_funtion(train_result, training_label).data)
4 fpr, tpr, thresholds = metrics.roc_curve(training_label.data.numpy()[:, 0], train_result.data.numpy()[:, 0], pos_label=1)
5 train_auc = metrics.auc(fpr, tpr)
6 print("AUC is: ", train_auc)

torch.Size([14000, 2])
loss for train_data is: tensor(0.0169)
AUC is: 0.9941657664903966

```

```

In [14]: 1 result = net(validate_data)
2 print(result.shape)
3 print("loss for train_data is: ", loss_funtion(result, validate_label).data)
4 fpr, tpr, thresholds = metrics.roc_curve(validate_label.data.numpy()[:, 0], result.data.numpy()[:, 0], pos_label=1)
5 validate_auc = metrics.auc(fpr, tpr)
6 print("AUC is: ", validate_auc)

torch.Size([1220, 2])
loss for train_data is: tensor(0.2119)
AUC is: 0.5375751552795032

```

For batch\_size = 1400, lr = 0.001, Epchs = 651:

As it shows, the loss was 0.0184, and AUC of validation data was 0.581. Hence, the model has been improved, and this would be the final version of the model.

```

loss for epoch 0 is tensor(0.3842)
loss for epoch 65 is tensor(0.0503)
loss for epoch 130 is tensor(0.0392)
loss for epoch 195 is tensor(0.0341)
loss for epoch 260 is tensor(0.0251)
loss for epoch 325 is tensor(0.0235)
loss for epoch 390 is tensor(0.0263)
loss for epoch 455 is tensor(0.0191)
loss for epoch 520 is tensor(0.0219)
loss for epoch 585 is tensor(0.0235)
loss for epoch 650 is tensor(0.0216)

```

```

In [13]: 1 train_result = net(training_data)
          2 print(train_result.shape)
          3 print("loss for train_data is: ", loss_funtion(train_result, training_label).data)
          4 fpr, tpr, thresholds = metrics.roc_curve(training_label.data.numpy()[ :, 0], train_result.data.numpy()[ :, 0], pos_label=1)
          5 train_auc = metrics.auc(fpr, tpr)
          6 print("AUC is: ", train_auc)

          torch.Size([14000, 2])
          loss for train_data is: tensor(0.0184)
          AUC is: 0.9931112853710314

```

```

In [14]: 1 result = net(validate_data)
          2 print(result.shape)
          3 print("loss for train_data is: ", loss_funtion(result, validate_label).data)
          4 fpr, tpr, thresholds = metrics.roc_curve(validate_label.data.numpy()[ :, 0], result.data.numpy()[ :, 0], pos_label=1)
          5 validate_auc = metrics.auc(fpr, tpr)
          6 print("AUC is: ", validate_auc)

          torch.Size([1220, 2])
          loss for train_data is: tensor(0.1993)
          AUC is: 0.5813813664596273

```

## Result Analyse:

As the final result shows, the final AUC of validation data was 0.581 and loss was 0.2, which was one of the best results and parameter setting for this model. However, this result did not match the expectation. Following are the reasons may cause this situation:

- Lack of data:  
While processing the training\_data and testing\_data based the features been designed, there were lots of unknow data. For lots of user\_id in friends\_list, no information can be found according to user\_id in users.csv. This means lots of the numbers of friend's attendance for the user were 0. Also, for user\_id in attended.csv had same issue. For the user in training data, lots of them did not have any record of the event attendance. Hence, the result for interest\_c\_1 to interest\_c\_100 could all be 0. The lack of data caused training data included many 0.
- Unused data:  
In the original data set, there were some data this model didn't apply. Those data were mainly location, timestamp, birthday and time zone. For those data, some needed higher skill to processing. Like location, the given data in same column has different format. Some were city and status, and some others were status and country. Hence, need other tool to determine the information. And for data like timestamp, with limited knowledge, those data cannot be transfer into useful data. Put timestamp in integer, like 20200314, into training data was not meaningful. Hence, some of unused data may be important features for model. However, based on limited skill and knowledge, those data have not been applied.
- Model:  
The model can be more complicated by applying different type of method.
- Parameters:  
More testing should be done to improve the parameters.

**Future Improvement:**

As been discussed in Result analyse, following are the future improvement:

- Search for more data set to complete the training data (the data was found on Kaggle, hence this is not doable)
- Apply more data in the original data set, learn more skill and theory to represent these data
- Complicate the model by using more methods
- Do more testing to improve the parameters

**Conclusion:**

For this event recommendation system model, it has 214 features, the loss of training data was 0.0184, the AUC of training data was 0.993, the loss for validation data was 0.2 and AUC of validation data was 0.831. Although the trained model did not have high performers, the improve directions have been found out. With more self-learning, it will have more useful features, more data, more complicated model and better parameters.