Whetprompt · Acceptance test-driven development

Acceptance test results

Run 2026-10-23 11:40:48 UTC · commit 5ef00cd (master) · v0.5.0

PASS

114	104	0	10
scenarios (acceptance criteria)	passed	failed	pending, with a stated reason

Every scenario below is a Gherkin acceptance criterion in `acceptance/features/`, executed by a same-named automated test in `acceptance/`. Pending scenarios are registered as tests so they appear in every run and cannot be forgotten.

1. Summary by capability

Capability group	Scenarios	Passed	Failed	Pending	Seams
A — Scoring a prompt, with no model involved	12	12	0	0	api
B — Fixing a prompt	10	10	0	0	api, browser
C — The strength contract and the rewrite guard	10	10	0	0	api
D — Learning from the user's own library	6	6	0	0	api
E — The prompt library	7	7	0	0	api
F — The local model	11	4	0	7	api, nightly, desktop, browser
G — Providers and privacy	6	5	0	1	api, nightly
H — The editor and the results interface	15	15	0	0	browser
I — Showing what changed	3	3	0	0	library-seam
J — The CI linter	6	6	0	0	cli
K — The desktop application	6	4	0	2	desktop, nightly, api
L — Configuration, limits and errors	4	4	0	0	api
M — Marking a rewrite and fixing it again	11	11	0	0	api, browser
N — Looking the same every time	7	7	0	0	visual
Total	**114**	**104**	**0**	**10**	**151.2 s of test time**

2. Defects found by the scenarios

A8 — "Missing input" was no longer detected for the documented example FIXED

DEMO.md and examples.js say the transcript prompt scores a high-severity "references input that is not clearly attached" with Context 24/100. It scored a low "pasted input is not delimited", because the heuristic counted the rest of the instruction sentence after "transcript below" as pasted input.

Fix: server/analyze.js: pasted input starts on a new line or after a colon; the rest of the referencing sentence is instruction.

G2 — An upstream error could carry the API key to the browser FIXED

A provider whose error body echoes the key had that body forwarded verbatim, in the error response and inside a successful reply's retry warning. The README promises keys never leave the server.

Fix: server/providers.js redact() blanks every configured key at the source; server/index.js applies it again in the error handler.

D6 — A saved library example returned verbatim was accepted as the rewrite FIXED

A parroted example shares enough vocabulary with the prompt to clear the Balanced retention floor, and the leak detector only recognised the <examples> wrapper, so another prompt's text was handed back as the user's rewrite.

Fix: server/metaprompt.js validateRewrite() receives the examples and treats an exact match with any example as a leak; after two attempts the user gets their original back with a warning naming the library toggle.

K6 / L3 — API errors did not all have the same shape FIXED

An unknown /api path returned Express's HTML "Cannot GET" page while every other failure is JSON, and the JSON envelope dropped code/provider when undefined.

Fix: server/index.js: JSON 404 for any unmatched /api path through the normal error handler; code and provider always present (null when unknown).

H12 — Tab count badges were below AA contrast FIXED

The count badge on an unselected tab ("Issues 11") used --text-faint on --panel-3: 4.18:1, below the 4.5:1 the token's own comment promises. Found by measuring every rendered text node in Chromium, not by reading the tokens.

Fix: src/styles.css: .tab .count uses --text-dim.

H13 — The results pane header pushed Save off the page at 1024px wide FIXED

Tabs, the history control and Copy/Apply/Save sit in a non-wrapping flex row; at 1024px the Save button ended at 1055px and the whole page scrolled horizontally.

Fix: src/styles.css: .pane-head wraps.

Observations not acted on

- Ollama shows as configured whenever its default URL is set, even with nothing listening (G1 is stricter than the code; a decision for the three amigos).
- Demo numbers in DEMO.md / examples.js are stale after the A8 fix (transcript example is now 66/C, not 62/D); the definition of done says DEMO.md is regenerated when the linter changes.
- server/data/library.json.tmp-27896 is a crashed-write leftover that is committed to git; it should be removed with git rm.
- H8: "download in progress" and "cancel settling" sub-cases need a model file and stay nightly; the other three states are asserted in the browser.

3. Environment

Operating system	Windows_NT 10.0.22631 (x64)
Node.js	v24.22.1
Playwright / Chromium	^1.63.0 / 1.63.0

Electron	^44.1.1
Model provider under test	Scripted OpenAI-compatible stub (no key, no model file); the local model tier is nightly on the GPU machine
Packaged installer	not built in this run
Isolation	Each test file boots its own server on an OS-assigned port with private data and model directories

4. Results by acceptance criterion

A — Scoring a prompt, with no model involved

As a person writing prompts I want an instant, deterministic score with concrete findings So that I can improve a prompt before spending any model time on it

ID	Scenario and acceptance criteria	Seam	Result	Time / note
A1	**A pasted prompt is scored before anything is contacted** • **When** I paste "write a blog post about our new feature, make it good and professional..." into the editor • **Then** within a few hundred milliseconds I see a score out of 100 and a letter grade • **And** I see five category bars: Clarity, Specificity, Context, Format and limits, Structure • **And** I see a non-empty list of issues • **And** no request has been made to any provider	api	PASS	685 ms
A2	**The same prompt always produces the same score** • **When** the same prompt is analysed twice with the same task type • **Then** the score, the category breakdown and the ordered issue list are identical	api	PASS	32 ms
A3	**Every finding tells the user what to do about it** • **When** a prompt with several defects is analysed • **Then** every issue has a title, a severity, a category and a suggestion • **And** issues are ordered from most severe to least	api	PASS	8 ms
A4	**A small edit never swings the score wildly** • **Given** a prompt scoring somewhere in the middle • **When** I add one neutral word to it • **Then** the overall score moves by at most a few points • **And** a rewrite that only removes filler words never scores lower than the original	api	PASS	26 ms
A5	**A broken short prompt scores below a clean short prompt** • **Given** two prompts of the same length, one clean and one with no verb, format or scope • **When** both are scored • **Then** the clean one scores materially higher	api	PASS	16 ms

A6	**The task type changes which findings apply** • **Given** the code prompt "fix my login function, it breaks sometimes..." • **When** it is scored with task type General • **Then** the "audience not identified" finding is present • **When** it is scored with task type Code and engineering • **Then** the "audience not identified" finding is absent • **And** the "no length or scope limit" finding is low priority rather than a defect	api	PASS	12 ms
A7	**Code inside a prompt is not linted as if it were prose** • **Given** a prompt containing a fenced code block with SHOUTED constants and vague-looking identifiers • **When** it is scored • **Then** no wording finding cites anything from inside the code • **But** the structure rules still see the whole prompt	api	PASS	8 ms
A8	**A prompt that refers to input it did not attach is a serious finding** • **Given** "Summarize the customer interview transcript below..." with nothing attached • **When** it is scored • **Then** there is a high-severity finding that input is referenced but not attached • **And** its suggestion tells me to add a delimited block • **Given** the same instruction with the material pasted right below it • **When** it is scored • **Then** the missing-input finding is absent and at most a low structure note remains	api	PASS	18 ms
A9	**A descriptor-style image prompt is not punished for being one** • **Given** a comma-separated image prompt • **When** it is scored with task type Image • **Then** there is no finding for a missing task verb, role or output format	api	PASS	13 ms
A10	**A good prompt is told what it got right** • **Given** a well-formed prompt with a role, an output format and a bounded scope • **When** it is scored • **Then** it is in the A band • **And** the panel lists what it does well	api	PASS	6 ms
A11	**An oversized prompt is refused politely rather than hanging the app** • **When** a prompt of exactly 60,000 characters is analysed • **Then** it returns within the interactive budget • **When** a prompt of 60,001 characters is analysed • **Then** it is refused with a message naming the length and the limit • **And** the fix route refuses it the same way	api	PASS	34 ms

A12	**An empty editor is an empty state, not an error** • **When** nothing at all is analysed • **Then** the result is an empty state rather than an error or a zero score presented as a judgement	api	PASS	9 ms

B — Fixing a prompt

As a person with a weak prompt I want the tool to rewrite it and show me exactly what changed and why So that I can trust the rewrite instead of taking it on faith

ID	Scenario and acceptance criteria	Seam	Result	Time / note
B1	**The whole journey, end to end** • **Given** the blog prompt that scores 60 with eleven issues • **When** I fix it at task type Writing and strength Balanced • **Then** I receive a rewritten prompt, a one-sentence summary, itemised changes with what and why • **And** any assumptions, questions and techniques the model reports • **And** a before score and an after score measured with identical settings • **And** the run details say which provider and model answered and how long it took	api	PASS	1.3 s
B2	**The rewrite addresses the problems the user was shown** • **Given** a prompt whose issue list I have read • **When** I fix it • **Then** the findings the model was given are exactly the findings I was shown	api	PASS	33 ms
B3	**The tool never invents facts about the user's situation** • **Given** a prompt that says "our new feature" without naming it • **When** the model returns a rewrite containing a marked placeholder • **Then** the placeholder is scored as a reminder, not a defect, in the after score • **But** the same placeholder in an original prompt is scored as a defect	api	PASS	36 ms
B4	**Failure has a face** • **Given** the provider answers with a server error • **When** I press Fix • **Then** I see one sentence naming the provider • **And** no stack trace, raw JSON or HTTP status appears in the message • **And** the error says whether retrying is worth it	api	PASS	22 ms
B5	**A fix can be cancelled and the machine is handed back** • **Given** the model takes a while to answer • **When** I cancel the fix mid-generation • **Then** the server abandons its request to the provider • **And** no corrective retry is started	api	PASS	1.2 s

B6	**A stalled provider gives up in bounded time** • **Given** the provider accepts the connection and never sends headers • **When** I press Fix • **Then** the attempt is abandoned at the timeout and marked retryable • **Given** the provider sends headers and then stalls the body • **When** I press Fix • **Then** the attempt is abandoned at the timeout and marked retryable	api	PASS	1.6 s
B7	**A truncated reply is reported as a truncated reply** • **Given** the provider stops at its output limit mid-answer • **When** I press Fix • **Then** I am told the reply was cut off and that retrying may help • **And** I am not told the model returned malformed data	api	PASS	11 ms
B8	**Nonsense from the client is coerced, never a server error** • **When** options are sent as a string, an array, null, or with unknown extra fields • **Then** each request succeeds with defaults or fails with a client error • **And** none of them produces a server error	api	PASS	55 ms
B9	**An empty prompt is refused before any model is contacted** • **When** I press Fix with only whitespace in the editor • **Then** it is refused with an explanation • **And** no provider call was made	api	PASS	5 ms
B10	**The last ten fixes stay comparable** • **Given** I have run twelve fixes in one session • **When** I use the previous and next controls • **Then** only the ten most recent are reachable • **And** the counter reads correctly and clamps at both ends • **And** the Fixed, Diff, Issues and Changes tabs all follow the selection together	api, browser	PASS	3.6 s

C — The strength contract and the rewrite guard

As a person who chose how much of my text may change I want that choice enforced and explained when the model ignores it So that "Light touch" means what it says

ID	Scenario and acceptance criteria	Seam	Result	Time / note
C1	**Strength is a promise about the user's own words** • **When** I fix the same prompt at Light touch, Balanced and Full rebuild • **Then** the run details state a retention floor of 60%, 30% and none respectively • **And** the presets offered to the interface list exactly those three strengths	api	PASS	1.0 s

C2	**A Light touch rewrite that throws the user's words away is retried, and the faithful attempt is kept** • **Given** the ten-word complaint "I changed the strgnth but it still changes a lot" • **And** the model first returns an entirely different prompt, then a faithful typo fix • **When** I fix it at Light touch • **Then** I receive the faithful edit • **And** the run details show two attempts and no warning • **And** the retry was told the specific reason the first attempt was rejected	api	PASS	20 ms
C3	**When both attempts overshoot, the user is warned and still gets the better one** • **Given** the model returns a different prompt twice • **When** I fix the complaint at Light touch • **Then** I still receive a rewrite • **And** a warning names the strength and the percentage of my words that survived • **And** the advice is never the strength I am already on	api	PASS	50 ms
C4	**Light touch is never asked to do the impossible** • **Given** a prompt whose findings include missing context, audience, format and limits • **When** I fix it at Light touch • **Then** the model was shown none of those additive findings • **When** I fix it at Balanced • **Then** the model was shown them	api	PASS	44 ms
C5	**Keeping every word and bolting scaffolding onto it is also a violation** • **Given** the model keeps every word and appends a role line and three sections, twice • **When** I fix the complaint at Light touch • **Then** it is retried once • **And** the warning says the model added too much, not that it removed too much	api	PASS	16 ms
C6	**Full rebuild is genuinely unbounded** • **Given** the model returns an entirely different prompt • **When** I fix the complaint at Full rebuild • **Then** I receive it with no warning of any kind • **And** only one attempt was made	api	PASS	11 ms
C7	**The tool's own instructions never reach the user** • **Given** the model pastes its instructions after my text, twice • **When** I fix the complaint at Light touch • **Then** the boilerplate is stripped from the result • **And** every line I wrote survives • **And** I am warned to check the result carefully • **And** the output is never empty	api	PASS	43 ms

C8	**A user's own finding-shaped text is not mistaken for our boilerplate** • **Given** my prompt legitimately contains bracketed severity tags like a linter report • **And** the model returns it lightly edited • **When** I fix it at Light touch • **Then** I get my text back with no leak warning	api	PASS	14 ms
C9	**When two attempts both fall short, the choice between them is predictable** • **Given** the first attempt diverges and the second leaks instructions • **When** I fix at Light touch • **Then** the divergent attempt is kept, with a retention warning • **Given** the first attempt leaks instructions and the second diverges • **When** I fix at Light touch • **Then** the divergent attempt is kept, with a retention warning	api	PASS	30 ms
C10	**A failed corrective retry never becomes a server error** • **Given** the first attempt overshoots and the retry fails upstream • **When** I fix at Light touch • **Then** I receive the first attempt • **And** the warning also says the retry failed and why	api	PASS	12 ms

D — Learning from the user's own library

As a person who has saved rewrites I liked I want future fixes to match the amount of change I kept before So that the tool adapts to me without any configuration

ID	Scenario and acceptance criteria	Seam	Result	Time / note
D1	**The tool learns how much change this user actually likes** • **Given** I have saved a rewrite of a similar blog prompt that scored higher than its original • **When** I fix a new blog prompt • **Then** the model was shown that before/after pair as an example • **And** the run details say one example was used	api	PASS	1.0 s
D2	**Only examples worth imitating are used** • **Given** a saved entry whose rewrite scored no better than its original • **When** I fix a similar prompt • **Then** that entry was not shown to the model • **Given** the prompt I am fixing is itself already in the library with a higher after score • **When** I fix it • **Then** it was not shown to the model as an example of itself	api	PASS	140 ms

D3	**The same task type is preferred** • **Given** two saved entries of equal resemblance, one with task type Writing and one with Code • **When** I fix a similar prompt at task type Writing and only one example fits • **Then** the Writing entry is the one shown	api	PASS	70 ms
D4	**The user can turn it off, and it never costs anything** • **Given** a saved entry that would normally be used • **When** I fix a similar prompt with the library toggle off • **Then** no examples were shown and the run details say zero were used • **And** the lookup made no network request beyond the model call itself	api	PASS	31 ms
D5	**A retry sees the same examples as the first attempt** • **Given** a saved entry that will be used • **And** the model overshoots on the first attempt • **When** I fix at Light touch • **Then** both attempts were shown the same example	api	PASS	60 ms
D6	**A rewrite that parrots an example back is caught** • **Given** a saved entry that will be used • **And** the model returns the example's text as its answer, twice • **When** I fix a similar prompt • **Then** it is treated as leaked boilerplate rather than returned as my rewrite	api	PASS	36 ms

E — The prompt library

As a person who fixes prompts regularly I want to keep the ones I liked, find them again, and move them between machines So that my work is never lost and never silently overwritten

ID	Scenario and acceptance criteria	Seam	Result	Time / note
E1	**Save it, find it, reopen it, delete it** • **When** I save a completed fix • **Then** it appears in the library with its scores, provider and model • **When** I search for a word from the original • **Then** only matching entries are listed • **When** I delete it • **Then** it is gone immediately	api	PASS	814 ms
E2	**A hand-edited library file loads anyway** • **Given** the library file contains a null entry, a number where a string belongs, an entry with no id and one valid entry • **When** I open the library • **Then** the valid entry is listed and the rest are dropped silently • **Given** the library file is not valid JSON at all • **When** I open the library • **Then** it is empty rather than an error • **And** the broken file has been moved aside, not deleted	api	PASS	37 ms

E3	**A crash during a save cannot corrupt the library** • **When** twenty saves race each other • **Then** the library file is valid JSON at every moment it is read • **And** every save is present afterwards • **And** no temporary file is left behind	api	**PASS**	1.8 s
E4	**The library is bounded and drops the oldest first** • **Given** the library holds 500 entries • **When** I save one more • **Then** the newest is present, the oldest is gone, and the count is still 500	api	**PASS**	108 ms
E5	**A library moves between machines** • **When** I export the library • **Then** I get a JSON file named with today's date • **When** I import that file into a library that already has some of the entries • **Then** the unknown entries are added and the known ones are skipped, not overwritten • **And** malformed entries are dropped • **And** the reply counts what was imported and skipped • **When** I import the same file again • **Then** nothing is added	api	**PASS**	243 ms
E6	**Importing the wrong file says so in plain words** • **When** I import a JSON object that is not a library • **Then** I am told what shape was expected • **And** the library is unchanged	api	**PASS**	48 ms
E7	**The library lives where the documentation says it lives** • **Given** the data directory override is set • **When** I save an entry • **Then** the library file is written inside that directory • **And** nothing is written to the project's own data folder	api	**PASS**	19 ms

F — The local model

As a person who wants nothing to leave my machine I want the built-in model to download, load and run without configuration So that the app works offline and I always know its state

ID	Scenario and acceptance criteria	Seam	Result	Time / note
F1	**A first-run user with no model is told exactly what to do** • **Given** the local provider is selected and no model is on disk • **When** I open the app • **Then** the status says the model is missing and names it with its size • **And** the catalogue shows every tier and whether it is downloaded • **When** I press Fix anyway • **Then** I am told the model is not downloaded, not a generic failure • **And** linting still works	api	**PASS**	1.0 s

F2	**The download is visible, resumable and cancellable** • **When** I start the download • **Then** I see bytes and a percentage • **When** I cancel it • **Then** the state is "missing" with no error and the Download button is back • **When** I interrupt and restart it • **Then** it resumes rather than starting from zero	nightly	PENDING	nightly on the GPU machine: needs a model file
F3	**A download that produced no usable file says so** • **Given** a download that completes but leaves a file of the wrong size • **When** it finishes • **Then** the state is an error with a message, not ready	nightly	PENDING	nightly on the GPU machine: needs a model file
F4	**The machine picks a sensible model on its own** • **Given** an explicit tier "lite" in configuration • **When** I open the app • **Then** the selected tier is lite regardless of this machine's memory	api	PASS	985 ms
F5	**Switching models is safe at any moment** • **When** I select an unrecognised tier • **Then** it is rejected with an explanation • **When** I select a valid tier that is not downloaded • **Then** the selection applies and the status says it is missing	api	PASS	28 ms
F6	**Loading is never confused about which model it is loading** • **Given** a load in flight for one tier • **When** a request arrives for a different tier • **Then** it is not satisfied by the load in flight	nightly	PENDING	nightly on the GPU machine: needs a model file
F7	**The GPU is used when it exists and its absence is not a failure** • **When** the model loads on this machine • **Then** the status names the backend, and on CPU the app still works	nightly	PENDING	nightly on the GPU machine: needs a model file
F8	**A prompt too long for the model is refused with advice, not truncated** • **Given** a prompt exceeding the model's context • **When** I press Fix • **Then** I am told it is too long for the local model and offered alternatives before generation starts	nightly	PENDING	nightly on the GPU machine: needs a model file
F9	**The result is always structurally valid** • **When** the smallest model generates on a difficult prompt • **Then** I get a structured result or a clear error, never a malformed one	nightly	PENDING	nightly on the GPU machine: needs a model file
F10	**Quitting releases the model** • **Given** a loaded model • **When** I close the window • **Then** the model is unloaded and the process exits within a bounded time	desktop, nightly	PENDING	desktop tier, nightly

F11	**Nothing leaves the machine** • **Given** no cloud provider is configured • **When** I lint, fix, save and export • **Then** all four succeed • **And** the server has reached no address off this machine • **And** the page has asked for nothing beyond its own origin	api, browser	PASS	4.3 s

G — Providers and privacy

As a person who may have put an API key in configuration I want it used only where I intended and never exposed
So that switching providers is safe

ID	Scenario and acceptance criteria	Seam	Result	Time / note
G1	**The app offers only providers that can actually work** • **Given** only the OpenAI-compatible endpoint is configured • **When** I read the configuration • **Then** that provider is marked configured and every other one is not • **And** the configured default provider is what the interface selects • **Given** nothing at all is configured • **Then** the default provider is local	api	PASS	1.5 s
G2	**Keys never reach the browser** • **When** every route is exercised, including failures • **Then** no response body contains the API key	api	PASS	353 ms
G3	**A client cannot redirect a keyed provider** • **Given** a request that supplies its own endpoint address for the keyed provider • **When** I fix a prompt • **Then** the request still goes to the configured endpoint • **Given** a request that supplies a non-http address for a key-less endpoint • **Then** it is refused	api	PASS	59 ms
G4	**Model lists are live where possible and honest where not** • **Given** the provider answers with its model list • **When** I ask for models • **Then** I get the live list, labelled live • **Given** the provider rejects the key • **When** I ask for models • **Then** I am told the key was rejected, not shown a fallback list • **Given** a provider with no key configured • **When** I ask for models • **Then** I am told the key is missing instead of a guess	api	PASS	20 ms
G5	**The journey is the same on every provider** • **When** the same prompt is fixed on the local provider and the compatible one • **Then** the shape of the result and the guard behaviour are identical	api, nightly	PENDING	nightly: needs the local model

G6	**The API is reachable only from this machine** • **When** a request arrives with a foreign origin • **Then** it is not granted cross-origin access • **When** a request arrives from a localhost origin • **Then** it is	api	PASS	11 ms

H — The editor and the results interface

As a first-time user I want the interface to explain itself and never lie about what it is showing So that I can trust the score on screen

ID	Scenario and acceptance criteria	Seam	Result	Time / note
H1	**The first thirty seconds** • **When** I open the app for the first time • **Then** I see an empty editor with an explanatory placeholder, an example gallery and a sample button • **When** I click an example • **Then** the prompt, task type and strength are set and the score and issues appear	browser	PASS	3.2 s
H2	**All eight built-in examples load and lint** • **When** I choose each example in turn • **Then** the prompt, task type and strength are set and every other option is left alone	browser	PASS	2.0 s
H3	**A broken example list is an empty gallery, not a broken app** • **Given** the examples cannot be fetched • **When** I open the app • **Then** the gallery is absent and everything else works	browser	PASS	1.8 s
H4	**Editing after a fix does the honest thing** • **Given** a completed fix on screen • **When** I edit the prompt • **Then** the Issues tab shows the live analysis of the new text and the fix result is parked	browser	PASS	1.9 s
H5	**A deliberately pinned older result keeps its tab** • **Given** I have stepped back to an earlier fix • **When** I continue to edit • **Then** the pinned result keeps the Issues tab	browser	PASS	1.5 s
H6	**Apply and undo** • **When** I press Apply • **Then** the fixed text replaces the editor content, the score re-lints and Undo appears • **When** I press Undo • **Then** the original text returns and Undo disappears • **When** I apply and then edit the applied text • **Then** Undo is no longer offered	browser	PASS	1.8 s
H7	**Copy puts the rewrite on the clipboard** • **When** I press Copy • **Then** the clipboard holds the fixed prompt exactly as displayed	browser	PASS	1.4 s

H8	**Fix is disabled when it cannot succeed, and says why** • **Given** each of: empty editor, no provider, model missing, download in progress, cancel settling • **Then** the Fix button is disabled with a visible reason	browser	PASS	1.5 s
H9	**A remembered model choice is reconciled with the server** • **Given** I previously chose a tier and the server is on another • **When** I open the app • **Then** my choice is sent to the server, not merely displayed	browser	PASS	463 ms
H10	**Warnings read like sentences a person wrote** • **Given** each kind of guard warning • **Then** the headline matches the kind and an unknown kind shows the raw text	browser	PASS	5.2 s
H11	**The app is usable from the keyboard** • **When** I tab through the interface • **Then** every control is reachable in a sensible order • **And** Ctrl+Enter runs a fix, Enter on a nested Delete deletes, Escape closes the drawer	browser	PASS	1.7 s
H12	**Text meets contrast requirements** • **Then** every foreground/background pairing meets AA contrast	browser	PASS	1.3 s
H13	**The window works at a small size** • **Given** a 1024 by 720 window • **Then** nothing is clipped and no pane scrolls horizontally	browser	PASS	1.2 s
H14	**Every action without a visible result reports itself** • **When** I save, import, export, copy and apply • **Then** each shows a confirmation stating the outcome	browser	PASS	1.9 s
H15	**The interface links to the project website, and the link leaves the app the safe way** • **Given** the server names the project website in its config • **When** I open the app • **Then** the top bar offers a "What's new" link to that address, marked to open outside the app • **When** I click it • **Then** the website opens in a page of its own and the editor is still where I left it	browser	PASS	374 ms

I — Showing what changed

As a person reading a rewrite I want to see exactly which words changed So that the guard's claims about "how much survived" are verifiable

ID	Scenario and acceptance criteria	Seam	Result	Time / note

I1	**The user can see exactly what changed and nothing is hidden** • **Given** an original and a rewrite • **When** I view the diff • **Then** removals and additions are distinguishable at word level • **Given** identical texts • **Then** the diff shows them as identical	library-seam	PASS	8 ms
I2	**One changed word in a long document is one changed word** • **Given** a prompt of over a thousand words with a single word inserted • **When** I view the diff • **Then** exactly one insertion is shown and it renders quickly • **Given** thousands of lines with one line changed • **Then** the diff finds the one line quickly	library-seam	PASS	70 ms
I3	**A region too large to align is reported, not hidden** • **Given** a change too large to align word by word • **When** I view the diff • **Then** the region is reported as replaced wholesale, not shown as empty	library-seam	PASS	48 ms

J — The CI linter

As a team keeping prompts in a repository I want to gate them in CI with the same rules the app uses So that a prompt below the bar cannot be merged

ID	Scenario and acceptance criteria	Seam	Result	Time / note
J1	**A team can gate its prompts in CI with no server, no model and no key** • **When** I run the linter over a passing set with a minimum score and a severity threshold • **Then** it exits 0 • **When** I run it over a set containing a vague prompt • **Then** it exits 1 and names the offending file	cli	PASS	440 ms
J2	**The gate uses the same rules as the app** • **When** the same text and task type are scored by the linter and by the app • **Then** the score, categories and issues are identical	cli	PASS	1.4 s
J3	**Directories are searched the way the documentation says** • **Given** a tree with .md, .txt and .prompt files and other file types • **When** I point the linter at the directory • **Then** exactly the three extensions are linted, recursively	cli	PASS	530 ms
J4	**A file can declare its own task type** • **Given** a file whose first line is the task-type comment • **When** it is linted • **Then** that task type is used and the comment does not affect the score	cli	PASS	844 ms

J5	**Machine-readable output is machine-readable** • **When** I run with --json • **Then** stdout is exactly one parseable object with every file's score, categories and issues • **When** I run with --quiet • **Then** only the summary line is printed	cli	PASS	446 ms
J6	**A misconfigured job is distinguishable from failing prompts** • **When** I run with no paths, an unknown flag, an unknown task type, or a missing path • **Then** each exits 2 with usage on stderr	cli	PASS	594 ms

K — The desktop application

As a person who installed Whetprompt I want it to behave like a well-mannered desktop app So that installing, quitting and configuring it hold no surprises

ID	Scenario and acceptance criteria	Seam	Result	Time / note
K1	**Install, run, uninstall, reinstall** • **Given** the built installer on a clean machine • **When** I install, run, uninstall and reinstall • **Then** the model and the library survive	desktop, nightly	PENDING	desktop tier, nightly: needs the packaged installer on a clean machine
K2	**The window opens our interface and nothing else** • **When** a same-origin navigation occurs • **Then** it proceeds • **When** a file is dropped, an external link followed, or a lookalike origin navigated to • **Then** each is blocked in the window	desktop, nightly	PASS	3.9 s
K3	**Quitting is deterministic** • **Given** a loaded model • **When** I quit • **Then** the quit waits for unload, and a failing or hung unload still quits in bounded time	desktop, nightly	PASS	2.0 s
K4	**Configuration is read from where the documentation says** • **Given** the packaged app • **Then** the per-user .env overrides the desktop defaults and the working-directory .env is ignored • **Given** the app run from source • **Then** the project .env wins over the per-user one, and a shell variable wins over both	desktop, nightly	PENDING	desktop tier, nightly: packaged vs source .env matrix (logic covered by electron/env.test.js)
K5	**The app finds a free port and its interface finds the app** • **When** two copies of the server start at once • **Then** both get a port and both answer	api	PASS	724 ms
K6	**An unknown API route is a not-found, not the application shell** • **When** I request an API path that does not exist • **Then** I get a not-found response, not the interface HTML	api	PASS	639 ms

L — Configuration, limits and errors

As a person who did not read the configuration section I want the app to work with no configuration and to enforce the limits it advertises So that nothing surprising happens later

ID	Scenario and acceptance criteria	Seam	Result	Time / note
L1	**Everything has a working default** • **Given** no configuration at all • **When** the server starts • **Then** it starts, selects the local provider and reports the limits it enforces	api	PASS	1.8 s
L2	**Port precedence and the development proxy** • **Given** a port of zero • **When** the server starts • **Then** it reports the port it was actually given	api	PASS	17 ms
L3	**Errors have one consistent shape** • **When** failures are produced on several routes • **Then** each carries a message, a code, a retryable flag and where relevant a provider	api	PASS	378 ms
L4	**The advertised limits are real** • **When** I walk up to the prompt length limit and one step past it • **Then** the boundary is accepted and the step past it is refused with the limit named • **When** I walk up to the library cap and one step past it • **Then** the cap holds	api	PASS	175 ms

M — Marking a rewrite and fixing it again

As a person reading a rewrite that is nearly right I want to point at the parts I loved and the parts I did not So that the next rewrite keeps the first and changes the second without my starting over

ID	Scenario and acceptance criteria	Seam	Result	Time / note

M1	**The model is shown what I marked, and the result says how many marks it was given** • **Given** I marked one passage of the rewrite to keep and one to change • **When** I fix again with my marks • **Then** the model was shown the rewrite I marked and both passages, each under its own verdict • **And** it was still asked to fix my original prompt, with the same findings as before • **And** the new rewrite has the kept passage word for word and no longer has the other as it was • **And** the run details say one kept passage and one passage to change were applied, and none ignored • **And** the before score is still the score of my original prompt • **Given** a rewrite in which two words of the sentence I kept stand once more, on their own, and there I marked them to change • **When** I fix again with my marks • **Then** the model is shown both marks, and told that inside the kept sentence the kept sentence wins • **And** a rewrite that rewords those words where they stood alone is accepted at the first attempt, with no warning	api	PASS	1.5 s
M2	**A rewrite that drops a passage I kept is retried, and the faithful attempt is kept** • **Given** the model first paraphrases the passage I kept and leaves the other as it was, then follows my marks • **When** I fix again with my marks • **Then** I receive the attempt that follows them, with no warning • **And** the run details show two attempts • **And** the retry was told which passage it had dropped and which it had left as it was, each under its own verdict • **And** it was shown my marks again	api	PASS	54 ms
M3	**When the model ignores my marks twice, I still get a result and I am told what was not honoured** • **Given** the model ignores my marks on both attempts • **When** I fix again with my marks • **Then** I still receive a rewrite • **And** a warning says how many kept passages are missing and how many passages to change are still there • **And** the run details name those passages • **And** in the interface the warning has its own headline, and the refined note claims no mark that was ignored	api, browser	PASS	1.9 s

M4	**Nonsense marks are coerced, never a server error** • **When** marks arrive as a string, a number, a list, null, or holding things that are not text • **Then** each request succeeds as an ordinary fix and none of them produces a server error • **When** every mark points at words that are not in the rewrite • **Then** it is an ordinary fix: the model is shown no marks and the result mentions none • **When** a passage is marked twice, or padded with spaces, among marks that point at nothing • **Then** the model is shown it once, trimmed, and nothing else • **When** a passage is marked both to keep and to change, and those words stand in only one place in the rewrite • **Then** the change wins • **When** the same words stand in two places and are marked both ways • **Then** the model is shown both marks, and rewording one of the two places honours both • **When** twenty-five passages are marked the same way, or one mark runs to 2,500 characters • **Then** the model is shown the first twenty, and the first 2,000 characters, and the result counts twenty • **When** the marked rewrite is longer than a prompt may be • **Then** it is refused with a message naming the length and the limit	api	PASS	445 ms
M5	**A fix without marks is the fix it always was** • **When** I fix the blog prompt with no marks • **Then** the model is shown no earlier rewrite and no marks • **And** the result says nothing about marks • **Given** I have since fixed again with marks • **When** I fix the blog prompt once more with no marks • **Then** the earlier marks have no influence on it • **Given** a model whose rewrite holds a "<user_feedback>" slot of its own for the prompt's user to fill • **When** I fix the blog prompt with no marks • **Then** the rewrite comes back with its slot intact, after one attempt and with no warning • **And** marking that rewrite and fixing again leaves the slot where it was, again with no warning	api	PASS	144 ms

M6	**I mark what I loved and what I did not** • **Given** a completed fix on the Fixed tab • **Then** both marking buttons are disabled, because nothing is selected • **When** I select words outside the rewrite, or drag from outside into it • **Then** both buttons stay disabled • **When** a selection starts in the rewrite and runs on into a toast • **Then** both buttons are disabled • **When** a selection of the last line ends where a triple click leaves it, just outside the rewrite • **Then** that line can be marked • **When** I double-click a word of the rewrite and press "Keep it — I loved it" • **Then** that word is highlighted as kept and the selection is gone • **When** I drag across a sentence and press "Change it — I didn't like it" • **Then** that sentence is highlighted as to change • **And** the bar counts one kept and one to change and offers "Fix again with my marks" • **Given** a rewrite longer than the window, scrolled until the marking bar is stuck above it • **When** I drag a selection upwards from the rewrite onto the bar, from plain text or from a highlight • **Then** the selection stays inside the rewrite and both buttons can be pressed • **And** the bar takes the mouse again when the press ends, even a press that ends without a mouse-up • **When** twenty passages are kept and I select another • **Then** "Keep it — I loved it" is disabled and says twenty is the most the model is shown, and the other button is not • **When** I remove one highlight • **Then** the passage can be kept	browser	PASS	6.9 s
M7	**A mark can be changed and taken back** • **Given** a rewrite with two passages kept and one to change • **When** I drag across a kept passage again and press "Change it — I didn't like it" • **Then** the newer verdict replaces the older one • **When** I click a highlighted passage • **Then** its highlight is removed and the count follows • **When** I press Enter on a highlighted passage from the keyboard • **Then** its highlight is removed too • **When** I press Ctrl+Enter in the rewrite or on the bar while a mark is showing • **Then** no fix is started and the mark is still there • **When** I press "Clear marks" from the keyboard • **Then** every highlight is gone, and so is the offer to fix again • **And** the focus is on the rewrite, which shows no ring, and not at the top of the page • **When** I click in the rewrite and press Ctrl+Enter • **Then** a fresh fix runs, as it does from anywhere else	browser	PASS	2.6 s

M8	**"Fix again with my marks" sends exactly what I marked** • **Given** I kept one passage and marked another to change • **When** I press "Fix again with my marks" from the keyboard • **Then** the model was shown exactly those two passages and the rewrite they came from • **And** I am told it was refined, with the before and after scores • **And** the new rewrite joins the history as "2 of 2" • **And** the What changed line says it was refined with my marks, one kept and one changed • **And** the new rewrite carries no highlights, and the focus is on it, not at the top of the page • **And** stepping back to the first rewrite does not bring the old highlights back • **When** I mark the first rewrite again and step forward and back through the history • **Then** the mark is gone • **When** I mark it once more and press "Fix prompt" • **Then** the fresh rewrite carries no highlights, and stepping back to the first one does not bring the mark back • **Given** the fresh rewrite has two words of the sentence I keep standing once more on their own, and there I mark them to change • **When** I press "Fix again with my marks" • **Then** the model was shown one passage to keep and one to change, as the bar counted • **And** the What changed line says one kept and one changed, with no warning	browser	PASS	2.3 s
M9	**The rewrite stays exact while marks are showing** • **Given** highlights of both kinds on the rewrite, one of two lines and one of four lines and more than a hundred characters • **Then** the rewrite on screen is still the fixed prompt, character for character • **And** each highlight is a button whose name gives a screen reader the verdict and the whole passage, its line breaks as spaces • **When** I press Copy • **Then** the clipboard holds the fixed prompt, with nothing from the marking bar in it	browser	PASS	1.6 s
M10	**Marks are readable and fit a small window** • **Given** a 1024 by 720 window with highlights of both kinds and the count showing • **Then** every piece of text, inside both highlight colours and on the bar, meets AA contrast • **And** nothing scrolls horizontally and "Fix again with my marks" is on screen	browser	PASS	1.4 s

M11	**Fixing again still works after I edited the prompt** • **Given** a completed fix on which I marked a passage • **When** I type a character in the editor • **Then** the rewrite is parked behind the edited-prompt notice, and there is nothing to fix again with • **When** I delete that character again • **Then** the rewrite is back with my mark on it • **When** I change the text in the editor and press "Show last fix" • **Then** the parked rewrite comes back with my mark still on it • **When** I press "Fix again with my marks" • **Then** the new rewrite is shown, not parked behind the edited-prompt notice • **And** the model was asked to refine the prompt that rewrite was made for, not the text now in the editor • **And** the editor still holds my edit	browser	PASS	1.6 s

N — Looking the same every time

As a developer changing Whetprompt's interface I want one command to tell me which screens look different, and which element changed So that a change to the look is something I approve, never something a user finds

ID	Scenario and acceptance criteria	Seam	Result	Time / note
N1	**Every screen, captured again, matches its approved picture** • **When** every screen is captured again at both window sizes • **Then** the check passes • **And** no screen reports a changed, added or removed region at either size	visual	PASS	22.8 s
N2	**A rewrite that came back different is reported on the Fixed screen, by name** • **Given** the model now words one line of the rewrite differently • **When** the Fixed, Issues and Changes screens are captured • **Then** the check fails • **And** the Fixed screen reports a change on that one line and names the rewrite as the element that changed • **And** the Issues and Changes screens, which do not show the rewrite, report nothing	visual	PASS	7.5 s

N3	**Marks are part of the picture** • **When** the approved picture of the marked screen is compared with the unmarked one • **Then** the difference names the marking bar, its "Clear marks" and "Fix again with my marks" buttons and both highlighted passages • **And** each highlighted passage is a reported region • **And** nothing in the editor pane, and nothing above the marking bar, is reported • **Given** both highlights have lost all their paint, and nothing has moved • **When** the marked screen is captured at both window sizes • **Then** at each size the check fails and names the two highlighted passages, each with changed pixels behind it, and nothing else • **Given** the highlight of a kept passage has lost its green • **When** the marked screen is captured • **Then** the check fails and names that highlighted passage, and nothing else	visual	PASS	5.6 s
N4	**What honestly varies between two runs raises no alarm** • **Given** a model that takes longer to answer and reports other token counts • **And** a server whose calendar is weeks ahead, so a saved prompt carries another date • **When** the Fixed, Changes and Library screens are captured • **Then** the check passes and no screen reports a region	visual	PASS	12.8 s
N5	**A screen with no approved picture, or a changed look, fails the check until I approve it** • **Given** approved pictures that lack one screen • **And** a Fix prompt button that has been restyled • **When** I run "npm run visual" • **Then** it fails: the screen without a picture is reported as new, and the other names the Fix prompt button • **When** I run "npm run visual:approve" • **Then** it succeeds • **When** I run "npm run visual" again • **Then** it passes	visual	PASS	11.1 s

N6	**The one command hands back the verdict and leaves nothing running** • **When** I run "npm run visual" on a screen that has not changed • **Then** it exits 0 • **When** I run it on a screen that has • **Then** it exits 1, and a report a CI job can read has been written • **When** I mistype the name of a screen • **Then** it exits 2 and lists the screens there are • **When** I run it against the commit I am working from instead of against approved pictures, having changed that screen • **Then** it exits 1 and the report names what I changed, although no picture was ever approved for it • **And** after each run the server it started no longer answers and its temporary folders are gone • **And** the commit it compared with is no longer checked out anywhere	visual	PASS	5.8 s
N7	**Pointed at the wrong place, the check says so and harms nothing** • **When** the check is run with no server to look at • **Then** it stops with an error that says to use "npm run visual" • **Given** a Whetprompt that somebody is using, with a prompt saved in its library • **When** the check is pointed at it • **Then** it stops with an error, and the saved prompt is still there	visual	PASS	1.4 s

Generated by `npm run test:report` from `acceptance\report\out\results.json`. Strategy: `docs/ATDD.md`. Narrative report: `docs/ATDD-REPORT.md`.