Whetprompt · Acceptance test-driven development

# Acceptance test results

Run 2026-10-28 12:00:51 UTC · commit 6e81540 (master) · v0.7.0

**PASS**

| 118 | 108 | 0 | 10 |
|---|---|---|---|
| scenarios (acceptance criteria) | passed | failed | pending, with a stated reason |

Every scenario below is a Gherkin acceptance criterion in `acceptance/features/`, executed by a same-named automated test in `acceptance/`. Pending scenarios are registered as tests so they appear in every run and cannot be forgotten.

## 1. Summary by capability

| Capability group | Scenarios | Passed | Failed | Pending | Seams |
|---|---|---|---|---|---|
| A — Scoring a prompt, with no model involved | 12 | 12 | 0 | 0 | api |
| B — Fixing a prompt | 10 | 10 | 0 | 0 | api, browser |
| C — The strength contract and the rewrite guard | 10 | 10 | 0 | 0 | api |
| D — Learning from the user's own library | 6 | 6 | 0 | 0 | api |
| E — The prompt library | 7 | 7 | 0 | 0 | api |
| F — The local model | 11 | 4 | 0 | 7 | api, nightly, desktop, browser |
| G — Providers and privacy | 8 | 7 | 0 | 1 | api, nightly |
| H — The editor and the results interface | 17 | 17 | 0 | 0 | browser |
| I — Showing what changed | 3 | 3 | 0 | 0 | library-seam |
| J — The CI linter | 6 | 6 | 0 | 0 | cli |
| K — The desktop application | 6 | 4 | 0 | 2 | desktop, nightly, api |
| L — Configuration, limits and errors | 4 | 4 | 0 | 0 | api |
| M — Marking a rewrite and fixing it again | 11 | 11 | 0 | 0 | api, browser |
| N — Looking the same every time | 7 | 7 | 0 | 0 | visual |
| **Total** | **118** | **108** | **0** | **10** | **164.4 s of test time** |

## 2. Defects found by the scenarios

**A8 — "Missing input" was no longer detected for the documented example** FIXED

DEMO.md and examples.js say the transcript prompt scores a high-severity "references input that is not clearly attached" with Context 24/100. It scored a low "pasted input is not delimited", because the heuristic counted the rest of the instruction sentence after "transcript below" as pasted input.

**Fix:** server/analyze.js: pasted input starts on a new line or after a colon; the rest of the referencing sentence is instruction.

**G2 — An upstream error could carry the API key to the browser** FIXED

A provider whose error body echoes the key had that body forwarded verbatim, in the error response and inside a successful reply's retry warning. The README promises keys never leave the server.

**Fix:** server/providers.js redact() blanks every configured key at the source; server/index.js applies it again in the error handler.

**D6 — A saved library example returned verbatim was accepted as the rewrite** FIXED

A parroted example shares enough vocabulary with the prompt to clear the Balanced retention floor, and the leak detector only recognised the <examples> wrapper, so another prompt's text was handed back as the user's rewrite.

**Fix:** server/metaprompt.js validateRewrite() receives the examples and treats an exact match with any example as a leak; after two attempts the user gets their original back with a warning naming the library toggle.

**K6 / L3 — API errors did not all have the same shape** FIXED

An unknown /api path returned Express's HTML "Cannot GET" page while every other failure is JSON, and the JSON envelope dropped code/provider when undefined.

**Fix:** server/index.js: JSON 404 for any unmatched /api path through the normal error handler; code and provider always present (null when unknown).

**H12 — Tab count badges were below AA contrast** FIXED

The count badge on an unselected tab ("Issues 11") used --text-faint on --panel-3: 4.18:1, below the 4.5:1 the token's own comment promises. Found by measuring every rendered text node in Chromium, not by reading the tokens.

**Fix:** src/styles.css: .tab .count uses --text-dim.

**H13 — The results pane header pushed Save off the page at 1024px wide** FIXED

Tabs, the history control and Copy/Apply/Save sit in a non-wrapping flex row; at 1024px the Save button ended at 1055px and the whole page scrolled horizontally.

**Fix:** src/styles.css: .pane-head wraps.

### Observations not acted on

- Ollama shows as configured whenever its default URL is set, even with nothing listening (G1 is stricter than the code; a decision for the three amigos).
- Demo numbers in DEMO.md / examples.js are stale after the A8 fix (transcript example is now 66/C, not 62/D); the definition of done says DEMO.md is regenerated when the linter changes.
- server/data/library.json.tmp-27896 is a crashed-write leftover that is committed to git; it should be removed with git rm.
- H8: "download in progress" and "cancel settling" sub-cases need a model file and stay nightly; the other three states are asserted in the browser.

## 3. Environment

| | |
|---|---|
| **Operating system** | Windows_NT 10.0.22631 (x64) |
| **Node.js** | v24.22.1 |
| **Playwright / Chromium** | ^1.63.0 / 1.63.0 |

| | |
|---|---|
| **Electron** | ^44.1.1 |
| **Model provider under test** | Scripted OpenAI-compatible stub (no key, no model file); the local model tier is nightly on the GPU machine |
| **Packaged installer** | not built in this run |
| **Isolation** | Each test file boots its own server on an OS-assigned port with private data and model directories |

## 4. Results by acceptance criterion

### A — Scoring a prompt, with no model involved

*As a person writing prompts I want an instant, deterministic score with concrete findings So that I can improve a prompt before spending any model time on it*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| **A1** | **A pasted prompt is scored before anything is contacted**<br>• **When** I paste "write a blog post about our new feature, make it good and professional..." into the editor<br>• **Then** within a few hundred milliseconds I see a score out of 100 and a letter grade<br>• **And** I see five category bars: Clarity, Specificity, Context, Format and limits, Structure<br>• **And** I see a non-empty list of issues<br>• **And** no request has been made to any provider | api | PASS | 651 ms |
| **A2** | **The same prompt always produces the same score**<br>• **When** the same prompt is analysed twice with the same task type<br>• **Then** the score, the category breakdown and the ordered issue list are identical | api | PASS | 23 ms |
| **A3** | **Every finding tells the user what to do about it**<br>• **When** a prompt with several defects is analysed<br>• **Then** every issue has a title, a severity, a category and a suggestion<br>• **And** issues are ordered from most severe to least | api | PASS | 9 ms |
| **A4** | **A small edit never swings the score wildly**<br>• **Given** a prompt scoring somewhere in the middle<br>• **When** I add one neutral word to it<br>• **Then** the overall score moves by at most a few points<br>• **And** a rewrite that only removes filler words never scores lower than the original | api | PASS | 27 ms |
| **A5** | **A broken short prompt scores below a clean short prompt**<br>• **Given** two prompts of the same length, one clean and one with no verb, format or scope<br>• **When** both are scored<br>• **Then** the clean one scores materially higher | api | PASS | 17 ms |

| | | | | |
|---|---|---|---|---|
| A6 | **The task type changes which findings apply**<br>• **Given** the code prompt "fix my login function, it breaks sometimes..."<br>• **When** it is scored with task type General<br>• **Then** the "audience not identified" finding is present<br>• **When** it is scored with task type Code and engineering<br>• **Then** the "audience not identified" finding is absent<br>• **And** the "no length or scope limit" finding is low priority rather than a defect | api | PASS | 10 ms |
| A7 | **Code inside a prompt is not linted as if it were prose**<br>• **Given** a prompt containing a fenced code block with SHOUTED constants and vague-looking identifiers<br>• **When** it is scored<br>• **Then** no wording finding cites anything from inside the code<br>• **But** the structure rules still see the whole prompt | api | PASS | 4 ms |
| A8 | **A prompt that refers to input it did not attach is a serious finding**<br>• **Given** "Summarize the customer interview transcript below..." with nothing attached<br>• **When** it is scored<br>• **Then** there is a high-severity finding that input is referenced but not attached<br>• **And** its suggestion tells me to add a delimited block<br>• **Given** the same instruction with the material pasted right below it<br>• **When** it is scored<br>• **Then** the missing-input finding is absent and at most a low structure note remains | api | PASS | 14 ms |
| A9 | **A descriptor-style image prompt is not punished for being one**<br>• **Given** a comma-separated image prompt<br>• **When** it is scored with task type Image<br>• **Then** there is no finding for a missing task verb, role or output format | api | PASS | 6 ms |
| A10 | **A good prompt is told what it got right**<br>• **Given** a well-formed prompt with a role, an output format and a bounded scope<br>• **When** it is scored<br>• **Then** it is in the A band<br>• **And** the panel lists what it does well | api | PASS | 6 ms |
| A11 | **An oversized prompt is refused politely rather than hanging the app**<br>• **When** a prompt of exactly 60,000 characters is analysed<br>• **Then** it returns within the interactive budget<br>• **When** a prompt of 60,001 characters is analysed<br>• **Then** it is refused with a message naming the length and the limit<br>• **And** the fix route refuses it the same way | api | PASS | 34 ms |

| | | | | |
|---|---|---|---|---|
| **A12** | **An empty editor is an empty state, not an error**<br>• **When** nothing at all is analysed<br>• **Then** the result is an empty state rather than an error or a zero score presented as a judgement | api | PASS | 7 ms |

## B — Fixing a prompt

*As a person with a weak prompt I want the tool to rewrite it and show me exactly what changed and why So that I can trust the rewrite instead of taking it on faith*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| **B1** | **The whole journey, end to end**<br>• **Given** the blog prompt that scores 60 with eleven issues<br>• **When** I fix it at task type Writing and strength Balanced<br>• **Then** I receive a rewritten prompt, a one-sentence summary, itemised changes with what and why<br>• **And** any assumptions, questions and techniques the model reports<br>• **And** a before score and an after score measured with identical settings<br>• **And** the run details say which provider and model answered and how long it took | api | PASS | 1.1 s |
| **B2** | **The rewrite addresses the problems the user was shown**<br>• **Given** a prompt whose issue list I have read<br>• **When** I fix it<br>• **Then** the findings the model was given are exactly the findings I was shown | api | PASS | 25 ms |
| **B3** | **The tool never invents facts about the user's situation**<br>• **Given** a prompt that says "our new feature" without naming it<br>• **When** the model returns a rewrite containing a marked placeholder<br>• **Then** the placeholder is scored as a reminder, not a defect, in the after score<br>• **But** the same placeholder in an original prompt is scored as a defect | api | PASS | 31 ms |
| **B4** | **Failure has a face**<br>• **Given** the provider answers with a server error<br>• **When** I press Fix<br>• **Then** I see one sentence naming the provider<br>• **And** no stack trace, raw JSON or HTTP status appears in the message<br>• **And** the error says whether retrying is worth it | api | PASS | 13 ms |
| **B5** | **A fix can be cancelled and the machine is handed back**<br>• **Given** the model takes a while to answer<br>• **When** I cancel the fix mid-generation<br>• **Then** the server abandons its request to the provider<br>• **And** no corrective retry is started | api | PASS | 1.2 s |

| | | | | |
|---|---|---|---|---|
| **B6** | **A stalled provider gives up in bounded time**<br>• **Given** the provider accepts the connection and never sends headers<br>• **When** I press Fix<br>• **Then** the attempt is abandoned at the timeout and marked retryable<br>• **Given** the provider sends headers and then stalls the body<br>• **When** I press Fix<br>• **Then** the attempt is abandoned at the timeout and marked retryable | api | PASS | 1.3 s |
| **B7** | **A truncated reply is reported as a truncated reply**<br>• **Given** the provider stops at its output limit mid-answer<br>• **When** I press Fix<br>• **Then** I am told the reply was cut off and that retrying may help<br>• **And** I am not told the model returned malformed data | api | PASS | 12 ms |
| **B8** | **Nonsense from the client is coerced, never a server error**<br>• **When** options are sent as a string, an array, null, or with unknown extra fields<br>• **Then** each request succeeds with defaults or fails with a client error<br>• **And** none of them produces a server error | api | PASS | 64 ms |
| **B9** | **An empty prompt is refused before any model is contacted**<br>• **When** I press Fix with only whitespace in the editor<br>• **Then** it is refused with an explanation<br>• **And** no provider call was made | api | PASS | 5 ms |
| **B10** | **The last ten fixes stay comparable**<br>• **Given** I have run twelve fixes in one session<br>• **When** I use the previous and next controls<br>• **Then** only the ten most recent are reachable<br>• **And** the counter reads correctly and clamps at both ends<br>• **And** the Fixed, Diff, Issues and Changes tabs all follow the selection together | api, browser | PASS | 3.6 s |

## C — The strength contract and the rewrite guard

*As a person who chose how much of my text may change I want that choice enforced and explained when the model ignores it So that "Light touch" means what it says*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| **C1** | **Strength is a promise about the user's own words**<br>• **When** I fix the same prompt at Light touch, Balanced and Full rebuild<br>• **Then** the run details state a retention floor of 60%, 30% and none respectively<br>• **And** the presets offered to the interface list exactly those three strengths | api | PASS | 812 ms |

| | | | | |
|---|---|---|---|---|
| C2 | **A Light touch rewrite that throws the user's words away is retried, and the faithful attempt is kept**<br>• **Given** the ten-word complaint "I changed the strgnth but it still changes a lot"<br>• **And** the model first returns an entirely different prompt, then a faithful typo fix<br>• **When** I fix it at Light touch<br>• **Then** I receive the faithful edit<br>• **And** the run details show two attempts and no warning<br>• **And** the retry was told the specific reason the first attempt was rejected | api | PASS | 23 ms |
| C3 | **When both attempts overshoot, the user is warned and still gets the better one**<br>• **Given** the model returns a different prompt twice<br>• **When** I fix the complaint at Light touch<br>• **Then** I still receive a rewrite<br>• **And** a warning names the strength and the percentage of my words that survived<br>• **And** the advice is never the strength I am already on | api | PASS | 36 ms |
| C4 | **Light touch is never asked to do the impossible**<br>• **Given** a prompt whose findings include missing context, audience, format and limits<br>• **When** I fix it at Light touch<br>• **Then** the model was shown none of those additive findings<br>• **When** I fix it at Balanced<br>• **Then** the model was shown them | api | PASS | 31 ms |
| C5 | **Keeping every word and bolting scaffolding onto it is also a violation**<br>• **Given** the model keeps every word and appends a role line and three sections, twice<br>• **When** I fix the complaint at Light touch<br>• **Then** it is retried once<br>• **And** the warning says the model added too much, not that it removed too much | api | PASS | 17 ms |
| C6 | **Full rebuild is genuinely unbounded**<br>• **Given** the model returns an entirely different prompt<br>• **When** I fix the complaint at Full rebuild<br>• **Then** I receive it with no warning of any kind<br>• **And** only one attempt was made | api | PASS | 10 ms |
| C7 | **The tool's own instructions never reach the user**<br>• **Given** the model pastes its instructions after my text, twice<br>• **When** I fix the complaint at Light touch<br>• **Then** the boilerplate is stripped from the result<br>• **And** every line I wrote survives<br>• **And** I am warned to check the result carefully<br>• **And** the output is never empty | api | PASS | 27 ms |

| | | | | |
|---|---|---|---|---|
| C8 | **A user's own finding-shaped text is not mistaken for our boilerplate**<br>• **Given** my prompt legitimately contains bracketed severity tags like a linter report<br>• **And** the model returns it lightly edited<br>• **When** I fix it at Light touch<br>• **Then** I get my text back with no leak warning | api | PASS | 9 ms |
| C9 | **When two attempts both fall short, the choice between them is predictable**<br>• **Given** the first attempt diverges and the second leaks instructions<br>• **When** I fix at Light touch<br>• **Then** the divergent attempt is kept, with a retention warning<br>• **Given** the first attempt leaks instructions and the second diverges<br>• **When** I fix at Light touch<br>• **Then** the divergent attempt is kept, with a retention warning | api | PASS | 33 ms |
| C10 | **A failed corrective retry never becomes a server error**<br>• **Given** the first attempt overshoots and the retry fails upstream<br>• **When** I fix at Light touch<br>• **Then** I receive the first attempt<br>• **And** the warning also says the retry failed and why | api | PASS | 12 ms |

## D — Learning from the user's own library

*As a person who has saved rewrites I liked I want future fixes to match the amount of change I kept before So that the tool adapts to me without any configuration*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| D1 | **The tool learns how much change this user actually likes**<br>• **Given** I have saved a rewrite of a similar blog prompt that scored higher than its original<br>• **When** I fix a new blog prompt<br>• **Then** the model was shown that before/after pair as an example<br>• **And** the run details say one example was used | api | PASS | 904 ms |
| D2 | **Only examples worth imitating are used**<br>• **Given** a saved entry whose rewrite scored no better than its original<br>• **When** I fix a similar prompt<br>• **Then** that entry was not shown to the model<br>• **Given** the prompt I am fixing is itself already in the library with a higher after score<br>• **When** I fix it<br>• **Then** it was not shown to the model as an example of itself | api | PASS | 92 ms |

| | | | | |
|---|---|---|---|---|
| **D3** | **The same task type is preferred**<br>• **Given** two saved entries of equal resemblance, one with task type Writing and one with Code<br>• **When** I fix a similar prompt at task type Writing and only one example fits<br>• **Then** the Writing entry is the one shown | api | PASS | 73 ms |
| **D4** | **The user can turn it off, and it never costs anything**<br>• **Given** a saved entry that would normally be used<br>• **When** I fix a similar prompt with the library toggle off<br>• **Then** no examples were shown and the run details say zero were used<br>• **And** the lookup made no network request beyond the model call itself | api | PASS | 31 ms |
| **D5** | **A retry sees the same examples as the first attempt**<br>• **Given** a saved entry that will be used<br>• **And** the model overshoots on the first attempt<br>• **When** I fix at Light touch<br>• **Then** both attempts were shown the same example | api | PASS | 46 ms |
| **D6** | **A rewrite that parrots an example back is caught**<br>• **Given** a saved entry that will be used<br>• **And** the model returns the example's text as its answer, twice<br>• **When** I fix a similar prompt<br>• **Then** it is treated as leaked boilerplate rather than returned as my rewrite | api | PASS | 47 ms |

## E — The prompt library

*As a person who fixes prompts regularly I want to keep the ones I liked, find them again, and move them between machines So that my work is never lost and never silently overwritten*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| **E1** | **Save it, find it, reopen it, delete it**<br>• **When** I save a completed fix<br>• **Then** it appears in the library with its scores, provider and model<br>• **When** I search for a word from the original<br>• **Then** only matching entries are listed<br>• **When** I delete it<br>• **Then** it is gone immediately | api | PASS | 786 ms |
| **E2** | **A hand-edited library file loads anyway**<br>• **Given** the library file contains a null entry, a number where a string belongs, an entry with no id and one valid entry<br>• **When** I open the library<br>• **Then** the valid entry is listed and the rest are dropped silently<br>• **Given** the library file is not valid JSON at all<br>• **When** I open the library<br>• **Then** it is empty rather than an error<br>• **And** the broken file has been moved aside, not deleted | api | PASS | 114 ms |

| | | | | |
|---|---|---|---|---|
| **E3** | **A crash during a save cannot corrupt the library**<br>• **When** twenty saves race each other<br>• **Then** the library file is valid JSON at every moment it is read<br>• **And** every save is present afterwards<br>• **And** no temporary file is left behind | api | **PASS** | 295 ms |
| **E4** | **The library is bounded and drops the oldest first**<br>• **Given** the library holds 500 entries<br>• **When** I save one more<br>• **Then** the newest is present, the oldest is gone, and the count is still 500 | api | **PASS** | 72 ms |
| **E5** | **A library moves between machines**<br>• **When** I export the library<br>• **Then** I get a JSON file named with today's date<br>• **When** I import that file into a library that already has some of the entries<br>• **Then** the unknown entries are added and the known ones are skipped, not overwritten<br>• **And** malformed entries are dropped<br>• **And** the reply counts what was imported and skipped<br>• **When** I import the same file again<br>• **Then** nothing is added | api | **PASS** | 78 ms |
| **E6** | **Importing the wrong file says so in plain words**<br>• **When** I import a JSON object that is not a library<br>• **Then** I am told what shape was expected<br>• **And** the library is unchanged | api | **PASS** | 28 ms |
| **E7** | **The library lives where the documentation says it lives**<br>• **Given** the data directory override is set<br>• **When** I save an entry<br>• **Then** the library file is written inside that directory<br>• **And** nothing is written to the project's own data folder | api | **PASS** | 14 ms |

## F — The local model

*As a person who wants nothing to leave my machine I want the built-in model to download, load and run without configuration So that the app works offline and I always know its state*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| **F1** | **A first-run user with no model is told exactly what to do**<br>• **Given** the local provider is selected and no model is on disk<br>• **When** I open the app<br>• **Then** the status says the model is missing and names it with its size<br>• **And** the catalogue shows every tier and whether it is downloaded<br>• **When** I press Fix anyway<br>• **Then** I am told the model is not downloaded, not a generic failure<br>• **And** linting still works | api | **PASS** | 962 ms |

| | | | | |
|---|---|---|---|---|
| F2 | **The download is visible, resumable and cancellable**<br>• **When** I start the download<br>• **Then** I see bytes and a percentage<br>• **When** I cancel it<br>• **Then** the state is "missing" with no error and the Download button is back<br>• **When** I interrupt and restart it<br>• **Then** it resumes rather than starting from zero | nightly | PENDING | nightly on the GPU machine: needs a model file |
| F3 | **A download that produced no usable file says so**<br>• **Given** a download that completes but leaves a file of the wrong size<br>• **When** it finishes<br>• **Then** the state is an error with a message, not ready | nightly | PENDING | nightly on the GPU machine: needs a model file |
| F4 | **The machine picks a sensible model on its own**<br>• **Given** an explicit tier "lite" in configuration<br>• **When** I open the app<br>• **Then** the selected tier is lite regardless of this machine's memory | api | PASS | 721 ms |
| F5 | **Switching models is safe at any moment**<br>• **When** I select an unrecognised tier<br>• **Then** it is rejected with an explanation<br>• **When** I select a valid tier that is not downloaded<br>• **Then** the selection applies and the status says it is missing | api | PASS | 16 ms |
| F6 | **Loading is never confused about which model it is loading**<br>• **Given** a load in flight for one tier<br>• **When** a request arrives for a different tier<br>• **Then** it is not satisfied by the load in flight | nightly | PENDING | nightly on the GPU machine: needs a model file |
| F7 | **The GPU is used when it exists and its absence is not a failure**<br>• **When** the model loads on this machine<br>• **Then** the status names the backend, and on CPU the app still works | nightly | PENDING | nightly on the GPU machine: needs a model file |
| F8 | **A prompt too long for the model is refused with advice, not truncated**<br>• **Given** a prompt exceeding the model's context<br>• **When** I press Fix<br>• **Then** I am told it is too long for the local model and offered alternatives before generation starts | nightly | PENDING | nightly on the GPU machine: needs a model file |
| F9 | **The result is always structurally valid**<br>• **When** the smallest model generates on a difficult prompt<br>• **Then** I get a structured result or a clear error, never a malformed one | nightly | PENDING | nightly on the GPU machine: needs a model file |
| F10 | **Quitting releases the model**<br>• **Given** a loaded model<br>• **When** I close the window<br>• **Then** the model is unloaded and the process exits within a bounded time | desktop, nightly | PENDING | desktop tier, nightly |

| | | | | |
|---|---|---|---|---|
| F11 | **Nothing leaves the machine**<br>• **Given** no cloud provider is configured<br>• **When** I lint, fix, save and export<br>• **Then** all four succeed<br>• **And** the server has reached no address off this machine<br>• **And** the page has asked for nothing beyond its own origin | api, browser | PASS | 3.5 s |

## G — Providers and privacy

*As a person who may have put an API key in configuration I want it used only where I intended and never exposed*
*So that switching providers is safe*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| G1 | **The app offers only providers that can actually work**<br>• **Given** only the OpenAI-compatible endpoint is configured<br>• **When** I read the configuration<br>• **Then** that provider is marked configured and every other one is not<br>• **And** the configured default provider is what the interface selects<br>• **Given** nothing at all is configured<br>• **Then** the default provider is local | api | PASS | 1.4 s |
| G2 | **Keys never reach the browser**<br>• **When** every route is exercised, including failures<br>• **Then** no response body contains the API key | api | PASS | 284 ms |
| G3 | **A client cannot redirect a keyed provider**<br>• **Given** a request that supplies its own endpoint address for the keyed provider<br>• **When** I fix a prompt<br>• **Then** the request still goes to the configured endpoint<br>• **Given** a request that supplies a non-http address for a key-less endpoint<br>• **Then** it is refused | api | PASS | 14 ms |
| G4 | **Model lists are live where possible and honest where not**<br>• **Given** the provider answers with its model list<br>• **When** I ask for models<br>• **Then** I get the live list, labelled live<br>• **Given** the provider rejects the key<br>• **When** I ask for models<br>• **Then** I am told the key was rejected, not shown a fallback list<br>• **Given** a provider with no key configured<br>• **When** I ask for models<br>• **Then** I am told the key is missing instead of a guess | api | PASS | 17 ms |
| G5 | **The journey is the same on every provider**<br>• **When** the same prompt is fixed on the local provider and the compatible one<br>• **Then** the shape of the result and the guard behaviour are identical | api, nightly | PENDING | nightly: needs the local model |

| | | | | |
|---|---|---|---|---|
| **G6** | **The API is reachable only from this machine**<br>• **When** a request arrives with a foreign origin<br>• **Then** it is not granted cross-origin access<br>• **When** a request arrives from a localhost origin<br>• **Then** it is<br>• **When** a request to change or test a key is addressed to a name other than this machine's<br>• **Then** it is refused, and the key is left as it was | api | PASS | 41 ms |
| **G7** | **A key added in Settings works at once and stays on this computer**<br>• **Given** a cloud provider with no key<br>• **When** I add a key for it in Settings<br>• **Then** the provider is offered as ready at once, with no restart, and Settings says the key is its own<br>• **And** no reply carries the key back<br>• **And** the key is written to the app's own settings file, where an app started again finds it<br>• **When** I remove the key<br>• **Then** the provider needs a key again, and the file holds it no longer | api | PASS | 620 ms |
| **G8** | **Settings refuses what is not a key, and leaves a key set elsewhere alone**<br>• **Given** a settings file that holds notes and settings of my own<br>• **When** I add a key with a line break, a space or a quote in it, or one too short to be a key<br>• **Then** it is refused without being repeated back, and the file is unchanged to the byte<br>• **When** I add a key copied together with its name, the way it stands in a settings file<br>• **Then** only the key is kept, and every other line of the file is as it was<br>• **Given** a key set in the system environment<br>• **Then** Settings says it is set elsewhere, and will neither replace nor remove it | api | PASS | 587 ms |

## H — The editor and the results interface

*As a first-time user I want the interface to explain itself and never lie about what it is showing So that I can trust the score on screen*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| **H1** | **The first thirty seconds**<br>• **When** I open the app for the first time<br>• **Then** I see an empty editor with an explanatory placeholder, an example gallery and a sample button<br>• **When** I click an example<br>• **Then** the prompt, task type and strength are set and the score and issues appear | browser | PASS | 3.1 s |
| **H2** | **All eight built-in examples load and lint**<br>• **When** I choose each example in turn<br>• **Then** the prompt, task type and strength are set and every other option is left alone | browser | PASS | 1.7 s |

| | | | | |
|---|---|---|---|---|
| H3 | **A broken example list is an empty gallery, not a broken app**<br>• **Given** the examples cannot be fetched<br>• **When** I open the app<br>• **Then** the gallery is absent and everything else works | browser | PASS | 1.5 s |
| H4 | **Editing after a fix does the honest thing**<br>• **Given** a completed fix on screen<br>• **When** I edit the prompt<br>• **Then** the Issues tab shows the live analysis of the new text and the fix result is parked | browser | PASS | 1.7 s |
| H5 | **A deliberately pinned older result keeps its tab**<br>• **Given** I have stepped back to an earlier fix<br>• **When** I continue to edit<br>• **Then** the pinned result keeps the Issues tab | browser | PASS | 1.7 s |
| H6 | **Apply and undo**<br>• **When** I press Apply<br>• **Then** the fixed text replaces the editor content, the score re-lints and Undo appears<br>• **When** I press Undo<br>• **Then** the original text returns and Undo disappears<br>• **When** I apply and then edit the applied text<br>• **Then** Undo is no longer offered | browser | PASS | 2.2 s |
| H7 | **Copy puts the rewrite on the clipboard**<br>• **When** I press Copy<br>• **Then** the clipboard holds the fixed prompt exactly as displayed | browser | PASS | 1.4 s |
| H8 | **Fix is disabled when it cannot succeed, and says why**<br>• **Given** each of: empty editor, no provider, model missing, download in progress, cancel settling<br>• **Then** the Fix button is disabled with a visible reason | browser | PASS | 1.4 s |
| H9 | **A remembered model choice is reconciled with the server**<br>• **Given** I previously chose a tier and the server is on another<br>• **When** I open the app<br>• **Then** my choice is sent to the server, not merely displayed | browser | PASS | 518 ms |
| H10 | **Warnings read like sentences a person wrote**<br>• **Given** each kind of guard warning<br>• **Then** the headline matches the kind and an unknown kind shows the raw text | browser | PASS | 5.1 s |
| H11 | **The app is usable from the keyboard**<br>• **When** I tab through the interface<br>• **Then** every control is reachable in a sensible order<br>• **And** Ctrl+Enter runs a fix, Enter on a nested Delete deletes, Escape closes the drawer | browser | PASS | 1.5 s |
| H12 | **Text meets contrast requirements**<br>• **Then** every foreground/background pairing meets AA contrast | browser | PASS | 1.3 s |

| | | | | |
|---|---|---|---|---|
| H13 | **The window works at a small size**<br>• **Given** a 1024 by 720 window<br>• **Then** nothing is clipped and no pane scrolls horizontally<br>• **And** the same holds with the real provider names, down to the narrowest window the desktop app allows | browser | PASS | 2.0 s |
| H14 | **Every action without a visible result reports itself**<br>• **When** I save, import, export, copy and apply<br>• **Then** each shows a confirmation stating the outcome | browser | PASS | 1.9 s |
| H15 | **The interface links to the project website, and the link leaves the app the safe way**<br>• **Given** the server names the project website in its config<br>• **When** I open the app<br>• **Then** the top bar offers a "What's new" link to that address, marked to open outside the app<br>• **When** I click it<br>• **Then** the website opens in a page of its own and the editor is still where I left it | browser | PASS | 317 ms |
| H16 | **A rewrite can be reported, and the report leaves the app the safe way**<br>• **Given** no prompt has been fixed yet<br>• **Then** there is nothing to report and no Report link<br>• **When** I fix a prompt<br>• **Then** a Report link beside the rewrite offers the project's report form, marked to open outside the app<br>• **And** the form is filled in with the app's version, the provider and the model, and with nothing I wrote or the model wrote<br>• **When** I click it<br>• **Then** the form opens in a page of its own and the rewrite is still where I left it | browser | PASS | 1.3 s |
| H17 | **A provider without a key says so, and Settings takes the key**<br>• **Given** a cloud provider with no key is selected<br>• **Then** the results pane says it needs a key and offers to add one, and Fix is disabled<br>• **When** I press Add key, paste a key and save it<br>• **Then** the provider is ready, the field is empty, and the key is nowhere on the page<br>• **When** I test the key<br>• **Then** I am told what the provider answered<br>• **When** I remove the key in Settings<br>• **Then** the provider needs a key again, and Fix is disabled | browser | PASS | 2.4 s |

## I — Showing what changed

*As a person reading a rewrite I want to see exactly which words changed So that the guard's claims about "how much survived" are verifiable*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|

| | | | | |
|---|---|---|---|---|
| I1 | **The user can see exactly what changed and nothing is hidden**<br>• **Given** an original and a rewrite<br>• **When** I view the diff<br>• **Then** removals and additions are distinguishable at word level<br>• **Given** identical texts<br>• **Then** the diff shows them as identical | library-seam | PASS | 10 ms |
| I2 | **One changed word in a long document is one changed word**<br>• **Given** a prompt of over a thousand words with a single word inserted<br>• **When** I view the diff<br>• **Then** exactly one insertion is shown and it renders quickly<br>• **Given** thousands of lines with one line changed<br>• **Then** the diff finds the one line quickly | library-seam | PASS | 66 ms |
| I3 | **A region too large to align is reported, not hidden**<br>• **Given** a change too large to align word by word<br>• **When** I view the diff<br>• **Then** the region is reported as replaced wholesale, not shown as empty | library-seam | PASS | 45 ms |

## J — The CI linter

*As a team keeping prompts in a repository I want to gate them in CI with the same rules the app uses So that a prompt below the bar cannot be merged*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| J1 | **A team can gate its prompts in CI with no server, no model and no key**<br>• **When** I run the linter over a passing set with a minimum score and a severity threshold<br>• **Then** it exits 0<br>• **When** I run it over a set containing a vague prompt<br>• **Then** it exits 1 and names the offending file | cli | PASS | 442 ms |
| J2 | **The gate uses the same rules as the app**<br>• **When** the same text and task type are scored by the linter and by the app<br>• **Then** the score, categories and issues are identical | cli | PASS | 1.4 s |
| J3 | **Directories are searched the way the documentation says**<br>• **Given** a tree with .md, .txt and .prompt files and other file types<br>• **When** I point the linter at the directory<br>• **Then** exactly the three extensions are linted, recursively | cli | PASS | 312 ms |
| J4 | **A file can declare its own task type**<br>• **Given** a file whose first line is the task-type comment<br>• **When** it is linted<br>• **Then** that task type is used and the comment does not affect the score | cli | PASS | 487 ms |

| | | | | |
|---|---|---|---|---|
| J5 | **Machine-readable output is machine-readable**<br>• **When** I run with --json<br>• **Then** stdout is exactly one parseable object with every file's score, categories and issues<br>• **When** I run with --quiet<br>• **Then** only the summary line is printed | cli | PASS | 379 ms |
| J6 | **A misconfigured job is distinguishable from failing prompts**<br>• **When** I run with no paths, an unknown flag, an unknown task type, or a missing path<br>• **Then** each exits 2 with usage on stderr | cli | PASS | 659 ms |

## K — The desktop application

*As a person who installed Whetprompt I want it to behave like a well-mannered desktop app So that installing, quitting and configuring it hold no surprises*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| K1 | **Install, run, uninstall, reinstall**<br>• **Given** the built installer on a clean machine<br>• **When** I install, run, uninstall and reinstall<br>• **Then** the model and the library survive | desktop, nightly | PENDING | desktop tier, nightly: needs the packaged installer on a clean machine |
| K2 | **The window opens our interface and nothing else**<br>• **When** a same-origin navigation occurs<br>• **Then** it proceeds<br>• **When** a file is dropped, an external link followed, or a lookalike origin navigated to<br>• **Then** each is blocked in the window | desktop, nightly | PASS | 9.8 s |
| K3 | **Quitting is deterministic**<br>• **Given** a loaded model<br>• **When** I quit<br>• **Then** the quit waits for unload, and a failing or hung unload still quits in bounded time | desktop, nightly | PASS | 7.6 s |
| K4 | **Configuration is read from where the documentation says**<br>• **Given** the packaged app<br>• **Then** the per-user .env overrides the desktop defaults and the working-directory .env is ignored<br>• **Given** the app run from source<br>• **Then** the project .env wins over the per-user one, and a shell variable wins over both | desktop, nightly | PENDING | desktop tier, nightly: packaged vs source .env matrix (logic covered by electron/env.test.js) |
| K5 | **The app finds a free port and its interface finds the app**<br>• **When** two copies of the server start at once<br>• **Then** both get a port and both answer | api | PASS | 607 ms |
| K6 | **An unknown API route is a not-found, not the application shell**<br>• **When** I request an API path that does not exist<br>• **Then** I get a not-found response, not the interface HTML | api | PASS | 420 ms |

## L — Configuration, limits and errors

*As a person who did not read the configuration section I want the app to work with no configuration and to enforce the limits it advertises So that nothing surprising happens later*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| L1 | **Everything has a working default**<br>• **Given** no configuration at all<br>• **When** the server starts<br>• **Then** it starts, selects the local provider and reports the limits it enforces | api | PASS | 1.8 s |
| L2 | **Port precedence and the development proxy**<br>• **Given** a port of zero<br>• **When** the server starts<br>• **Then** it reports the port it was actually given | api | PASS | 16 ms |
| L3 | **Errors have one consistent shape**<br>• **When** failures are produced on several routes<br>• **Then** each carries a message, a code, a retryable flag and where relevant a provider | api | PASS | 170 ms |
| L4 | **The advertised limits are real**<br>• **When** I walk up to the prompt length limit and one step past it<br>• **Then** the boundary is accepted and the step past it is refused with the limit named<br>• **When** I walk up to the library cap and one step past it<br>• **Then** the cap holds | api | PASS | 94 ms |

## M — Marking a rewrite and fixing it again

*As a person reading a rewrite that is nearly right I want to point at the parts I loved and the parts I did not So that the next rewrite keeps the first and changes the second without my starting over*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|

| | | | | |
|---|---|---|---|---|
| M1 | **The model is shown what I marked, and the result says how many marks it was given**<br>• **Given** I marked one passage of the rewrite to keep and one to change<br>• **When** I fix again with my marks<br>• **Then** the model was shown the rewrite I marked and both passages, each under its own verdict<br>• **And** it was still asked to fix my original prompt, with the same findings as before<br>• **And** the new rewrite has the kept passage word for word and no longer has the other as it was<br>• **And** the run details say one kept passage and one passage to change were applied, and none ignored<br>• **And** the before score is still the score of my original prompt<br>• **Given** a rewrite in which two words of the sentence I kept stand once more, on their own, and there I marked them to change<br>• **When** I fix again with my marks<br>• **Then** the model is shown both marks, and told that inside the kept sentence the kept sentence wins<br>• **And** a rewrite that rewords those words where they stood alone is accepted at the first attempt, with no warning | api | PASS | 939 ms |
| M2 | **A rewrite that drops a passage I kept is retried, and the faithful attempt is kept**<br>• **Given** the model first paraphrases the passage I kept and leaves the other as it was, then follows my marks<br>• **When** I fix again with my marks<br>• **Then** I receive the attempt that follows them, with no warning<br>• **And** the run details show two attempts<br>• **And** the retry was told which passage it had dropped and which it had left as it was, each under its own verdict<br>• **And** it was shown my marks again | api | PASS | 49 ms |
| M3 | **When the model ignores my marks twice, I still get a result and I am told what was not honoured**<br>• **Given** the model ignores my marks on both attempts<br>• **When** I fix again with my marks<br>• **Then** I still receive a rewrite<br>• **And** a warning says how many kept passages are missing and how many passages to change are still there<br>• **And** the run details name those passages<br>• **And** in the interface the warning has its own headline, and the refined note claims no mark that was ignored | api, browser | PASS | 2.0 s |

| | | | | |
|---|---|---|---|---|
| M4 | **Nonsense marks are coerced, never a server error**<br>• **When** marks arrive as a string, a number, a list, null, or holding things that are not text<br>• **Then** each request succeeds as an ordinary fix and none of them produces a server error<br>• **When** every mark points at words that are not in the rewrite<br>• **Then** it is an ordinary fix: the model is shown no marks and the result mentions none<br>• **When** a passage is marked twice, or padded with spaces, among marks that point at nothing<br>• **Then** the model is shown it once, trimmed, and nothing else<br>• **When** a passage is marked both to keep and to change, and those words stand in only one place in the rewrite<br>• **Then** the change wins<br>• **When** the same words stand in two places and are marked both ways<br>• **Then** the model is shown both marks, and rewording one of the two places honours both<br>• **When** twenty-five passages are marked the same way, or one mark runs to 2,500 characters<br>• **Then** the model is shown the first twenty, and the first 2,000 characters, and the result counts twenty<br>• **When** the marked rewrite is longer than a prompt may be<br>• **Then** it is refused with a message naming the length and the limit | api | PASS | 346 ms |
| M5 | **A fix without marks is the fix it always was**<br>• **When** I fix the blog prompt with no marks<br>• **Then** the model is shown no earlier rewrite and no marks<br>• **And** the result says nothing about marks<br>• **Given** I have since fixed again with marks<br>• **When** I fix the blog prompt once more with no marks<br>• **Then** the earlier marks have no influence on it<br>• **Given** a model whose rewrite holds a "<user_feedback>" slot of its own for the prompt's user to fill<br>• **When** I fix the blog prompt with no marks<br>• **Then** the rewrite comes back with its slot intact, after one attempt and with no warning<br>• **And** marking that rewrite and fixing again leaves the slot where it was, again with no warning | api | PASS | 94 ms |

| | | | | |
|---|---|---|---|---|
| M6 | **I mark what I loved and what I did not** | browser | PASS | 7.6 s |

- **Given** a completed fix on the Fixed tab
- **Then** both marking buttons are disabled, because nothing is selected
- **When** I select words outside the rewrite, or drag from outside into it
- **Then** both buttons stay disabled
- **When** a selection starts in the rewrite and runs on into a toast
- **Then** both buttons are disabled
- **When** a selection of the last line ends where a triple click leaves it, just outside the rewrite
- **Then** that line can be marked
- **When** I double-click a word of the rewrite and press "Keep it — I loved it"
- **Then** that word is highlighted as kept and the selection is gone
- **When** I drag across a sentence and press "Change it — I didn't like it"
- **Then** that sentence is highlighted as to change
- **And** the bar counts one kept and one to change and offers "Fix again with my marks"
- **Given** a rewrite longer than the window, scrolled until the marking bar is stuck above it
- **When** I drag a selection upwards from the rewrite onto the bar, from plain text or from a highlight
- **Then** the selection stays inside the rewrite and both buttons can be pressed
- **And** the bar takes the mouse again when the press ends, even a press that ends without a mouse-up
- **When** twenty passages are kept and I select another
- **Then** "Keep it — I loved it" is disabled and says twenty is the most the model is shown, and the other button is not
- **When** I remove one highlight
- **Then** the passage can be kept

| | | | | |
|---|---|---|---|---|
| M7 | **A mark can be changed and taken back** | browser | PASS | 2.8 s |

- **Given** a rewrite with two passages kept and one to change
- **When** I drag across a kept passage again and press "Change it — I didn't like it"
- **Then** the newer verdict replaces the older one
- **When** I click a highlighted passage
- **Then** its highlight is removed and the count follows
- **When** I press Enter on a highlighted passage from the keyboard
- **Then** its highlight is removed too
- **When** I press Ctrl+Enter in the rewrite or on the bar while a mark is showing
- **Then** no fix is started and the mark is still there
- **When** I press "Clear marks" from the keyboard
- **Then** every highlight is gone, and so is the offer to fix again
- **And** the focus is on the rewrite, which shows no ring, and not at the top of the page
- **When** I click in the rewrite and press Ctrl+Enter
- **Then** a fresh fix runs, as it does from anywhere else

| | | | | |
|---|---|---|---|---|
| M8 | **"Fix again with my marks" sends exactly what I marked**<br>• **Given** I kept one passage and marked another to change<br>• **When** I press "Fix again with my marks" from the keyboard<br>• **Then** the model was shown exactly those two passages and the rewrite they came from<br>• **And** I am told it was refined, with the before and after scores<br>• **And** the new rewrite joins the history as "2 of 2"<br>• **And** the What changed line says it was refined with my marks, one kept and one changed<br>• **And** the new rewrite carries no highlights, and the focus is on it, not at the top of the page<br>• **And** stepping back to the first rewrite does not bring the old highlights back<br>• **When** I mark the first rewrite again and step forward and back through the history<br>• **Then** the mark is gone<br>• **When** I mark it once more and press "Fix prompt"<br>• **Then** the fresh rewrite carries no highlights, and stepping back to the first one does not bring the mark back<br>• **Given** the fresh rewrite has two words of the sentence I keep standing once more on their own, and there I mark them to change<br>• **When** I press "Fix again with my marks"<br>• **Then** the model was shown one passage to keep and one to change, as the bar counted<br>• **And** the What changed line says one kept and one changed, with no warning | browser | PASS | 2.2 s |
| M9 | **The rewrite stays exact while marks are showing**<br>• **Given** highlights of both kinds on the rewrite, one of two lines and one of four lines and more than a hundred characters<br>• **Then** the rewrite on screen is still the fixed prompt, character for character<br>• **And** each highlight is a button whose name gives a screen reader the verdict and the whole passage, its line breaks as spaces<br>• **When** I press Copy<br>• **Then** the clipboard holds the fixed prompt, with nothing from the marking bar in it | browser | PASS | 1.8 s |
| M10 | **Marks are readable and fit a small window**<br>• **Given** a 1024 by 720 window with highlights of both kinds and the count showing<br>• **Then** every piece of text, inside both highlight colours and on the bar, meets AA contrast<br>• **And** nothing scrolls horizontally and "Fix again with my marks" is on screen | browser | PASS | 1.5 s |

| | | | | |
|---|---|---|---|---|
| M11 | **Fixing again still works after I edited the prompt**<br>• **Given** a completed fix on which I marked a passage<br>• **When** I type a character in the editor<br>• **Then** the rewrite is parked behind the edited-prompt notice, and there is nothing to fix again with<br>• **When** I delete that character again<br>• **Then** the rewrite is back with my mark on it<br>• **When** I change the text in the editor and press "Show last fix"<br>• **Then** the parked rewrite comes back with my mark still on it<br>• **When** I press "Fix again with my marks"<br>• **Then** the new rewrite is shown, not parked behind the edited-prompt notice<br>• **And** the model was asked to refine the prompt that rewrite was made for, not the text now in the editor<br>• **And** the editor still holds my edit | browser | PASS | 1.5 s |

## N — Looking the same every time

*As a developer changing Whetprompt's interface I want one command to tell me which screens look different, and which element changed So that a change to the look is something I approve, never something a user finds*

| ID | Scenario and acceptance criteria | Seam | Result | Time / note |
|---|---|---|---|---|
| N1 | **Every screen, captured again, matches its approved picture**<br>• **When** every screen is captured again at both window sizes<br>• **Then** the check passes<br>• **And** no screen reports a changed, added or removed region at either size | visual | PASS | 22.9 s |
| N2 | **A rewrite that came back different is reported on the Fixed screen, by name**<br>• **Given** the model now words one line of the rewrite differently<br>• **When** the Fixed, Issues and Changes screens are captured<br>• **Then** the check fails<br>• **And** the Fixed screen reports a change on that one line and names the rewrite as the element that changed<br>• **And** the Issues and Changes screens, which do not show the rewrite, report nothing | visual | PASS | 7.6 s |

| | | | | |
|---|---|---|---|---|
| **N3** | **Marks are part of the picture**<br>• **When** the approved picture of the marked screen is compared with the unmarked one<br>• **Then** the difference names the marking bar, its "Clear marks" and "Fix again with my marks" buttons and both highlighted passages<br>• **And** each highlighted passage is a reported region<br>• **And** nothing in the editor pane, and nothing above the marking bar, is reported<br>• **Given** both highlights have lost all their paint, and nothing has moved<br>• **When** the marked screen is captured at both window sizes<br>• **Then** at each size the check fails and names the two highlighted passages, each with changed pixels behind it, and nothing else<br>• **Given** the highlight of a kept passage has lost its green<br>• **When** the marked screen is captured<br>• **Then** the check fails and names that highlighted passage, and nothing else | visual | PASS | 5.8 s |
| **N4** | **What honestly varies between two runs raises no alarm**<br>• **Given** a model that takes longer to answer and reports other token counts<br>• **And** a server whose calendar is weeks ahead, so a saved prompt carries another date<br>• **When** the Fixed, Changes and Library screens are captured<br>• **Then** the check passes and no screen reports a region | visual | PASS | 12.9 s |
| **N5** | **A screen with no approved picture, or a changed look, fails the check until I approve it**<br>• **Given** approved pictures that lack one screen<br>• **And** a Fix prompt button that has been restyled<br>• **When** I run "npm run visual"<br>• **Then** it fails: the screen without a picture is reported as new, and the other names the Fix prompt button<br>• **When** I run "npm run visual:approve"<br>• **Then** it succeeds<br>• **When** I run "npm run visual" again<br>• **Then** it passes | visual | PASS | 11.6 s |

| | | | | |
|---|---|---|---|---|
| **N6** | **The one command hands back the verdict and leaves nothing running**<br>• **When** I run "npm run visual" on a screen that has not changed<br>• **Then** it exits 0<br>• **When** I run it on a screen that has<br>• **Then** it exits 1, and a report a CI job can read has been written<br>• **When** I mistype the name of a screen<br>• **Then** it exits 2 and lists the screens there are<br>• **When** I run it against the commit I am working from instead of against approved pictures, having changed that screen<br>• **Then** it exits 1 and the report names what I changed, although no picture was ever approved for it<br>• **And** after each run the server it started no longer answers and its temporary folders are gone<br>• **And** the commit it compared with is no longer checked out anywhere | visual | PASS | 6.2 s |
| **N7** | **Pointed at the wrong place, the check says so and harms nothing**<br>• **When** the check is run with no server to look at<br>• **Then** it stops with an error that says to use "npm run visual"<br>• **Given** a Whetprompt that somebody is using, with a prompt saved in its library<br>• **When** the check is pointed at it<br>• **Then** it stops with an error, and the saved prompt is still there | visual | PASS | 1.4 s |

Generated by `npm run test:report` from `acceptance\report\out\results.json`. Strategy: `docs/ATDD.md`. Narrative report: `docs/ATDD-REPORT.md`.