CNG 351 - Assignment 1

Data Management and File Structures

Fall 2026-2027

Entity-Relationship Database Designs

Team / Group ID: 8

Team member	**Student ID**
Osman Caner Cakmak	2584829
Bedri Can Guneser	2585032

Notation and model organization

The three use cases are presented in eight drawing views: 1A-1B for Use Case 1, 2A-2C for Use Case 2 and 3A-3C for Use Case 3. An entity shown in more than one view is the same entity throughout, with the same key, attributes and relationships.

Chen notation

Symbol / marking	Meaning
Single rectangle	Strong entity type.
Double rectangle	Weak entity; its full identity includes its owner's key.
Single / double diamond	Binary relationship / identifying relationship.
Oval / branched oval	Simple attribute / composite attribute with components.
Double oval / dashed oval	Multivalued attribute / derived attribute.
Solid underline	Chosen entity key. Other stated uniqueness constraints are listed in the rules.
Dashed underline	Partial key of a weak entity. BookingDate and StartTime together form Booking's partial key.
Single / double connection	Partial participation / total participation of that entity in the relationship.
(min,max) beside an entity	Number of relationship occurrences for each instance of that entity; N means many.

How to read a constraint

For example, Season (0,10) - Contains - Episode (1,1) means that each season contains at most ten episodes, while each episode belongs to exactly one season. The double line on Episode makes its mandatory participation explicit.

Additional rules

Every relationship is binary: each diamond has exactly two entity roles, even when the relationship has attributes. The business rules accompanying each use case specify temporal requirements, subset constraints and aggregate calculations that ordinary Chen symbols cannot fully express. EmployeeCount* is derived automatically and also stored, as required.

Requirements source: CNG 351 Assignment 1, Fall 2026-2027, provided course handout. The eight vector drawing pages were exported from draw.io.

Use Case 1

Who Wants to Be a Millionaire?

Requirements: course assignment brief, pages 3-4.

The quiz-show model distinguishes episode production from a contestant's sequence of questions and joker uses.

Entity identities

Entity	Chosen full key
Season	SeasonID
Episode	EpisodeID
Host	HostID
Contestant	ContestantID
Question	QuestionID
Category	CategoryID
QuestionAttempt (weak)	(ContestantID, AttemptNo)
JokerUse (weak)	(ContestantID, UseNo)
JokerType	TypeName

Design decisions

QuestionAttempt records a question being asked to a contestant. It is weak under Contestant: AttemptNo is a local sequence number that also records asking order, and UsesQuestion links the attempt to the relevant Question. JokerUse is also weak under Contestant. Its UsedFor link identifies the exact QuestionAttempt, and OfType identifies the JokerType. These binary links support zero to four joker uses without a ternary relationship.

The question bank has four fixed answer attributes: ChoiceA, ChoiceB, ChoiceC and ChoiceD. CorrectChoice identifies the correct slot. Questions and categories are linked through a many-to-many relationship, with mandatory participation by Question.

Host and Contestant both have a composite FullName made up of FirstName and Surname. Contestant.Age is derived from DateOfBirth using completed years.

Use Case 1 - Rules and assumptions

Business rules and additional constraints

1. A season contains at most ten episodes; each episode belongs to exactly one season and is presented by exactly one host. A contestant belongs to exactly one episode. The system keeps one Contestant record for each person, enforcing a single participation in the show.

2. Host.Email is unique in addition to the chosen HostID key. EpisodeNumber is recorded as a separate attribute; the brief does not state that it is globally unique.

3. Each question has exactly four labelled answer slots, one CorrectChoice in {A, B, C, D}, question text and a DifficultyLevel label such as easy, medium or hard. Every question belongs to at least one category.

4. A completed contestant participation must have at least one QuestionAttempt. AttemptNo values are distinct within a contestant and increase in asking order. GivenAnswer is the submitted slot; the stored IsCorrect value must agree with GivenAnswer = Question.CorrectChoice.

5. The number of JokerUse occurrences owned by a contestant is between zero and four. Each occurrence has one date-time UsedAt, one joker type and one referenced QuestionAttempt. The attempt must be owned by the same contestant as the JokerUse.

6. The JokerType catalogue contains Fifty-Fifty, Phone a Friend and Ask the Audience, together with a description for each type.

Assumptions

A1. Seasons, planned episodes, hosts, categories and question-bank questions may be registered before they are used. Their unspecified minimum participation is therefore zero.


A2. The same question may be asked to a contestant more than once; separate AttemptNo values distinguish these events. No prohibition of repeated questions is stated.

A3. A joker type may be used more than once, subject to the stated total limit of four uses. The brief lists three types but gives no per-type usage limit.

A4. Every recorded contestant has been asked at least one question, so Contestant participates totally in HasAttempt.

Use Case 1A - Production and participation

Chen ERD | Entity attributes continue in View 1B where marked. All relationships are binary.




Notes

Contestant.Age is calculated in completed years from DateOfBirth. Host.Email is unique in addition to HostID.

Each person has one Contestant record linked to exactly one episode, so participation is limited to one episode.

Use Case 1B - Questions, answers and jokers

Chen ERD | Contestant is the same entity as in View 1A. Dashed underlines denote partial keys.



Notes

QuestionAttempt is identified by (ContestantID, AttemptNo), and JokerUse by (ContestantID, UseNo). AttemptNo records the order in which questions are asked.

Each JokerUse must refer to a QuestionAttempt owned by the same contestant. IsCorrect is stored and checked by comparing GivenAnswer with Question.CorrectChoice.

JokerType.TypeName is Fifty-Fifty, Phone a Friend or Ask the Audience.

Use Case 2

CleanCampus

Requirements: course assignment brief, pages 4-6.

CleanCampus records shared machines, dormitory allocations and student residence alongside machine use and maintenance.

Entity identities

Entity	Chosen full key
LaundryRoom	RoomID
Machine	MachineID
MachineModel	ModelID
Dormitory	DormID
Student	StudentID
Stay	StayID
UsageSession (weak)	(MachineID, SessionNo)
Supplier	SupplierID
MaintenanceContract	ContractID

Design decisions

MachineModel holds the specifications shared by machines: composite Capacity consists of MinLoad and MaxLoad, and SupportedPrograms is multivalued. Each machine is based on one model; Brand remains an attribute of Machine, as stated in the brief. The binary many-to-many relationship AllocatedTo carries UsageRank and FreeCreditAmount for each Machine-Dormitory pair. IsLeadingDorm is derived from that allocation's UsageRank.

A student returning to a dormitory creates another period of residence, so each Stay has its own StayID and links to one Student and one Dormitory. CurrentlyIn records the current dormitory, and the business rules require it to match the open stay.

UsageSession is weak under Machine, with SessionNo as its partial key and an identifying relationship to Machine. MaintenanceContract has its own identifier so that renewals between the same supplier and machine can be retained as separate contracts.

Use Case 2 - Rules and assumptions

Business rules and additional constraints

1. Machine.Type is standard or industrial. Dormitory.Level is undergraduate or graduate. Student.Username is unique in addition to StudentID. Student.Age is a stored attribute because no birth date is given.

2. Each machine is based on exactly one model and is located in exactly one laundry room. MinLoad must not exceed MaxLoad; the model records its supported program names.

3. Each Machine-Dormitory pair has at most one allocation, with its own UsageRank and FreeCreditAmount. IsLeadingDorm is true exactly when UsageRank = 1 for that machine.

4. Each student has exactly one CurrentlyIn dormitory and at least one recorded stay. Exactly one stay is current: its EndDate is NULL and its dormitory equals CurrentlyIn. A later return to the same dormitory creates a new StayID. Stay periods for one student must not overlap.

5. SessionNo is unique only within its machine. Status is scheduled, completed, cancelled or interrupted. Duration is calculated from StartTime and EndTime when both are known.

6. A completed or interrupted usage session must identify one dormitory. At the time a machine is actually used, that Machine-Dormitory allocation must exist. Scheduled or cancelled sessions may have no actual-use dormitory.

7. Every maintenance contract identifies exactly one supplier and one machine, and records StartDate, EndDate and ContractAmount. Supplier-machine renewals remain separate contracts.

Assumptions

A1. A machine is installed in one shared laundry room at a time. RoomID distinguishes these locations; historical room changes are not required.


A2. Stay history includes the current open stay. EndDate is filled when a student leaves; CurrentlyIn is maintained consistently with that stay.

A3. Usage ranks are distinct positive integers within one machine's current allocations, with rank 1 identifying its sole leading dormitory.

A4. A usage session ends on its SessionDate. EndTime may be unknown for an unfinished or cancelled session; no duration is calculated until both time bounds are available.

Use Case 2A - Equipment and dormitory allocation

Chen ERD | Allocation attributes belong to the Machine-Dormitory pair.




Notes

IsLeadingDorm is derived separately for each machine and is true exactly when UsageRank = 1.

Capacity is composite, with MinLoad and MaxLoad as its components. SupportedPrograms is multivalued.

Use Case 2B - Current residence and stay history

Chen ERD | Dormitory is the same entity as in View 2A. Each separate stay has its own StayID.




Notes

Student.Username is unique in addition to StudentID. Student.Age is stored because no birth date is supplied.

Each student has exactly one open Stay, with EndDate = NULL and the same dormitory as CurrentlyIn. Returning to a dormitory creates a new StayID.

Use Case 2C - Usage sessions and maintenance

Chen ERD | Machine and Dormitory are references to View 2A. A usage session is weak under its machine.



Notes

UsageSession is identified by (MachineID, SessionNo). Duration is calculated from StartTime and EndTime when both are known.

Completed and interrupted sessions must identify a dormitory. The machine must be allocated to that dormitory when it is used.

Each maintenance agreement has its own ContractID, so contracts between the same supplier and machine remain separate over time.

Use Case 3

METU NCC KALTEV

Requirements: course assignment brief, pages 6-7.

The KALTEV model distinguishes current employment and internships from office rental history, project activity, meeting-room bookings and investments.

Entity identities

Entity	Chosen full key
Company	TaxNumber
Employee	NationalID
Office	OfficeNumber
Rental	RentalID
Project	ProjectCode
Deliverable (weak)	(ProjectCode, DeliverableNo)
Intern	StudentID
MeetingRoom	RoomNumber
Booking (weak)	(RoomNumber, BookingDate, StartTime)
Investor	InvestorID
Investment	InvestmentID

Design decisions

Rental and Investment have their own identifiers so that repeated events between the same parties can be retained. Each Investment is one dated transaction; Company.TotalInvestmentReceived and investor-company totals are calculated from those transactions. Deliverable and Booking use their owners' keys instead: DeliverableNo is local to Project, and the composite partial key (BookingDate, StartTime) is local to MeetingRoom. Their identifying relationships preserve ownership and uniqueness.

Company.Contact groups Email and PhoneNumber, while Employee.PhoneNumbers is multivalued. CompanyAge is derived from FoundingDate. EmployeeCount* is also derived, but its value is stored for access and refreshed automatically whenever the current WorksFor links change. The asterisk marks this storage requirement.

Use Case 3 - Rules and assumptions

Business rules and additional constraints

1. TaxNumber and NationalID are the chosen Company and Employee keys. Employee.Email is also unique. Each employee WorksFor one current company; EmploymentStartDate is an attribute of that relationship.

2. Each company has one representative, and an employee represents at most one company. Represents must be a subset of WorksFor for the same employee-company pair. This also implies at least one employee per company.

3. Each Rental links one company to one office and records StartDate, EndDate and MonthlyRent. A rental is ongoing when StartDate is on or before today and EndDate is NULL or later than today. Every company currently operating in KALTEV has at least one ongoing rental. Ended rentals are kept as history, and an office may have no ongoing rental. Rental periods of the same office cannot overlap.

4. Each project belongs to one company and has status proposed, active, completed or cancelled. It has at least one deliverable. Deliverable numbering restarts at D1 for each project; ActualSubmissionDate may be NULL until submission.

5. WorksOn records HoursPerWeek for each employee-project pair. Each project has one manager. Manages must be a subset of WorksOn, so the chosen manager is a worker on that project.

6. Every intern InternsAt one company and has one supervisor. The supervisor must WorksFor that same company. Only the current internship is retained; the Intern record is removed when that internship ends.

7. There are exactly ten MeetingRoom records. Each booking has one room and one company. The full key (RoomNumber, BookingDate, StartTime) prevents two bookings with the same room, date and start time, while allowing simultaneous starts in different rooms.

8. Each Investment has one investor and one receiving company. Company.TotalInvestmentReceived is the sum of Amount over its investments, or zero when there are none. The total from investor i to company c is the sum over investments linked to both i and c.

Assumptions

A1. WorksFor records current employment; previous employer histories are not required. Employees work only on projects belonging to their current company.

A2. Rental periods are interpreted as half-open intervals [StartDate, EndDate), with NULL EndDate for an ongoing rental. A company may rent the same office again under a new RentalID.


A3. A booking starts and ends on the same date, with StartTime earlier than EndTime. The key (RoomNumber, BookingDate, StartTime) prevents two bookings for the same room from starting on the same date at the same time.

A4. An investor may invest in the same company more than once. InvestmentID distinguishes those dated transactions. Investor email is not assumed to be unique. An investor may be registered before making any investment, so Investor participates partially in ProvidedBy.

A5. A company that has left KALTEV stays in the system so that its past rentals remain linked to it. The ongoing-rental rule applies only to companies currently operating in the building.

Use Case 3A - Companies, employees and offices

Chen ERD | Company.EmployeeCount* is a stored, automatically maintained derived value.



Notes


A company's representative must be one of its current employees: Represents is a subset of WorksFor.

Companies currently operating in KALTEV must have at least one ongoing rental. Rental periods for the same office cannot overlap.

Employee.Email is unique in addition to NationalID. EmployeeCount* counts the current WorksFor employees; it is stored and maintained automatically.

Use Case 3B - Projects, deliverables and interns

Chen ERD | Company and Employee refer to View 3A. Every project manager must also work on that project.



Notes


Deliverable is identified by (ProjectCode, DeliverableNo). Deliverable numbering starts again at D1 for each project.

Manages is a subset of WorksOn, so every project manager also works on that project. Project workers must belong to the company running the project.

Each intern's supervisor must work for the same company as the intern. Only current internships are retained.

Use Case 3C - Meeting rooms and investment

Chen ERD | Company is the same entity as in View 3A; TotalInvestmentReceived is shown here.



Notes

Booking is identified by (RoomNumber, BookingDate, StartTime); (BookingDate, StartTime) is its partial key.

The system has exactly ten MeetingRoom records. Each booking links one room to one company.

Each investment remains a separate transaction. Totals sum Amount for a company or an investor-company pair.