KU Leuven

Faculty of Engineering Technology

Your Thesis Title Here

Oskar De Clerck

A thesis submitted for the degree of
Master of Science in *industriële wetenschappen: Elektromechanica*

Academic Year 2025–2026

Promotor: ir. Maurizio Grossi
Copromotor: prof. dr. ir. Dino Accoto

Abstract

Acknowledgements

Contents

Abstract **i**

Acknowledgements **iii**

Nomenclature **xi**

1 Introduction **1**

1.1 Background and Motivation 1

1.1.1 Musculoskeletal disorders and ergonomic work environments 1

1.1.2 Industrial motivation for ergonomic improvement 2

1.1.3 Physical human–robot interaction 2

1.2 Problem Statement 4

1.3 Thesis Outline 6

2 Literature Review **7**

2.1 Theoretical Background 7

2.1.1 Example subsection 7

2.1.2 Another subsection 7

2.2 State of the Art 7

2.3 Gap Analysis 7

3 System Design and Implementation **9**

3.1 System Overview and Requirements 9

3.2 Mechanical Design 9

3.3 Hardware Architecture 9

3.3.1 CAN Bus Topology 9

3.3.2 Sensor Architecture 9

3.4 Sensor and Actuator Modelling 9

3.4.1 SET Spring Model 9

3.4.2 Motor and Transmission Model 9

3.5 Control Architecture 9

3.5.1 State Machine 9

3.5.2 Gravity Compensation and Floating Mode 9

3.5.3 Weighing Mode 9

3.5.4 Carrying Mode 9

3.5.5 Put-Down Mode . . . 9
3.6 Software Implementation . . . 9
3.6.1 Real-Time Architecture . . . 9
3.6.2 Configuration . . . 10

4 Validation and Results **11**
4.1 Experimental Setup . . . 11
4.1.1 Hardware Configuration . . . 11
4.1.2 Parameter Identification . . . 11
4.2 Spring and Sensor Characterisation . . . 11
4.3 Controller Performance . . . 11
4.4 Assisted Load Handling Evaluation . . . 11
4.5 Discussion . . . 11

5 Conclusion and Future Work **13**
5.1 Conclusion . . . 13
5.2 Future Work . . . 13

References **15**

2D Manufacturing Drawings **17**
.1 CNC Part 1 . . . 17
.2 CNC Part 2 . . . 17
.3 CNC Part 3 . . . 17

Additional Experimental Results **19**

Source Code **21**

List of Figures

1.1 Human, robot, and shared workspace from Fraunhofer [6]. 3
1.2 Levels of cooperation between human worker and robot from Fraunhofer [6]. . 3
1.3 Collaborative robot with sensorized end–effector from [6]. 5

List of Tables

4.1 Example results table. 11

Nomenclature

Symbols

$\boldsymbol{q}$	Joint position vector	[rad]
K_s	Spring stiffness	[Nm/rad]

Abbreviations

CAN	Controller Area Network
SET	Series Elastic Transmission

Chapter 1

Introduction

1.1 Background and Motivation

1.1.1 Musculoskeletal disorders and ergonomic work environments

Non-ergonomic work environments place strain on the human body, which can cause painful complications and limit the worker's ability to perform tasks optimally. How these complications arise, which parts of the body are affected, and how they can be prevented are explained in this section.

The musculoskeletal system contains muscles, bones, joints and connective tissues like tendons and ligaments. Musculoskeletal disorders (MSDs) can therefore be defined as injuries of the muscles, nerves, tendons, joints, cartilage, and spinal discs. When these injuries are sustained or worsened by exposure to risk factors in the workplace, they are also known as work-related musculoskeletal disorders (WMSDs). These disorders can go from minor aches to severe pain and chronic illness requiring medical treatment, potentially preventing workers from performing physical tasks.

WMSDs develop over time due to non-ergonomic working conditions and can be categorized into two main groups:

- Back disorders related to handling loads
- Upper limb disorders, also known as repetitive strain injuries (RSIs)

MSDs can be caused by, for example:

- Twisting and bending movements while handling loads
- Repetitive or forceful movements
- Awkward and static postures
- Exposure to vibrating tools
- Prolonged sitting or standing in the same position

An increase in MSDs has been reported worldwide. This rise is partly attributed to improved recognition and reporting, but also to the tendency for work to be more segmented and specialized. This trend is driven by an increasingly competitive global economy, where fast-paced repetitive work environments are more widespread.

1.1.2 Industrial motivation for ergonomic improvement

Musculoskeletal disorders affect approximately one in three people worldwide. Within the European Union, MSDs represent the most costly health-related problems, affecting 45 million workers, many individuals are unable to continue working after the age of 60 due to these conditions, resulting in billions of euros in lost revenue and a substantial burden on the public healthcare system.

A declining physical condition can also lead to mental health issues such as depression or frustration, resulting in reduced job satisfaction and indirectly lower work performance, even when workers are still physically able to continue working.

The increase in education in the workforce, combined with higher expectations regarding job satisfaction, has reduced workers' tolerance for WMSDs. An ergonomic work environment can prevent the development of WMSDs and directly reduce both the cost to companies due to sick leave and the societal impact. Ergonomics can be defined as the study of work, where the goal is to fit tasks and jobs to workers' capabilities, rather then forcing workers to adapt to the job. An ergonomic work environment therefore implements task-specific strategies to prevent reduced work ability.

Reduced work ability can be categorized in absenteeism and presenteeism. Absenteeism refers to the absence from work due to injuries sustained on the job. Presenteeism describes the situation in which workers continue to attend their expected working duties despite existing injuries, often due to concerns about job security. In such cases, work is performed in a self–protective manner to reduce physical strain.

In Belgium, 2.5 million people were affected by MSDs in 2018 (approximately 62% of the Belgian working population in 2015), resulting in 3 billion euros in direct medical costs and 2 billion in work absenteeism, corresponding to 0.3% of Belgium's gross domestic product [1][2][3][4][5].

1.1.3 Physical human–robot interaction

There is a clear need to address reduced work efficiency resulting from physical injuries since this improves the quality of life of an increasingly aging workforce, but also to reduce the impact on social welfare systems and increase overall economic productivity. Industry has already adapted robotic solutions to achieve accuracy, speed, and repeatability that human workers cannot provide. Humans, however, can provide flexibility and have the capability to react to unforeseen circumstances. By increasing the degree of human participation, the strength and repeatability of robots is combined with the adaptability and decision making skills of humans. This schematic shown below illustrates the different workspaces in which robot and human operate.

Human–robot cooperation generally refers to the use of robots without safety fencing, also called cage–free robots. This in contrast to traditional robots which are stiff, heavy, and lack safety features that allow them to safely operate in the same space as humans, and are consequently only allowed to operate in closed of workspaces.



Figure 1.1: Human, robot, and shared workspace from Fraunhofer [6].

Human and robot can work together in different types of operation, as illustrated in Figure 1.3.



Figure 1.2: Levels of cooperation between human worker and robot from Fraunhofer [6].

From left to right an increasing level of interaction is shown.

- Cell: Robot operates in traditional cage, fenced of from human contact
- Coexistence: Human and cage–free robot work at the same time, but in different workspaces
- Synchronized: Human and cage–free robot work in the same workspace, but one at a time
- Cooperation: Human and cage–free robot have tasks in the same workspace at the same time, but to do not work together on the same task
- Collaboration: Human and cage–free robot work in the same workspace on the same task

The robotic testbench that was built in this thesis falls under coexistence and collaboration

depending on how it is implemented. This is clarified in chapter x?

Collaborative robots, defined as robots capable of performing collaborative tasks as described above, are widely used in industry. However, they are still primarily applied in traditional robotic operations such as pick–and–place tasks. In many cases, humans and robots remain either physically separated or operate in a coexistence mode, where no physical barrier is present but no direct interaction takes place. Such implementations are only economically viable for large batch sizes, since a whole production line needs to be tuned towards that specific robotic solution.

Cage–free robotic arms that share a workspace with a human worker are introduced to increase production flexibility. Interactive robotic solutions for small batches and varying product sizes has become a clear need since 70% of collaboration between human worker and robotic solutions are found in assembly applications. An industry survey reported that 86% of respondents were willing to invest in robotic solutions, indicating strong industrial interest. The primary motivations for introducing robotic arms in assembly environments are:

- Improving operational efficiency
- Improving ergonomics

Cage–free robotic solutions generally involve higher initial costs compared to traditional fenced systems due to safety certification requirements and conformity procedures to minimize the risk of injuries. Companies are however often willing to accept longer payback periods for implementing and testing company specific robotic solutions which increase ergonomics [6].

1.2 Problem Statement

Normative ISO/TS 15066 covers the safety requirements for collaborative operations between human worker and robot. This normative classifies four different collaborative operations modes [7]:

- Safety–rated monitor stop
- Hand–guiding
- Power and force limiting
- Speed and seperation monitoring

One of these categorized modes of human robot collaboration (HRC) is hand–guiding, and is a potential solution for safe collaboration between human and robot. Hand–guided robotic applications are defined as a direct physical interaction between human and robot, where the human operator has full control over the robot motion. In this approach, a direct input device is located at or near the end–effector to measure input forces and simultaneously define the position of the human in the shared workspace.

A direct consequence of this approach is that robotic applications with sensorised end–effectors can only react in a passive compliant manner when handled at a specific point on the robotic arm. Collisions or attemted handling of the robotic arm elsewhere will result in a safety stop

of the robotic arm[8].

Existing robotic solutions that allow a human worker to hand–guide a robotic arm by grasping it wherever is most convenient are, to the best of the authors' knowledge, practically non–existent in assembly and packaging industries. When hand–guiding is discussed in literature, it is typically limited to sensorised end–effectors on conventional stiff robots[9][10].

This absence in current industrial applications is further supported by surveys of end users, system integrators and researchers, which indicate that collaborative robots are still primarily implemented as traditional stiff robots with limited or no direct human interaction [11].

I just started yapping a bit, this is were i am stuck. I think we can sell it as some kind of solution between cobots which have low load capacity and industrial robots which have high load capacity. With only 3 dof it can be a taylored solution for packaging and assembly industry which does not always need 6+ dof (expensive...)

In this thesis, a robotic testbench is developed to test the practical implementation of an intrinsic safe robotic arm, that will be used for weight compensation of loads of varying weights that are guided by a human worker. Compared to existing collaborative robots, where the weight on the end–effector has to be specified before hand in software, this testbench utilizes build in torque sensors which are embedded in the compliant transmissions used for this testbench.

It is important that this solution is intuitive to use to limit the amount of recourced needed to be spend on training of the human workers. The robotic arm should be useable only by buttons that are readily avaible on the arm itself, and not need any software interface which is gebruikelijk for existing cobots.



Figure 1.3: Collaborative robot with sensorized end–effector from [6].

1.3 Thesis Outline

Chapter 2

Literature Review

2.1 Theoretical Background

2.1.1 Example subsection

Example equation:

$$\tau = K_s \, \theta_s \tag{2.1}$$

2.1.2 Another subsection

2.2 State of the Art

2.3 Gap Analysis

Intrinsic safe robot Grasp wherever you want 3dof enough for packaging applications, no need for more dof

Chapter 3

System Design and Implementation

3.1 System Overview and Requirements

3.2 Mechanical Design

3.3 Hardware Architecture

3.3.1 CAN Bus Topology

3.3.2 Sensor Architecture

3.4 Sensor and Actuator Modelling

3.4.1 SET Spring Model

3.4.2 Motor and Transmission Model

3.5 Control Architecture

3.5.1 State Machine

3.5.2 Gravity Compensation and Floating Mode

3.5.3 Weighing Mode

3.5.4 Carrying Mode

3.5.5 Put-Down Mode

3.6 Software Implementation

3.6.1 Real-Time Architecture

Example code listing:

```
while (running) {
    clock_nanosleep(...);
    // your code here
}
```

Listing 3.1: Example listing.

3.6.2 Configuration

Chapter 4

Validation and Results

4.1 Experimental Setup

4.1.1 Hardware Configuration

4.1.2 Parameter Identification

4.2 Spring and Sensor Characterisation

4.3 Controller Performance

4.4 Assisted Load Handling Evaluation

4.5 Discussion

Example table:

Table 4.1: Example results table.

Metric	Target	Achieved
Value 1	X	Y
Value 2	X	Y

Chapter 5

Conclusion and Future Work

5.1 Conclusion

5.2 Future Work

References

[1] B. Oral, Y. Solak, and H. Durmuş, "Evaluation of absenteeism and presenteeism status of factory employees," *WORK: A Journal of Prevention, Assessment & Rehabilitation*, vol. 79, no. 1, pp. 449–457, Sep. 11, 2024, ISSN: 1051-9815, 1875-9270. DOI: 10.3233/WOR-230642. [Online]. Available: https://journals.sagepub.com/doi/10.3233/WOR-230642 (visited on 02/01/2026).

[2] A. Yassi, "Repetitive strain injuries," *THE LANCET*,

[3] R. C. Vilella and A. K. R. Reddivari, "Musculoskeletal Examination,"

[4] IBV, "Musculoskeletal disorders caused by the most common job demands and ergonomic risks," 2017. [Online]. Available: https://ec.europa.eu/programmes/erasmus-plus/project-result-content/c7cc4b4d-52c9-4b5e-a282-46f53f5f5e98/D2.1.MSDs_job_demands_Revised.pdf.

[5] V. Gorasso, J. Van Der Heyden, R. De Pauw, I. Pelgrims, E. M. De Clercq, K. De Ridder, S. Vandevijvere, S. Vansteelandt, B. Vaes, D. De Smedt, and B. Devleesschauwer, "The health and economic burden of musculoskeletal disorders in Belgium from 2013 to 2018," *Population Health Metrics*, vol. 21, no. 1, p. 4, Apr. 21, 2023, ISSN: 1478-7954. DOI: 10.1186/s12963-023-00303-z. [Online]. Available: https://pophealthmetrics.biomedcentral.com/articles/10.1186/s12963-023-00303-z (visited on 02/01/2026).

[6] M. Bender, M. Braun, P. Rally, and O. Scholtz, "Lightweight robots in manual assembly - best to start simply!" Fraunhofer institute for industrial engineering, 2016, p. 63. [Online]. Available: https://publica-rest.fraunhofer.de/server/api/core/bitstreams/961b5036-c442-47db-84a6-b5334b4c1221/content.

[7] M. J. Rosenstrauch, T. J. Pannen, and J. Krüger, "Human robot collaboration - using kinect v2 for ISO/TS 15066 speed and separation monitoring," *Procedia CIRP*, vol. 76, pp. 183–186, 2018, ISSN: 22128271. DOI: 10.1016/j.procir.2018.01.026. [Online]. Available: https://linkinghub.elsevier.com/retrieve/pii/S2212827118300404 (visited on 02/02/2026).

[8] B. Siciliano and O. Khatib, Eds., *Springer Handbook of Robotics* (Springer Handbooks). Cham: Springer International Publishing, 2016, ISBN: 978-3-319-32550-7 978-3-319-32552-1. DOI: 10.1007/978-3-319-32552-1. [Online]. Available: https://link.springer.com/10.1007/978-3-319-32552-1 (visited on 04/14/2026).

[9] R. Gregor, A. Babinec, F. Duchoň, and M. Dobiš, "Hand Guiding a Virtual Robot Using a Force Sensor," *Acta Mechanica et Automatica*, vol. 15, no. 3, pp. 177–186, Sep. 1, 2021, ISSN: 2300-5319. DOI: 10.2478/ama-2021-0023. [Online]. Available: https://www.sciendo.com/article/10.2478/ama-2021-0023 (visited on 02/03/2026).

[10] A. Hameed, A. Ordys, J. Możaryn, and A. Sibilska-Mroziewicz, "Control System Design and Methods for Collaborative Robots: Review," *Applied Sciences*, vol. 13, no. 1, p. 675, Jan. 3, 2023, ISSN: 2076-3417. DOI: 10.3390/app13010675. [Online]. Available: https://www.mdpi.com/2076-3417/13/1/675 (visited on 02/03/2026).

[11] E. Montini, F. Daniele, L. Agbomemewa, M. Confalonieri, V. Cutrona, A. Bettoni, P. Rocco, and A. Ferrario, "Collaborative Robotics: A Survey From Literature and Practitioners Perspectives," *Journal of Intelligent & Robotic Systems*, vol. 110, no. 3, p. 117, Aug. 6, 2024, ISSN: 1573-0409. DOI: 10.1007/s10846-024-02141-z. [Online]. Available: https://link.springer.com/10.1007/s10846-024-02141-z (visited on 02/03/2026).

2D Manufacturing Drawings

.1 CNC Part 1

.2 CNC Part 2

.3 CNC Part 3

Additional Experimental Results

Source Code

https://github.com/username/repository