

DigiSign Identify PoC

User Manual

Real staging setup, current UI workflow, public callback requirements, and end-to-end identity-verification testing.

1 Prepare	2 Publish	3 Verify	4 Review
---------------------	---------------------	--------------------	--------------------

Audience	Version
Administrators, developers, testers, operators, and first-time users	1.2 - July 2026

Important change

Real DigiSign staging rejects localhost as redirectUrl because the host has no top-level domain. Use an approved public HTTPS origin and open the PoC through that same origin.

Contents

Section	Topic	Page
1	About this manual	3
2	Official API facts and observed staging rules	4
3	Real-life test prerequisites	5
4	Obtain staging access	6
5	Configure Identify scenarios	7
6	Create API credentials	8
7	Install and run the PoC	9
8	Publish the PoC for a real test	10
9	Current application UI	11
10	Authenticate and select a scenario	12
11	Configure and start verification	13
12	Complete verification and review result	14
13	Manual acceptance test	15
14	Troubleshooting	16
15	Security and production limitations	17
16	API contract reference	18
17	Glossary and references	19

Shortest reading path

For the first real test, read sections 2, 3, 8, 9, 10, 11, and 12.

Flow diagram Appendix A on page 20 shows the complete browser, PoC, and DigiSign sequence.

1. About this manual

This manual describes the current DigiSign Identify PoC and the conditions required to execute a real provider test.

What the PoC demonstrates

- Requesting a bearer JWT from DigiSign using accessKey and secretKey, or accepting an existing JWT.
- Loading available Identify scenarios and visibly confirming the selected scenario.
- Creating and starting an identification.
- Opening DigiSign in a new tab, not an iframe.
- Returning through redirectUrl and retrieving the authoritative status from DigiSign.

What changed in version 1.2

- The current UI places callback URL and link expiry under Additional options.
- One loaded scenario is selected automatically; the selected name, approval mode, and ID are shown.
- The Create button stays disabled until local readiness checks pass.
- Provider validation details are displayed when DigiSign returns an error.
- The manual no longer treats localhost as a workable real-provider callback.

PoC scope

The application remains intentionally small. It is not a production identity-verification service.

Flow diagram See Appendix A, page 20, for the complete server-to-server and browser redirect flow.

2. Official API facts and observed staging rules

Source: DigiSign staging OpenAPI, version **2026-07-10**, published at <https://api.staging.digisign.org/api/docs>.

Documented by the official OpenAPI

Input	Official contract
identifyScenario	Required string in UUID format.
redirectUrl	Optional Url schema: string, URI format. Official example: https://example.com .
name	Optional string, maximum 255 characters.
linkExpiration	Optional integer from 1 to 10080 minutes; documented default is 5.
Authentication	Bearer JWT; /api/auth-token accepts required accessKey and secretKey.

Confirmed by the real staging validator

localhost is rejected

A create request with <https://localhost:7025/Callback> returned: **redirectUrl: Teto URL neni domena nejvyssiho radu**. Meaning: the URL does not contain a top-level domain.

The public schema says URI and gives a normal HTTPS domain as its example. The explicit top-level-domain rule is a runtime validation condition confirmed by the staging response. This manual distinguishes those two evidence sources.

Practical interpretation

- Do not use localhost, 127.0.0.1, a machine name, or an internal-only host for a real DigiSign test.
- Use a valid host with a top-level domain, for example a company test domain or an approved tunnel domain.
- Use HTTPS with a browser-trusted certificate for a realistic and safe identity flow.

3. Real-life test prerequisites

Required	Condition
DigiSign environment	Staging account with Identify and REST API access.
Credentials	Active staging API key or valid staging bearer JWT.
Scenario	Active Identify scenario available to the same account; ID is a UUID.
Callback host	Valid hostname with a top-level domain; localhost is rejected.
Reachability	Callback is reachable by the participant's browser for the full test.
Transport	Public HTTPS with a trusted certificate is the recommended real-test setup.
Same origin/session	Open the PoC through the same public origin used in redirectUrl.
Browser	Same browser session, cookies enabled, pop-up/new-tab allowed.
Participant	Authorised tester, supported identity document, working camera.
Application	PoC remains running until callback status has been retrieved.

Same-origin rule for this PoC

The PoC stores Base URL, bearer JWT, and identification ID in its in-memory browser session. If you start at localhost but return to a public domain, the callback uses a different cookie origin and cannot find the session.

Correct real-test pattern

Open PoC: `https://poc-test.your-company.cz`
redirectUrl: `https://poc-test.your-company.cz/Callback`

Both addresses use the same scheme and host.

The domain above is illustrative. Use a real approved test domain assigned to your environment.

4. Obtain DigiSign staging access

Staging and production have separate accounts, credentials, scenarios, and data.

Request

To: podpora@digisign.cz
Subject: DigiSign Identify staging access for PoC

Please provide a staging account with DigiSign Identify, REST API access, API-key administration, and permission to create or use Identify verification scenarios.

Verify after login

- 1 Open <https://app.staging.digisign.org/selfcare/login>.
- 2 Confirm that Identify settings and verification scenarios are visible.
- 3 Confirm that API keys can be created or an administrator can create one.
- 4 Ask DigiSign support to enable any missing module or permission.

Environment mapping

Purpose	Staging	Production
Administration	https://app.staging.digisign.org	https://app.digisign.org
API	https://api.staging.digisign.org	https://api.digisign.org

Never mix environments

Staging credentials and scenario IDs must be used with the staging API.

5. Configure Identify scenarios

The scenario is configured manually in DigiSign. The PoC sends its ID; it does not decide document, selfie, or liveness rules.

- 1 Open **Settings / DigiSign IDENTIFY / Verification scenarios**.
- 2 Create or open the intended scenario.
- 3 Use a clear name and set it Active.
- 4 For the ID-card test, enable the required country and ID card as a primary document.
- 5 Use Automatic when the test must include automated document/person checks.
- 6 Review selfie, liveness, manual-review, consent, evaluation, and retention settings.
- 7 Save the scenario.

Supported approval modes in the official API

Mode	Meaning for the PoC
none	Evidence collection without a provider approval decision.
manual	An administrator reviews and approves or denies.
automatic	Automated checks; uncertain cases may require review.

ID-card scenario

Supported. The PoC can use any available Identify scenario UUID. The actual ID-card support depends on the scenario configuration and DigiSign account capabilities.

6. Create API credentials

- 1 Open **Settings / For developers / API keys** in staging administration.
- 2 Create a key with access to authentication, scenario information, and identifications.
- 3 Save accessKey and secretKey immediately in an approved password manager.
- 4 Do not add either value to appsettings.json, Git, screenshots, or work items.

API-key example		
Environment	Staging	Must match API Base URL
accessKey	Longer-lived key identifier	Required for /api/auth-token
secretKey	Secret shown at key creation	Required for /api/auth-token
Bearer JWT	Returned by DigiSign	Short-lived API credential

Current UI behavior

Enter accessKey and secretKey and select Get bearer token. The secret is cleared after the request. Alternatively, paste an existing bearer JWT.

7. Install and run the PoC

Required software

Software	Requirement	Check
.NET SDK	Version 10.x	dotnet --version
Git	Current Windows version	git --version
Browser	Edge or Chrome	Open normally
Camera	Working device	Test with Windows Camera

Update, trust HTTPS, build, and run

```
cd C:\Projects\PoC_DigiSign
git pull origin main
cd DigiSignPoC
dotnet dev-certs https --trust
dotnet build
dotnet run --launch-profile https
```

Local endpoints are normally:

- https://localhost:7025
- http://localhost:5144

Localhost limitation

Local endpoints are useful for application development and mock testing. The current DigiSign staging create endpoint rejects a localhost redirectUrl, so a public-domain setup is required for the real provider flow.

8. Publish the PoC for a real test

Use an organisation-approved temporary deployment or HTTPS tunnel that gives the PoC a valid public domain.

Required routing

Public request	Forwarded to the PoC
https://poc-test.your-company.cz/	PoC home page
https://poc-test.your-company.cz/Callback	PoC /Callback route

Procedure

- 1 Start the PoC.
- 2 Start the approved HTTPS tunnel or deploy the PoC to an approved test host.
- 3 Verify the public home page opens without a certificate warning.
- 4 Open the PoC using the **public URL**, not localhost.
- 5 Under Additional options, set redirectUrl to the same public origin plus **/Callback**.
- 6 Complete the test in the same browser session.
- 7 Remove the tunnel/deployment immediately after testing if it is temporary.

Incorrect

Open https://localhost:7025 but set redirectUrl to https://public-domain/Callback. The public callback will not have the localhost session cookie.

Correct

Open https://public-domain and use https://public-domain/Callback. The session cookie and callback share the same origin.

9. Current application UI

1. DigiSign environment		
Base URL	https://api.staging.digisign.org	Staging keys only

2. Authentication		
Bearer token	Existing JWT or generated value	Required before API calls
accessKey	Optional when JWT exists	
secretKey	Optional when JWT exists	Cleared after token request
	Get bearer token	

3. Verification scenario		
Scenario	Loaded dropdown or manual UUID	
Selection status	Green panel: name, mode, and ID	One scenario auto-selects
	Load available scenarios	

4. Identification settings		
Display name	PoC Verification	Administrator-friendly label
Additional options	redirectUrl and link validity	Collapsed by default
	Create and start verification	

Readiness validation

The Create button is disabled until the page has a syntactically valid API URL, authentication input, scenario, display name, callback URL, and link-expiration value.

Readiness is not provider validation

The browser currently checks URL syntax, but it does not detect DigiSign's top-level-domain rule. A localhost URL can appear Ready and still be rejected by DigiSign.

10. Authenticate and select a scenario

Authenticate

- 1 Confirm the staging API Base URL.
- 2 Enter accessKey and secretKey.
- 3 Select **Get bearer token**.
- 4 Confirm that the token was obtained. Do not expose it in screenshots.

Load and confirm scenario

- 1 Select **Load available scenarios**.
- 2 If exactly one scenario is returned, the PoC selects it automatically.
- 3 If multiple scenarios are returned, select the intended one.
- 4 Verify the green panel shows the expected scenario name, approval mode, and UUID.

Selected scenario confirmation		
Name	ECUPK PoC - automatic Czech ID card	Example
Approval mode	automatic	
Scenario ID	xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx	Must be UUID

Do not proceed on assumption

The scenario shown in the green selected-scenario panel is the scenario sent to POST /api/identifications.

11. Configure and start verification

Main field

Field	Recommended value
Display name	A non-sensitive test label, for example ECUPK PoC test 001.

Additional options

Field	Real-test value
redirectUrl	Public HTTPS URL with a real top-level domain, same origin used to open the PoC, ending /Callback.
Start-link validity	Keep 0. The PoC omits the field and DigiSign uses its documented default of 5 minutes.

Example only:
`https://poc-test.your-company.cz/Callback`

- 1 Confirm the readiness panel is green.
- 2 Confirm the public callback value again.
- 3 Allow pop-ups/new tabs.
- 4 Select **Create and start verification**.
- 5 If DigiSign rejects the request, read the displayed DigiSign details.
- 6 Use the fallback link if the verification tab is blocked.

No iframe

The returned identifyUrl must be opened in a new tab or window for document verification.

12. Complete verification and review the result

In DigiSign

- 1 Accept the required consent.
- 2 Choose an allowed document, for example ID card.
- 3 Capture the document with good lighting and all edges visible.
- 4 Complete selfie and liveness instructions when required.
- 5 Submit and wait for processing.
- 6 Let DigiSign return the browser to the public /Callback URL.

On the callback page

Verification Result		
Authoritative status	approved / for_review / denied / ...	Fetches from DigiSign API
Identification ID	Provider UUID	
Approval mode	none / manual / automatic	
Provider timestamps	Completed, approved, or denied	
Query parameters	Technical analysis only	Not trusted as result
	Refresh DigiSign status	

Status	Interpretation
approved	DigiSign approved the identification.
completed	Evidence was submitted; this is not necessarily approval.
for_review	Administrator decision is required; refresh afterwards.
denied	Identification was rejected or failed.
cancelled / expired	Flow was cancelled or not completed in time.

13. Manual acceptance test

Check	Expected result	Result
Environment	Staging credentials, API URL, and scenario belong together.	_____
Public origin	PoC opens through valid public HTTPS domain with trusted certificate.	_____
Callback	Same public origin plus /Callback; no localhost.	_____
Authentication	UI obtains JWT or accepts existing JWT.	_____
Scenario	Expected scenario is visibly selected.	_____
AK-01	Scenario, callback, and display name are configurable.	_____
AK-02	Identification is created and ID displayed.	_____
AK-03	Start returns identifyUrl.	_____
AK-04	DigiSign opens outside iframe.	_____
AK-05	Callback displays authenticated API result and query parameters.	_____
AK-06	0 uses provider default; custom value only when deliberately tested.	_____
AK-07	No credential is committed or shared.	_____
AK-08	Flow, limitations, provider response, and questions are recorded.	_____

Record safely

Date / tester / environment:
Public test origin:
Scenario name / mode / ID:
Identification ID:
Document, selfie, liveness observed:
Callback status:
DigiSign administration status:
Open questions:

14. Troubleshooting

Problem	Cause	Action
redirectUrl: no top-level domain	localhost, IP, machine name, or invalid host.	Use approved public HTTPS domain with TLD.
Callback says session missing	PoC started on a different origin/browser or app restarted.	Open PoC on the same public origin used by redirectUrl and restart flow.
401 token request	Wrong/revoked keys, environment mismatch, or permission.	Re-enter staging keys and verify permissions.
No scenarios	Identify disabled, missing permission, or no available scenario.	Check DigiSign administration/support.
Bad scenario	Wrong UUID, inactive scenario, or environment mismatch.	Reload and confirm the green selection panel.
400 create	Provider rejected scenario, redirectUrl, or name.	Read DigiSign details shown by the PoC.
Start fails	Unsupported expiration or provider state.	Keep link validity 0 for the first test.
No new tab	Pop-up blocked.	Allow pop-ups or use fallback link.
Camera unavailable	Permission denied or camera busy.	Allow camera; close Teams/Zoom/Camera.
for_review remains	Administrator has not decided.	Review in DigiSign, then refresh status.

Provider details

The current PoC displays the provider response below the HTTP error. Include the text in the technical test record, but remove personal data and credentials.

15. Security and production limitations

PoC protections

- secretKey is cleared after token acquisition.
- API keys are not stored in session.
- JWT and identification correlation are kept only in in-memory session.
- Callback status is retrieved from DigiSign's authenticated API.

Exposure risk during a public test

- A tunnel makes the PoC reachable from the internet.
- The PoC has no production login or access-control layer.
- The in-memory session is not suitable for multiple instances or restarts.
- Credentials and identity evidence are sensitive.

Required operational controls

Use an approved temporary hostname, restrict access where possible, use only authorised testers, monitor the test, and remove the public endpoint immediately afterwards.

Production design still required

- Server-side secret storage and token lifecycle.
- Persistent user-to-identification correlation.
- Business rules for every provider status and required check.
- Reliable polling/webhooks, audit, retention, privacy, monitoring, retries, and incident procedures.

16. API contract reference

Official source checked: **DigiSign API OpenAPI 2026-07-10**.

Authenticate

```
POST https://api.staging.digisign.org/api/auth-token
{"accessKey":"...", "secretKey":"..."}
```

Load scenarios

```
GET https://api.staging.digisign.org/api/account/identify-scenarios/info
```

Create

```
POST https://api.staging.digisign.org/api/identifications
{
  "identifyScenario": "<UUID>",
  "redirectUrl": "https://public-test-domain.example/Callback",
  "name": "ECUPK PoC test 001"
}
```

Start

```
POST /api/identifications/{identification}/start
{}
```

PoC behavior: link validity 0 omits linkExpiration.
Official default: 5 minutes.

Retrieve result

```
GET /api/identifications/{identification}
```

Example domain

The hostname public-test-domain.example illustrates URL shape only. Use the real public hostname assigned to your test.

17. Glossary and references

Term	Meaning
PoC	Small proof used to validate provider behavior.
Identify scenario	Configured verification rules and evidence requirements.
Identification	One verification attempt.
Bearer JWT	Short-lived API credential.
redirectUrl	Browser return address sent during identification creation.
Top-level domain	Final DNS suffix such as .cz, .com, or .app. localhost has none.
Public origin	Scheme plus public host (and port when non-default), for example https://poc-test.company.cz .
Same origin	The PoC start page and callback use the same scheme, host, and port.
identifyUrl	DigiSign-hosted verification address returned by start.
Authoritative status	Status retrieved from DigiSign's authenticated API.

Official references

- Current staging API documentation: <https://api.staging.digisign.org/api/docs>
- API version list: <https://api.staging.digisign.org/docs>
- Staging administration: <https://app.staging.digisign.org>
- DigiSign website: <https://www.digisign.cz>
- PoC repository: https://github.com/Ota85/PoC_DigiSign

Support

DigiSign staging, permissions, scenario, or provider-validation questions: podpora@digisign.cz.

End of manual

Version 1.2 - updated for the current UI and the mandatory real-domain callback behavior observed in DigiSign staging.

Appendix A. DigiSign verification flow

Why the PoC uses both the DigiSign API address and the application callback address.

