General Purpose Transistors

PNP Silicon

BC856ALT1G Series



Features

- S and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant



SOT−23 (TO−236)
CASE 318
STYLE 6

MARKING DIAGRAM



xx = Device Code
xx = (Refer to page 6)
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Date Code orientation and/or overbar may vary depending upon manufacturing location.

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Collector-Emitter Voltage BC856, SBC856 BC857, SBC857 BC858, NSVBC858, BC859	V_{CEO}	 −65 −45 −30	V
Collector-Base Voltage BC856, SBC856 BC857, SBC857 BC858, NSVBC858, BC859	V_{CBO}	 −80 −50 −30	V
Emitter−Base Voltage	V_{EBO}	−5.0	V
Collector Current − Continuous	I_C	−100	mAdc
Collector Current − Peak	I_C	−200	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR−5 Board, (Note 1) T_A = 25°C Derate above 25°C	P_D	 225 1.8	 mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	556	°C/W
Total Device Dissipation Alumina Substrate, (Note 2) T_A = 25°C Derate above 25°C	P_D	 300 2.4	 mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	417	°C/W
Junction and Storage Temperature	T_J, T_{stg}	−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. FR−5 = 1.0 x 0.75 x 0.062 in.
2. Alumina = 0.4 x 0.3 x 0.024 in 99.5% alumina.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector – Emitter Breakdown Voltage (I_C = −10 mA) BC856, SBC856 Series	$V_{(BR)CEO}$	−65	–	–	V
BC857, SBC857 Series		−45	–	–	
BC858, NSBVC858 BC859 Series		−30	–	–	
Collector – Emitter Breakdown Voltage (I_C = −10 μA, V_{EB} = 0) BC856 S, SBC856eries	$V_{(BR)CES}$	−80	–	–	V
BC857A, SBC857A, BC857B, SBC857B Only		−50	–	–	
BC858, NSVB858, BC859 Series		−30	–	–	
Collector – Base Breakdown Voltage (I_C = −10 μA) BC856, SBC856 Series	$V_{(BR)CBO}$	−80	–	–	V
BC857, SBC857 Series		−50	–	–	
BC858, NSVBC858, BC859 Series		−30	–	–	
Emitter – Base Breakdown Voltage (I_E = −1.0 μA) BC856, SBC856 Series	$V_{(BR)EBO}$	−5.0	–	–	V
BC857, SBC857 Series		−5.0	–	–	
BC858, NSVBC858, BC859 Series		−5.0	–	–	
Collector Cutoff Current (V_{CB} = −30 V)	I_{CBO}	–	–	−15	nA
(V_{CB} = −30 V, T_A = 150°C)		–	–	−4.0	μA
ON CHARACTERISTICS					
DC Current Gain (I_C = −10 μA, V_{CE} = −5.0 V) BC856A, SBC856A, BC857A, SBC857A, BC858A	h_{FE}	–	90	–	–
BC856B, SBC856B, BC857B, SBC857B, BC858B, NSVBC858B		–	150	–	
BC857C, SBC857C BC858C		–	270	–	
(I_C = −2.0 mA, V_{CE} = −5.0 V) BC856A, SBC856A, BC857A, SBC857A, BC858A		125	180	250	
BC856B, SBC856B, BC857B, SBC857B, BC858B, NSVBC858B, BC859B		220	290	475	
BC857C, SBC857C, BC858C, BC859C		420	520	800	
Collector – Emitter Saturation Voltage	$V_{CE(sat)}$				V
(I_C = −10 mA, I_B = −0.5 mA)		–	–	−0.3	
(I_C = −100 mA, I_B = −5.0 mA)		–	–	−0.65	
Base – Emitter Saturation Voltage	$V_{BE(sat)}$				V
(I_C = −10 mA, I_B = −0.5 mA)		–	−0.7	–	
(I_C = −100 mA, I_B = −5.0 mA)		–	−0.9	–	
Base – Emitter On Voltage	$V_{BE(on)}$				V
(I_C = −2.0 mA, V_{CE} = −5.0 V)		−0.6	–	−0.75	
(I_C = −10 mA, V_{CE} = −5.0 V)		–	–	−0.82	
SMALL– SIGNAL CHARACTERISTICS					
Current – Gain – Bandwidth Product (I_C = −10 mA, V_{CE} = −5.0 Vdc, f = 100 MHz)	f_T	100	–	–	MHz
Output Capacitance (V_{CB} = −10 V, f = 1.0 MHz)	C_{ob}	–	–	4.5	pF
Noise Figure (I_C = −0.2 mA, V_{CE} = −5.0 Vdc, R_S = 2.0 kΩ, f = 1.0 kHz, BW = 200 Hz)	NF				dB
BC856, SBC856, BC857, SBC857, BC858, NSVBC858 Series		–	–	10	
BC859 Series		–	–	4.0	
SWITCHING CHARACTERISTICS					
Delay Time (V_{CC} = −3.0 Vdc, I_C = −10 mA, I_E = −1 mA)	t_d	–	35	–	ns
Rise Time (V_{CC} = −3.0 Vdc, I_C = −10 mA, I_E = −1 mA)	t_r	–	25	–	ns
Storage Time (V_{CC} = −3.0 Vdc, I_C = −10 mA, I_E = −1 mA)	t_s	–	310	–	ns
Fall Time (V_{CC} = −3.0 Vdc, I_C = −10 mA, I_E = −1 mA)	t_f	–	40	–	ns

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.



Figure 1. Normalized DC Current Gain



Figure 2. “Saturation” and “On” Voltages



Figure 3. Collector Saturation Region



Figure 4. Base−Emitter Temperature Coefficient



Figure 5. Capacitances



Figure 6. Current−Gain − Bandwidth Product

BC856/SBC856



Figure 7. DC Current Gain



Figure 8. “On” Voltage



Figure 9. Collector Saturation Region



Figure 10. Base−Emitter Temperature Coefficient



Figure 11. Capacitance



Figure 12. Current−Gain − Bandwidth Product



Figure 13. Thermal Response



Figure 14. Active Region Safe Operating Area

The safe operating area curves indicate I_C–V_{CE} limits of the transistor that must be observed for reliable operation. Collector load lines for specific circuits must fall below the limits indicated by the applicable curve.

The data of Figure 14 is based upon $T_{J(pk)}$ = 150°C; T_C or T_A is variable depending upon conditions. Pulse curves are valid for duty cycles to 10% provided $T_{J(pk)} \leq 150°C$. $T_{J(pk)}$ may be calculated from the data in Figure 13. At high case or ambient temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by the secondary breakdown.

ORDERING INFORMATION

Device	Marking	Package	Shipping†
BC856ALT1G	3A	SOT−23 (Pb−Free)	3,000 / Tape & Reel
SBC856ALT1G*			
BC856ALT3G			10,000 / Tape & Reel
BC856BLT1G	3B	SOT−23 (Pb−Free)	3,000 / Tape & Reel
SBC856BLT1G*			
BC856BLT3G			10,000 / Tape & Reel
SBC856BLT3G*			
BC857ALT1G	3E	SOT−23 (Pb−Free)	3,000 / Tape & Reel
SBC857ALT1G*			
BC857BLT1G	3F	SOT−23 (Pb−Free)	3,000 / Tape & Reel
SBC857BLT1G*			
BC857BLT3G			10,000 / Tape & Reel
NSVBC857BLT3G*			
BC857CLT1G	3G	SOT−23 (Pb−Free)	3,000 / Tape & Reel
SBC857CLT1G*			
BC857CLT3G			10,000 / Tape & Reel
BC858ALT1G	3J	SOT−23 (Pb−Free)	3,000 / Tape & Reel
BC858BLT1G	3K	SOT−23 (Pb−Free)	
NSVBC858BLT1G*			
BC858BLT3G		SOT−23 (Pb−Free)	10,000 / Tape & Reel
BC858CLT1G	3L	SOT−23 (Pb−Free)	3,000 / Tape & Reel
BC858CLT3G		SOT−23 (Pb−Free)	10,000 / Tape & Reel
BC859BLT1G	4B	SOT−23 (Pb−Free)	3,000 / Tape & Reel
BC859BLT3G		SOT−23 (Pb−Free)	10,000 / Tape & Reel
BC859CLT1G	4C	SOT−23 (Pb−Free)	3,000 / Tape & Reel
BC859CLT3G		SOT−23 (Pb−Free)	10,000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

*S and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable.

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS



SCALE 4:1

SOT−23 (TO−236)
CASE 318
ISSUE AT

DATE 01 MAR 2023



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M,1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

	MILLIMETERS			INCHES		
DIM	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.89	1.00	1.11	0.035	0.039	0.044
A1	0.01	0.06	0.10	0.000	0.002	0.004
b	0.37	0.44	0.50	0.015	0.017	0.020
c	0.08	0.14	0.20	0.003	0.006	0.008
D	2.80	2.90	3.04	0.110	0.114	0.120
E	1.20	1.30	1.40	0.047	0.051	0.055
e	1.78	1.90	2.04	0.070	0.075	0.080
L	0.30	0.43	0.55	0.012	0.017	0.022
L1	0.35	0.54	0.69	0.014	0.021	0.027
H_E	2.10	2.40	2.64	0.083	0.094	0.104
T	0°	---	10°	0°	---	10°

GENERIC MARKING DIAGRAM*



XXX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.



RECOMMENDED
MOUNTING FOOTPRINT

* For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42226B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**SOT−23 (TO−236)**		**PAGE 1 OF 2**

SOT−23 (TO−236)
CASE 318
ISSUE AT

DATE 01 MAR 2023

STYLE 1 THRU 5:
CANCELLED

STYLE 6:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 7:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

STYLE 8:
PIN 1. ANODE
2. NO CONNECTION
3. CATHODE

STYLE 9:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 10:
PIN 1. DRAIN
2. SOURCE
3. GATE

STYLE 11:
PIN 1. ANODE
2. CATHODE
3. CATHODE−ANODE

STYLE 12:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 13:
PIN 1. SOURCE
2. DRAIN
3. GATE

STYLE 14:
PIN 1. CATHODE
2. GATE
3. ANODE

STYLE 15:
PIN 1. GATE
2. CATHODE
3. ANODE

STYLE 16:
PIN 1. ANODE
2. CATHODE
3. CATHODE

STYLE 17:
PIN 1. NO CONNECTION
2. ANODE
3. CATHODE

STYLE 18:
PIN 1. NO CONNECTION
2. CATHODE
3. ANODE

STYLE 19:
PIN 1. CATHODE
2. ANODE
3. CATHODE−ANODE

STYLE 20:
PIN 1. CATHODE
2. ANODE
3. GATE

STYLE 21:
PIN 1. GATE
2. SOURCE
3. DRAIN

STYLE 22:
PIN 1. RETURN
2. OUTPUT
3. INPUT

STYLE 23:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 24:
PIN 1. GATE
2. DRAIN
3. SOURCE

STYLE 25:
PIN 1. ANODE
2. CATHODE
3. GATE

STYLE 26:
PIN 1. CATHODE
2. ANODE
3. NO CONNECTION

STYLE 27:
PIN 1. CATHODE
2. CATHODE
3. CATHODE

STYLE 28:
PIN 1. ANODE
2. ANODE
3. ANODE

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales