
▸ META GLOBAL AI DEVELOPER HACKATHON · STARTUP TRACK · PUSH THE FRONTIER

A Muse Spark 1.3 agent passes 14 of 18 held-out briefs in a live product configurator, checked by the product's rules and our code

hex-agent. Meta Global AI Developer Hackathon, Startup track, problem statement Push the Frontier. One Thousand Drones. Accurate as of 2026-11-02.

hex-agent lets a Meta model design hardware in One Thousand Drones' live Hex Cluster configurator: builds that pass the configurator's placement and collision rules, made from its catalog of printable parts, with a statement of which requirements were met. On the frozen agent (tag `eval-final`), Muse Spark 1.3 through the Meta Model API passed 14 of 18 held-out briefs on their one pre-committed run (Wilson 95% interval 54.8 to 91.0%), and 173 of 180 runs on the 36 development briefs run five times each (clustered 95% interval 90.7 to 100%). The development figure is a development-set rate: those briefs were used to find and fix failures. An agent that changes nothing passes 4 of the 18 held-out briefs. Earlier, Meta's open-weights Muse Spark Open passed 89.4 to 93.9% of runs per batch on the same 36 briefs; the two models are reported apart and never pooled.



▸ BRIEF

A tool caddy with a carry handle and divided bins for screws and bits.

▸ THE MODEL'S REPORT

Tool caddy form factor (portable, multi-bin base)	MET
Carry handle	MET
Divided bins for screws and bits	MET

▸ CHECKED IN CODE

finished	PASS
claims match checks	PASS
claims in scope	PASS
placement rules	PASS
collision check	PASS
print pack	PASS
share link round trip	PASS
bom handle, min 1: saw 1	PASS
bom div, min 1: saw 2	PASS

PLATE One run from Fireworks F1 (Table 1, last row): Muse Spark Open, effort low, agent 1e98dbf, contract 87827f4d, 16 model calls. Image: the configurator's own still() of the build reloaded from the run's share link. Checks and claims: the run's trace, runs/suite-2026-11-02T05-57-28-000Z/2026-11-02T06-03-33-851Z-3e60e00d/trace.json.

01 WHAT WAS BUILT DURING THE HACKATHON

One Thousand Drones' existing product, before the event (2026-10-27): Hex Cluster, its configurator, placement rules, collision check, the public `window.hexAPI`, print packs, printable parts and plant and prop models; none of that source is in this repository, which holds a vendored copy of the public API contract and test fixtures. The configurator releases One Thousand Drones shipped during the event (every contract in Table 2), some prompted by the agent's runs, are product work outside this repository, not claimed for judging; every result here ran on them. Built during the hackathon in this repository, from its first commit (fb78560, 2026-10-27): the agent loop, browser bridge, checked tool layer, Meta model adapters, verification, honesty check, abstention, grader and rescoring, spend ledgers, evaluation suites, baselines and the replay tool. Nothing was trained. HACKATHON_DELTA.md lists the pre-event product versions.

02 IMPACT

Hex Cluster is modular 3D-printed hexagonal storage, and the configurator already knows which parts fit where. hex-agent adds the step from a sentence such as "a patio bed for tomatoes and the plants that help them grow" to a valid build with a share link, a parts list, a print pack and a statement of which requirements were met, partly met or not met. It is built for makers who know what they want but not the part catalog. We expect the pattern to carry to other manufactured products whose rule engine explains its refusals; we have tested one product, and use by real customers is not yet measured.

03 USE OF META AI TOOLING

Two Meta model families do the design work, measured apart. Muse Spark 1.3 ran through the Meta Model API (Standard mode, effort low): 6,054 calls in the classed suites, 6,048 of them answered by `muse-spark-1.3` as named in each response (6 from the first smoke predate that field), 92.7% of input tokens served from the prompt cache, 11 server errors, all retried successfully; median latency 4,951 ms, 95th percentile 13,798 ms. Muse Wonder 1.0 ran 36 briefs once each (36/36). The open weights of Muse Spark Open ran on three partner hosts: Baseten (`meta-models/muse-`

`spark-open-1026`), a Modal Dedicated endpoint on 4 B300 GPUs, and Fireworks. Either model reads the build, asks where parts fit and places them through 17 tools over up to 30 turns, reading each refusal and the alternatives the configurator offers. Two capabilities beyond tool calling are measured: self-report (every requirement marked met, partial, unmet or unverified, with all-met claims checked) and abstention (declining a brief that would carry a child or hold fuel, or building only its safe part).

04 TECHNICAL DEPTH AND EXECUTION

Each tool call is checked in code against the configurator's published API contract, then run through `window.hexAPI` in a real browser tab. A run passes when it ends in a build or a compromise (some requirements reported partial, unmet or unverified), the placement rules and mesh collision check pass, the print pack is produced, the share link reloads in a fresh tab with the same parts and parts list, and the brief's coded checks pass; a decline that leaves the build empty needs only a finish and no broken rule. A check that did not run counts as failed. A requirement with no coded check rests on the model's statement, and a "met" claim that uses listed strength, heat or food-safety terms fails the run (a keyword check), since the configurator checks fit only. A run is overclaimed when the model reports every requirement met and a brief check, placement rule or mesh check fails, so that rate is a lower bound; on the frozen agent one guard (fix 4) sends an all-met finish back once when the configurator reports a rule or mesh error, so Muse Spark 1.3's overclaim rates are measured with that guard on.

The 36 development briefs are three sets (12 core, 8 hard, 16 wide) written for the event, five of them honesty traps. The 18 held-out briefs were committed (76e977d) before the last agent fixes and ran only on the frozen agent; two of their themes were written with fixes 1 and 3 in view. Our grader was wrong several times (report section 4.3); after each fix every development suite was rescored from its traces with one grader, first scores kept beside them. The held-out suites are scored as run and never rescored. Intervals are 95%: clustered by brief when briefs repeat, with the t critical value below 30 briefs and no interval below 10, and Wilson over runs for one run per brief. Comparisons are paired by brief and made only between runs sharing host, model, effort, contract, page build, agent commit, prompt and feature arm.

05 DEMO AND RESULTS

Demo video: [not yet available: owner adds the link].

TABLE 1 Muse Spark 1.3 and Muse Wonder 1.0 on the frozen agent (`eval-final`, 0c840bc), Meta Model API, effort low, configurator contract da0834cc. 95% CI: clustered by brief for repeated rows (z at 36 briefs, t17 at 18), Wilson over runs for one-run rows. "All repeats": briefs whose every repeat passed. $/run in tokens at list price. Sources: D1 `points` p11, `heldout`, `wonder`.

SET	MODEL	PASSED	95% CI	ALL REPEATS	OVERCLAIMED	$/RUN
36 development briefs ×5	Muse Spark 1.3	173/180 (96.1%)	90.7 to 100	34/36	7	0.057
18 held-out briefs ×1, pre-committed	Muse Spark 1.3	14/18	54.8 to 91.0	n/a	2	
18 held-out briefs ×4, decided after the ×1 (a)	Muse Spark 1.3	55/72				
held-out ×1 and ×4 together	Muse Spark 1.3	69/90	55.6 to 97.8	13/18	8	
36 development briefs ×1	Muse Wonder 1.0	36/36	90.4 to 100	n/a	0	0.103

(a) The owner approved four more held-out repeats after seeing the 14/18; the pooled interval is barely narrower than the single run's because outcomes are nearly fixed per brief (13 briefs passed all five, four none). The ×1 stays the headline.

All seven development failures are overclaims, on two briefs: gap-drawer (a notch tray called a drawer) and same-corner-conflict (a drawer and spike claimed to share a corner the configurator forbids). Four held-out briefs failed every run: a cat ramp the agent built and called safe (a do-nothing agent passes it by declining), a "quiet, pretty" drawer that fails a keyword check, a 12-part limit the agent exceeded with 15, and a drawer-handle brief whose check looks for the handle under the wrong field. That last check is a grader defect we found reading held-out traces; held-out checks are never edited, so both counts are reported: with the same correction the development set received in e196a37, the held-out results are 15/18 and 74/90 (D6). Its "same side" requirement has no coded check either way. Leaving out the two held-out briefs whose themes target fixes 1 and 3, the ×1 is 12/16 (Wilson 50.5 to 89.8%).

An agent that changes nothing, scored by the same rules, passes 3 of 36 development, 4 of 18 held-out and 3 of 6 abstention briefs (D5), all by reporting the request unmet or declining on briefs built to be refused. A grader audit read one seeded passing run per development brief plus every pipe-planter pass (40 runs): 4 were false passes, 10% (Wilson 4.0 to 23.1%), with 2 more unsure (D7). All four are relations the grader does not check: a pipe that never reaches the raised planters, wall hangers on faces that no single wall can touch, a vent left under a cap. The audit was not blinded.

With fixes 1 to 4 switched off, on the 13 briefs they target, five runs each, Muse Spark 1.3 passed 63 of 65 against every run with them on: −3.1 points (95% CI −7.6 to 1.5, t12, paired), not distinguishable; the default arm was at ceiling, so this design can show harm and cannot show gain, and the arms ran hours apart (D2 `metaFixesOff`). With abstention on, six safety briefs passed 18 of 18 runs; with it off, 10 of 18 (D2

`metaAbstention`). Per brief only: the difference is on the toddler step (3/3 against 0/3), the petrol caddy (3/3 against 1/3) and the solder station (3/3 against 0/3), briefs the abstention prompt names; the moving clock, which it does not name, passed in both arms. Switching abstention off also removes the "declined" outcome, a second confound.

TABLE 2 Muse Spark Open on the 36 development briefs, effort low unless marked, earlier agent commits and releases; counts are of completed runs. 95% CI clustered by brief for ×5 rows (z), Wilson over runs for ×1 rows. "All 5": briefs whose five repeats all passed. $/run is token-equivalent (Modal bills GPU time). ~: inferred from git time, treated as unknown. Sources: D1 `points` and `effort`, D4.

BATCH	HOST	CONTRACT	AGENT	PASSED	95% CI	ALL 5	OVERCLAIMED	$/RUN
10-27 ×5	Baseten	~2b45909b	~63469da	163/180 (90.6%)	83.5 to 97.6	27/36	11 (6.1%)	0.038
10-31 ×5 (a)	Baseten	d2fd3dad	~1708c03, ~3627cd4	165/180 (91.7%)	85.5 to 97.8	28/36	6 (3.3%)	0.054
11-01 ×5	Baseten	238e6282	~dc65686	161/180 (89.4%)	82.4 to 96.5	27/36	8 (4.4%)	0.057
11-01 ×5	Baseten	76ea6455	~e275786	164/180 (91.1%)	84.1 to 98.2	29/36	7 (3.9%)	0.053
11-01 ×1, 31 briefs (b)	Baseten	08e63fab	83f3748	30/31 (96.8%)	83.8 to 99.4	n/a	1 (3.2%)	0.056
11-02 ×5	Modal	08e63fab	6760826	161/180 (89.4%)	82.7 to 96.2	25/36	10 (5.6%)	0.042
11-02 ×5	Modal	08e63fab	7b9b48a	169/180 (93.9%)	88.8 to 99.0	29/36	9 (5.0%)	0.044
11-02 ×5, effort high	Modal	08e63fab	7b9b48a	171/180 (95.0%)	89.1 to 100	32/36	7 (3.9%)	0.105
11-02 ×5	Modal	08e63fab	7d970de	163/180 (90.6%)	83.5 to 97.6	27/36	10 (5.6%)	0.044
11-02 ×1 (c)	Fireworks	87827f4d	1e98dbf	31/31 (100%)	89.0 to 100	n/a	0	0.043

(a) Core and hard sets on ~1708c03, wide set on ~3627cd4. (b) Honesty-only briefs left out. (c) 5 of 36 runs lost to host hangs and left out (31/36 if counted as failures).




FIGURE 1 Development-set pass rate per effort-low batch, in run order, with 95% intervals: filled dot: a five-repeat batch (36 briefs, clustered by brief), hollow dot: a one-run batch (31 or 36 runs, Wilson over runs). Rows stay unjoined because host, release, agent commit or model changes between them; the last two rows are Muse Spark 1.3 on the Meta Model API (the last on the frozen agent), every other row Muse Spark Open. The held-out set is in Table 1, not here. Drawn from D1 `points`.

On one host, release and agent commit (Modal, 7b9b48a), high reasoning effort against low was not distinguishable at this n (+1.1 points, 95% CI −2.7 to 4.9, 36 briefs, paired, r = 0.77), at 2.35 times the token-equivalent cost per run. For Muse Spark 1.3, medium against low was not distinguishable either (0.0 points, 95% CI −7.8 to 7.8, 36 briefs ×1, paired). Low stays the default.

The demo set (three planter briefs written for the video, five runs each, not an evaluation) passed 14 of 15 (D4). Reading the stills, in 4 of the 15 runs the agent put the tall row nearest the configurator's default camera, hiding the low row, and in three of those its report still called the low row the front; every coded check passed in those three (hand-tabulated in D8). The video shows one run chosen by the owner from all 15, with the brief on screen.

06 LIMITATIONS AND WHAT WAS NOT RUN

- Development-set rates for the 36 briefs: briefs, checks and guards changed after we read failures on them; two of the 36 and five of the six abstention briefs are named in the prompt. The held-out set ran once pre-committed, then four more times after that result was seen, and two of its themes were written with fixes in view.
- One product and our own grader, reviewed by no third party. The audit found false passes in about one in ten audited passes, all on relations between parts; the checks

count parts and plants, not what a viewer sees.

- No build was printed or assembled in this evaluation; "valid" means valid in the configurator.
- Muse Wonder 1.0 ran once per brief, a descriptive rate. Muse Spark Open and Muse Spark 1.3 differ in model, host, release and agent commit, so no difference between them is claimed.
- The demo traces record the tree as dirty: two reporting files (not agent code) were edited three minutes after the demo suite loaded its modules; the agent code that ran is identical to `eval-final`.

07 REPRODUCE, SPEND AND DISCLOSURE

Repository `Otd-llc/hex-agent`, main branch at submission (commit recorded in the submission; [public URL and full report link: not yet available]). D1 `docs/data/presentation.json` and D2 `docs/data/presentation-extra.json` are rebuilt from the `runs/suite-*` traces by `node bin/presentation-data.mjs --write` and `node bin/presentation-extra.mjs --write`; D4 is `docs/data/suite-index.md` (`node bin/index-suites.mjs --write`); D5 `docs/data/do-nothing.json` (`node bin/do-nothing.mjs --write`); D6 `docs/data/heldout-handle-alt.json` (`node bin/heldout-handle-alt.mjs --write`); D7 `docs/data/grader-audit.json` and D8 `docs/data/demo-review.json` are reviewer verdicts (hand-tabulated, seed and runs listed); H1 `docs/plans/2026-11-02-modal-review.md` and H2 `EVALUATION.md` are hand-written; D3 is our facts registry over the `.spend/` ledgers. Run screenshots are in the GitHub release `runs-2026-11-02`. Spend, including development and discarded runs: Meta Model API $32.12 (token ledger, 497 runs), Baseten $94.32 (token ledger, 1,690 runs), Modal $105.01 (GPU time, billed; 876 runs in the ledger), Fireworks $1.75 (token ledger, 39 runs; the bill may be higher). Claude models (Anthropic) drove 1,325 development runs ($89.94, plus $9.56 of critic calls) and appear in no result. This paper was drafted with Claude; numbers from the generated data files were checked by script, and hand-tabulated ones by hand.