

It's how you use the items that counts: An intelligent procedure for item selection in Item Response Theory

Ottavia M. Epifania¹, Pasquale Anselmi³, Egidio Robusto³

¹ Psychology and Cognitive Science Department, University of Trento, Italy

² Psicostat, University of Padova, Italy

³ Department of Philosophy, Sociology, Education, and Applied Psychology, University of Padova, Italy

Convegno ASA 2024

Contributed session: Developing, administering and refining
measurement instruments in Social Sciences

19 Settembre 2024

1 Aim

2 Item Response Theory and Information Functions

- 2-Parameter Logistic Model
- Item and Test Information Functions

3 Item Selection Procedures

- Item Locating Algorithm – ILA
- Brute Force Procedure

4 Simulation Study

- Simulation design
- Comparison
- Results

New Item Response Theory-based algorithm for the development of
informative short test forms

1 Aim

2 Item Response Theory and Information Functions

- 2-Parameter Logistic Model
- Item and Test Information Functions

3 Item Selection Procedures

- Item Locating Algorithm – ILA
- Brute Force Procedure

4 Simulation Study

- Simulation design
- Comparison
- Results

1 Aim

2 Item Response Theory and Information Functions

- 2-Parameter Logistic Model
- Item and Test Information Functions


3 Item Selection Procedures

- Item Locating Algorithm – ILA
- Brute Force Procedure

4 Simulation Study

- Simulation design
- Comparison
- Results

$$P(x_{pi} = 1 | \theta_p, b_i, a_i) = \frac{\exp[a_i(\theta_p - b_i)]}{1 + \exp[a_i(\theta_p - b_i)]}$$



1 Aim

2 Item Response Theory and Information Functions

- 2-Parameter Logistic Model
- Item and Test Information Functions

3 Item Selection Procedures


- Item Locating Algorithm – ILA
- Brute Force Procedure

4 Simulation Study

- Simulation design
- Comparison
- Results


Item Information Function (IIF):

$$I_i(\theta) = a_i^2 P_i(\theta, b_i, a_i)[1 - P_i(\theta, b_i, a_i)]$$



Test Information Function (TIF):

$$I(\theta) = \sum_{i=1}^I I_i(\theta)$$



- 1 Aim
- 2 Item Response Theory and Information Functions
 - 2-Parameter Logistic Model
 - Item and Test Information Functions
- 3 Item Selection Procedures**
 - Item Locating Algorithm – ILA
 - Brute Force Procedure
- 4 Simulation Study
 - Simulation design
 - Comparison
 - Results

- ① Aim
- ② Item Response Theory and Information Functions
 - 2-Parameter Logistic Model
 - Item and Test Information Functions
- ③ **Item Selection Procedures**
 - Item Locating Algorithm – ILA
 - Brute Force Procedure
- ④ Simulation Study
 - Simulation design
 - Comparison
 - Results

Q^k : vector of the item indexes selected for inclusion in the STF up to iteration k ($Q^0 = \emptyset$)

TIF^* : TIF target

$TIF^0 = 0$

Termination criterion: $|TIF^* - TIF^k| \leq |TIF^* - TIF^{k-1}|$

Iterate:

$$\textcircled{1} \quad \theta_{target} = \arg \max |TIF^* - TIF^{k-1}|$$

$$\textcircled{2} \quad Q^k = Q^{k-1} \cup \arg \min_{i \in \{1, \dots, N\} \setminus Q^{k-1}} |\theta_{target} - b_i|$$

$$\textcircled{3} \quad TIF^k = \frac{\sum_{i \in Q^k} IIF_i}{||Q^k||}$$

$$\textcircled{4} \quad k = k + 1$$

1 Aim

2 Item Response Theory and Information Functions

- 2-Parameter Logistic Model
- Item and Test Information Functions

3 Item Selection Procedures

- Item Locating Algorithm – ILA
- Brute Force Procedure

4 Simulation Study

- Simulation design
- Comparison
- Results

N : Number of items in the item bank

$L = N - 1$: Maximum length of the STFs that can developed from the item bank

$\binom{N}{l}$: number of STFs resulting from the combination of the $l = \{1, \dots, L\}$ items

The algorithm iterates the following steps until the termination criterion is reached:

- ① \overline{TIF} for each STF of length l
- ② $\Delta_{TIF} = TIF^* - \overline{TIF}$
- ③ $\overline{\Delta}_{TIF}$

The best STF is the one with the lowest value of $\overline{\Delta}_{TIF}$, that is the one that presents the lowest absolute distance from the TIF target.

- ① Aim
- ② Item Response Theory and Information Functions
 - 2-Parameter Logistic Model
 - Item and Test Information Functions
- ③ Item Selection Procedures
 - Item Locating Algorithm – ILA
 - Brute Force Procedure
- ④ **Simulation Study**
 - Simulation design
 - Comparison
 - Results

- ① Aim
- ② Item Response Theory and Information Functions
 - 2-Parameter Logistic Model
 - Item and Test Information Functions
- ③ Item Selection Procedures
 - Item Locating Algorithm – ILA
 - Brute Force Procedure
- ④ **Simulation Study**
 - Simulation design
 - Comparison
 - Results

100 iterations:

- ① Generate an item bank of $N = 6$ items:
 - Difficulty parameters: $\mathcal{U}(-3, 3)$
 - Discrimination parameters: $\mathcal{U}(.90, 2.0)$
- ② Generate TIF^* by randomly selecting items from the item bank (Mean number of items = 3.34 ± 1.13). The parameters of the selected items are modified according to values drawn from uniform distributions $\mathcal{U}(-0.20, 0.20)$.
- ③ Considering the TIF^* at Step 2 and the item parameters at Step 1:
 - ILA \rightarrow Forwardly searches for the best item selection to recover the TIF^*
 - BFP \rightarrow tries every possible item combination to find the STF best able to recover TIF^* $N = 6$ items, $L = 5$ and $\binom{6}{1} + \binom{6}{2} + \binom{6}{3} + \binom{6}{4} + \binom{6}{5} = 62$ STFs are developed and compared.

- ① Aim
- ② Item Response Theory and Information Functions
 - 2-Parameter Logistic Model
 - Item and Test Information Functions
- ③ Item Selection Procedures
 - Item Locating Algorithm – ILA
 - Brute Force Procedure
- ④ **Simulation Study**
 - Simulation design
 - Comparison
 - Results

- $||Q_{\text{BFP}}|| - ||Q_{\text{ILA}}||$
- Percentile rank of the distance between the STF selected by BFP and that selected by ILA

- ① Aim
- ② Item Response Theory and Information Functions
 - 2-Parameter Logistic Model
 - Item and Test Information Functions
- ③ Item Selection Procedures
 - Item Locating Algorithm – ILA
 - Brute Force Procedure
- ④ **Simulation Study**
 - Simulation design
 - Comparison
 - Results

57% $\|Q_{\text{BFP}}\| - \|Q_{\text{ILA}}\| = 0 \rightarrow 72\%$ same item selection







Figure: 43% $\|Q_{\text{BFP}}\| - \|Q_{\text{ILA}}\| \neq 0$




$$\|Q_{\text{BFP}}\| = \|Q_{\text{ILA}}\|, Q_{\text{BFP}} \neq Q_{\text{ILA}}$$



$$\|Q_{\text{BFP}}\| > \|Q_{\text{ILA}}\|$$



$$\|Q_{\text{BFP}}\| < \|Q_{\text{ILA}}\|$$



$$\|Q_{\text{BFP}}\| < \|Q_{\text{ILA}}\|$$

