

First Steps with Item Response Theory

Introduction to Item Response Theory models

Dr. Ottavia M. Epifania

University of Trento, 17 November 2023

Rovereto (TN)

① Introduction

② 1-PL

③ 2PL

④ 3PL

⑤ 4PL

⑥ Relationship between models

| | | | | | |
|----------------------|----------------------|----------------------|----------------------|------|-----------------------------|
| Introduction | 1-PL | 2PL | 3PL | 4PL | Relationship between models |
| oooooooooooooooooooo | oooooooooooooooooooo | oooooooooooooooooooo | oooooooooooooooooooo | oooo | oooooooooooo |

Introduction

Latent variables

Latent variables

- Variables that cannot be directly observed → **Latent variables** (e.g., Intelligence)
- Inferred from **directly observed indicators** → **Observed variables** (e.g., the response to the Raven's matrices)
- *Operationalization of the latent variable* is crucial


Introduction

Modelling latent variables

The **latent variables** must be linked to the **observed variables** →
mathematical and statistical models

Assumptions:

- The **latent variables** are the underlying cause of the **observed variables**
- *Local independence*: The correlation between the **observed variables** disappears after controlling for the influence of the **latent variable**



○○○○○○●○○○○○○○○

○○○○○○○○○○○○○○○○○○


○○○○○○○○○○○○○○○○○○

○○○○○○○○○○○○○○○○○○

○○○○

○○○○○○○○○○○○

Modelling latent variables



IRT models and Rasch model → **Models for latent trait**

Introduction

IRT vs. CTT

IRT models and Classical Test Theory (CTT) models have the same aim
 → “measuring” people → locate the position of each person on a latent
 trait

IRT

Focus → **Items**

CTT

Focus → **Test**

Introduction

Basics of IRT

The probability of an observed response (**observed variable**) depends on the characteristics of both the **person** and the **item**

The characteristics of the **person** can be described by a parameter of the person → **latent trait** (e.g., intelligence, self-esteem, extroversion etc.)

The characteristics of the **item** can be described by one or more parameters, (**difficulty, discrimination, guessing, careless error**)

The item, the person and their characteristics are located on the same latent trait


 A_{Lisa}
Q1

$$3 + 2 = ?$$

 d_{Q1}
Q2

$$3x - 2y + 4 = ?$$

 d_{Q2}

 A_{Bart}

Different IRT models according to:

① Latent trait:

- Unidimensional model
- Multidimensional model

② Response categories:

- Dichotomous items (Two response categories, e.g., true/false, agree/disagree)
- Polytomous items (at least 3 response categories, e.g., Likert-type scale)

These models can be distinguished according to the number of parameters describing the characteristics of the items.

- One-Parameter Logistic Model (1-PL)
- Two-Parameter Logistic Model (2-PL; Birnbaum, 1968)
- Three-Parameter Logistic Model (3-PL; Lord, 1980)
- Four-Parameter Logistic Model (4-PL; Barton & Lord, 1981)

- Person and items parameters are on the same latent trait
- As the distance on the latent trait between the person parameter and the item parameter increases, the probability of a correct response changes
- When the parameter of the person matches the parameter of the item, then the probability of observing a correct response is 50% (Only for the 1-PL)

1-PL

1-PL

Item Response Function

The probability that person p responds correctly to item i is formalized as

$$P(x_{pi} = 1 | \theta_p, b_i) = \frac{\exp(\theta_p - b_i)}{1 + \exp(\theta_p - b_i)}$$

θ_p : Ability of the person (i.e., latent trait level of the person) \rightarrow The value of θ_p , the higher the amount of latent trait of p

b_i : difficulty of item i (location of the item on the latent trait) \rightarrow The higher the value of b_i , the more difficult the item is

1-PL

Item Characteristic Curve

oooooooooooooooooooo

oooo●ooooooooooooo

oooooooooooooooooooo


oooooooooooooooooooo

oooo

oooooooooooo

Item Characteristic Curve

Item Characteristic Curve (ICC)



oooooooooooooooooooo

ooo●oooooooooooo

oooooooooooooooooooo


oooooooooooooooooooo

oooo

oooooooooooo

Item Characteristic Curve

ICC – Different locations



| | item1 | item2 | item3 | item4 | item5 |
|---|-------|-------|-------|-------|-------|
| b | -2.50 | -1.25 | 0.00 | 1.25 | 2.50 |

1-PL

Item Information Function


Measure of the precision with which the item assesses different levels of the latent trait → *Item Information Function*:

$$I_i = P_i(\theta, b_i)Q_i(\theta, b_i)$$

$Q = 1 - P_i(\theta_p, b_i)$ is the probability of choosing the incorrect response

The IIFs maximized when $\theta_p = b_i \rightarrow P(x_{pi} = 1) = P(x_{pi} = 0) = 0.50 \rightarrow I_i = .25$

Item Information Function – IIF



The item is mostly informative for subjects with a latent trait level close to the location of the item → the higher the distance between the latent trait level of the person and the location of the item, the lower the IFF

High variability in the latent trait levels of the respondents → items with locations spread along the entire latent trait

IRT

The more the item locations are spread along the trait, the merrier


CTT

Items should be as homogeneous as possible

oooooooooooooooooooo ooooooooooooo●oooooooo ooooooooooooooooooooo ooooooooooooooooooooo ooooo ooooooooooooo

Item Information Function

IIF- Item with different locations



| | item1 | item2 | item3 | item4 | item5 |
|-----|-------|-------|-------|-------|-------|
| b | -2.50 | -1.25 | 0.00 | 1.25 | 2.50 |

1-PL

Test Information Function

Test Information Function

Measure of the precision with which the test assesses the latent trait:

$$I(\theta) = \sum I_i(\theta, b_i) =$$

oooooooooooooooooooo

oooooooooooooooooooo●ooo


oooooooooooooooooooo

oooooooooooooooooooo

oooo

oooooooooooo

Test Information Function



| | item1 | item2 | item3 | item4 | item5 |
|---|-------|-------|-------|-------|-------|
| b | -2.50 | -1.25 | 0.00 | 1.25 | 2.50 |


$$SEM(\theta) = \sqrt{\frac{1}{I(\theta)}} = \sqrt{\frac{1}{P_i(\theta, b_i)Q_i(\theta, b_i)}}$$

The higher the information, the lower the SEM

The lower the information, the higher the SEM

Differently from CTT → the error of measurement can vary for different levels of the latent trait

Test Information Function



| | item1 | item2 | item3 | item4 | item5 |
|---|-------|-------|-------|-------|-------|
| b | -2.50 | -1.25 | 0.00 | 1.25 | 2.50 |

2PL

2PL

Item Response Function

Item Response Function


$$P(x_{pi} = 1|\theta_p, b_i, a_i) = \frac{\exp[a_i(\theta_p - b_i)]}{1 + \exp[a_i(\theta_p - b_i)]}$$

θ_p : Ability of the person (i.e., latent trait level of the person)

b_i ; difficulty of item i (location of the item on the latent trait) \rightarrow

a_j : Discrimination of the item \rightarrow ability of the item to tell apart subjects with different levels of the latent trait


Item Response Function



Item 1 ($a_1 = 0.50$):

$2 + 2 = ?$

Item Response Function



Item 1 ($a_1 = 0.50$):

$2 + 2 = ?$

oooooooooooooooooooo

oooooooooooooooooooo


oooo●oooooooooooo

oooooooooooooooooooo

oooo


oooooooooooo

Item Response Function

Item 1 ($a_1 = 0.50$): $2 + 2 = ?$ Item 2 ($a_2 = 2.50$): $5 + 14 = ?$

Item Response Function

Negative discrimination



The higher the level of the latent trait... the lower the probability of responding correctly!

2PL

oooooooooooooooooooo


oooooooooooooooooooo

oooooooo●ooooooooo

oooooooooooooooooooo

oooo

oooooooooooo



| | item1 | item2 | item3 | item4 |
|---|-------|-------|-------|-------|
| b | 0.00 | 0.00 | 0.00 | 2.00 |
| a | 0.50 | 0.90 | 1.50 | 1.50 |

2PL

Item Information Function

$$l_i(\theta, b_i, a_i) = a_i^2 P_i(\theta, b_i, a_i) Q_i(\theta, b_i, a_i)$$

$Q_j = 1 - P_j(\theta, b_j, a_j)$ is the probability of giving the incorrect response

oooooooooooooooooooo

oooooooooooooooooooo


oooooooooo●oooo

oooooooooooooooooooo

oooo

oooooooooooo

Item Information Function



| | item1 | item2 | item3 | item4 |
|---|-------|-------|-------|-------|
| b | 0.00 | 0.00 | 0.00 | 2.00 |
| a | 0.50 | 0.90 | 1.50 | 1.50 |


2PL

Test Information Function

oooooooooooooooooooo oooooooooooooooooooooo ooooooooooooo●o ooooooooooooooooooooo oooo oooooooooooooo

Test Information Function


$$I(\theta) = \sum I_i(\theta, b_i, a_i)$$



| | item1 | item2 | item3 | item4 |
|---|-------|-------|-------|-------|
| b | 0.00 | 0.00 | 0.00 | 2.00 |
| a | 0.50 | 0.90 | 1.50 | 1.50 |

Test Information Function

$$SEM(\theta) = \sqrt{\frac{1}{I(\theta)}} = \sqrt{\frac{1}{a^2 P_i(\theta, b_i) Q_i(\theta, b_i)}}$$



| | item1 | item2 | item3 | item4 |
|---|-------|-------|-------|-------|
| b | 0.00 | 0.00 | 0.00 | 2.00 |
| a | 0.50 | 0.90 | 1.50 | 1.50 |

3PL

3PL

Item Response Function

Item Response Function

The lower asymptote is moved upward by adding a third item parameter, the pseudo-guessing (c_j):

$$P(x_{pi} = 1|\theta_p, b_i, a_i) = c_i + (1 - c_i) \frac{\exp[a_i(\theta_p - b_i)]}{1 + \exp[a_i(\theta_p - b_i)]}$$

θ_p : Ability of the person (i.e., latent trait level of the person)

b_i ; difficulty of item i (location of the item on the latent trait) \rightarrow

a_i : Discrimination of the item \rightarrow ability of the item to tell apart subjects with different levels of the latent trait

c_i : pseudo-guessing of item $i \rightarrow$ probability of giving the correct response even if the latent trait approaches $-\infty$

oooooooooooooooooooo

oooooooooooooooooooo

oooooooooooooooooooo


ooo●oooooooooooo

oooo

oooooooooooo

Item Response Function

Item 1: $b_1 = 0$, $a_1 = 1.4$ e $c_1 = 0.2$, Item 2: $b_1 = 0$, $a_1 = 1.4$ e $c_1 = 0.3$ (item 2)



The probability of responding correctly is approximately c (0.20, 0.30) for low levels of the latent trait

oooooooooooooooooooo

oooooooooooooooooooo


oooooooooooooooooooo

oooo●oooooooooooo

oooo

oooooooooooo

Item Response Function



The probability of responding correctly when $\theta_p = b_i$ is higher than .50
 $(P(x_{pi} = 1) = c + (1 - c)/2)$

3PL

Item Information Function

Item Information Function

$$I_i(\theta, b_i, a_i, c_i) = a_i^2 \frac{P_i(\theta, b_i, a_i, c_i)}{Q_i(\theta, b_i, a_i, c_i)} \left[\frac{P_i(\theta, b_i, a_i, c_i) - c_i}{1 - c_i} \right]$$

The higher the guessing, the lower the IIF

$Q_i = 1 - P_i(\theta, b_i, a_i, c_i)$ è la probabilità di osservare una risposta errata

oooooooooooooooooooo

oooooooooooooooooooo


oooooooooooooooooooo

oooooooo●ooooo

oooo

oooooooooooo

Item Information Function



| | item1 | item2 |
|---|-------|-------|
| b | 0.00 | 1.00 |
| a | 1.40 | 1.40 |
| c | 0.20 | 0.30 |

3PL


Test Information Function

Test Information Function

$$I(\theta) = \sum I_i(\theta, b_i, a_i, c_i)$$

oooooooooooooooooooo oooooooooooooooooooooo ooooooooooooooooooooo ooooooooooooo●oooo ooooo oooooooooooooo

Test Information Function




| | item1 | item2 |
|---|-------|-------|
| b | 0.00 | 1.00 |
| a | 1.40 | 1.40 |
| c | 0.20 | 0.30 |

Test Information Function

$$SEM(\theta) = \sqrt{\frac{1}{I(\theta)}} = \sqrt{\frac{1}{a^2 P_i(\theta, b_i, a_i, c_i) Q_i(\theta, b_i, a_i, c_i)}}$$

oooooooooooooooooooo oooooooooooooooooooooo ooooooooooooooooooooo oooooooooooooo●oooo ooooo oooooooooooooo

Test Information Function



| | item1 | item2 |
|---|-------|-------|
| b | 0.00 | 1.00 |
| a | 1.40 | 1.40 |
| c | 0.20 | 0.30 |

4PL

4PL

Item Response Function

Lower the upper asymptote by adding a **careless error** parameter

$$P(x_{pi} = 1 | \theta_p, b_i, a_i) = c_i + (d_i - c_i) \frac{\exp[a_i(\theta_p - b_i)]}{1 + \exp[a_i(\theta_p - b_i)]}$$

Dove:

θ_p : Ability of the person (i.e., latent trait level of the person)

b_i, a_i, c_i ; Difficulty, discrimination, and pseudo-guessing of item i

d_i : careless-error, probability of endorsing the item when the latent trait approaches $+\infty$

The lower then value of d_i , the lower the probability that a person with high level of the latent trait gives the correct response to item i

oooooooooooooooooooo

oooooooooooooooooooo

oooooooooooooooooooo

oooooooooooooooooooo


ooo●

oooooooooooo

Item Response Function

Item 1: $b = 0$, $a = 1.4$, $c = 0.20$,
 $d = .9$

Item 2: $b = 0$, $a = 1.4$, $c = 0.30$,
 $d = .7$



Relationship between models

Relationship between models

- Constraining the d_i parameters of all items to be 1 \rightarrow from 4-PL to 3-PL
- Constraining the c_i parameters of all items to be 0 \rightarrow from 3-PL to 2-PL
- Constraining the a_i parameters of all items to be 1 \rightarrow from 2-PL to 1-PL

The Rasch Model?

Relationship between models

The Rasch Model?

The Rasch Model?

Formally, the Rasch model and the 1-PL are the same model

IRT

Fit of the **models** to the data

The model that fit better the data
is chosen

Rasch

Fit of the data to the **model**

The data are modified as long as
they don't fit to the model



All models are wrong...

Relationship between models

All models are wrong...

All models are wrong...

The model can be chosen

- A priori:
 - Theoretical considerations
 - Item characteristics
- A posteriori:
 - Estimation of all the IRT models
 - Model comparison

All models are wrong...

Comparative fit indexes

- $-2\log\text{likelihood}$ \rightarrow nested models only
- Akaike's Information Criterion (AIC)
- Bayesian Information Criterion (BIC)

The significance of the difference between the *LogLikelihood* can be tested considering a χ^2 distribution with degrees of freedom equal to the difference in the degrees of freedom of the two nested models:

- Significant difference: The most complex model is the best one
- Non significant difference: The simplest model is the best one

All models are wrong...

AIC and BIC are entropy indexes → the lower the better

AIC penalizes most complex models regardless of the sample size

$$AIC = -2\log Lik + 2p$$

BIC penalizes most complex models also accounting for the sample size

$$BIC = -2\log Lik + p \cdot \log(N)$$