

Who aRe you?  
ooooo

Get help  
oo

Be tidy  
oooooo

Working directories  
oo

Structures in R  
oooooooooooooooooooooooooooooooooooo

# An intRoduction to R

Univerisity of Padova (IT)

Who aRe you?

●oooo

Get help

oo

Be tidy

oooooo

Working directories

oo

Structures in R

oooooooooooooooooooooooooooooooooooo

Who aRe you?

- R is an open source software for statistical computing, graphics, and so much more
- RStudio is the perfect IDE for R → allows for a better, easier use of R
- R runs on Windows, MacOS, Unix

R ignores everything after # (it's a comment)

# Assign

The results of the operations can be “stored” into objects with specific names defined by the users.

To assign a value to an object, there are two operators:


1. `= x = exp(2^2)`

2. `<- X <- log(2^2)`

The elements on the right are assigned to the object on the left

**Careful!** R is case sensitive: `x` and `X` are two different objects!!!

## Variable names



Valid variable names are letters, numbers, dots, underscores (e. g., `variable_name`)

Variables names cannot start with numbers

Again, R is case sensitive

Who aRe you?  
ooooo

Get help  
●o

Be tidy  
oooooo

Working directories  
oo

Structures in R  
oooooooooooooooooooooooooooooooooooo

Get help

R is open source and it used world wide → there's a huge community ready to help you

Just copy & paste any error message or warning in google or ask google  
"how to something in r"

Ask R to help you! Type `?` in your console followed by the name of the function:

?mean()

Will show you the help page of the `mean()` function



Who aRe you?  
ooooo

Get help  
oo

Be tidy  
●ooooo

Working directories  
oo

Structures in R  
oooooooooooooooooooooooooooooooooooo

Be tidy

## Organize your files

## R projects are the best way to organize your files (and your workflow)

It allows you to have all your files in a folder organized in sub folders

You don't have to worry about the wording directories because it's all there!

By creating a nw project, you can also initialize a shiny app

and so much more

## Take out the trash

The R environment should be always tidy

If it feels like you're losing it, just clean it up:

```
ls()  # list objects in the envrinoment
rm(A)  # remove object A from the environment
rm(list = ls())  # remove everything from the environment
```

## Save the environment

It might be useful to save all the computations you have done:

```
save.image("my-computations.RData")
```

Then you can upload the environment back:

```
load("my-Computations.RData")
```

## When to save the environment

The computations are slow and you need them to be always and easily accessible

The best practice wis to save the script and document it in an RMarkdown file

Who aRe you?  
ooooo

Get help  
oo

Be tidy  
oooooo

Working directories  
●o

Structures in R  
oooooooooooooooooooooooooooooooooooo

## Working directories

If you choose not to use the R projects (`{what a bad, bad, bad idea}`), you need to know your directories:

```
getwd() # the working directory in which you are right now
```

```
dir() # list of what's inside the current working directory
```

Change your working directory:

```
setwd("C:/Users/huawei/OneDrive/Documents/GitHub/RcouRse")
```



Who aRe you?  
ooooo

Get help  
oo

Be tidy  
oooooo

Working directories  
oo

Structures in R  
●oooooooooooooooooooooooooooooooooooo

## Structures in R

## Functions and arguments (pt. I)

Almost everything in R is done with functions, consisting of:

- a name: `mean`
- a pair of brackets: `()`
- some arguments: `na.rm = TRUE`

```
mean(1:5, trim = 0, na.rm = TRUE)
```

```
[1] 3
```

Arguments may be set to default values; what they are is documented in  
`?mean`

## Functions and arguments (pt. II)

Arguments can be passed

- without name (in the defined order)
- with name (in arbitrary order) → keyword matching

`mean(x, trim = 0.3, na.rm = TRUE)`

No arguments? No problems, just brackets:

`ls(), dir(), getwd()`

Want to see the code of a function? Just type its name in the console without brackets:

`mean`

# Vectors

Vectors are created by **combining** together different objects

Vectors are created by using the `c()` function.

All elements inside the `c()` function **must** be separated by a comma

Different types of objects → types of vectors:

- `int`: numeric integers
- `num`: numbers
- `logi`: logical
- `chr`: characters
- `factor`: factor with different levels

## int and num

int: refers to integer -3, -2, -1, 0, 1, 2, 3

```
months = c(5, 6, 8, 10, 12, 16)
```

```
[1] 5 6 8 10 12 16
```

num: refers to all numbers from  $-\infty$  to  $\infty$  1.0840991, 0.8431089, 0.494389, -0.7730161, 2.9038161, 0.9088839

```
weight = seq(3, 11, by = 1.5)
```

```
[1] 3.0 4.5 6.0 7.5 9.0 10.5
```

## logi

Logical values can be TRUE (T) or FALSE (F)

```
v_logi = c(TRUE, TRUE, FALSE, FALSE, TRUE)
```

```
[1] TRUE TRUE FALSE FALSE TRUE
```

logical vectors are often obtained from a comparison:

```
months > 12
```

```
[1] FALSE FALSE FALSE FALSE FALSE TRUE
```

## chr and factor

chr: characters a, b, c, D, E, F

```
v_chr = c(letters[1:3], LETTERS[4:6])
```

```
[1] "a" "b" "c" "D" "E" "F"
```

factor: use numbers or characters to identify the variable levels

```
ses = factor(c(rep(c("low", "medium", "high"), each = 2)))
```

```
[1] low    low    medium medium high    high
```

```
Levels: high low medium
```

Change order of the levels:

```
ses1 = factor(ses, levels = c("medium", "high", "low"))
```

```
[1] low    low    medium medium high    high
```

```
Levels: medium high low
```

## Create vectors

Concatenate elements with `c()`: `vec = c(1, 2, 3, 4, 5)`

Sequences:

```
-5:5 # vector of 11 numbers from -5 to 5
```

```
[1] -5 -4 -3 -2 -1 0 1 2 3 4 5
```

```
seq(-3, 3, by = 0.5) # sequence in steps of 0.5 from -3 to 3
```

```
[1] -3.0 -2.5 -2.0 -1.5 -1.0 -0.5 0.0 0.5 1.0 1.5 2.0 2.5 3
```

Repeating elements:

```
rep(1:3, 4)
```

```
[1] 1 2 3 1 2 3 1 2 3 1 2 3
```



## Create vectors II

```
rep(c("condA", "condB"), each = 3)
```

```
[1] "condA" "condA" "condA" "condB" "condB" "condB"
```

```
rep(c("on", "off"), c(3, 2))
```

```
[1] "on" "on" "on" "off" "off"
```

```
paste0("item", 1:4)
```

```
[1] "item1" "item2" "item3" "item4"
```

Don't mix them up unless you truly want to

`int + num → num`

`int/num + logi → int/num`

`int/num + factor → int/num`

`int/num + chr → chr`

`chr + logi → chr`

## Vectors and operations

Vectors can be summed/subtracted/divided and multiplied with one another

```
a = c(1:8)
```

```
a
```

```
[1] 1 2 3 4 5 6 7 8
```

```
b = c(4:1)
```

```
b
```

```
[1] 4 3 2 1
```

```
a - b
```

```
[1] -3 -1 1 3 1 3 5 7
```

If the vectors do not have the same length, you get a warning

## Vectors and operations PT. II

The function is applied to each value of the vector:

```
sqrt(a)
```

```
[1] 1.000000 1.414214 1.732051 2.000000 2.236068 2.449490 2.6
```

The same operation can be applied to each element of the vector:

```
(a - mean(a))^2 # squared deviation
```

```
[1] 12.25  6.25  2.25  0.25  0.25  2.25  6.25 12.25
```

## Matrices and arrays

Create a  $3 \times 4$  matrix:

```
A = matrix(1:12, nrow = 3, ncol = 4, byrow = TRUE)
```

Label and transpose:

```
rownames(A) = c(paste("a", 1:3)) # colnames()  
t(A) # transpose matrix
```

	a 1	a 2	a 3
[1,]	1	5	9
[2,]	2	6	10
[3,]	3	7	11
[4,]	4	8	12

# Matrices and arrays

Matrix can be created by concatenating columns or rows:

```
cbind(a1 = 1:4, a2 = 5:8, a3 = 9:12) # column bind
```

```
rbind(a1 = 1:4, a2 = 5.8, a3 = 9:12) # row bind
```

## Matrices and arrays

```
array(data, c(nrow, ncol, ntab))
```

```
my_array = array(1:30, c(2, 5, 3)) # 2 x 5 x 3 array
```

```
, , 1
```

	[,1]	[,2]	[,3]	[,4]	[,5]
[1,]	1	3	5	7	9
[2,]	2	4	6	8	10

```
, , 2
```

	[,1]	[,2]	[,3]	[,4]	[,5]
[1,]	11	13	15	17	19
[2,]	12	14	16	18	20

```
, , 3
```

	[,1]	[,2]	[,3]	[,4]	[,5]
[1,]	21	23	25	27	29
[2,]	22	24	26	28	30

## Work with vectors, atrices, arrays

Index elements in vectors `vector_name[position]`

```
weight[2]    # second element in vector weight
weight[6] = 15.2 # replace sixth element of weight
weight[seq(1, 6, by = 2)] # elements 1, 3, 5
weight[2:6]   # elements 2 to 6
weight[-2]    # without elemt 2
```

Logic applies as well:

```
weight[weight > 7] # values greater than 7
weight[weight >= 4.5 & weight < 8] # values between 4.5 and
```



## Work with vectors, atrices, arrays II

Access elements in matrices: `matrix_name[row, column]`

`A[2, 3]` # cell in row 2 column 3

`A[2, ]` # second row

`A[, 3]` # third column

## Work with vectors, atrices, arrays III

Access elements in arrays `array_name[row, col, tab]`

```
my_array[2, 1, 3] # cell in 2nd row 1st col of 3rd tab
```

```
my_array[, , 3] # 3rd tab
```

```
my_array[1, , 2] # 1st row in tab 2
```

## Lists

Can store different objects (e.g., vectors, data frames, other lists):

```
my_list = list(w = weight, m = months, s = ses1, a = A)
```

The components of the list can be extracted with `$` or `[[ ]]` and the name (or position) of the component:

Extract months:

```
my_list[["m"]]  # my_list$a  
[1]  5  6  8 10 12 16
```

Extract weight:

```
my_list[[1]]  # my_list$months or my_list[['a']]  
[1]  3.0  4.5  6.0  7.5  9.0 10.5
```

## The king of data structure: data frames

Data frames are lists that consist of vectors and factors of equal length.  
The rows in a data frame refer to one unit:

```
id = paste0("sbj", 1:6)
babies = data.frame(id, months, weight)
```

`babies`

	id	months	weight
1	sbj1	5	3.0
2	sbj2	6	4.5
3	sbj3	8	6.0
4	sbj4	10	7.5
5	sbj5	12	9.0
6	sbj6	16	10.5

## Working with data frames

Index elements in a data frame:

```
babies$months # column months of babies
```

```
babies$months[2] # second element of column months
```

```
babies[, "id"] # column id
```

```
babies[2, ] # second row of babies (obs on baby 2)
```

Logic applies:

```
babies[babies$weight > 7, ] # all obs above 7 kg
```

```
babies[babies$id %in% c("sbj1", "sbj6"), ] # obs of sbj1 and
```

## Working with data frames II

```
dim(babies) # show the dimensions of the data frame
```

```
[1] 6 3
```

```
names(babies) # variable names (= colnames(babies))
```

```
[1] "id"      "months" "weight"
```

```
View(babies) # open data viewer
```

```
plot(babies) # pariwise plot
```

You can use these commands also on other R objects

## Working with data frames III

```
str(babies) # show details on babies
```

```
'data.frame':  6 obs. of  3 variables:
 $ id      : chr  "sbj1" "sbj2" "sbj3" "sbj4" ...
 $ months: num   5  6  8 10 12 16
 $ weight: num   3 4.5  6 7.5  9 10.5
```

```
summary(babies) # descriptive statistics
```

id	months	weight
Length:6	Min. : 5.0	Min. : 3.000
Class :character	1st Qu.: 6.5	1st Qu.: 4.875
Mode :character	Median : 9.0	Median : 6.750
	Mean : 9.5	Mean : 6.750
	3rd Qu.:11.5	3rd Qu.: 8.625
	Max. :16.0	Max. :10.500

You can use these commands also on other R objects

## Sorting

`order()`:

```
babies[order(babies$weight), ] # sort by increasing weight
```

	id	months	weight
1	sbj1	5	3.0
2	sbj2	6	4.5
3	sbj3	8	6.0
4	sbj4	10	7.5
5	sbj5	12	9.0
6	sbj6	16	10.5

```
babies[order(babies$weight, # sort by decreasing weight  
             decreasing = T), ]
```

Multiple arguments in `order`:

```
babies[order(babies$weight, babies$months, decreasing = TRUE), ]
```



## Aggregating

Aggregate a response variable according to grouping variable(s) (e.g., averaging per experimental conditions):

# Single response variable, single grouping variable

```
aggregate(y ~ x, data = data, FUN, ...)
```

# Multiple response variables, multiple grouping variables

```
aggregate(cbind(y1, y2) ~ x1 + x2, data = data, FUN, ...)
```

## Aggregating: Example

```
head(ToothGrowth) # Vitamin C and tooth growth (Guinea Pigs)
```

```
      len supp dose
1   4.2   VC  0.5
2  11.5   VC  0.5
3   7.3   VC  0.5
4   5.8   VC  0.5
5   6.4   VC  0.5
6  10.0   VC  0.5
```

Aggregate across supplement and dose of Vitamin C:

```
aggregate(len ~ supp + dose, data = ToothGrowth, mean)
```

```
      supp dose    len
1     OJ  0.5 13.23
2     VC  0.5  7.98
3     OJ  1.0 22.70
4     VC  1.0 16.77
5     OJ  2.0 26.06
```

## Reshaping: Long to wide

Data can be organized in wide format (i.e., one line for each statistical unit) or in long format (i.e., one line for each observation).

```
head(Indometh) # Long format
```

	Subject	time	conc
1	1	0.25	1.50
2	1	0.50	0.94
3	1	0.75	0.78
4	1	1.00	0.48
...			

## Long to wide

```
# From long to wide
```

```
df.w <- reshape(Indometh, v.names = "conc", timevar = "time",  
  idvar = "Subject", direction = "wide")
```

```
  Subject conc.0.25 conc.0.5 conc.0.75 conc.1 conc.1.25 conc.  
1         1       1.50      0.94      0.78    0.48      0.37    0.  
12        2       2.03      1.63      0.71    0.70      0.64    0.  
23        3       2.72      1.49      1.16    0.80      0.80    0.  
34        4       1.85      1.39      1.02    0.89      0.59    0.  
45        5       2.05      1.04      0.81    0.39      0.30    0.  
56        6       2.31      1.44      1.03    0.84      0.64    0.  
  conc.5 conc.6 conc.8  
....
```

## Reshaping: Wide to long

```
# From wide to long
```

```
df.l <- reshape(df.w, varying = list(2:12), v.names = "conc",  
  idvar = "Subject", direction = "long", times = c(0.25, 0.5,  
    0.75, 1, 1.25, 2, 3, 4, 5, 6, 8))
```

```
      Subject time conc  
1.0.25      1 0.25 1.50  
2.0.25      2 0.25 2.03  
3.0.25      3 0.25 2.72  
....
```

```
# reorder by subject
```

```
df.l[order(df.l$Subject), ]
```

```
      Subject time conc  
1.0.25      1 0.25 1.50  
1.0.5       1 0.50 0.94  
1.0.75      1 0.75 0.78  
....
```

## Execersizes

- Open a new R script
- Create one vector for each type (`int`, `num`, `chr`, `logi`, `factor`) and assign each of them to an object
- Compute the mean of the `int` and `num` vectors
- Standardize the values of the `int` and `num` vectors and store them in two new objects:

$$z = \frac{x_i - \bar{X}}{sd}$$

- Create a new vector by combining together the `logi` and `int` vectors
- Add the `logi` vector to the `num` vector