

Package ‘OuhscMunge’

January 10, 2016

Title Data Manipulation Operations

Description Data manipulation operations frequently used in OUHSC BBMC projects.

Version 0.1.6.9000

Date 2016-01-08

Author Will Beasley [aut, cre]

Maintainer Will Beasley <wibeasley@hotmail.com>

URL <https://github.com/OuhscBbmc/OuhscMunge>, <http://ouhsc.edu/bbmc/>

BugReports <https://github.com/OuhscBbmc/OuhscMunge/issues>

License GPL-2

LazyData TRUE

Depends R(>= 3.1.0)

Imports devtools (>= 1.8.0),
lubridate

Suggests RODBC,
testthat

RoxygenNote 5.0.1

R topics documented:

clump_month_date	2
headstart_utilities	3
OuhscMunge	3
replace_nas_with_explicit	4
Index	6

clump_month_date	<i>Assign date for a given year & month</i>
------------------	---

Description

This accepts a date, but changes the day. Set/degrade/clump all the days within a month to the same day.

Usage

```
clump_month_date(date_detailed, day_of_month = 15L)
```

Arguments

date_detailed	The Date value containing the desired year and month. The day will be over-written. Required
day_of_month	The factor label assigned to the missing value. Defaults to 15.

Details

We use this frequently to set/degrade/clump all the days to the middle of their respective month (ie, the 15th day). The midpoint of a month is usually the most appropriate summary location. It makes graphs more intuitive. Using the midpoint of month can also avoid problems with timezones. A date won't get nudged to a neighboring month accidentally.

Value

An array of Date values.

Note

A stop error will be thrown if date_detailed is not a Date, or if day_of_month is not bounded by [1, 31]. Be careful that if you set a November date the 31st day, the result will be December 1st. Consequently, we recommend not setting the day to a value after the 28.

Author(s)

Will Beasley

Examples

```
library(OuhscMunge)
detailed <- seq.Date(from=as.Date("2011-04-21"), to=as.Date("2011-07-14"), by="day")
clumped <- clump_month_date(detailed)
table(clumped)
# 2011-04-15 2011-05-15 2011-06-15 2011-07-15
#           10           31           30           14
```

headstart_utilities *Utilities for outputting characteristics of a dataset used in code.*

Description

These functions are used during the execution of a program. Rather they produce snippets that can be pasted into code, and help the developer avoid some typing.

Usage

```
column_rename_headstart( d )
column_class_headstart( d )
column_value_headstart( x )
```

Arguments

d A data.frame to describe.
x A vector to describe.

Value

Prints formatted code to the console.

Author(s)

Will Beasley

Examples

```
column_rename_headstart(datasets::OrchardSprays)
column_class_headstart(datasets::OrchardSprays)
column_value_headstart(datasets::OrchardSprays$treatment)
```

OuhscMunge *Data manipulation operations frequently used in OUHSC BBMC projects. <<http://www.ouhsc.edu/bbmc/>>*

Description

Thanks to Funders, including **HRSA/ACF D89MC23154**

OUHSC CCAN Independent Evaluation of the State of Oklahoma Competitive Maternal, Infant, and Early Childhood Home Visiting (MIECHV) Project., which evaluates MIECHV expansion and enhancement of Evidence-based Home Visitation programs in four Oklahoma counties.

Details

OuhscMunge.

Note

The release version will eventually be available through CRAN by running `install.packages('OuhscMunge')`. The most recent development version is available through [GitHub](#) by running `devtools::install_github(repo = 'OuhscBbmc/OuhscMunge')` (make sure [devtools](#) is already installed). If you're having trouble with the package, please install the development version. If this doesn't solve your problem, please create a [new issue](#), or email Will.

Author(s)

[William Howard Beasley](#), University of Oklahoma Health Sciences Center, College of Medicine, Dept of Pediatrics, [BBMC](#).

Maintainer: Will Beasley <wibeasley@hotmail.com>

Examples

```
## Not run:
# Install/update REDCapR with the release version from CRAN.
install.packages('OuhscMunge') #But it's not on CRAN yet.

# Install/update REDCapR with the development version from GitHub
#install.packages('devtools') #Uncomment if `devtools` isn't installed already.
devtools::install_github('OuhscBbmc/OuhscMunge')

## End(Not run)
```

```
replace_nas_with_explicit
```

Create explicit factor level for missing values.

Description

Missing values are converted to a factor level. This explicit assignment can reduce the chances that missing values are inadvertently ignored. It also allows the presence of a missing to become a predictor in models.

Usage

```
replace_nas_with_explicit(scores, new_na_label = "Unknown",
  create_factor = FALSE, add_unknown_level = FALSE)
```

Arguments

scores	An array of values, ideally either factor or character. Required
new_na_label	The factor label assigned to the missing value. Defaults to Unknown.
create_factor	Converts scores into a factor, if it isn't one already. Defaults to FALSE.
add_unknown_level	Should a new factor level be created? (Specify TRUE if it already exists.) Defaults to FALSE.

Value

An array of values, where the NA values are now a factor level, with the label specified by the new_na_label value.

Note

The create_factor parameter is respected only if scores isn't already a factor. Otherwise, levels without any values would be lost.

A stop error will be thrown if the operation fails to convert all the NA values.

Author(s)

Will Beasley

Examples

```
library(OuhscMunge) #Load the package into the current R session.
missing_indices <- c(3, 6, 8, 25)
# With a character variable:
a <- letters
a[missing_indices] <- NA_character_
a <- OuhscMunge::replace_nas_with_explicit(a)

# With a factor variable:
b <- factor(letters, levels=letters)
b[missing_indices] <- NA_character_
b <- OuhscMunge::replace_nas_with_explicit(b, add_unknown_level=TRUE)
```

Index

clump_month_date, [2](#)
column_class_headstart
 (headstart_utilities), [3](#)
column_rename_headstart
 (headstart_utilities), [3](#)
column_value_headstart
 (headstart_utilities), [3](#)

headstart_utilities, [3](#)

OuhscMunge, [3](#)
OuhscMunge-package (OuhscMunge), [3](#)

replace_nas_with_explicit, [4](#)