

CS-322 Introduction to Database Systems

Project Deliverable #2


Due on Sunday, May 4th, 2014

Group 24
Klay, Ameho, Vinh Mau



ÉCOLE POLYTECHNIQUE
FÉDÉRALE DE LAUSANNE

ER model for music database



SQL DDL code for table creations

```

CREATE TABLE Areas (
  areaID INTEGER,
  name VARCHAR(255) NOT NULL,
  type VARCHAR(255),
  PRIMARY KEY (areaID) );

CREATE TABLE Genres (
  genreID INTEGER,
  name VARCHAR(255) NOT NULL,
  count INTEGER DEFAULT 0,
  PRIMARY KEY (genreID) );

CREATE TABLE Artists (
  artistID INTEGER,
  name VARCHAR(255) NOT NULL,
  areaID INTEGER,
  gender CHAR(1),
  PRIMARY KEY (artistID),
  FOREIGN KEY (areaID) REFERENCES Areas );

CREATE TABLE Recordings (
  recordingID INTEGER,

```

```
25     name VARCHAR(255) ,
    length INTEGER,
    PRIMARY KEY (recordingID) ) ;

30 CREATE TABLE Albums (
    albumID INTEGER,
    name VARCHAR(255) NOT NULL,
    PRIMARY KEY (albumID) ) ;

35 CREATE TABLE Mediums (
    mediumID INTEGER,
    albumID INTEGER,
    format VARCHAR(255),
    PRIMARY KEY (mediumID),
40    FOREIGN KEY (albumID) REFERENCES Albums ) ;

CREATE TABLE Tracks (
45     trackID INTEGER,
    mediumID INTEGER,
    recordingID INTEGER,
    position INTEGER,
    PRIMARY KEY (trackID),
    FOREIGN KEY (mediumID) REFERENCES Mediums,
50    FOREIGN KEY (recordingID) REFERENCES Recordings ) ;
```

SQL script for entities table creation

```
CREATE TABLE Artist_genre (
    artistID INTEGER,
    genreID INTEGER,
    PRIMARY KEY (artistID, genreID),
5    FOREIGN KEY (artistID) REFERENCES Artists,
    FOREIGN KEY (genreID) REFERENCES Genres ) ;

CREATE TABLE Track_artist (
10     artistID INTEGER,
    trackID INTEGER,
    PRIMARY KEY (artistID, trackID),
    FOREIGN KEY (trackID) REFERENCES Tracks ,
    FOREIGN KEY (artistID) REFERENCES Artists ) ;
```

SQL script for relations table creation

Design choices & data constraints

There are three main concepts in our music database : **Song**, **Artist** and **Album**. Both **Song** and **Album** were divided between their descriptive data and their physical incarnation. We decided to enforce **Song** as the only necessary information to describe music, emulating the approach taken by most popular music player softwares since data can be incomplete. We put a NOT NULL constraint on most of the name attributes of the entities, with the exception of **Song** for the reason just stated. Since they are not required fields to describe music, they should have a valid name when they are in fact used.

- A **Song** is related to:

Artist: A song can exist without known artists, but can also have several artists to describe collaborations.

Medium: Though a song is not necessarily part of an album, it has to be recorded on some medium. There is therefore a participation constraint of **Song** in **Medium**. Their relation is characterized by the track position on the medium.

- An **Artist** is defined by a:

Genre: A genre can regroup multiple artists, but makes no sense as an empty container, thus triggering a participation constraint, whereas an artist can be difficult to define as catering to a specific genre, or crossing boundaries between genres nullifying the need for a constraint. We kept the count attribute, choosing small update costs over on-demand higher computation costs.

Area: An artist's location can be pinpointed to a specific creation grounds, hence can be expressed by a foreign key constraint. But several artists can be compelled to share their musical feelings in the same studio, and a place which doesn't house such a creative conundrum isn't worth keeping track of in a music database.

- An **Album** is the logical aggregation of songs, labeled by a title, and can be recorded on multiple — at least one, participation constraint— media. Conversely, a medium identifies a singular recording of an album, enforced by a foreign key constraint.

Some constraints, the integrity of the count attribute in **Genre** and the several "at least one" constraints, are not guaranteed by the table creation. They will later be enforced later on by the import and delete data commands.

SQL Queries

```
SELECT a.name
FROM artists a, areas l
WHERE a.areaID=l.areaID AND l.name='Switzerland' ;
```

SQL script for query A

```
SELECT area.name
FROM Areas area
WHERE area.areaid = (
    SELECT AreaId areafemale
    FROM (
        SELECT AreaId , count(*) c
        FROM Artists
```

```

WHERE (gender = 'Male')
GROUP BY AreaId
ORDER BY c DESC
)
WHERE ROWNUM <=1
);

```

SQL script for query B

```

SELECT Name
FROM Artists arti
INNER JOIN ( SELECT ArtistId
              FROM ( SELECT ArtistId , count(*) numb
                    FROM TRACK_ARTIST
                    GROUP BY ArtistId
                    ORDER BY numb DESC )) artiId
ON arti.ArtistId = artiId.ArtistId
WHERE ROWNUM <=10 ;

```

SQL script for query C

```

SELECT name
FROM Artists arti
INNER JOIN ( SELECT ArtistId, COUNT(DISTINCT AlbumId) num
              FROM track_artist trackarti
              INNER JOIN ( SELECT *
                          FROM Tracks track
                          INNER JOIN ( SELECT mediums.mediumid, mediums.albumid
                                      FROM Mediums
                                      INNER JOIN Albums
                                      ON mediums.albumid = albums.albumid
                                      ON track.mediumid = medi.mediumid
                          GROUP BY ArtistId
                          ORDER BY num DESC
                        ) artiId
ON arti.ArtistId = artiId.ArtistId
WHERE ROWNUM <=10 ;

```

SQL script for query D

```

SELECT name
FROM Artists arti
INNER JOIN ( SELECT arti.artistid, COUNT(DISTINCT genre.genreid) numb
              FROM Artists arti
              INNER JOIN Artist_Genre genre
              ON arti.artistId = genre.artistId
              WHERE arti.gender = 'Female'
              GROUP BY arti.ArtistId
              ORDER BY numb DESC
            ) artigenre
ON arti.artistid = artigenre.artistid
WHERE ROWNUM <=1 ;

```

SQL script for query E

```
SELECT AreaId
FROM ( SELECT city.areasid, count(CASE WHEN arti.gender = 'Female' THEN 1 END) AS females, count(C
      FROM Artists arti
      INNER JOIN Areas city
      ON city.areasid = arti.areaId
      WHERE city.type = 'City'
      GROUP BY city.areasid ) areamalefemale
WHERE areamalefemale.Females > areamalefemale.Males
```

SQL script for query F

```
SELECT medi.albumid, count(DISTINCT track.trackid)
FROM Tracks track
INNER JOIN ( SELECT mediums.mediumid ,mediums.albumid
              FROM Mediums
              INNER JOIN Albums ON mediums.albumid = albums.albumid ) medi
ON track.mediumid = medi.mediumid
GROUP BY medi.albumid ;
```

SQL script for query G

Interface