

RESTful APIs

REST

Representational State Transfer

architectural style, set of design constraints

coined in Roy T. Fielding's dissertation (2000)

the Web is the largest implementation

three important technologies: HTTP, URL,
HTML

<http://shop.oreilly.com/product/0636920028468.do>

www.w3.org/TR/2004/REC-webarch-20041215/

HTTP

Hypertext Transfer Protocol

request-response protocol

“all about applying verbs to nouns”

nouns: resources (*i.e.*, concepts)

verbs: GET, POST, PUT, DELETE

RESOURCES

If your users might “want to create a hypertext link to it, make or refute assertions about it, retrieve or cache a representation of it, include all or part of it by reference into another representation, annotate it, or perform other operations on it”, make it a resource

can be anything: a document, a row in a database, the result of running an algorithm, etc.

URL

Uniform Resource Locator

every resource must have a URL

type of URI (Identifier)

specifies the location of a resource on a network

REPRESENTATION OF RESOURCES

when a client issues a GET request for a resource, server responds with **representations** of resources and not the resources themselves

any machine-readable document containing any information about a resource

server may send data from its database as HTML, XML, JSON, etc.

REPRESENTATIONAL STATE TRANSFER

representations are transferred back and forth
from client and server

server sends a representation describing the state
of a resource

client sends a representation describing the state it
would like the resource to have

MULTIPLE REPRESENTATIONS

a resource can have more than one representation:
different languages, different formats (HTML, XML,
JSON)

client can distinguish between representations based
on the value of Content-Type (HTTP header)

A resource can have multiple representations—one
URL for every representation

Rest in Action

LOADING A PAGE IN A BROWSER

representations of resources

Browser

HTML

Other Resources



→
HTTP GET

```
http://creativecommons.org
<a><span id="home-button">
</span></a>
<div id="logo">
  <span>
    Creative Commons
  </span>
</div>
```


→
HTTP GET

```
cforms.js
//Collap
String.p
function
return
this.rep

creativecommons.css
topbar #home-button{
  position: relative;
  float: left;
  display: block;
  height: 40px;
  width: 150px;

cc-logo.png
creative commons
```

Document Object Model (DOM)



Rendered Page

HTTP GET Request

method

url

version

GET /index.html HTTP/1.1

Host: www.example.com

User-Agent: Mozilla/5.0

Accept: text/xml,application/
xml,application/xhtml+xml,text/html*/*

Accept-Language: en-us

Accept-Charset: ISO-8859-1,utf-8

Connection: keep-alive

<blank line>

request
headers

HTTP GET Response

version status code text explanation

HTTP/1.1 200 OK

Date: Mon, 23 May 2005 22:38:34 GMT

Server: Apache/1.3.3.7 (Unix) (Red-Hat/Linux)

Content-Type: text/html; charset=UTF-8

Content-Length: 131

response headers

<!DOCTYPE html>

<html>

...

</html>

entity-body/body

Client

MY BLOG

This is my first post.

ADD POST

MY BLOG

02/23/15


This is my first post.

NEW POST

Server

API

DATABASE



HTTP POST Request

POST /messages HTTP/1.1

Host: www.anotherblogpost.com

Content-type: application/x-
www-form-urlencoded

<blank line>

entity-body

HTTP POST Response

HTTP/1.1 303 See Other

Content-type: text/html

Location: [http://
www.anotherblogpost.com/
messages/3486152](http://www.anotherblogpost.com/messages/3486152)


Client



HTTP POST

HTTP GET

Server



Http Methods

GET Get a representation of resource

DELETE Destroy resource

POST Create a new resource based on the given representation

PUT Replace resource state with the one described in the given representation

HEAD Get the headers that would be sent with a representation, but not the representation itself

OPTIONS Discover which HTTP methods this resource responds to

PATCH Modify part of the state of this resource based on the given representation

GET

retrieve representations of resources

no side effects: not intended to change any resource state

no data in request body

response codes: 200 (OK), 302 (Moved Permanently), 404 (Not Found)

safe method

DELETE

destroy a resource on the server

success response codes: 200 (OK),
204 (No Content), 202 (Accepted)

not safe, but idempotent

POST

upload data from the browser to server

usually means “create a new resource,” but can be used to convey *any* kind of change: PUT, DELETE, etc.

side effects are likely

data contained in request body

success response codes: 201 (Created), **Location** header contains URL for created resource; 202 (Accepted), new resource will be created in the future

Not safe or idempotent

PUT

request to modify resource state

success response codes: 200 (OK), 204 (No Content)

can also be used like POST

idempotent

PATCH

representations can be big: PUTs can be inefficient

send the server the parts of the document you want to change

neither safe nor idempotent

Rest Constraints

CLIENT-SERVER

separation between clients from servers
servers and clients be replaced and
developed independently as long as the
interface between them is not altered

STATELESSNESS

server doesn't know about client's
application state

client has no direct control over
resource state

pass representations around to
change state

UNIFORM INTERFACE

Identification of resources

manipulation of resources through
these representations

self-descriptive messages

hypermedia as the engine of
application state (HATEOAS)

OTHER CONSTRAINTS

cacheable

layered system

code-on-demand (optional)

Web Apis

WEB APIs

application program interface to a defined
request-response message system between
clients and servers

accessible via standard HTTP methods

request URLs that transfer representations
(JSON, XML)

REST vs SOAP

resources vs operations

REST new-hotness

SOAP security, ACID transactions,
reliable messaging

XMLHttpRequest

most widely deployed API client in the world

a copy in every web browser

most sites today are built on top of APIs

designed for consumption by

XMLHttpRequest

arRESTed Development

SEMANTIC CHALLENGE

Learning one API doesn't help
a client learn the next one

Follow ProgrammableWeb to get API news and alerts as they break

+Follow

Sign In/Sign Up



[API News](#)

[API Directory](#)

[For API Providers](#)

[For Developers](#)

[Listings](#)

[Forum](#)

ProgrammableWeb: the world's largest API repository, **GROWING DAILY**

Search Over 13,068 APIs

Search APIs

Filter APIs

By Category

By Protocols/Formats

☐ Include Deprecated APIs

API Name	Description	Category	Updated
Google Maps	The Google Maps API allow for the embedding of Google Maps onto web pages of outside developers, using a simple JavaScript interface or a Flash interface. It is designed to work on both mobile...	Mapping	12.05.2005
Twitter	The Twitter micro-blogging service includes two RESTful APIs. The Twitter REST API methods allow developers to access core Twitter data. This includes update timelines, status data, and user...	Social	12.08.2006
YouTube	The Data API allows users to integrate their program with YouTube and allow it to perform many of the operations available on the website. It provides the capability to search for videos, retrieve...	Video	02.08.2006
Flickr	The Flickr API can be used to retrieve photos from the Flickr photo sharing service using a variety of	Photos	09.04.2005

API Directory Search

Search over 13,068 APIs updated daily

Search APIs, mashups, developers



Browse by Category

Newest APIs


Latest Mashups

Add an API +

PW Research Center

Our data. Your PowerPoints. Use our API research for your next presentation. [See all](#) →

Growth In Web APIs Since 2005



Designing Restful Apis

blog.mwaysolutions.com/2014/06/05/10-best-practices-for-better-restful-api/

www.vinaysahni.com/best-practices-for-a-pragmatic-restful-api

Apply Verbs to Nouns

Resources



Http Methods



COLLECTIONS

<VERB> `http://example.com/users`

GET Return all the objects in the collection

POST Create a new entry in the collection;
automatically assign new URI and return it

PUT and **DELETE** not generally used

ELEMENTS

<VERB> `http://example.com/users/12345`

GET Return the specific object in collection

PUT Replace object with another one

DELETE Delete element

POST not generally used

USING PARAMETERS

<VERB> `http://example.com/users?`
`where={ "num_posts" : { "$gt" : 100 } }`

 *Json-encoded filter*

other parameters can be used to select fields, sort, etc.

parameters can also be URL-encoded

ONE-TO-FEW

How would you access the address of a particular user?

ONE-TO-FEW

GET `http://example.com/users/12345`

 *embedded in Json*

ONE-TO-MANY

How would you access the posts of a particular user?

ONE-TO-MANY

GET `http://example.com/users/12345`

GET `http://example.com/posts?
where={"_id":{"$in":[...]}}`



not HATEOS

PAGINATION

GET `http://example.com/users?
offset=60&limit=20`

offset *ith object*

limit *number of returned objects*

can also use **Link** header to specify next,
prev, first, last URLs

CHECKLIST: BASICS

Use nouns but no verbs

Use plural nouns

Don't expose irrelevant nouns

GET method and query parameters should not alter the state

CHECKLIST: BASICS

Use parameters to filter, sort, and select fields from collections


Use offset and limit parameters to paginate results

CHECKLIST: RELATIONS

if a relation is usually requested alongside the resource, **embed the relation's representation** within the output representation of the resource

if a relation can exist independently, **include an identifier** for it within the output representation of the resource

CHECKLIST: FORMATS



Content-Type and **Accept** headers

Can also explicitly declare format in URL

CHECKLIST: INTERFACING WITH CONSUMERS

Handle Errors with HTTP status
codes

An API is only as good as its
documentation

 *Self-documenting APIs*

CHECKLIST: HATEOS?

Hypermedia as the Engine of Application State

navigate the Web by following links

should the API consumer create links or should they be provided?

Better to assume the user has access to the documentation
& include resource identifiers in the output representation

Advantages: stored data and data over the network
minimized, ids more stable than URLs

CHECKLIST: PREVENT ABUSE

Rate Limiting

Authentication

CHECKLIST: CACHING

ETag contains a hash or checksum of the representation validated against client's **If-None-Match**. If match, the API returns a 304 Not Modified status code

Last-Modified contains a timestamp which is validated against **If-Modified-Since**

NEXT CLASS: LAB NODE AND EXPRESS

courses.engr.illinois.edu/cs498rk1/