

MIX GRADE	DESIGN REF. CODE	REVISION	STATUS
—	—	—	DRAFT
MIX DESCRIPTION	CREATED	APPROVED	Pending
—	—	—	—

MIX DESIGN SUMMARY		
Compressive Strength (f'ck) at 28 days — MPa	Standard Deviation (SD) — MPa	Maximum Aggregate Size —
Target Mean Strength (f'ck + 1.65 x SD) — MPa	Free Water / Binder Ratio (W/B) —	Water Content — kg/m3
Total Binder (Cement + Fly Ash) — kg/m3	Target Workability at Site —	Design Density —

MIX PROPORTIONS (SSD/m3)	
Cement	— kg/m3
Total Binder (Cement + Fly Ash)	— kg/m3
Free Water Content	— kg/m3
Free Water / Binder Ratio (W/B)	—
Fine Aggregate	— kg/m3
Coarse Aggregate — 20 mm	— kg/m3
Coarse Aggregate — 12.5 mm	— kg/m3
Total Aggregate	— kg/m3

MATERIALS — TYPE / SOURCE / SP. GR.		
MATERIAL	TYPE / SOURCE	SP.GR.
Fine Aggregate	—	—
Coarse Aggregate — 20 mm	—	—
Coarse Aggregate — 12.5 mm	—	—

AGGREGATE PROPORTIONS		
FRACTION	QTY (kg/m3)	% OF TOTAL
Fine Aggregate	0	0%
Coarse — 20 mm	0	0%
Coarse — 12.5 mm	0	0%
Total	1	100%

Coarse / Fine Aggregate Ratio



Aggregate Proportion

- M-Sand (fine) — 0%
- 20 mm (coarse) — 0%
- 12.5 mm (coarse) — 0%

NOTE
1. Admixture dosage to be adjusted based on ambient temperature and transport time.
2. Moisture correction of aggregates to be carried out daily.
3. All quantities are in SSD condition unless specified.

Quality Control Engineer
Quality Control, Our Own Ready Mix

Disclaimer: This mix design has been prepared in accordance with applicable Indian Standards based on laboratory trials and the materials specified herein. Actual field performance is dependent upon proper batching, transportation, placement, compaction, finishing, curing and site conditions. Any change in material source or characteristics may require review and revision of the mix design.